

2025

**Affordable Housing Development
Raheen, Athenry, Co. Galway
Traffic and Transport Assessment**





**Affordable Housing Development Raheen, Athenry, Co. Galway
Traffic and Transport Assessment Report**

Document Control Sheet

Client:	Paul Keogh Architect
Document No:	252139-ORS-XX-XX-RP-TR-13g-001

Revision	Status	Author:	Reviewed by:	Approved By:	Issue Date
P01	Draft	JP	AGK	AGK	16/12/2025
P02	S2	JP	AGK	AGK	12/01/2026

Table of Contents

Executive Summary	2
1 Introduction	4
1.1 Objectives of this TTA	4
1.2 Methodology	5
2 The Proposed Development	6
2.1 Development Site Location	6
2.2 Land Use	6
2.3 Description of the Proposed Development	8
2.4 Accessibility and Parking	9
2.4.1 Site Access	10
2.4.2 Internal Road Layout	12
2.4.3 Pedestrian and Cyclist Connectivity	13
2.4.4 Service Arrangements	14
2.4.5 Vehicle Parking	14
2.4.6 Cycle Storage	15
3 Traffic Conditions	17
3.1 Existing Road Network	17
3.2 Pedestrian and Cyclist Connectivity	20
3.3 Public Transport Provision	23
3.4 Proposed Transport Infrastructure	25
3.4.1 Proposed Public Transport	26
3.4.2 Proposed Rail Service	26
3.4.3 Active Travel	27
3.4.4 Proposed Road Improvements	28
3.5 Existing Traffic Flows	29
3.6 Traffic Collisions Data in the Vicinity of the Site	34
4 Trip Generation, Distribution and Impact on the Road Network Conclusion	35
4.1 Trip Generation	35
4.2 Cumulative Impact	36
4.3 Future Year Traffic Growth	40
4.4 Generated Traffic Splits Through Neighbouring Junctions	41
4.5 Traffic and Transport Assessment Guidelines	43
5 Capacity Analysis	45
5.1 Introduction	45
5.2 Traffic Impacts of the Proposed Development on the Local Road Network	46
5.2.1 Junction 1 – Raheen Woods Road (Gort Mhaoilir Road)/ L-3103 Priority Junction	46
5.2.2 Junction 2 – Raheen Woods Road (Gort Mhaoilir Road)/ L-3105 Priority Junction	48
6 Conclusions	50
Appendix A – Traffic Data	51
Appendix B – TRICS Data	52
Appendix C – Junctions11 Modelling Data	53

Executive Summary

ORS were engaged by *SDS Design engineers*, on behalf of Galway County Council, to undertake a Traffic and Transport Assessment (TTA) as part of the planning application for a proposed affordable housing development at Raheen, Athenry, Co. Galway. This document forms part of the planning application and should be read in conjunction with all drawings, reports, specifications, and particulars associated with the planning application.

The report will examine existing and proposed traffic conditions and transport activity to determine the effects on the surrounding road network by the proposed development.

The development consists of the construction of 28No. two-storey dwellings, including 18No. 3-bedroom semi-detached houses and 10No. 2-bedroom terraced houses, located on a greenfield site accessed from the Raheen Woods Road (Gort Mhaoilir Road). The proposal also involves the construction of hard and soft landscape works including new roadways and paths, provision of 56No. new car parking spaces including 7No. universal access spaces with EV charging facilities, provision of 14No. cycle parking, public open space, public lighting, signage, boundary treatments and all associated infrastructure.

The site is greenfield land, located 650m west of Athenry's town centre.

ORS scoped the requirements for the Traffic Assessment following the same approach previously applied to a nearby proposed residential development (to the northeast of the proposed site, in the immediate vicinity), where the methodology and assessment extents were agreed with Galway County Council. In line with that earlier agreement, and to ensure consistency in the evaluation of traffic conditions in the area, the present assessment similarly focuses on the same two key junctions in the vicinity of the Proposed Development, as described below.

Automatic Junction Turning Counts (JTC) were carried out on Tuesday 11th March 2025 at the following junctions by a third-party company named IDASO:

- Site 1: 3-arm Junction of Raheen Woods Road (Gort Mhaoilir Road) and the L-3103,
- Site 2: 3-arm Junction of Raheen Woods Road (Gort Mhaoilir Road) and the L-3105.

The traffic counts encompass all movements along the junctions and are assumed to be representative of a normal weekday.

The traffic profile likely to be generated by the proposed development was obtained by the Trip Rate Information Computer System (TRICS) database. Therefore, the methodology used to estimate the generated traffic is considered conservative. The estimated traffic was split through the junctions in proportion to the existing traffic flows measured on the traffic counts.

The National Planning Application website was consulted to include proposed developments in the area that will affect the road network in the vicinity of the proposed development.

The junctions were tested using *PICADY* (Priority Intersection Capacity and Delay) software for the base year (2025), the year of opening (assumed 2027), 5-year, and 15-year future design scenarios. Appropriate TII Traffic Growth Factors for Co. Galway were applied to the traffic flows to ensure that the future growth of the road network has been considered in the analysis.



Upon building the traffic model for the proposed development, junction capacity analysis was carried out on the existing junctions to assess the potential worst-case scenarios associated with the development.

Based on the findings of the traffic analysis and the estimated trip generation associated with the proposed residential development, it can be concluded that the development is anticipated to generate a low volume of additional traffic. The results of the junction analysis confirm that the surrounding road network has sufficient capacity to accommodate the projected traffic without adverse impacts. All assessed junctions are expected to operate well below their theoretical capacity, with no operational issues anticipated during peak periods.

1 Introduction

The purpose of this Traffic and Transport Assessment (TTA) is to address the traffic and transport related issues that may arise in relation to the proposed affordable housing development at Raheen, Athenry, Co. Galway. This document will form part of the planning application.

This report will follow the principles set out in the TII Publication PE-PDV-02045 'Traffic and Transport Assessment Guidelines' and the Galway County Development Plan 2022 – 2028 and will assess the impact the proposed development, and the associated traffic flows, will have on the public road network in the vicinity of the site.

1.1 Objectives of this TTA

The objective of this report is to assess the impact the proposed residential development will have on the surrounding road network, with the assessment focusing primarily on 2No. key junctions in the vicinity of the site.

The selected junctions are illustrated in **Figure 1.1** below.




Figure 1.1: Locations of Junctions Analysed shown in red (Source: OpenStreetMap, 2025)

In summary, the objectives of this report are to assess:

- The prevailing traffic conditions on the public road network in the vicinity of the proposed

development;

- The potential effect on the surrounding road network due to the anticipated traffic generated by the proposed development;
- Review of the committed developments adjacent to the proposed development;
- The pedestrian, cyclist, and public transport connectivity in the vicinity of the site; and
- The proposed parking requirements for the development.

1.2 Methodology

The TII Publication PE-PDV-02045 sets out the methodology to be followed in any given TTA. The methodology that will be used in this assessment follows the guidelines set in this document and can be outlined as follows:

- 12-hour classified automatic junction turning counts (JTC) were carried out on Tuesday 11th March 2025 at the junctions mentioned above by a third-party company named IDASO. The traffic counts encompass all movements along the junctions and are assumed to be representative of a normal weekday.
- Traffic distribution splits on the public road network could be determined from the traffic counts and applied to the anticipated future generated traffic as a result of the proposed development.
- The predicted traffic to be generated by the proposed development was obtained using TRICS (Trip Rate Information Computer System) traffic generation software for similar developments, to ensure a worst-case scenario was incorporated into the assessment.
- The effect caused by the proposed development in the neighbouring junctions could be calculated using the existing traffic flows and the expected additional traffic to be generated by the development.
- The effect the generated traffic will have on the road network was assessed against the TII threshold and it was found that for the junctions under assessment, the threshold of 5% increase in traffic, where congestion is observed, is not exceeded. Nevertheless, a TTA was proactively prepared to demonstrate the limited impact of the proposed development on the surrounding road network and to support a robust planning submission.
- The junctions were modelled using the Transport Research Laboratory (TRL) software *Junctions 11* (PICADY) for future design years using Central Sensitivity Growth Factors for Co. Galway to obtain the existing and proposed traffic profiles at the junctions analysed for the year of opening, 5-years, and 15 years after the completion of the proposed development.
- Parking requirements were assessed against standards set in the Galway County Development Plan 2022 – 2028.

2 The Proposed Development

2.1 Development Site Location

The proposed development site is located approximately 650m west of Athenry town centre and is currently a greenfield site. It is bordered to the North by the existing Gort Mhaoilir housing, and to the West by the Willow Estate. The Athenry Primary Care Centre and Pharmacy are located to the Northeast of the site.

The proposed site is well connected to the local road network, with nearby access to the R347 (Tuam Road), L-3105 and L-3103. The site is situated at the intersection of the Gort Mhaoilir Road (Raheen Woods Road) and the L-3103. It lies south of the existing Gort Mhaoilir housing estate. Its perimeter is defined by various features: block walls mark the boundary with neighbouring residential gardens to the north-east and north-west, while the south-east and south-west edges are characterised by palisade fencing, hedgerows, and a low natural stone wall.

Figure 2.1 below shows the environs of the proposed residential development.



Figure 2.1 Site location map and surroundings (Source: Google Earth, 2025. Notes by ORS)

2.2 Land Use

Athenry is Galway's sixth largest town. It serves a rural hinterland as a market town and service centre. It is identified in the Galway Council Development Plan (GCDP) 2022 - 2028 as an Area of Strategic Potential (Level 3) - "Large economically active service centre that provides

employment for the surrounding areas". Athenry can develop further and accommodate enterprises, e.g. Economic Corridor from Oranmore to Athenry, which "*must be developed/promoted and serviced to high international standards to attract further Foreign Direct Investment and indigenous industries/ businesses, building on the existing strategic location and infrastructure*".

The GCDP 2022 – 2028 Policy Objective is "*to support the development of Athenry as a town of Strategic Potential, as outlined in the Core Strategy and Settlement Strategy, in order to sustain a strong, vibrant urban centre which will act as an important driver for the local economy, reduce travel demand and support a large rural hinterland, while providing a complementary role to the Key Towns and Metropolitan Area Strategic Plan and the smaller towns and villages in the County*".

The development strategy is to strengthen the urban fabric of the county, with an emphasis on building critical mass in the towns, including the Strategic Potential Town of Athenry. "*The focus is on achieving the consolidated growth of the settlements, with a significantly high proportion of housing in the existing built-up footprints of each settlement, strengthening town centres to their full potential by utilising under-utilised land and buildings and developing the settlements in a sequential manner to develop the Strategic Potential Town to grow to a sustainable level*".

Policy DS1 - Development Strategy: "*It is the overarching policy of the Council to support and facilitate the sustainable development of Athenry in line with the preferred Development Strategy Option 4 - Managed Phased Development which allows Athenry to develop in a manner that maintains and enhances the quality of life of local communities, promotes opportunities for economic development, sustainable transport options and social integration, protects the cultural, built and natural heritage and environment and complies with relevant statutory requirements.*" The preferred development strategy option is considered to be the most appropriate option for securing the managed growth of Athenry, while retaining its medieval fabric and taking account of environmental and other planning and sustainable development considerations over the Plan period.

The Plan's strategic vision for Athenry envisions that the town "*will be a sustainable, self-sufficient, vibrant and socially inclusive key town, which protects and enhances its attractive medieval character while becoming an innovative growth centre within the Strategic Economic Corridor, supporting an educated workforce, providing a range of services/amenities and with a high quality of life for the local community*". This will be delivered through a managed and phased development strategy on appropriately zoned and serviced lands in a manner that is balanced and sustainable for Athenry and the environs that it serves.

The site is currently zoned as 'R – Residential Phase 1', as shown in **Figure 2.2** overleaf.




Figure 2.2: Land Use Zoning Objectives Map (Source: Athenry Local Area Plan 2024 - 2030)

2.3 Description of the Proposed Development

This development involves the construction of 28No. two-story residential units on a 1.0815-hectare undeveloped plot. The homes consist of 18No. three-bedroom semi-detached houses and 10No. two-bedroom terraced houses. Access will be provided via the Raheen Woods Road (Gort Mhaoilir Road).

The project also encompasses all required supporting infrastructure, including new roads, paths, and public open space. Parking facilities will provide 56No. car spaces, including 7No. designated accessible spaces, while 4No. spaces will support EV charging. Additionally, 14No. spaces for bicycles will be provided for visitors. The site is generally flat and is situated at the corner of the Raheen Woods Road (Gort Mhaoilir Road) and the L-3103, just south of the existing Gort Mhaoilir housing estate. The current site boundaries are defined by various walls, fencing, and hedgerows, and an existing waste-water treatment tank in the southern corner will be decommissioned and removed.

The proposed site layout is illustrated in **Figure 2.3** overleaf.



Figure 2.3: Proposed Ground Floor Plan. Cropped (Source: Paul Keogh Architects)

2.4 Accessibility and Parking

The layout of the Athenry town comprises of a relatively compact town centre with a main administrative focus around Market Square and a commercial core centred within Church Street, Old Church Street, Cross Street and North Gate Street. The more recent pattern of development in the town has consisted of residential development in the environs complemented by commercial development in the form of neighbourhood centres and retail parks.

Objective 1 of the Athenry Local Transport Plan is Accessibility & Social Inclusion: *Support and implement transport measures which reduce car dependency and improve access to local services by sustainable modes.*

In reference to the town centre, Galway County Council has a vision for “*a pleasant place for people to live, work and visit*” which must be accessible to all, including those with impaired mobility. Sustainable modes of transport will be prioritised in the town centre, with good connectivity to the nearby residential and employment locations. The rebalancing of the transport system and space allocation reflects the need for a greater emphasis placed on infrastructure in relation to walking, using buggies, wheelchairs or cycling.

Policy **ILUTP** specifically encourages ‘*transition towards sustainable and low carbon transport modes, through the promotion of alternative modes of transport, and ‘walkable communities’ and Active Travel, together with promotion of compact urban forms close to public transport corridors to encourage more sustainable patterns of movement*’.

The main car parks in Athenry are located around the town centre, at Church Street, Tuam Road, North Gate Street and at the train station, see **Figure 2.4**. Additional public parking facilities are available on-street on many streets within the town centre and in Market Square.



Figure 2.4: Public Car Parks in Athenry (Source: Google Maps, 2025)

2.4.1 Site Access

The proposed development, situated within an established residential area, has direct access to the local road network. The site will be served by one new entrance connecting to Raheen Woods Road (Gort Mhaoilir Road) and the nearby L-3103 and L-3105 local roads, which provide direct routes to Athenry town centre approximately 650m to the east. The site benefits from proximity to local amenities including the Athenry Primary Care Centre and Pharmacy.

Vehicular access to the site will be provided via a priority T-junction to the Raheen Woods Road (Gort Mhaoilir Road), at the location shown in **Figure 2.5** overleaf.

While the site currently has a direct access via the Raheen Woods Road (Gort Mhaoilir Road), as shown in **Figure 2.6**, this existing access point does not align with the proposed location for the future development junction.



Figure 2.5: Proposed Vehicular Access Location shown in red (Source: <https://satellites.pro/>)



Figure 2.6: Currently site access located in the Gort Mhaoilir Road (Source: Google Earth, Street View, May 2025)

The proposed access point mentioned above is currently serviced by pedestrian footpaths running along the Raheen Woods Road (Gort Mhaoilir Road). There are no other proposed pedestrian permeability points connecting the proposed development with the existing Gort Mhaoilir Estate.

Please refer to **Figure 2.7** overleaf for the proposed pedestrian access.



Figure 2.7: Proposed Pedestrian Access Locations shown in red. Cropped (Source: Paul Keogh Architects)

2.4.2 Internal Road Layout

The main function of the internal road network is to provide a safe and efficient parking and circulatory system that reduces the potential for conflicting movement. The layout prioritises place function, pedestrian permeability, and cyclist safety while ensuring appropriate vehicular access for residents, visitors, and service vehicles. This system is designed to comfortably accommodate the anticipated volume of arrivals and departures without presenting a safety risk and not negatively affecting the road network that it connects to.

The site layout plan (**Figure 2.3**) illustrates a well-designed internal road network that will integrate with the existing road infrastructure. The layout includes:

- A self-regulating local street network serving residential units only, providing efficient two-way circulation and supporting the Design Manual for Urban Roads and Streets (DMURS) objectives by discouraging through-traffic, reducing vehicle speeds, and enhancing overall safety.
- Primary vehicular access is provided via a priority T-junction located on the southern boundary along Raheen Woods Road (Gort Mhaoilir Road). This junction interfaces with a two-way internal access road, facilitating both inbound and outbound movements.
- Appropriate sight lines at the junctions to ensure traffic safety.
- Dedicated pedestrian infrastructure throughout the development.

Resident and visitor parking spaces are distributed along the internal street and in small clusters to minimise visual impact and reduce hard surfacing. EV-charging spaces and accessible parking bays are located centrally for ease of use. Parking courts are designed to minimise turning movements on the street and reinforce a slow-speed environment while maintaining adequate manoeuvring space.

A future pedestrian access point is strategically located to allow ease of movement for residents, promote walkability, and provide potential links to the town centre. There will be several pedestrian crossings located at strategic positions which will enhance pedestrian safety

within the development.

Street trees and verge planting are used to reinforce the spatial structure of the internal streets, create visual narrowing, and support the place-based approach advocated by DMURS. The presence of landscaped spaces and green corridors further enhances walkability and contributes to a high-quality public realm.

2.4.3 Pedestrian and Cyclist Connectivity

A continuous footpath network is provided on both sides of the primary internal street, as illustrated in **Figure 2.3**, ensuring step-free pedestrian access throughout the development. Footpaths are designed to DMURS minimum widths and are separated from the carriageway by landscaped verges and tree planting, enhancing the pedestrian environment and improving passive surveillance.

The road layout is supplemented by direct pedestrian links through green spaces, connecting residential blocks to shared amenity areas and perimeter walking routes. These connections align with DMURS principles of permeability and modal priority, providing attractive alternatives to vehicle trips within the development.

The internal streets operate at low speeds consistent with a shared-street cycling environment, as recommended by DMURS for residential areas. Cyclists are safely accommodated on-carriageway due to the calmed traffic environment, short block lengths, and the absence of through-traffic. Bicycle parking is provided within residential units and designated communal areas.

According to the Athenry Local Transport Plan 2024-2030 document, the quality of pedestrian infrastructure in the town is *“quite varied...Outside of main roads and streets, the residential areas north of the railway line suffer from poor permeability in places, particularly in an east-west direction... This can significantly increase walking distances to key services for residents in the town”*.

The proposed development is situated among residential estates and can be accessed via the existing Raheen Woods Road (Gort Mhaoilir Road) and associated footpaths leading to the L-3105 or L-3103 Roads and onwards to the town centre. The site is situated within walking distance from the local amenities and educational developments, including:

- 200m Northwest of the Athenry Primary Care Centre & Pharmacy,
- 750m West of GRET B (Galway and Roscommon Education and Training Board),
- 750m from Athenry Rail Station,
- 700m due East from Kenny Park, the local GAA Stadium,
- 1000m South of the 418 Bus Stop (Athenry – Galway Bus Service),
- 1000m from the Athenry Gaelscoil Riada,
- 900m North of the Athenry Shopping Centre,
- 300m Northeast of Presentation College.

The footpaths along the Raheen Woods Road (Gort Mhaoilir Road) into Athenry town are of decent quality equipped with dropped kerbs, well-maintained surfacing and sufficient width. These footpaths lead to Station Road, where they continue into the town centre. The majority of the junctions in the area provide good pedestrian crossing facilities in the form of dropped

kerbs and tactile paving.

The nearest pedestrian crossing and tactile paving on Raheen Woods Road (Gort Mhaoilir Road) is located approximately 30m from the development entrance and provides access to the local road L-3103, leading further to Presentation College. A second pedestrian crossing is located approximately 500m to the northeast of the entrance at the junction between Raheen Woods Road (Gort Mhaoilir Road) and the L-3105. This existing pedestrian crossing is shown in **Figure 2.8** below.



Figure 2.8: Pedestrian Crossing on Raheen Woods Road (Gort Mhaoilir Road), View from Southwest (Source: Google Earth)

There is currently no dedicated cycling infrastructure in the nearby vicinity of the proposed development. At present, cyclists must utilise existing roadways alongside motorists to reach the proposed site via Raheen Woods Road (Gort Mhaoilir Road).

2.4.4 Service Arrangements

The internal road network is primarily designed to accommodate private cars which is the main vehicle type to use the residential housing development. However, adequate provision to facilitate the circulation and turning movements of emergency vehicles and bin collection vehicles should be made. An Autotrack analysis has not been carried out to confirm that emergency vehicles, such as fire trucks, will be able to manoeuvre the site in a safe and efficient manner.

2.4.5 Vehicle Parking

Chapter 15 of the Galway County Development Plan 2022 - 2028 was consulted in order to obtain the car parking standards for the development. The document states in Table 15.5, as summarised in **Table 2.1** overleaf, the maximum requirements for developments such as the proposed residential development.

It should be noted that a flexible approach to these standards may be applied where such a case is substantiated, there is no traffic safety issue, and it is clearly demonstrated to the Planning Authority in the interest of proper planning and development, that the standard should be adjusted to facilitate the site-specific context.

Table 2.1 – Car Park Standards as per Galway CDP 2022 – 2028

Development	Car Parking Standard	No. of Units	Parking Spaces (Min. as per CPD)	Parking Spaces (Proposed)
Residential: Dwellings (1-3 bedrooms)	1.5 Spaces Per Dwelling	28	42	56

The proposed total number of car parking spaces is 56No., which is above the minimum requirement standard as presented in the Development Plan.

The Galway County Development Plan 2022 – 2028 advises that car parking provision shall be provided for the disabled and mobility-impaired in all car-parking developments and should be located in the most convenient locations for ease of uses, with the minimum provision being 4No. spaces within 50-75 spaces. The proposal includes 3No. standard accessible parking spaces and 4No. accessible spaces combined with EV charging infrastructure, which is above the minimum Development Plan requirement of 4No. spaces.

Mention is given to electric vehicle charging points. The Galway County Development Plan 2022 - 2028 specifies in DM Standard 31(g) that all developments should provide facilities for the charging of battery-operated cars at a rate of up to 20% of the total car parking spaces. A total of 56No. car parking spaces are being provided as part of this development, therefore minimum of 11No. car parking spaces should be provided with EV charging points in accordance with the requirement.

2.4.6 Cycle Storage

Providing high-quality, safe, secure, and convenient bicycle parking is crucial to support sustainable transportation options such as cycling, walking, and public transport. The Galway County Development Plan 2022 - 2028 recognises the importance of secure cycle parking facilities to promote sustainable transport, mentioning that bicycle parking shall be located in a prominent position within 30m of the facility served and should have a shelter and be signposted.

According to the Development Plan, in Housing Developments 1No. private secure bicycle space should be provided per 1No. bed space, with minimum 1No. visitor bicycle space per 2No. housing units.

Resident parking will be accommodated within each individual property.

At present, the plans propose to include 14No. visitor spaces at the communal open space, as shown in **Figure 2.9** overleaf. This meets the minimum requirement of No. spaces for visitors.



Figure 2.9: Proposed visitor bicycle parking areas outlined in red (Source: Paul Keogh Architects)

3 Traffic Conditions

3.1 Existing Road Network

Athenry town is strategically located 22km east of Galway Gateway within the Eastern Strategic Corridor and is accessible by rail and motorway networks. The primary road serving Athenry is the M6, which bypasses the town and provides direct connections to Galway and Dublin. Approximately 3 km west of Athenry, the M6/M17/M18 interchange facilitates further connectivity to Ennis, Limerick, Tuam, and beyond to Claremorris and Sligo. Please refer to **Figure 3.1** below.




Figure 3.1: Road Network in Co. Galway

Access to Athenry's local road network from the M6 is via Junction 17, which connects to the town through the R348, as shown in **Figure 3.2** overleaf. In addition to this national route, two main regional roads serve the town: the R347, which connects Athenry to Tuam and Craughwell, and the R348, which links to Oranmore and Ballinasloe, acting as key arterial routes. Additionally, the L-3107 towards Monivea and the L-3112 from the east provide further access to the town.

Therefore, the proposed development at Gort Mhaoilir is strategically located with excellent access to Ireland's national road network. The site is approximately 3km from Junction 17 of the M6 motorway, which provides a key east-west transportation corridor connecting Galway City to Dublin. This proximity to the M6 offers residents convenient access to Ireland's wider motorway network.

Distance to Key Towns and Cities:

The development's location provides convenient access to several key urban centres:

- Athenry Town Center: 650m (approximately 8-minute walk);
- Galway City: 24km (approximately 25-minute drive via M6);
- Dublin: 185km (approximately 2-hour drive via M6);
- Ballinasloe: 35km (approximately 30-minute drive via M6);

- Oranmore: 13km (approximately 15-minute drive via R348); and
- Loughrea: 20km (approximately 20-minute drive via R446).




Figure 3.2: Athenry town. Access to Regional Roads and Motorway (Source: Galway County Development Plan 2022 - 2028)

The L-3103 local road provides essential local access to the Gort Mhaoilir development and surrounding residential areas, serving as a key connector between neighbourhoods and Athenry town centre. The road is configured as a two-lane, two-way carriageway with one lane in each direction, featuring a well-maintained asphalt surface suitable for local traffic volumes. The posted speed limit is 50kmph, appropriate for its residential setting and proximity to homes and community facilities. This moderate speed limit enhances safety for all road users, particularly at residential access points and pedestrian crossing locations.

The L-3103 features continuous concrete footpaths on both sides. Street lighting columns are positioned at regular intervals along the route, providing adequate illumination for both vehicular traffic and pedestrians during evening hours. Road markings include centre lines and junction indicators. The road's geometry includes gentle curves and good visibility, allowing for safe navigation throughout its length while naturally controlling vehicle speeds.

The L-3105 local road serves as another vital access route for the proposed development, connecting residential areas to community facilities and the wider road network. It is designed as a standard two-lane, two-way carriageway with single lanes in each direction, constructed with a durable asphalt surface capable of accommodating local traffic flows. The road operates under a 50kmph speed limit, consistent with its residential character and supporting safe interaction between vehicles, pedestrians and cyclists in this community setting.

Pedestrian facilities along the L-3105 include well-maintained footpaths that provide continuous routes along both sides of the carriageway, with dropped kerbs at crossing points to facilitate accessibility for all users. Street lighting is consistently provided along the route, mounted on

columns at appropriate intervals to ensure visibility and safety during darker hours. Clear road markings delineate traffic lanes and junction approaches, while boundary features such as stone walls at estate entrances contribute to the road's character and help define the streetscape. The road's design incorporates appropriate sightlines at junctions and accesses, ensuring safe movement for vehicles entering and exiting connecting streets and properties.

Gort Mhaoilir Estate Road is a quieter residential road network within the estate, of an approximate kerb to kerb width of 5m, which accommodates two-way traffic at reduced speeds appropriate for a residential environment (30kmph). Street lighting is provided within the Gort Mhaoilir Estate. Gort Mhaoilir Estate Road is also equipped with footpaths on at least one side, providing pedestrian access and connectivity to Raheen Woods Road and local facilities.

Traffic arriving or departing from the site will utilise the under-assessment priority junctions, one to the northeast and another one to the southwest, shown in **Figure 1.1** above.

The accessed junctions and roads included in this assessment are existing roads already in active usage, as such, their condition and suitability for purpose are not subject to assessment as part of this report. For visual detail of the junctions tested as part of this assessment, please refer to **Figure 3.3**, **Figure 3.4** and **Figure 3.5** below.



Figure 3.3: Gort Mhaoilir Estate Road/L-3103 Junction. Approach from south (Source: Google Earth, May 2025)



Figure 3.4: Gort Mhaoilir Estate Road/L-3103 Junction. Approach from minor road. Stop sign and road markings in place (Source: Google Earth, May 2025)



Figure 3.5: Gort Mhaoilir Estate Road/L-3105 Junction. Approach from North (Source: Google Earth, May 2025)

3.2 Pedestrian and Cyclist Connectivity

The proposed residential development is located to the northwest of the Athenry town centre and is well connected to the wider environs with footpaths generally in good condition. Due to the size of the town, it is expected that a 15-minute walk from the development can reach a significant portion of the town. Generally, the existing pedestrian infrastructure in the vicinity of the site includes:

- Continuous concrete footpaths along one side of the Gort Mhaoilir (Raheen Woods) Road, as shown in **Figure 3.6**, extending to both sides on the approach to the junction with the L-3105 local road, as shown in **Figure 3.7**;
- Continuous concrete footpaths along one side in the Gort Mhaoilir (Raheen Woods) Road connecting to the L-3103 local road, as shown in **Figure 3.8**;
- Dropped kerbs at junctions facilitating accessibility for mobility-impaired users and those with strollers;
- Street lighting providing adequate illumination for pedestrian safety during evening hours;
- Grass verges along sections of the route creating separation between pedestrians and vehicular traffic.



Figure 3.6: Pedestrian Infrastructure on Gort Mhaoilir (Raheen Woods) Road approaching the Development Access. View to North (Source: Google Earth, May 2025)



Figure 3.7: Pedestrian Infrastructure on Gort Mhaoilir (Raheen Woods) Road approaching the Junction (Source: Google Earth, May 2025)



Figure 3.8: Pedestrian Infrastructure on Gort Mhaoilir (Raheen Woods) Road approaching the Development Access. View to South (Source: Google Earth, May 2025)

The site's proximity to key local destinations enhances its pedestrian connectivity:

- Athenry Primary Care Centre and Pharmacy: 220 m (3 minute walk);
- Athenry Town Centre and commercial services: 650m (8-10 minute walk);
- Local schools: Within 700-1.5km (10-20 minute walk);
- Athenry Railway Station: Approximately 700m (10 minute walk);
- Presentation College: 440m (6 minute walk).

Proposed Pedestrian Enhancements

The development proposal includes several enhancements to the local pedestrian network:

- New footpaths throughout the development connecting to the existing external network;
- Pedestrian access point to maintain permeability and connectivity;

- Dedicated pedestrian crossings at key internal locations; and
- Landscaped pedestrian zones creating a pleasant walking environment.

Athenry currently has limited dedicated cycling infrastructure, which is typical of many smaller Irish towns. Generally, it is expected that a 15-minute cycle from the site can reach all locations of the town. Currently, the road network is not especially cycle friendly and there are very few dedicated cycle ways or cycling facilities within the town, and therefore cyclists must utilise existing roadways alongside motorists to reach the proposed site via either the L-3103 or the L-3105 Road.

The map shown in **Figure 3.9** illustrates locations of cycleways in the vicinity of the site.

According to the Athenry Local Transport Plan 2024-2030, *‘there are grade separated cycle tracks on the completed sections of the Athenry Relief Road to the north of the town and along the newly completed section of road at Presentation College, however there are no cycle tracks along the section at the school gate. These cycle tracks have a version of a cycle friendly roundabout at junctions, featuring shared space, but no raised crossings resulting in priority for vehicular traffic and reduced safety for cyclists and pedestrians. In addition, there is a new section of one-way cycle track along the R348 between Clarin College and the Baunmore Roundabout, stopping short of the roundabout itself’.*




Figure 3.9: Existing Cycle Infrastructure in Athenry (Source: Athenry LTP 2024 - 2030)

Proposed Cycling Enhancements

The development will contribute to improved cycling facilities through:

- Provision of secure and sheltered cycle parking facilities throughout the development; and

- Road design that naturally moderates vehicle speeds, creating safer environments for cyclists.

The site's location within easy walking and cycling distance of Athenry's amenities supports sustainable travel patterns and reduced car dependency, in line with national and local policy objectives. The relatively short distances to key destinations, combined with the proposed enhancements to pedestrian and cycling infrastructure, will encourage active travel modes for everyday journeys.

3.3 Public Transport Provision

Currently, there are no dedicated town bus services; the primary service is a commuter route to Galway City operated by Farrells, which primarily runs during the AM and PM peak hours (see **Table 3.1** below).

Also, a return route to Loughrea operated by Local Link Galway/Bealach na Gallaimhe Teo runs on Thursdays. It departs at 09:30 and returns at 13:30, operating on a door-to-door basis with advance booking required.

Table 3.1 – Bus Routes Serving Athenry			
Route No.	Route	Operator	Number of Weekday Services
418	Athenry - Galway	Philip Farrell	7
(Door to Door Service)	Athenry - Loughrea	Local Link	1

There is no formal bus stop infrastructure provided in Athenry; however, the Route 418 operates at 3No. stops shown in **Figure 3.10** overleaf:

1. Londis, Tuam Road,
2. Arch Car Park,
3. Athenry Shopping Centre.

These stopping points currently lack essential facilities such as bus stop poles, shelters, seating, tactile paving, timetable displays, or real-time passenger information.

Additionally, the School Transport Scheme operated by Bus Éireann on behalf of the Department of Education provides transport to local educational institutions for students who live remote from their nearest school.




Figure 3.10: Atheryn Bus Network (Source: Atheryn Local Transport Plan 2024-2030)

Atheryn benefits from an essential regional and intercity connectivity by rail services, as shown in **Figure 3.11** below.

Atheryn Rail Station, situated on the Western Rail Corridor, is located in a 10-minute walk (approx. 750m) to the northeast of the proposed site, on Church Street, in the town centre. It provides accessibility to the Dublin-Galway and Galway-Limerick lines with onward connections to Cork and Belfast.




Figure 3.11: Rail Services to/from Atheryn (shown in red) (Source: www.irishrail.ie)

Table 3.2 overleaf presents an overview of the Atheryn Train Station Services to/ from Atheryn.

Table 3.2 – Athenry Daily Rail Services (Source: Athenry LTP 2024-2030)

Origin	Destination	Number of Weekday Services	Number of Weekend Services
Athenry	Galway	17	15
Galway	Athenry	19	15
Limerick	Athenry	9	9
Athenry	Limerick	8	8
Athenry	Dublin	10	9
Dublin	Athenry	9	8

3.4 Proposed Transport Infrastructure

For Athenry, several transport infrastructure proposals are under consideration, and some are already in planning stages, especially in line with Ireland's national goals for sustainable travel. Improvements in cycling and public transport infrastructure, enhancing connectivity and promoting sustainable travel, are in line with Athenry Local Area Plan Objectives **ASP 50**, **ASP 51** and **ASP 52**.

The Galway County Transport and Planning Study (GCTPS) makes a number of recommendations for improvement and alteration of travel patterns within the County, to conform to the policy objectives of both the GCTPS and the County Development Plan 2022–2028. As forecasted in the GCTPS, internal trips within Athenry will increase by 8% between 2022-2028, reflecting forecast population growth within and in the vicinity of the town. The following measures, identified as part of the Travel Corridor assessments, are included in Table 30 (Appendix 3 of the document), as shown in **Figure 3.12** below.

These measures have been promoted to support growth within Athenry and the wider settlement area, favouring sustainable mode shift and promotion in uptake of active travel, with additional safety-led, congestion and demand management schemes identified as part of this corridor assessment.

Table 30. Proposed Physical Measures – Athenry	
CATEGORY	DESCRIPTION
Public Transport	Dual Railing (Athenry to Galway)
Multi-Modal	Athenry Multi-Modal Hub
Active Travel	Galway – Athlone Cycleway

Figure 3.12: Proposed Physical Measures in Athenry (Source: Galway County Transport and Planning Study)

The Athenry Local Transport Plan “will build upon key recommendations within the GCDP 2022 – 2028 and GCTPS to deliver a framework of local measures to support modal shift for internal journeys and promote connectivity to public transport services through the provision of a multi-

modal hub to allow for seamless connections and last mile journeys. LTP will also consider key connections within the town and develop infrastructure to improve these linkages to existing amenities and facilities and consider improvements to support the identification of key corridor movements from Athenry identified within the GCTPS including connections to Galway, Tuam and Ballinasloe”.

3.4.1 Proposed Public Transport

The Connecting Ireland Rural Mobility Plan is a significant national public transport initiative developed by the National Transport Authority (NTA). Its goal is to enhance connectivity, particularly for those living outside major cities and towns. While new or enhanced bus routes directly serving Athenry are not present in the available summary, the plan emphasises the NTA's commitment to improving rural bus services. This includes introducing new routes and enhancing existing ones to better serve rural communities.

Figure 3.13 below shows the envisaged Connecting Ireland network for County Galway.




Figure 3.13: Co. Galway Proposed Public Transport Network (Source: NTA)

3.4.2 Proposed Rail Service

The Connecting Ireland Rural Mobility Plan highlights the importance of the existing train route that connects Dublin to Galway, with stops including Athenry and Oranmore. Plans are

underway to double-track the railway line between Galway and Athenry. This initiative is part of broader efforts to increase train frequency and reduce journey times, aligning with Galway's designation as a metropolitan area in the National Planning Framework.

The reopening of Oranmore station has reduced traffic into Galway City which has obvious benefits in terms of lowering traffic congestion, improving air quality and reducing harmful emissions. The redevelopment of Galway train station will involve work on five platforms as well as a 10-minute commuter train service between Athenry and Oranmore. Therefore, Iarnród Éireann has announced plans to enhance commuter rail services in Galway, including Athenry.

The All-Island Rail Review, put together by Arup on behalf of the Republic of Ireland's Department of Transport, shows the proposed improvements in the connections between the major cities and towns, see **Figure 3.14** below.




Figure 3.14: Proposed Irish Rail Network (Source: All-Island Rail Review)

3.4.3 Active Travel

A relative high majority of internal trips in Athenry are currently made by private vehicle (60%), and the proposed measures seek to encourage shorter journeys to be made by walking and cycling.

One of the main proposals for the area is a 1.3-km Active Travel link connecting the northern and southern parts of the railway, thereby improving access to the town centre for residents of over 1,000 homes. The scheme includes the development of cycle facilities, widened footpaths, traffic calming measures, and new and upgraded pedestrian crossings, all aimed at enhancing safety and comfort for pedestrians and cyclists. It will cover the road network from Athenry Church to the Tuam Road, via Station Road. This proposal is a part of the broader Active Travel scheme for Athenry designed by SYSTRA Ltd. for Galway County Council.

Additionally, the Athenry Local Transport Plan outlines plans for new or improved walking and cycling infrastructure on routes such as the Tuam Road, Raheen Road, Raheen Woods Road,

R348, and the River Clarin Walk. These improvements include upgrading the pedestrian footpaths, designing and constructing a dedicated cycle track, upgrading key junctions, and installing new crossing points to enhance connectivity and safety for vulnerable road users.

The National Transport Authority's (NTA) CycleConnects initiative aims to establish a comprehensive cycling network across Ireland, enhancing sustainable travel by providing safe, accessible, and convenient cycling routes. The CycleConnects plan encompasses urban cycle networks for towns with populations over 5,000 and includes connections between larger towns, villages and settlements. It also integrates existing and planned cycle routes such as greenways and blueways. As part of this initiative, inter-urban routes are proposed for Athenry, as demonstrated in **Figure 3.15** below.




Figure 3.15: Proposed Cycle Network for Athenry region (Source: NTA)

The Athenry to Oranmore Cycleway is part of the cross-country Dublin to Galway Greenway, which is largely built between Athlone and Dublin. By linking these major cycling routes, the Athenry to Oranmore Cycleway would enhance regional and national cycling networks, offering cyclists extended and varied routes across the country.

3.4.4 Proposed Road Improvements

The western section of the **Athenry Northern Ring Road** is a planned part of the wider Athenry ring road scheme, intended to improve traffic flow around the town rather than through its centre. The project is part of the Athenry Local Area Plan (2024-2030) and is seen as necessary infrastructure to support housing growth, economic development, and job creation.

It involves constructing about 0.9-1 km of new local road west of the existing centre of Athenry, in the Ballygarraun North and South areas. The works include a new roundabout, pedestrian and cycle facilities, drainage, lighting, landscaping, and other associated infrastructure.

The project links to the existing ring road and the Raheen Road (L-3103), reorganising how traffic is routed around the town.

The design also supports active travel (walking/cycling) with dedicated paths alongside the road.

Construction of the western section is underway (contracts signed in June 2025) with the aim of completion by late 2025. One of the main aims is to take through-traffic out of Athenry town centre, easing congestion on local streets and improving journey times. The ring road will provide a clearer, safer route for traffic around the northern and western edges of the town, connecting residential areas with regional roads more efficiently.

An indicative area of the proposed works is shown in **Figure 3.16** below.




Figure 3.16: Western Section of the Athenry Northern Ring Road – Indicative Project Route (Source: Galway County Council)

3.5 Existing Traffic Flows

Automated Junction Turning Counts (JTC) have been undertaken at 2No. junctions on Tuesday 11th March 2025, shown in **Figure 3.17**, by a third-party company named IDASO. These key junctions are:

- JTC 1 – 3-arm Raheen Woods Road (Gort Mhaoilir Estate Road)/L-3103 Priority Junction;
- JTC 2 – 3-arm Raheen Woods Road (Gort Mhaoilir Estate Road)/L-3105 Priority Junction.

The traffic counts were carried out during a 12-hour period from 07:00 AM to 07:00 PM and encompass all movements at the junctions. The traffic counts cover movements of pedal cycles, cars, taxis, buses, LGVs and HGVs and the final number of traffic is presented in **Passenger Car Unit (PCU)**.

PCU is the impact that a mode of transport has on traffic compared to a single car, e.g., a private car represents 1 PCU whereas an HGV represents 2.3 PCUs.




Figure 3.17: Assessed Junctions' Location (Source: OpenStreetMap, notes by ORS)

Based on the gathered data, it is evident that the morning peak period occurs between 08:15 and 09:15. The evening peak period, on the other hand varies. It takes place between 15:45 and 16:45 in JTC 1 and between 17:00 and 18:00 in JTC 2. **Table 3.3** displays the traffic flows observed in the junctions during the AM and PM periods.

During the modelling process, it's important to note that each junction was assessed individually for the network's peak hours according to JTC 1 flows, considering their peak time flows. Therefore, peak time volumes were incorporated in every junction, as this would represent the worst-case scenario.

Table 3.3 – March 2025 Traffic Flows (PCUs)		
Junction	Peak Time	
	AM	PM
JTC1	611.7	656.3
JTC2	485.6	507.6

Figure 3.18 overleaf shows the existing traffic flows in Junction 1.




Figure 3.18: March AM and PM 2025 Traffic Counts in JTC1

The traffic data for **JTC 1** indicates the turning movement percentages for the priority junction. From the analysis of the available data, it is evident that:

- Vehicles from the L-3103-northern arm are almost equally split during the AM peak:
 - 52% turn towards Raheen Woods – Arm A
 - 48% continue on the L-3103 (South) – Arm B
- Vehicles from Raheen Woods:
 - 66% turn right (North) – Arm C
 - 34% turn left (South) – Arm B
- Vehicles from the L-3103-southern arm:
 - 54% continue straight (Northbound) – Arm C
 - 46% go to Arm B (Raheen Woods) – Arm A

Traffic is relatively well distributed between all arms in the morning, but there's a slight preference for turning towards the L-3103-northern arm from both the Raheen Woods Road and Arm B.

During the PM peak:

- Vehicles from the L-3103-northern arm are almost equally split during the AM peak:
 - 46% turn towards Raheen Woods – Arm A
 - 54% continue on the L-3103 (South) – Arm B

- Vehicles from Raheen Woods:
 - 46% turn right (North) – Arm C
 - 54% turn left (South) – Arm B
- Vehicles from the L-3103-southern arm:
 - 69% continue straight (Northbound) – Arm C
 - 31% go to Arm B (Raheen Woods) – Arm A.

There is a slight shift compared to the AM peak:

- Arm C now has a very strong preference for turning north - 69%.
- Movements from the northern arm are almost evenly split between Raheen Woods and South (46% / 54%).
- Raheen Woods Road sends slightly more to the southern L-3103 arm (54%) than the arm to the North (46%).

From the traffic counts, the percentage of Heavy Goods Vehicles (HGVs) travelling along the estate road network during both the morning and evening peak periods was calculated. Overall, there is a low presence of HGVs at the junction, with the highest recorded percentage being 11% along the L-3103, during the evening peak (16No. out of 140No. vehicles on the northbound traffic).

Figure 3.19 below shows the existing traffic flows in Junction 2.




Figure 3.19: March AM and PM 2025 Traffic Counts in JTC2

JTC 2, the junction between Raheen Woods and the L-3105 Road, experiences slightly lower traffic levels. During the morning peak, the main flow is between Arm A and Arm B - this is the

critical movement.

There's a heavy two-way exchange between L-3105 South (A) and Raheen Woods (B):

- Morning traffic probably involves people moving from L-3105 South (A) into Raheen Woods (B).
- Also, there is a noticeable movement from Raheen Woods (B) toward L-3105 South (A) and the town centre.

Movements involving Arm C (L-3105 North) are lighter but still important:

- Vehicles from the North (C) mostly prefer to head south to Arm A (85.0 vehicles).

With regards to turning movements:

- From Arm A (L-3105 South):
 - 74% of vehicles turn towards Raheen Woods – Arm B
 - 26% of vehicles continue on the L-3105 – Arm C (North)
- From Arm B (Raheen Woods):
 - 79% turn towards the town centre – Arm A (South)
 - 21% turn towards Arm C (North)
- From Arm C (L-3105 North):
 - 57% turn continues on the L-3105 – Arm A (South)
 - 43% turn towards Raheen Woods – Arm B

During the PM peak:

- From Arm A (L-3105 South):
 - 59% of vehicles turn towards Raheen Woods – Arm B
 - 41% of vehicles continue on the L-3105 – Arm C (North)
- From Arm B (Raheen Woods):
 - 64% turn towards the town centre – Arm A (South)
 - 36% turn towards Arm C (North)
- From Arm C (L-3105 North):
 - 72% turn continues on the L-3105 – Arm A (South)
 - 28% turn towards Raheen Woods – Arm B

The dominant movement remains between Arm B and Arm A - especially from B to A in the PM.

- Arm B sees a significant outflow towards Arm A, indicating strong residential-to-arterial commuting patterns from Raheen Woods heading south to the town centre.
- Arm A distributes fairly well between turning left to B and right to C.
- Arm C mostly sends its vehicles southward to Arm A, maintaining a similar behaviour as in AM (but slightly stronger at 72% now).



From the traffic counts, the percentage of Heavy Goods Vehicles (HGVs) travelling along the road network during both the morning and evening peak periods was calculated. Overall, there is a low presence of HGVs at the junction, with the highest recorded percentage being 4% in the morning on the traffic movement from arm A to arm C direction, thus travelling away from the town.

3.6 Traffic Collisions Data in the Vicinity of the Site

Traffic data on collisions in the vicinity of the site could not be obtained as the Road Safety Authority website is currently in process of reviewing its road traffic collision data.

4 Trip Generation, Distribution and Impact on the Road Network Conclusion

In order to obtain a comparative trip rate for the proposed mixed-use development once operational, the Trip Rate Information Computer System (TRICS) database was consulted. The TRICS database contains traffic generation data for developments of a similar nature to the proposed development. TRICS was established in the UK and is a substantial source of validated empirical data which contains information on arrival and departure rates for a range of different types and sizes of development throughout Ireland.

4.1 Trip Generation

For the purposes of generating a robust representation of likely traffic profile for the future, a traffic generation profile based on the proposed layout was prepared. The proposed residential development was evaluated using the most relevant option available in TRICS. The trip rate data for the proposed development has been summarised in **Table 4.1**.

Table 4.1 – TRICS Output for the Residential Development						
TRICS 7.11.4						
Trip Rate Parameter: No. of Dwellings						
TRIP RATE for Land Use 03 - RESIDENTIAL/A - HOUSES PRIVATELY OWNED						
Calculation Factor: 1 DWELLS						
Count Type: TOTAL VEHICLES						
TIME RANGE	ARRIVALS			DEPARTURE		
	No. Days	Ave. Dwells	Trip Rate	No. Days	Ave. Dwells	Trip Rate
07:00-08:00	431	158	0.074	431	158	0.274
08:00-09:00	436	156	0.160	436	156	0.397
09:00-10:00	436	156	0.151	436	156	0.201
10:00-11:00	436	156	0.139	436	156	0.171
11:00-12:00	436	156	0.157	436	156	0.169
12:00-13:00	436	156	0.196	436	156	0.175
13:00-14:00	436	156	0.187	436	156	0.184
14:00-15:00	436	156	0.187	436	156	0.187
15:00-16:00	436	156	0.257	436	156	0.198
16:00-17:00	436	156	0.296	436	156	0.193
17:00-18:00	436	156	0.387	436	156	0.214
18:00-19:00	436	156	0.303	436	156	0.213
19:00-20:00	52	167	0.271	52	167	0.215
20:00-21:00	49	167	0.204	49	167	0.162
Daily Trips Rates:			2.969			2.953

The TRICS output is presented in a trip rate per unit. The unit reference is dependent on the development in question, such as per person, per house or unit area. In this case, the

multiplication factor to be applied to the unit rate is the number of dwellings which is 28No.

Morning peak occurs between 08:00 and 09:00 AM, with a total trip rate of 0.557 for the vehicles travelling to and from the site, and evening peak is between 17:00 and 18:00 with a total trip rate of 0.601. **Table 4.2** below shows the expected traffic generation profile once the proposed development is fully operational.

Table 4.2 – Typical Daily Generated Profile			
Time Range	Arrivals	Departures	Total
AM	4	11	15
PM	11	6	17

4.2 Cumulative Impact

As part of this Traffic Assessment, to assess the existing and expected traffic along the road network in the vicinity of the proposed development, the National Planning Application website was consulted to include all committed developments in the area. One large committed development was identified which will affect the R-3103/Raheen Woods junction analysed in the vicinity of the proposed development, to the southwest of the site, as shown in **Figure 4.1**, with vehicular access to the development from R348 via an existing roundabout, located on the northern boundary of the site, under planning reference number **23/61035**.




Figure 4.1: Planning application in the vicinity of the proposed development, to the Southwest (Source: myplan.ie)

The proposed development consists of the construction of a medical devices production facility. It is proposed to provide a 1.8-3.0 metres wide footpath/shared path along the northern side of Prospect Road, between its junction with L-3103 and the site access junction, as well as a signal-controlled crossing across the R348 Northern arm of Athenry Roundabout. Planning permission was granted on 27th November 2023.

As the development is not implemented yet, the traffic profile generated was not contained in the traffic counts carried out in March 2025. Therefore, this Traffic Assessment has included the expected traffic flows in the future year scenarios in the assessed junctions to ensure a robust assessment of the future conditions of the road network.

A Traffic and Transport Assessment (TTA) was available in the planning application records and was referenced to include the expected traffic generation from this development along the R-3103/Raheen Woods Road junction.

The above development is presented in **Table 4.3** below.

Table 4.3 – Committed Developments in the Vicinity of the Facility - Medical Device Manufacturing Facility				
Planning Reference	Decision Type	Description	Traffic generation on L-3103/Raheen Woods	
			AM	PM
PA 23/61035	Conditional	Construction of a 4no. storey medical device manufacturing facility providing warehousing, production areas, administration offices & restaurant (GIA: 40,226.6 m ²) and 4no. surface car park areas (500no. car parking spaces)	Total: 25 arrival: 21 departures: 4	Total: 25 arrival: 3 departures: 22

In addition to the abovementioned committed development, a Planning application has been submitted for the construction of a 2No. storey Industrial Warehousing Unit and Ancillary Office Space which will affect the R-3103/Raheen Woods junction under assessment, as shown in **Figure 4.1** above, with planning reference number **22/61321**.

A new site access junction is proposed onto Ballydavid South Road to allow access to the site. A Traffic and Transport Assessment (TTA) was available in the planning application records and was referenced to include the expected traffic generation from this development along the R-3103/Raheen Woods Road junction. Planning permission was granted on 02nd October 2023.

The above development is presented in **Table 4.4** and **Table 4.5** overleaf, showing the corresponding traffic generation on the L-3103/Raheen Woods and the L-3105/Raheen Woods junction, respectively.

Table 4.4 – Committed Developments in the Vicinity of the Facility - Industrial Warehousing Unit

Planning Reference	Decision Type	Description	Traffic generation on L-3103/Raheen Woods	
			AM	PM
PA 22/61321	Conditional	Construction of a 2no. storey industrial warehousing unit & ancillary office space (8826.3sqm.) and provision of 163no. car parking spaces	Total: 16 arrival: 6 departures: 10	Total: 19 arrival: 8 departures: 11

Table 4.5 – Committed Developments in the Vicinity of the Facility - Industrial Warehousing Unit

Planning Reference	Decision Type	Description	Traffic generation on L-3105/Raheen Woods	
			AM	PM
PA 22/61321	Conditional	Construction of a 2no. storey industrial warehousing unit & ancillary office space (8826.3sqm.) and provision of 163no. car parking spaces	Total: 4 arrival: 3 departures: 1	Total: 2 arrival: 2 departures: 0

It is important to note that the Traffic and Transport Assessment for the Industrial Warehousing Unit incorporate the cumulative impact of all committed developments within its study area. This includes developments that have secured planning approval but are not yet operational. Specifically, the assessment accounts for planning application Ref. **22/141**, which pertains to the construction of 128 No. residential units, inclusive of associated parking and ancillary site infrastructure at Ballygarraun South (The Willows Estate).

In addition, several planning permissions have been granted over the past five years for one-off houses and residential extensions within the wider area. Of particular relevance is a committed development located in close proximity to the subject site, granted under planning reference **19/1077**, which provides for the construction of 13No. residential units. The potential traffic impact of this development has been incorporated into the junction capacity analysis. For the purposes of estimating traffic generation along the L-3103 local road, trip rates derived from the TRICS database, outlined in **Table 4.1** above, were applied to the committed development.

The above development is presented in **Table 4.6** overleaf.

Table 4.6 – Committed Developments in the Vicinity of the Facility – Residential Development

Planning Reference	Decision Type	Description	Traffic generation on L-3103/Raheen Woods	
			AM	PM
PA 19/1077	Conditional	Construction of 13No. dwellings (the initial application included 17No. units, but 13No. were permitted)	Total: 7 arrival: 2 departures: 5	Total: 7 arrival: 4 departures: 3

To the southeast of the site, adjacent to the Athenry Primary Care Centre, a storage warehouse is proposed, as shown in **Figure 4.1** above, under planning reference number **23/60393**. Gross floor space of proposed works is 875 sqm. For the purposes of estimating traffic generation along the L-3103 and the L-3105 local roads, trip rates derived from the TRICS database, outlined in **Table 4.7** below, were applied to the committed development.

Table 4.7 – TRICS Output for the P.A. 23/60393

TRICS 7.11.4						
Trip Rate Parameter: Gross Floor Area						
TRIP RATE for Land Use 02 - EMPLOYMENT/E - WAREHOUSING (SELF STORAGE)						
Calculation Factor: 100 sqm						
Count Type: TOTAL VEHICLES						
TIME RANGE	ARRIVALS			DEPARTURE		
	No. Days	Ave. GFA	Trip Rate	No. Days	Ave. GFA	Trip Rate
07:00-08:00	7	3020	0.057	7	3020	0.028
08:00-09:00	7	3020	0.118	7	3020	0.076
09:00-10:00	7	3020	0.184	7	3020	0.147
10:00-11:00	7	3020	0.161	7	3020	0.17
11:00-12:00	7	3020	0.137	7	3020	0.114
12:00-13:00	7	3020	0.203	7	3020	0.203
13:00-14:00	7	3020	0.175	7	3020	0.142
14:00-15:00	7	3020	0.175	7	3020	0.199
15:00-16:00	7	3020	0.156	7	3020	0.18
16:00-17:00	7	3020	0.109	7	3020	0.118
17:00-18:00	7	3020	0.052	7	3020	0.128
18:00-19:00	7	3020	0.024	7	3020	0.043
Daily Trips Rates:			1.551			1.548

The TRICS output is presented in a trip rate per unit. The unit reference is dependent on the development in question, such as per person, per house or unit area. In this case, the multiplication factor to be applied to the unit rate is the GFA which is 875 sqm. **Table 4.8** shows

the expected traffic generation profile once the proposed development is fully operational.

Table 4.8 – Typical Daily Generated Profile by P.A. 23/60393

Time Range	Arrivals	Departures	Total
AM	2	1	3
PM	1	1	2

Furthermore, a planning application under planning reference number 25/60251, was identified to the north-east of the site for a proposed Large-Scale Residential Development of 133 no. residential units located off the L3105 Road, in the townland of Cullairbaun. A Traffic and Transport Assessment (TTA) was available in the planning application records and was referenced to include the expected traffic generation from this development along the R-3105/Raheen Woods Road junction. Planning permission was granted on 10th June 2025.

The trip generation, according to the TTA, will impact slightly the L-3105/Raheen Woods Road junction, with no traffic expected to turn to/from Raheen Woods Road. **Table 4.9** shows the expected traffic generation profile once the proposed development is fully operational, that will travel along the L-3105/Raheen Woods Road junction.

Table 4.9 – Typical Daily Generated Profile by P.A. 25/60251

Time Range	Arrivals	Departures	Total
AM	20	38	58
PM	44	26	70

In addition to the abovementioned committed developments, a Part 8 application has been submitted for the construction of 31No. dwelling units at Gort Mhaoilir, adjacent to the proposed site, which will affect both junctions under assessment, as shown in **Figure 4.1**. A Traffic and Transport Assessment (TTA) was created by ORS and was referenced to include the expected traffic generation from this development along the L-3103/Raheen Woods Road and L-3105/Raheen Woods Road junctions.

The above development expected traffic generation profile is presented in **Table 4.10**.

Table 4.10 – Typical Daily Generated Profile – Part 8 Application for a

Time Range	Arrivals	Departures	Total
AM	8	17	25
PM	14	9	23

4.3 Future Year Traffic Growth

Transport Infrastructure Ireland (TII) issues a range of forecasts: low growth, central growth, and high growth. The implementation of policies relating to the National Sustainable Mobility Policy will act as a deterrent to high growth in car-based travel. Low growth factors are however likely to be equally unrealistic at present, therefore, this assessment has used central growth factors, which were extracted from the TII Publication PE-PAG-02017 Project Appraisal

Guidelines for National Roads Unit 5.3 – Travel Demand Projections, published in October 2021, outlined in **Table 4.11**, **Table 4.12** and **Table 4.13** below.

Table 4.11 – Development Location Information

Location of Development	Galway
Sensitivity Area	Central
Year of Traffic Counts	2025
Year of Assessment	2025
Year of Development Construction	2027

Table 4.12 - TII Annual Growth Rates (Central Growth) for Co. Galway

Year	LGV	HGV
2016 – 2030	1.0259	1.0446
2030 – 2040	1.0109	1.0198
2040 – 2050	1.0105	1.0236

Table 4.13 – Growth Factors for Future Design Years for Co. Galway

	Counts	Completion	Completion +5	Completion +15
	2025	2027	2032	2042
LGV	1.000	1.052	1.161	1.293
HGV	1.000	1.091	1.294	1.585

4.4 Generated Traffic Splits Through Neighbouring Junctions

The traffic survey conducted along Raheen Woods Road at JTC 1 and JTC 2 revealed a relatively balanced distribution of traffic between the two surveyed locations. During the morning peak, approximately 57% of total traffic along the road travels southwest towards JTC 1, with the remaining 43% heading northeast towards JTC 2. A slight shift is observed during the evening peak, with around 48% of traffic moving southwest towards JTC 1 and 52% northeast towards JTC 2.

For the purposes of the junction analysis, a conservative assumption of an even 50/50 split was adopted, with 50% of entering and exiting traffic assigned to each junction.

From the traffic counts obtained, it is evident that the AM and PM peak at JTCs 1 and 2 aligns with the projected peak times for a residential development, as indicated by the TRICS analysis, occurring between 08:00 and 09:00 in the morning and between 17:00 and 18:00 in the evening.

Taking these observations into account, all junctions were modelled for the existing individual network's AM and PM peak time, incorporating the peak morning and afternoon traffic associated with the development which coincides with the junctions' peak traffic.

Figure 4.2 and **Figure 4.3** overleaf display the expected levels of the generated traffic on the 2No. junctions affected in the vicinity of the site, projected for the proposed year of

development conclusion in 2027.




Figure 4.2: AM and PM Development traffic splits in JTC1




Figure 4.3: AM and PM Development traffic splits in JTC2

4.5 Traffic and Transport Assessment Guidelines

The Galway County Development Plan 2022 – 2028, in **Section 6.5.3.1**, requires a Traffic and Transport Assessment to be provided as part of a development proposal in the case of developments with significant car trip generation potential and shall be in accordance with the Traffic and Transport Assessment Guidelines (TII 2014).

The TII Publication PE-PDV-02045 Traffic and Transport Assessment Guidelines, published in May 2014, recommends that junction modelling should be carried out where new traffic exceeds 5% of existing flows if congestion already exists and if traffic generated by the development exceeds 10% where no traffic congestion is present.

As the proposed development is assumed to be fully constructed and operational in 2027, the projected 2027 traffic flows could be calculated using TII's Central Growth Factor for Co. Galway. The impact on traffic for the assessed junctions is presented in **Table 4.14**.

Table 4.14 – Traffic Impact on Neighbouring Junctions from the development

Junction	2027 Projected Traffic		Traffic from Development		Increase in Traffic		TII Threshold of 5%	
	AM Peak	PM Peak	AM Peak	PM Peak	AM Peak	PM Peak	AM Peak	PM Peak
JTC1	710	756	8	9	1.1%	1.2%	Below	Below
JTC2	628	652	8	9	1.3%	1.4%	Below	Below

As can be seen from **Table 4.14**, the predicted traffic from the proposed development is not expected to generate an increase of more than 5% on the assessed junctions, and therefore they do not exceed the TII 5% threshold, where congestion is considered to exist, which automatically requires a Traffic and Transport Assessment.

Table 4.15 provides the thresholds for a Traffic and Transport Assessment (TTA).

Table 4.15 – Traffic Management Guidelines Thresholds for Transport Assessments (TII)

N/A	Traffic to and from the development exceeds 10% of the traffic flow on the adjoining road.
NO	Traffic to and from the development exceeds 5% of the traffic flow on the adjoining road where congestion exists, or the location is sensitive
NO	Residential development in excess of 200 dwellings
N/A	Retail and leisure development in excess of 100m ²
N/A	Office, education and hospital development in excess of 2,500m ²
N/A	Industrial development in excess of 5,000m ²
N/A	Distribution and warehousing in excess of 10,000m ²

When assessing the traffic generated by the development against the threshold criteria outlined



in **Table 4.15** above, none of the conditions that would typically trigger the requirement for a Traffic and Transport Assessment (TTA), as set out by TII, are met. Nevertheless, a TTA was proactively prepared to demonstrate the limited impact of the proposed development on the surrounding road network and to support a robust planning submission.

5 Capacity Analysis

5.1 Introduction

A capacity assessment was undertaken at 2No. junctions in the vicinity of the site, as previously noted. The performance of the junctions during the AM and PM peak hours was assessed using PICADY software for priority junctions for the following design years:

- 2025, the base year
- 2027, the opening year
- 2032, 5 years after development conclusion
- 2042, 15 years after development conclusion.

Figure 5.1 below shows the junctions in which a traffic simulation was undertaken in order to obtain the **Ratio of Flow to Capacity (RFC)** and the **queue levels** to determine if the junctions would cater for the predicted level of traffic by the mixed-use development.



Figure 5.1: Location of junctions analysed (Source: Google Earth, notes by ORS)

The **Ratio of Flow to Capacity (RFC)** describes the capacity of each approach to the junction and determines if the junction will cater for the predicted level of traffic. An RFC below 0.85 (85%) implies that an approach road is operating satisfactorily well within capacity; between 0.85 to 1.0 RFC means the approach operates well within capacity but at less optimal efficiency; and an RFC above 1.0 means that demand and capacity are equal and no further traffic can progress through the junction.

The queue levels are presented in **Passenger Car Unit (PCU)** and quantify the total number of vehicles queueing on each arm.

5.2 Traffic Impacts of the Proposed Development on the Local Road Network

As stated in **Section 3.5** above, traffic counts were undertaken in March 2025 at the 2No. junctions. The cumulative effect of adjacent developments described in **Section 4.2** was considered in the analysis. Central traffic growth rates for Co. Galway, specified in the TII's Publication PE-PAG-02017 of October 2021, were applied to existing road traffic only and were not applied to the development traffic, since it is limited by development size. The capacity assessment was modelled for three different scenarios:

- Base-year: 2025 traffic flows modelled according to traffic counts obtained in March 2025.
- Do-nothing: modelled without the intervention of the proposed development. For this analysis, the traffic counts were factored up using TII's Growth Factor for the design years 2027, 2032 and 2042.
- Do-something: the impact of the traffic generated by the development was added to the design years 2027, 2032 and 2042. This analysis will enable the comparison with the 'Do-nothing' scenario.

5.2.1 Junction 1 – Raheen Woods Road (Gort Mhaoilir Road)/ L-3103 Priority Junction

In the following analysis, the junction was assessed for the AM and PM peak period, and the arms were labelled as shown in **Figure 5.2**:



Figure 5.2: JTC1 Arm Names (Source: Google Earth, notes by ORS)

Table 5.1 shows the results of the analysis of the junction modelled using PICADY transport modelling software for priority junctions for the assessment year (2025), the expected year of opening (2027), 5 years after the development completion (2032) and 15 years after the development completion (2042) for the 'Do-Nothing' and 'Do-Something' scenarios.

Table 5.1 – PICADY Results for JTC1 Analysis

Analysis	Stream	AM		PM	
		Queue (PCU)	Ratio of Flow to Capacity (RFC)	Queue (PCU)	Ratio of Flow to Capacity (RFC)
1 – 2025, base traffic	B-AC	0.8	0.43	0.6	0.39
	C-AB	0.3	0.18	0.2	0.15
2 – 2027, do-nothing	B-AC	1.0	0.50	0.8	0.44
	C-AB	0.3	0.21	0.3	0.17
3 – 2027, do-something	B-AC	1.1	0.51	0.8	0.45
	C-AB	0.3	0.21	0.3	0.18
4 – 2032, do-nothing	B-AC	1.3	0.56	1.0	0.49
	C-AB	0.4	0.23	0.3	0.19
5 – 2032, do-something	B-AC	1.4	0.57	1.0	0.50
	C-AB	0.4	0.24	0.4	0.20
6 – 2042, do-nothing	B-AC	1.7	0.63	1.3	0.56
	C-AB	0.5	0.27	0.4	0.22
7 – 2042, do-something	B-AC	1.9	0.65	1.3	0.57
	C-AB	0.5	0.27	0.4	0.23

Analysis 1 represents the base year scenario, reflecting current traffic conditions in the study area without the proposed development or any committed developments. As shown in the table above, the highest Ratio of Flow to Capacity (RFC) recorded is 0.43 (43%) during the AM peak at Stream B – AC (Raheen Woods Road), with no significant queue formation observed.

Analysis 2 reflects the **Do-Nothing** scenario for future years, incorporating committed developments only (excluding the proposed scheme). In this scenario, an increase of 0.07 in RFC is observed during the 2027 AM peak at Stream B – AC, resulting in an RFC of 0.50 (50%), still with no significant queuing. **Analysis 3**, the **Do-Something** scenario for the 2027 design year, includes both committed developments and the proposed scheme. Here, the RFC for Stream B – AC increases marginally by 0.01 to 0.51 (51%) during the AM peak, indicating a negligible impact from the proposed development.

Looking ahead to the 2042 design year, **Analysis 6 (Do-Nothing scenario)** shows Stream B – AC reaching an RFC of 0.63 (63%) in the AM peak. With the proposed development included (**Analysis 7 – Do-Something scenario**), this increases slightly to 0.65 (65%), representing an increase of just 0.02.

These results confirm that the proposed residential development will have a **minimal** impact on the operational performance of the junction, with all movements remaining well within capacity thresholds and no adverse queuing expected.

5.2.2 Junction 2 – Raheen Woods Road (Gort Mhaoilir Road)/ L-3105 Priority Junction

In the following analysis, the junction was assessed for the AM and PM peak period and the arms were labelled as shown in **Figure 5.3**:




Figure 5.3: JTC2 Arm Names (Source: Google Earth, notes by ORS)

Table 5.2 shows the results of the analysis of the junction modelled using PICADY transport modelling software for priority junctions for the expected year of opening (2027), 5 years (2032) and 15 years after the development completion (2042) for the ‘Do-Nothing’ and ‘Do-Something’ scenarios.

Table 5.2 – PICADY Results for JTC2 Analysis					
Analysis	Stream	AM		PM	
		Queue (PCU)	Ratio of Flow to Capacity (RFC)	Queue (PCU)	Ratio of Flow to Capacity (RFC)
1 – 2025, base traffic	B-AC	0.5	0.33	0.9	0.48
	C-AB	0.2	0.12	0.1	0.05
2 – 2027, do-nothing	B-AC	0.8	0.43	1.4	0.59
	C-AB	0.2	0.15	0.1	0.07
3 – 2027, do-something	B-AC	0.8	0.45	1.5	0.60
	C-AB	0.2	0.15	0.1	0.07

Table 5.2 – PICADY Results for JTC2 Analysis

Analysis	Stream	AM		PM	
		Queue (PCU)	Ratio of Flow to Capacity (RFC)	Queue (PCU)	Ratio of Flow to Capacity (RFC)
4 – 2032, do-nothing	B-AC	0.9	0.48	1.8	0.65
	C-AB	0.2	0.16	0.1	0.08
5 – 2032, do-something	B-AC	1.0	0.49	1.9	0.66
	C-AB	0.2	0.16	0.1	0.08
6 – 2042, do-nothing	B-AC	1.1	0.53	2.5	0.73
	C-AB	0.3	0.18	0.1	0.08
7 – 2042, do-something	B-AC	1.2	0.55	2.7	0.74
	C-AB	0.3	0.19	0.1	0.09

Analysis 1 represents the base year scenario, reflecting current traffic conditions in the study area without the proposed development or any committed developments. As shown in the table above, the highest Ratio of Flow to Capacity (RFC) recorded is 0.48 (48%) during the PM peak at Stream B – AC (Raheen Woods Road), with no significant queue formation observed.

Analysis 2 reflects the **Do-Nothing** scenario for future years, incorporating committed developments only (excluding the proposed scheme). In this scenario, an increase of 0.11 in RFC is observed during the 2027 PM peak at Stream B – AC, resulting in an RFC of 0.59 (59%) in the evening, still with no significant queuing. **Analysis 3**, the **Do-Something** scenario for the 2027 design year, includes both committed developments and the proposed scheme. Here, the RFC for Stream B – AC increases marginally by 0.02 to 0.45 (45%) during the AM peak and by 0.01 to 0.60 (60%) in the PM peak, indicating a negligible impact from the proposed development.

Looking ahead to the 2042 design year, **Analysis 6 (Do-Nothing scenario)** shows Stream B – AC reaching an RFC of 0.73 (73%) in the PM peak. With the proposed development included (**Analysis 7 – Do-Something scenario**), this increases slightly to 0.74 (74%), representing an increase of just 0.01. Similarly, the morning peak reached a maximum RFC of 0.55 at Stream B – AC, compared to the 0.53 in Analysis 6.

These results confirm that the proposed residential development will have a **minimal** impact on the operational performance of the junction, with all movements remaining well within capacity thresholds and no adverse queuing expected.

It can be concluded that both junctions will perform satisfactorily in the future and have **minimal** impact on the existing roads.

6 Conclusions

The main conclusions of this study are summarised as follows:

- This Traffic and Transport Assessment was conducted to accompany the planning application for the proposed residential development at Gort Mhaoilir, Athenry, Co. Galway.
- The proposed development, presented by Paul Keogh Architects, involves the construction of 28No. dwellings featuring 1No. site entrance and all associated ancillary site development works.
- The proposed total number of car parking spaces is 56No., including 3No. standard accessible parking spaces and 7No. accessible spaces equipped with EV charging stations. It is proposed to include 14No. visitor bicycle parking spaces at the communal open space.
- ORS scoped the requirements for this Traffic Assessment based on the same methodology previously applied to a Part 8 application for a residential development adjacent to the Proposed Development site (within Gort Mhaoilir). In that earlier assessment, the approach was agreed with Galway County Council, focusing on two key junctions that were identified as the most relevant to development-related traffic movements. To ensure consistency and continuity in the evaluation of local network impacts, the same two junctions are assessed in this report, namely the 3-arm Raheen Woods Road (Gort Mhaoilir Road)/ L-3103 Priority Junction (JTC 1) and the 3-arm Raheen Woods Road (Gort Mhaoilir Road)/ L-3105 Priority Junction (JTC 2).
- Automatic junction turning counts (JTCs) were undertaken by a third-party company named IDASO, on Tuesday the 11th of March 2025. The recorded AM peak hours were between 08:15 and 09:15 in both junctions. The evening peak period varies: it takes place between 15:45 and 16:45 in JTC 1 and between 17:00 and 18:00 in JTC 2.
- The National Planning Application website was consulted to obtain information about committed developments near the proposed site to be included in this traffic analysis. It was found that 5No. granted planning application will make use of the junctions, therefore, they were included in future scenarios of the junctions' modelling. The assessment also included the Part 8 application mentioned above, as a committed development.
- The traffic splits in the examined junctions could be calculated from the traffic counts, and it is expected that the traffic from the development will follow the same trend. The trip generation from the development was assessed from the TRICS database.
- The junctions analysed in this traffic assessment were assessed against the TII threshold, and it was found that the additional traffic will not exceed the threshold of 5% increase in traffic, therefore a TTA is not required. Nevertheless, a TTA was proactively prepared to demonstrate the limited impact of the proposed development on the surrounding road network and to support a robust planning submission.
- The junctions were examined using *Junctions 11* PICADY software for the AM and the PM peak conditions under conservative future projections and Central background Traffic Growth for the considered year of opening, 2027, 5-years and 15-years after development conclusion.
- From a transportation planning perspective, the proposed development is expected to generate a low volume of traffic during peak times. The junction analysis results indicate that the surrounding road network can easily accommodate this traffic, considering the prevailing road conditions. The junctions are projected to operate well below their theoretical capacity, with no issues anticipated during peak times.



Appendix A – Traffic Data

IDASO
Innovative Data Solutions



 Idaso Ltd
National Science Park,
Dublin Road, Mullingar,
Co Westmeath, Ireland

 Office
Ph: +353 (0) 4493 18019
Email: info@idaso.ie


 www.idaso.ie

Data Analysis Services
Traffic-Transportation- Commercial-Innovation

25216 - Athenry, Co. Galway

with compliments

Survey Name: 25216 - Athenry, Co. Galway
Date: Tue 11 Mar 2025





IDASO

Survey Name: 25216 - Athenry, Co. Galway
Site: Site 1
Location: Junction of Gort Mhaoilir Road & L3103
Date: Tue 11-Mar-2025
AM Peak: 08:15 — 09:15
PM Peak: 15:45 — 16:45
15 Min Peak: 08:45 — 09:00

Arm A - Gort Mhaoilir
 Arm B - L3103
 Arm C - L3103


Total: 598
Total: 635
Total: 210

TIME	A => A									A => B										
	P/C	M/C	CAR	LGV	OGV1	OGV2	PSV	TOT	PCU	P/C	M/C	CAR	LGV	OGV1	OGV2	PSV	TOT	PCU	P/C	M/C
07:00	0	0	0	0	0	0	0	0	0	0	0	11	0	0	0	0	11	11	0	0
07:15	0	0	0	0	0	0	0	0	0	0	0	15	2	1	0	0	18	18.5	0	0
07:30	0	0	0	0	0	0	0	0	0	0	0	7	3	0	0	0	10	10	0	0
07:45	0	0	0	0	0	0	0	0	0	0	0	5	0	1	0	0	6	6.5	0	0
H/TOT	0	0	0	0	0	0	0	0	0	0	0	38	5	2	0	0	45	46	0	0
08:00	0	0	0	0	0	0	0	0	0	0	0	8	1	0	0	0	9	9	0	0
08:15	0	0	0	0	0	0	0	0	0	0	0	13	0	0	0	0	13	13	0	0
08:30	0	0	0	0	0	0	0	0	0	0	0	12	1	0	0	0	13	13	0	0
08:45	0	0	0	0	0	0	0	0	0	0	0	23	1	0	0	0	24	24	1	0
H/TOT	0	0	0	0	0	0	0	0	0	0	0	56	3	0	0	0	59	59	1	0
09:00	0	0	0	0	0	0	0	0	0	0	0	12	0	1	0	0	13	13.5	0	0
09:15	0	0	0	0	0	0	0	0	0	0	0	7	1	0	0	0	8	8	0	0
09:30	0	0	0	0	0	0	0	0	0	0	0	17	0	1	0	0	18	18.5	0	0
09:45	0	0	0	0	0	0	0	0	0	0	0	8	0	0	0	0	8	8	0	0
H/TOT	0	0	0	0	0	0	0	0	0	0	0	44	1	2	0	0	47	48	0	0
10:00	0	0	0	0	0	0	0	0	0	0	0	14	3	1	0	0	18	18.5	0	0
10:15	0	0	0	0	0	0	0	0	0	0	0	15	3	1	0	0	19	19.5	0	0
10:30	0	0	0	0	0	0	0	0	0	0	0	8	3	1	0	0	12	12.5	0	0
10:45	0	0	0	0	0	0	0	0	0	0	0	13	2	0	0	0	15	15	1	0
H/TOT	0	0	0	0	0	0	0	0	0	0	0	50	11	3	0	0	64	65.5	1	0
11:00	0	0	0	0	0	0	0	0	0	1	0	15	2	1	1	0	20	21	0	0
11:15	0	0	0	0	0	0	0	0	0	0	0	10	2	1	0	0	13	13.5	0	0
11:30	0	0	0	0	0	0	0	0	0	0	0	9	0	1	0	0	10	10.5	0	0
11:45	0	0	0	0	0	0	0	0	0	0	0	9	2	0	0	0	11	11	0	0
H/TOT	0	0	0	0	0	0	0	0	0	1	0	43	6	3	1	0	54	56	0	0
12:00	0	0	0	0	0	0	0	0	0	0	0	17	1	0	0	0	18	18	0	0
12:15	0	0	0	0	0	0	0	0	0	0	0	9	0	0	0	0	9	9	0	0
12:30	0	0	0	0	0	0	0	0	0	0	0	16	1	2	0	0	19	20	0	0
12:45	0	0	0	0	0	0	0	0	0	0	0	10	0	0	1	0	11	12.3	0	0
H/TOT	0	0	0	0	0	0	0	0	0	0	0	52	2	2	1	0	57	59.3	0	0
13:00	0	0	0	0	0	0	0	0	0	0	0	19	1	1	0	0	21	21.5	0	0
13:15	0	0	0	0	0	0	0	0	0	0	0	17	1	0	0	0	18	18	0	0
13:30	0	0	0	0	0	0	0	0	0	0	0	13	1	0	0	0	14	14	0	0
13:45	0	0	0	0	0	0	0	0	0	0	0	14	1	0	0	0	15	15	0	0
H/TOT	0	0	0	0	0	0	0	0	0	0	0	63	4	1	0	0	68	68.5	0	0
14:00	0	0	0	0	0	0	0	0	0	0	0	12	1	0	0	0	13	13	0	0
14:15	0	0	0	0	0	0	0	0	0	0	0	14	1	1	1	0	17	18.8	0	0
14:30	0	0	0	0	0	0	0	0	0	0	0	10	0	0	0	0	10	10	0	0
14:45	0	0	0	0	0	0	0	0	0	0	0	11	0	2	0	0	13	14	0	0
H/TOT	0	0	0	0	0	0	0	0	0	0	0	47	2	3	1	0	53	55.8	0	0
15:00	0	0	0	0	0	0	0	0	0	0	0	10	1	0	0	0	11	11	0	0
15:15	0	0	0	0	0	0	0	0	0	0	0	9	3	0	0	0	12	12	0	0
15:30	0	0	0	0	0	0	0	0	0	0	0	18	1	0	0	0	19	19	0	0
15:45	0	0	0	0	0	0	0	0	0	0	0	25	0	0	0	0	25	25	0	0
H/TOT	0	0	0	0	0	0	0	0	0	0	0	62	5	0	0	0	67	67	0	0
16:00	0	0	0	0	0	0	0	0	0	0	0	37	1	1	0	0	39	39.5	0	0
16:15	0	0	0	0	0	0	0	0	0	0	0	6	0	0	0	1	7	8	0	0
16:30	0	0	0	0	0	0	0	0	0	0	0	23	2	0	0	0	25	25	1	0
16:45	0	0	0	0	0	0	0	0	0	0	0	10	1	0	0	0	11	11	0	0
H/TOT	0	0	0	0	0	0	0	0	0	0	0	76	4	1	0	1	82	83.5	1	0
17:00	0	0	0	0	0	0	0	0	0	0	0	18	2	0	0	0	20	20	0	0
17:15	0	0	0	0	0	0	0	0	0	0	0	23	1	0	0	0	24	24	1	0
17:30	0	0	0	0	0	0	0	0	0	0	0	14	0	0	0	0	14	14	0	0
17:45	0	0	0	0	0	0	0	0	0	0	0	20	1	0	0	0	21	21	0	0
H/TOT	0	0	0	0	0	0	0	0	0	0	0	75	4	0	0	0	79	79	1	0
18:00	0	0	0	0	0	0	0	0	0	0	0	8	1	1	0	0	10	10.5	0	0
18:15	0	0	0	0	0	0	0	0	0	0	0	7	0	0	1	0	8	9.3	0	0
18:30	0	0	0	0	0	0	0	0	0	0	0	11	0	0	0	0	11	11	0	0
18:45	0	0	0	0	0	0	0	0	0	0	0	14	1	0	0	0	15	15	0	0
H/TOT	0	0	0	0	0	0	0	0	0	0	0	40	2	1	1	0	44	45.8	0	0
12 TOT	0	0	0	0	0	0	0	0	0	1	0	646	49	18	4	1	719	733.4	4	0

A => C					TOT	PCU	B => A					TOT	PCU	B => B							
CAR	LGV	OGV1	OGV2	PSV			P/C	M/C	CAR	LGV	OGV1			OGV2	PSV	P/C	M/C	CAR	LGV	OGV1	OGV2
9	1	3	0	0	13	14.5	0	0	2	0	1	0	0	3	3.5	0	0	0	0	0	0
15	2	1	0	0	18	18.5	0	0	6	1	0	0	0	7	7	0	0	0	0	0	0
22	3	0	0	0	25	25	0	0	10	1	0	0	0	11	11	0	0	0	0	0	0
17	4	0	0	1	22	23	0	0	5	1	0	0	0	6	6	0	0	0	0	0	0
63	10	4	0	1	78	81	0	0	23	3	1	0	0	27	27.5	0	0	0	0	0	0
20	2	0	0	0	22	22	0	0	8	0	0	0	0	8	8	0	0	0	0	0	0
33	3	0	0	4	40	44	0	0	12	0	0	0	0	12	12	0	0	0	0	0	0
28	1	0	1	0	30	31.3	0	0	17	1	1	0	0	19	19.5	0	0	0	0	0	0
33	0	1	0	0	35	34.7	0	0	38	1	1	0	0	40	40.5	0	0	0	0	0	0
114	6	1	1	4	127	132	0	0	75	2	2	0	0	79	80	0	0	0	0	0	0
15	1	0	0	0	16	16	0	0	21	0	0	0	0	21	21	0	0	0	0	0	0
15	2	0	0	0	17	17	0	0	18	1	0	0	0	19	19	0	0	0	0	0	0
16	1	0	0	0	17	17	0	0	16	1	1	1	0	19	20.8	0	0	0	0	0	0
13	0	0	0	0	13	13	0	0	12	1	0	0	0	13	13	0	0	1	0	0	0
59	4	0	0	0	63	63	0	0	67	3	1	1	0	72	73.8	0	0	1	0	0	0
12	3	1	1	0	17	18.8	0	0	6	2	0	0	0	8	8	0	0	0	0	0	0
7	3	0	1	0	11	12.3	0	0	8	1	0	0	0	9	9	0	0	0	0	0	0
10	0	1	0	1	12	13.5	0	0	14	0	1	0	0	15	15.5	0	0	0	0	0	0
13	2	0	0	0	16	15.2	0	0	10	2	0	0	0	12	12	0	0	0	0	0	0
42	8	2	2	1	56	59.8	0	0	38	5	1	0	0	44	44.5	0	0	0	0	0	0
6	0	0	0	0	6	6	0	0	8	0	1	0	0	9	9.5	0	0	0	0	0	0
7	0	0	0	0	7	7	0	0	4	1	0	0	0	5	5	0	0	0	0	0	0
4	0	0	0	0	4	4	0	0	8	2	1	0	0	11	11.5	0	0	0	0	0	0
7	1	0	0	0	8	8	0	0	12	0	0	0	0	12	12	0	0	0	0	0	0
24	1	0	0	0	25	25	0	0	32	3	2	0	0	37	38	0	0	0	0	0	0
7	1	0	0	0	8	8	0	0	17	2	0	0	0	19	19	0	0	0	0	0	0
9	0	1	0	0	10	10.5	0	0	9	1	0	0	0	10	10	0	0	0	0	0	0
6	2	0	0	0	8	8	0	0	6	1	0	0	0	7	7	0	0	0	0	0	0
8	0	0	0	0	8	8	0	0	6	1	1	0	0	8	8.5	0	0	0	0	0	0
30	3	1	0	0	34	34.5	0	0	38	5	1	0	0	44	44.5	0	0	0	0	0	0
12	3	0	0	0	15	15	0	0	10	1	0	0	0	11	11	0	0	0	0	0	0
9	0	0	0	0	9	9	0	0	15	3	0	0	0	18	18	0	0	0	0	0	0
16	0	0	0	0	16	16	0	0	18	2	0	0	0	20	20	0	0	0	0	0	0
11	0	1	0	0	12	12.5	0	0	13	2	0	0	0	15	15	0	0	0	0	0	0
48	3	1	0	0	52	52.5	0	0	56	8	0	0	0	64	64	0	0	0	0	0	0
12	1	1	0	0	14	14.5	0	0	9	0	0	1	0	10	11.3	0	0	0	0	0	0
8	1	0	0	0	9	9	0	0	16	2	0	0	0	18	18	0	0	0	0	0	0
14	2	0	0	0	16	16	0	0	13	1	1	1	0	16	17.8	0	0	0	0	0	0
9	2	0	0	0	11	11	0	0	12	1	1	0	0	14	14.5	0	0	0	0	0	0
43	6	1	0	0	50	50.5	0	0	50	4	2	2	0	58	61.6	0	0	0	0	0	0
8	5	0	1	0	14	15.3	0	0	19	1	0	0	0	20	20	0	0	0	0	0	0
10	2	1	0	1	14	15.5	0	0	11	2	0	0	0	13	13	0	0	0	0	0	0
29	0	1	0	0	30	30.5	0	0	14	0	1	0	0	15	15.5	0	0	0	0	0	0
17	1	0	0	0	18	18	0	0	19	1	0	0	0	20	20	0	0	0	0	0	0
64	8	2	1	1	76	79.3	0	0	63	4	1	0	0	68	68.5	0	0	0	0	0	0
18	2	0	0	1	21	22	0	0	19	0	0	0	0	19	19	0	0	0	0	0	0
15	0	0	0	0	15	15	0	0	17	0	0	0	0	17	17	0	0	0	0	0	0
26	1	1	0	0	29	28.7	0	0	14	1	0	0	0	15	15	0	0	0	0	0	0
28	2	2	0	0	32	33	0	0	16	0	1	0	0	17	17.5	0	0	0	0	0	0
87	5	3	0	1	97	98.7	0	0	66	1	1	0	0	68	68.5	0	0	0	0	0	0
25	1	0	0	0	26	26	0	1	18	4	0	0	0	23	22.4	0	0	0	0	0	0
13	0	0	0	0	14	13.2	0	0	17	1	0	0	0	18	18	0	0	0	0	0	0
25	1	0	0	0	26	26	0	0	17	1	2	0	0	20	21	0	0	0	0	0	0
26	1	0	0	0	27	27	0	0	19	0	0	1	0	20	21.3	0	0	0	0	0	0
89	3	0	0	0	93	92.2	0	1	71	6	2	1	0	81	82.7	0	0	0	0	0	0
18	0	1	0	0	19	19.5	0	0	16	0	0	0	0	16	16	0	0	0	0	0	0
18	1	0	0	0	19	19	0	0	8	0	0	0	0	8	8	0	0	0	0	0	0
20	0	0	0	0	20	20	1	0	14	2	0	0	0	17	16.2	0	0	0	0	0	0
18	1	0	0	0	19	19	0	0	7	4	0	0	0	11	11	0	0	0	0	0	0
74	2	1	0	0	77	77.5	1	0	45	6	0	0	0	52	51.2	0	0	0	0	0	0
737	59	16	4	8	828	846	1	1	624	50	14	4	0	694	704.8	0	0	1	0	0	0

PSV	TOT	PCU	B => C							C => A							TOT	PCU	P/C		
			P/C	M/C	CAR	LGV	OGV1	OGV2	PSV	TOT	PCU	P/C	M/C	CAR	LGV	OGV1				OGV2	PSV
0	0	0	0	0	4	1	1	0	0	6	6.5	1	0	5	0	1	0	0	7	6.7	0
0	0	0	0	0	5	4	0	0	0	9	9	0	0	6	1	0	0	0	7	7	0
0	0	0	0	0	10	2	0	0	1	13	14	0	0	11	0	0	0	0	11	11	0
0	0	0	0	0	10	3	0	0	2	15	17	0	0	21	3	0	0	0	24	24	0
0	0	0	0	0	29	10	1	0	3	43	46.5	1	0	43	4	1	0	0	49	48.7	0
0	0	0	0	0	10	0	1	0	1	12	13.5	0	0	13	1	0	0	0	14	14	1
0	0	0	1	0	14	2	0	0	1	18	18.2	1	0	16	3	0	1	0	21	21.5	0
0	0	0	0	0	23	1	0	0	4	28	32	1	0	33	2	0	0	0	36	35.2	0
0	0	0	0	0	42	2	0	1	0	45	46.3	0	0	26	3	0	0	0	29	29	0
0	0	0	1	0	89	5	1	1	6	103	110	2	0	88	9	0	1	0	100	99.7	1
0	0	0	0	0	14	0	0	0	0	14	14	0	0	22	5	0	0	0	27	27	0
0	0	0	0	0	22	2	2	0	0	26	27	0	0	10	1	1	0	0	12	12.5	0
0	0	0	0	0	29	0	0	0	0	29	29	1	0	10	0	1	1	0	13	14	0
0	1	1	0	0	15	2	0	1	0	18	19.3	1	0	9	1	0	1	0	12	12.5	0
0	1	1	0	0	80	4	2	1	0	87	89.3	2	0	51	7	2	2	0	64	66	0
0	0	0	0	0	14	2	1	1	0	18	19.8	0	0	7	2	2	0	0	11	12	0
0	0	0	0	0	17	3	2	1	0	23	25.3	0	0	12	0	1	0	0	13	13.5	1
0	0	0	2	0	21	0	1	0	0	24	22.9	0	0	5	2	0	0	0	7	7	0
0	0	0	0	0	13	0	0	0	2	15	17	0	0	6	1	0	0	2	9	11	0
0	0	0	2	0	65	5	4	2	2	80	85	0	0	30	5	3	0	2	40	43.5	1
0	0	0	0	0	10	3	0	0	0	13	13	0	0	9	2	0	0	0	11	11	0
0	0	0	0	0	14	2	1	1	1	19	21.8	0	0	6	0	0	0	0	6	6	0
0	0	0	0	0	7	1	0	0	0	8	8	0	0	8	2	0	0	0	10	10	0
0	0	0	0	0	21	6	0	1	0	28	29.3	1	0	12	2	0	1	0	16	16.5	0
0	0	0	0	0	52	12	1	2	1	68	72.1	1	0	35	6	0	1	0	43	43.5	0
0	0	0	0	0	8	1	0	0	0	9	9	0	0	6	2	0	0	0	8	8	0
0	0	0	1	0	11	2	0	1	0	15	15.5	0	0	11	0	0	0	1	12	13	0
0	0	0	0	0	19	2	1	0	0	22	22.5	0	0	8	3	0	1	0	12	13.3	0
0	0	0	0	0	14	2	1	1	0	18	19.8	0	0	4	0	0	0	0	4	4	1
0	0	0	1	0	52	7	2	2	0	64	66.8	0	0	29	5	0	1	1	36	38.3	1
0	0	0	1	0	21	1	2	0	0	25	25.2	0	0	12	1	0	0	1	14	15	0
0	0	0	0	0	16	4	0	0	1	21	22	0	0	15	0	0	0	0	15	15	0
0	0	0	0	0	20	3	1	0	1	25	26.5	0	0	13	2	0	0	0	15	15	1
0	0	0	0	0	15	6	1	2	0	24	27.1	0	0	19	0	2	0	0	21	22	0
0	0	0	1	0	72	14	4	2	2	95	100.8	0	0	59	3	2	0	1	65	67	1
0	0	0	0	0	10	4	1	0	0	15	15.5	0	0	18	3	1	1	0	23	24.8	0
0	0	0	0	0	14	0	0	0	0	14	14	0	0	11	3	0	0	0	14	14	0
0	0	0	0	0	17	1	0	0	0	18	18	0	0	9	0	0	0	0	9	9	0
0	0	0	0	0	17	3	1	2	0	23	26.1	0	0	19	3	0	0	0	22	22	0
0	0	0	0	0	58	8	2	2	0	70	73.6	0	0	57	9	1	1	0	68	69.8	0
0	0	0	0	0	13	2	1	2	0	18	21.1	0	0	11	3	0	0	0	14	14	0
0	0	0	0	0	15	0	1	0	0	16	16.5	0	0	12	0	1	0	0	13	13.5	0
0	0	0	1	0	20	4	1	0	0	26	25.7	0	0	18	3	0	0	0	21	21	0
0	0	0	0	0	37	3	1	0	3	44	47.5	0	0	19	4	0	0	0	23	23	0
0	0	0	1	0	85	9	4	2	3	104	110.8	0	0	60	10	1	0	0	71	71.5	0
0	0	0	0	0	27	0	1	1	5	34	40.8	0	0	40	2	0	0	0	42	42	0
0	0	0	0	0	35	3	0	2	2	42	46.6	0	0	22	2	0	0	0	24	24	0
0	0	0	0	0	17	2	1	0	0	20	20.5	1	0	20	4	1	0	0	26	25.7	0
0	0	0	1	0	17	6	0	0	0	24	23.2	0	0	17	3	0	0	0	20	20	0
0	0	0	1	0	96	11	2	3	7	120	131.1	1	0	99	11	1	0	0	112	111.7	0
0	0	0	0	0	25	5	0	0	0	30	30	0	0	21	3	0	0	0	24	24	1
0	0	0	0	0	34	1	1	0	0	36	36.5	0	0	18	4	0	0	0	22	22	2
0	0	0	0	0	25	5	0	0	0	30	30	0	0	20	3	0	0	0	23	23	0
0	0	0	1	0	26	1	0	0	0	28	27.2	0	0	18	4	1	0	0	23	23.5	0
0	0	0	1	0	110	12	1	0	0	124	123.7	0	0	77	14	1	0	0	92	92.5	3
0	0	0	0	0	33	2	0	0	0	35	35	0	0	18	1	0	0	0	19	19	0
0	0	0	0	1	35	2	1	0	0	39	38.9	0	0	22	2	0	0	0	24	24	0
0	0	0	0	0	17	2	0	0	0	19	19	0	0	19	0	0	0	0	19	19	0
0	0	0	0	0	32	1	0	0	0	33	33	0	0	26	2	0	0	0	28	28	0
0	0	0	0	1	117	7	1	0	0	126	125.9	0	0	85	5	0	0	0	90	90	0
0	1	1	8	1	905	104	25	17	24	1084	1135.6	7	0	713	88	12	6	4	830	842.2	7

C => B								C => C								
M/C	CAR	LGV	OGV1	OGV2	PSV	TOT	PCU	P/C	M/C	CAR	LGV	OGV1	OGV2	PSV	TOT	PCU
0	4	2	0	0	0	6	6	0	0	0	0	0	0	0	0	0
0	9	2	0	0	0	11	11	0	0	0	0	0	0	0	0	0
0	6	1	0	0	0	7	7	0	0	0	0	0	0	0	0	0
0	8	2	1	0	0	11	11.5	0	0	0	0	0	0	0	0	0
0	27	7	1	0	0	35	35.5	0	0	0	0	0	0	0	0	0
0	7	5	0	1	0	14	14.5	0	0	0	0	0	0	0	0	0
0	18	3	0	0	0	21	21	0	0	0	0	0	0	0	0	0
0	23	2	1	0	0	26	26.5	0	0	0	0	0	0	0	0	0
0	32	3	2	0	0	37	38	0	0	0	0	0	0	0	0	0
0	80	13	3	1	0	98	100	0	0	0	0	0	0	0	0	0
0	18	1	1	0	0	20	20.5	0	0	0	0	0	0	0	0	0
0	13	2	0	0	0	15	15	0	0	0	0	0	0	0	0	0
0	13	3	1	1	0	18	19.8	0	0	0	0	0	0	0	0	0
0	17	1	0	2	0	20	22.6	0	0	0	0	0	0	0	0	0
0	61	7	2	3	0	73	77.9	0	0	0	0	0	0	0	0	0
0	17	1	2	1	0	21	23.3	0	0	0	0	0	0	0	0	0
0	21	3	0	0	0	25	24.2	0	0	0	0	0	0	0	0	0
0	13	3	1	2	1	20	24.1	0	0	0	0	0	0	0	0	0
0	22	1	0	0	0	23	23	0	0	0	0	0	0	0	0	0
0	73	8	3	3	1	89	94.6	0	0	0	0	0	0	0	0	0
0	25	1	0	2	1	29	32.6	0	0	0	0	0	0	0	0	0
1	14	0	2	0	0	17	17.4	0	0	0	0	0	0	0	0	0
0	10	4	1	2	0	17	20.1	0	0	0	0	0	0	0	0	0
0	16	4	1	1	0	22	23.8	0	0	0	0	0	0	0	0	0
1	65	9	4	5	1	85	93.9	0	0	0	0	0	0	0	0	0
0	17	4	0	0	0	21	21	0	0	0	0	0	0	0	0	0
0	14	2	0	0	0	16	16	0	0	0	0	0	0	0	0	0
0	21	0	0	0	0	21	21	0	0	0	0	0	0	0	0	0
0	8	2	0	0	0	11	10.2	0	0	0	0	0	0	0	0	0
0	60	8	0	0	0	69	68.2	0	0	0	0	0	0	0	0	0
0	24	3	1	0	1	29	30.5	0	0	0	0	0	0	0	0	0
0	14	0	0	0	0	14	14	0	0	0	0	0	0	0	0	0
0	17	2	1	0	1	22	22.7	0	0	0	1	0	0	0	1	1
0	11	1	0	0	1	13	14	0	0	0	0	0	0	0	0	0
0	66	6	2	0	3	78	81.2	0	0	0	1	0	0	0	1	1
1	14	2	0	0	0	17	16.4	0	0	0	0	0	0	0	0	0
0	9	1	2	0	0	12	13	0	0	0	0	0	0	0	0	0
0	42	1	0	0	0	43	43	0	0	0	0	0	0	0	0	0
0	20	3	1	0	2	26	28.5	0	0	0	0	0	0	0	0	0
1	85	7	3	0	2	98	100.9	0	0	0	0	0	0	0	0	0
0	21	2	1	0	0	24	24.5	0	0	0	0	0	0	0	0	0
0	18	2	0	1	0	21	22.3	0	0	0	0	0	0	0	0	0
0	17	1	0	0	0	18	18	0	0	0	0	0	0	0	0	0
0	35	1	2	0	0	38	39	0	0	0	0	0	0	0	0	0
0	91	6	3	1	0	101	103.8	0	0	0	0	0	0	0	0	0
0	30	4	5	0	0	39	41.5	0	0	0	0	0	0	0	0	0
0	16	2	1	0	0	19	19.5	0	0	0	0	0	0	0	0	0
0	31	3	0	0	0	34	34	0	0	0	0	0	0	0	0	0
0	27	3	1	0	0	31	31.5	0	0	0	0	0	0	0	0	0
0	104	12	7	0	0	123	126.5	0	0	0	0	0	0	0	0	0
0	18	3	0	0	0	22	21.2	0	0	0	0	0	0	0	0	0
0	16	2	0	0	0	20	18.4	0	0	0	0	0	0	0	0	0
0	16	0	0	0	0	16	16	0	0	0	0	0	0	0	0	0
0	18	4	1	0	0	23	23.5	0	0	0	0	0	0	0	0	0
0	68	9	1	0	0	81	79.1	0	0	0	0	0	0	0	0	0
0	24	1	0	0	0	25	25	0	0	0	0	0	0	0	0	0
0	20	1	2	0	0	23	24	0	0	0	0	0	0	0	0	0
0	15	0	0	0	0	15	15	0	0	0	0	0	0	0	0	0
0	27	3	0	0	0	30	30	0	0	0	0	0	0	0	0	0
0	86	5	2	0	0	93	94	0	0	0	0	0	0	0	0	0
2	866	97	31	13	7	1023	1055.6	0	0	0	1	0	0	0	1	1



IDASO

Survey Name: 25216 - Athenry, Co. Galway
Site: Site 2
Location: Junction of Gort Mhaoilir Road & L3105
Date: Tue 11-Mar-2025
AM Peak: 08:15 — 09:15
PM Peak: 17:00 — 18:00
15 Min Peak: 16:00 — 16:15

Arm A - L3105 Raheen road
 Arm B - Gort Mhaoilir
 Arm C - L3105 Raheen road

Total: 483
Total: 515
Total: 169

TIME	A => A									A => B										
	P/C	M/C	CAR	LGV	OGV1	OGV2	PSV	TOT	PCU	P/C	M/C	CAR	LGV	OGV1	OGV2	PSV	TOT	PCU	P/C	M/C
07:00	0	0	0	0	0	0	0	0	0	2	0	8	0	1	0	0	11	9.9	0	0
07:15	0	0	0	0	0	0	0	0	0	1	0	20	2	0	0	0	23	22.2	0	0
07:30	0	0	0	0	0	0	0	0	0	0	1	17	2	0	0	0	20	19.4	0	0
07:45	0	0	0	0	0	0	0	0	0	1	0	26	3	0	0	1	31	31.2	0	0
H/TOT	0	0	0	0	0	0	0	0	0	4	1	71	7	1	0	1	85	82.7	0	0
08:00	0	0	0	0	0	0	0	0	0	0	0	19	2	0	0	0	21	21	0	0
08:15	0	0	0	0	0	0	0	0	0	0	0	29	0	0	0	3	32	35	0	0
08:30	0	0	0	0	0	0	0	0	0	0	0	38	2	0	0	0	40	40	0	0
08:45	0	0	0	0	0	0	0	0	0	1	0	50	1	0	0	0	52	51.2	0	0
H/TOT	0	0	0	0	0	0	0	0	0	1	0	136	5	0	0	3	145	147.2	0	0
09:00	0	0	0	0	0	0	0	0	0	0	0	20	1	0	0	0	21	21	0	0
09:15	0	0	0	0	0	0	0	0	0	0	0	17	1	0	1	0	19	20.3	0	0
09:30	0	0	0	0	0	0	0	0	0	0	0	17	1	0	0	0	18	18	0	0
09:45	0	0	0	0	0	0	0	0	0	0	0	21	1	0	0	0	22	22	0	0
H/TOT	0	0	0	0	0	0	0	0	0	0	0	75	4	0	1	0	80	81.3	0	0
10:00	0	0	0	0	0	0	0	0	0	0	0	11	2	1	1	0	15	16.8	0	0
10:15	0	0	0	0	0	0	0	0	0	0	0	11	4	0	0	0	15	15	0	0
10:30	0	0	0	0	0	0	0	0	0	0	0	18	2	0	0	1	21	22	0	0
10:45	0	0	0	0	0	0	0	0	0	0	0	18	1	0	0	0	19	19	0	0
H/TOT	0	0	0	0	0	0	0	0	0	0	0	58	9	1	1	1	70	72.8	0	0
11:00	0	0	0	0	0	0	0	0	0	0	0	15	1	1	0	0	17	17.5	0	0
11:15	0	0	0	0	0	0	0	0	0	0	0	18	1	0	0	0	19	19	0	0
11:30	0	0	0	0	0	0	0	0	0	0	0	9	0	0	0	0	9	9	0	0
11:45	0	0	0	0	0	0	0	0	0	0	0	15	1	0	0	0	16	16	1	0
H/TOT	0	0	0	0	0	0	0	0	0	0	0	57	3	1	0	0	61	61.5	1	0
12:00	0	0	1	0	0	0	0	1	1	0	0	16	0	0	0	0	16	16	0	0
12:15	0	0	0	0	0	0	0	0	0	0	0	13	1	0	0	0	14	14	0	0
12:30	0	0	0	0	0	0	0	0	0	0	0	14	1	1	0	0	16	16.5	0	0
12:45	0	0	0	0	0	0	0	0	0	0	0	14	0	1	0	0	15	15.5	0	0
H/TOT	0	0	1	0	0	0	0	1	1	0	0	57	2	2	0	0	61	62	0	0
13:00	0	0	0	0	0	0	0	0	0	0	0	16	2	1	0	0	19	19.5	0	0
13:15	0	0	0	0	0	0	0	0	0	0	0	18	1	0	0	0	19	19	0	0
13:30	0	0	0	0	0	0	0	0	0	0	0	15	1	0	0	0	16	16	0	0
13:45	0	0	0	0	0	0	0	0	0	0	0	21	2	0	0	0	23	23	0	0
H/TOT	0	0	0	0	0	0	0	0	0	0	0	70	6	1	0	0	77	77.5	0	0
14:00	0	0	0	0	0	0	0	0	0	0	0	21	3	0	0	0	24	24	0	0
14:15	0	0	0	0	0	0	0	0	0	0	0	17	1	1	0	0	19	19.5	0	0
14:30	0	0	0	0	0	0	0	0	0	0	0	21	2	0	0	0	23	23	0	0
14:45	0	0	0	0	0	0	0	0	0	0	0	18	1	1	0	0	20	20.5	0	0
H/TOT	0	0	0	0	0	0	0	0	0	0	0	77	7	2	0	0	86	87	0	0
15:00	0	0	0	0	0	0	0	0	0	0	0	8	3	0	0	0	11	11	0	0
15:15	0	0	0	0	0	0	0	0	0	0	0	17	3	1	0	1	22	23.5	0	0
15:30	0	0	0	0	0	0	0	0	0	1	0	32	0	0	0	0	33	32.2	1	0
15:45	0	0	0	0	0	0	0	0	0	0	0	29	1	0	0	0	30	30	0	0
H/TOT	0	0	0	0	0	0	0	0	0	1	0	86	7	1	0	1	96	96.7	1	0
16:00	0	0	0	0	0	0	0	0	0	0	0	28	3	0	0	1	32	33	1	0
16:15	0	0	0	0	0	0	0	0	0	0	0	20	0	1	0	1	22	23.5	0	0
16:30	0	0	0	0	0	0	0	0	0	1	0	20	3	0	0	0	24	23.2	0	0
16:45	0	0	0	0	0	0	0	0	0	0	0	24	1	0	0	0	25	25	0	0
H/TOT	0	0	0	0	0	0	0	0	0	1	0	92	7	1	0	2	103	104.7	1	0
17:00	0	0	0	0	0	0	0	0	0	0	0	16	2	0	0	0	18	18	0	0
17:15	0	0	0	0	0	0	0	0	0	1	0	26	0	0	0	0	27	26.2	0	0
17:30	0	0	0	0	0	0	0	0	0	0	0	24	3	0	0	0	27	27	1	0
17:45	0	0	0	0	0	0	0	0	0	1	0	37	1	1	0	0	40	39.7	0	0
H/TOT	0	0	0	0	0	0	0	0	0	2	0	103	6	1	0	0	112	110.9	1	0
18:00	0	0	0	0	0	0	0	0	0	0	0	18	0	0	1	0	19	20.3	0	0
18:15	0	0	0	0	0	0	0	0	0	0	0	11	1	0	0	0	12	12	1	0
18:30	0	0	0	0	0	0	0	0	0	0	0	20	1	0	0	0	21	21	0	0
18:45	0	0	0	0	0	0	0	0	0	1	0	29	3	0	0	0	33	32.2	0	0
H/TOT	0	0	0	0	0	0	0	0	0	1	0	78	5	0	1	0	85	85.5	1	0
12 TOT	0	0	1	0	0	0	0	1	1	10	1	960	68	11	3	8	1061	1069.8	5	0

A => C					TOT	PCU	B => A					TOT	PCU	B => B							
CAR	LGV	OGV1	OGV2	PSV			P/C	M/C	CAR	LGV	OGV1			OGV2	PSV	P/C	M/C	CAR	LGV	OGV1	OGV2
3	0	0	0	0	3	3	1	0	5	0	0	0	0	6	5.2	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0	12	0	0	0	0	12	12	0	0	0	0	0	0
2	0	1	0	0	3	3.5	0	0	6	1	0	0	0	7	7	0	0	0	0	0	0
2	1	0	0	0	3	3	0	0	12	2	0	0	0	14	14	0	0	0	0	0	0
7	1	1	0	0	9	9.5	1	0	35	3	0	0	0	39	38.2	0	0	0	0	0	0
3	0	0	0	0	3	3	0	0	18	1	0	0	0	19	19	0	0	0	0	0	0
5	0	0	0	0	5	5	1	0	14	3	0	0	0	18	17.2	0	0	0	0	0	0
10	0	2	0	0	12	13	1	0	25	5	0	0	0	31	30.2	0	0	0	0	0	0
22	1	0	0	0	23	23	0	0	33	3	0	0	0	36	36	0	0	0	0	0	0
40	1	2	0	0	43	44	2	0	90	12	0	0	0	104	102.4	0	0	0	0	0	0
10	1	0	0	0	11	11	0	0	23	2	0	0	0	25	25	0	0	0	0	0	0
2	1	0	0	0	3	3	0	0	8	0	0	0	0	8	8	0	0	0	0	0	0
2	0	0	0	0	2	2	1	0	17	2	1	0	0	21	20.7	0	0	0	0	0	0
5	2	0	0	0	7	7	1	0	19	3	0	1	0	24	24.5	0	0	0	0	0	0
19	4	0	0	0	23	23	2	0	67	7	1	1	0	78	78.2	0	0	0	0	0	0
5	2	1	0	0	8	8.5	0	0	14	0	0	0	0	14	14	0	0	0	0	0	0
2	0	0	0	0	2	2	1	0	22	2	0	0	0	25	24.2	0	0	0	0	0	0
11	0	0	0	0	11	11	1	0	13	0	0	0	0	14	13.2	0	0	0	0	1	0
12	0	0	0	0	12	12	0	0	14	0	0	0	1	15	16	0	0	0	0	0	0
30	2	1	0	0	33	33.5	2	0	63	2	0	0	1	68	67.4	0	0	0	0	1	0
4	0	0	0	0	4	4	0	0	13	2	0	0	1	16	17	0	0	0	0	0	0
5	0	0	0	0	5	5	0	0	6	0	1	0	0	7	7.5	0	0	0	0	0	0
4	1	0	0	0	5	5	0	0	10	2	0	0	0	12	12	0	0	0	0	0	0
15	1	0	0	0	17	16.2	1	0	20	3	1	0	0	25	24.7	0	0	0	1	0	0
28	2	0	0	0	31	30.2	1	0	49	7	2	0	1	60	61.2	0	0	0	1	0	0
6	1	0	0	0	7	7	0	0	18	0	0	0	0	18	18	0	0	0	0	0	0
7	0	0	0	0	7	7	0	0	9	1	0	0	1	11	12	0	0	0	0	0	0
12	1	0	0	0	13	13	0	0	12	3	0	0	0	15	15	0	0	0	0	0	0
12	1	0	0	0	13	13	0	0	21	1	0	0	0	22	22	0	0	0	0	0	0
37	3	0	0	0	40	40	0	0	60	5	0	0	1	66	67	0	0	0	0	0	0
12	1	0	0	0	13	13	0	0	25	3	0	0	1	29	30	0	0	0	0	0	0
9	1	0	0	0	10	10	0	0	14	1	0	0	0	15	15	0	0	0	0	0	0
11	1	0	0	0	12	12	0	0	27	2	0	0	0	29	29	0	0	0	0	0	0
6	0	0	0	0	6	6	0	0	21	0	0	0	0	21	21	0	0	0	0	0	0
38	3	0	0	0	41	41	0	0	87	6	0	0	1	94	95	0	0	0	0	0	0
3	1	0	0	0	4	4	0	0	20	4	0	0	0	24	24	0	0	0	0	0	0
9	0	0	0	0	9	9	0	0	19	2	1	0	0	22	22.5	0	0	0	0	0	0
12	0	0	0	0	12	12	0	0	10	0	1	0	0	11	11.5	0	0	0	0	0	0
11	1	0	0	1	13	14	1	0	22	3	0	0	0	26	25.2	0	0	0	0	0	0
35	2	0	0	1	38	39	1	0	71	9	2	0	0	83	83.2	0	0	0	0	0	0
11	1	1	0	0	13	13.5	0	0	16	2	0	0	0	18	18	0	0	0	0	0	0
8	0	0	0	0	8	8	0	0	13	2	0	0	0	15	15	0	0	0	0	0	0
21	1	0	0	0	23	22.2	0	0	26	1	1	0	0	28	28.5	0	0	0	0	0	0
13	1	0	0	0	14	14	0	0	16	2	0	0	0	18	18	0	0	0	0	0	0
53	3	1	0	0	58	57.7	0	0	71	7	1	0	0	79	79.5	0	0	0	0	0	0
12	0	0	0	0	13	12.2	1	0	59	2	0	0	0	62	61.2	0	0	0	0	0	0
23	0	0	0	0	23	23	0	0	31	1	0	0	0	32	32	0	0	0	0	0	0
9	1	1	0	0	11	11.5	1	0	29	4	0	0	0	34	33.2	0	0	0	0	0	0
11	0	0	0	0	11	11	0	0	22	4	1	0	0	27	27.5	0	0	0	0	0	0
55	1	1	0	0	58	57.7	2	0	141	11	1	0	0	155	153.9	0	0	0	0	0	0
15	3	0	0	0	18	18	4	0	39	6	0	0	0	49	45.8	0	0	0	0	0	0
20	1	0	0	0	21	21	1	0	33	3	0	0	0	37	36.2	0	0	0	0	0	0
10	2	1	0	0	14	13.7	1	0	29	3	0	0	0	33	32.2	0	0	0	0	0	0
22	3	0	0	0	25	25	0	0	21	2	0	0	0	23	23	0	0	0	0	0	0
67	9	1	0	0	78	77.7	6	0	122	14	0	0	0	142	137.2	0	0	0	0	0	0
15	0	0	0	0	15	15	0	0	30	1	0	1	0	32	33.3	0	0	0	0	0	0
14	0	0	0	0	15	14.2	0	0	16	2	0	0	0	18	18	0	0	0	0	0	0
8	0	0	0	0	8	8	0	0	18	1	0	0	0	19	19	0	0	0	0	0	0
21	1	0	0	0	22	22	0	0	23	3	0	0	0	26	26	0	0	0	0	0	0
58	1	0	0	0	60	59.2	0	0	87	7	0	1	0	95	96.3	0	0	0	0	0	0
467	32	7	0	1	512	512.5	17	0	943	90	7	2	4	1063	1059.5	0	0	0	1	1	0

PSV	TOT	PCU	B => C							C => A							TOT	PCU	P/C		
			P/C	M/C	CAR	LGV	OGV1	OGV2	PSV	TOT	PCU	P/C	M/C	CAR	LGV	OGV1				OGV2	PSV
0	0	0	0	0	5	0	0	0	0	5	5	0	0	3	0	0	0	0	3	3	0
0	0	0	0	0	2	1	1	0	0	4	4.5	0	0	3	0	0	0	0	3	3	0
0	0	0	0	0	2	0	0	0	0	2	2	0	0	6	0	0	0	0	6	6	0
0	0	0	0	0	4	0	0	0	0	4	4	0	0	9	1	0	0	0	10	10	0
0	0	0	0	0	13	1	1	0	0	15	15.5	0	0	21	1	0	0	0	22	22	0
0	0	0	0	0	1	1	0	0	0	2	2	0	0	4	1	0	0	0	5	5	1
0	0	0	0	0	3	1	0	0	0	4	4	0	0	6	0	0	0	0	6	6	0
0	0	0	0	0	2	1	0	0	0	3	3	0	0	38	1	0	0	0	39	39	0
0	0	0	0	0	9	0	0	0	0	9	9	0	0	21	1	0	0	0	22	22	0
0	0	0	0	0	15	3	0	0	0	18	18	0	0	69	3	0	0	0	72	72	1
0	0	0	0	0	10	2	0	0	0	12	12	0	0	17	1	0	0	0	18	18	0
0	0	0	0	0	6	1	0	0	0	7	7	0	0	14	2	0	0	0	16	16	0
0	0	0	0	0	3	0	0	1	0	4	5.3	0	0	10	1	0	0	0	11	11	0
0	0	0	0	0	2	0	0	0	0	2	2	0	0	12	0	0	0	0	12	12	0
0	0	0	0	0	21	3	0	1	0	25	26.3	0	0	53	4	0	0	0	57	57	0
0	0	0	0	0	2	1	1	0	0	4	4.5	0	0	7	3	0	0	0	10	10	0
0	0	0	0	0	1	0	0	0	0	1	1	1	0	5	0	0	0	0	6	5.2	0
0	1	1.5	0	0	5	0	0	0	0	5	5	0	0	8	0	0	0	0	8	8	0
0	0	0	0	0	4	1	0	0	0	5	5	0	0	6	0	0	0	0	6	6	1
0	1	1.5	0	0	12	2	1	0	0	15	15.5	1	0	26	3	0	0	0	30	29.2	1
0	0	0	0	0	6	1	0	0	0	7	7	0	0	10	1	0	0	0	11	11	2
0	0	0	0	0	5	0	0	0	0	5	5	0	0	7	1	0	0	0	8	8	0
0	0	0	0	0	6	0	0	0	0	6	6	0	0	7	1	0	0	0	8	8	0
0	1	1	0	0	9	0	0	0	0	9	9	0	0	10	0	0	0	0	10	10	0
0	1	1	0	0	26	1	0	0	0	27	27	0	0	34	3	0	0	0	37	37	2
0	0	0	0	0	4	1	0	0	0	5	5	0	0	16	1	1	0	0	18	18.5	0
0	0	0	0	0	8	1	0	1	0	10	11.3	0	0	6	2	0	0	0	8	8	0
0	0	0	0	0	3	0	0	0	0	3	3	0	0	7	2	0	0	0	9	9	0
0	0	0	0	0	4	1	1	0	0	6	6.5	0	0	6	1	0	0	0	7	7	0
0	0	0	0	0	19	3	1	1	0	24	25.8	0	0	35	6	1	0	0	42	42.5	0
0	0	0	0	0	4	0	0	0	0	4	4	0	0	6	2	0	0	0	8	8	0
0	0	0	0	0	6	1	1	0	0	8	8.5	0	0	10	0	0	0	0	10	10	1
0	0	0	0	0	7	0	0	0	0	7	7	0	0	5	1	1	0	0	7	7.5	0
0	0	0	0	0	6	0	0	0	0	6	6	0	0	8	0	1	0	0	9	9.5	0
0	0	0	0	0	23	1	1	0	0	25	25.5	0	0	29	3	2	0	0	34	35	1
0	0	0	0	0	2	1	0	1	0	4	5.3	0	0	11	2	0	0	0	13	13	0
0	0	0	0	0	4	1	0	0	0	5	5	0	0	5	1	1	1	0	8	9.8	0
0	0	0	0	0	8	1	0	0	0	9	9	0	0	12	1	0	0	0	13	13	0
0	0	0	0	0	8	1	1	0	0	10	10.5	0	0	12	0	0	0	0	12	12	0
0	0	0	0	0	22	4	1	1	0	28	29.8	0	0	40	4	1	1	0	46	47.8	0
0	0	0	0	0	12	0	0	0	0	12	12	2	0	17	2	0	0	0	21	19.4	0
0	0	0	0	0	7	0	0	0	0	7	7	0	0	15	2	0	0	0	17	17	0
0	0	0	0	0	10	0	0	0	0	10	10	0	0	11	2	0	0	0	13	13	0
0	0	0	0	0	9	1	0	0	0	10	10	0	0	8	1	0	0	0	9	9	0
0	0	0	0	0	38	1	0	0	0	39	39	2	0	51	7	0	0	0	60	58.4	0
0	0	0	0	0	32	1	0	0	0	33	33	0	0	14	0	0	0	0	14	14	0
0	0	0	0	0	16	1	0	0	0	17	17	0	0	8	0	0	0	0	8	8	0
0	0	0	0	0	15	0	0	0	0	15	15	0	0	15	2	0	0	0	17	17	0
0	0	0	0	0	17	1	0	0	0	18	18	0	0	16	3	0	0	0	19	19	0
0	0	0	0	0	80	3	0	0	0	83	83	0	0	53	5	0	0	0	58	58	0
0	0	0	1	1	25	1	0	0	0	28	26.6	1	0	16	1	0	0	0	18	17.2	0
0	0	0	0	0	14	2	0	0	0	16	16	0	0	21	1	0	0	0	22	22	0
0	0	0	0	0	15	3	1	0	0	19	19.5	0	0	20	1	1	0	0	22	22.5	0
0	0	0	0	0	14	2	0	0	0	16	16	0	0	11	2	0	0	0	13	13	0
0	0	0	1	1	68	8	1	0	0	79	78.1	1	0	68	5	1	0	0	75	74.7	0
0	0	0	0	0	13	0	1	0	0	14	14.5	0	0	20	1	0	0	0	21	21	0
0	0	0	0	0	15	0	0	0	0	15	15	0	0	21	0	0	0	0	21	21	0
0	0	0	0	0	12	1	0	0	0	13	13	0	1	18	3	0	0	0	22	21.4	0
0	0	0	0	0	6	2	0	0	0	8	8	0	0	18	1	0	0	0	19	19	0
0	0	0	0	0	46	3	1	0	0	50	50.5	0	1	77	5	0	0	0	83	82.4	0
0	2	2.5	1	1	383	33	7	3	0	428	434	4	1	556	49	5	1	0	616	616	5

C => B								C => C								
M/C	CAR	LGV	OGV1	OGV2	PSV	TOT	PCU	P/C	M/C	CAR	LGV	OGV1	OGV2	PSV	TOT	PCU
0	10	1	0	0	0	11	11	0	0	0	0	0	0	0	0	0
0	18	2	1	0	0	21	21.5	0	0	0	0	0	0	0	0	0
0	18	3	0	0	0	21	21	0	0	0	0	0	0	0	0	0
0	13	2	1	0	0	16	16.5	0	0	0	0	0	0	0	0	0
0	59	8	2	0	0	69	70	0	0	0	0	0	0	0	0	0
0	11	0	0	0	0	12	11.2	0	0	0	0	0	0	0	0	0
0	17	1	0	0	1	19	20	0	0	0	0	0	0	0	0	0
0	9	2	0	0	0	11	11	0	0	0	0	0	0	0	0	0
0	19	1	0	0	0	20	20	0	0	0	0	0	0	0	0	0
0	56	4	0	0	1	62	62.2	0	0	0	0	0	0	0	0	0
0	14	0	0	0	0	14	14	0	0	0	0	0	0	0	0	0
0	12	2	0	0	0	14	14	0	0	0	0	0	0	0	0	0
0	6	0	0	0	0	6	6	0	0	0	0	0	0	0	0	0
0	8	0	0	0	0	8	8	0	0	0	0	0	0	0	0	0
0	40	2	0	0	0	42	42	0	0	0	0	0	0	0	0	0
0	4	1	0	0	0	5	5	0	0	0	0	0	0	0	0	0
0	9	1	2	0	0	12	13	0	0	0	0	0	0	0	0	0
0	4	0	0	0	0	4	4	0	0	0	0	0	0	0	0	0
0	10	0	0	0	0	11	10.2	0	0	0	0	0	0	0	0	0
0	27	2	2	0	0	32	32.2	0	0	0	0	0	0	0	0	0
0	1	0	0	0	0	3	1.4	0	0	0	0	0	0	0	0	0
0	1	1	0	0	0	2	2	0	0	0	0	0	0	0	0	0
0	4	0	0	0	0	4	4	0	0	0	0	0	0	0	0	0
0	5	0	0	0	0	5	5	0	0	0	0	0	0	0	0	0
0	11	1	0	0	0	14	12.4	0	0	0	0	0	0	0	0	0
0	8	0	0	0	0	8	8	0	0	0	0	0	0	0	0	0
0	2	0	0	0	0	2	2	0	0	0	0	0	0	0	0	0
0	5	1	1	0	0	7	7.5	0	0	0	0	0	0	0	0	0
0	6	0	0	0	0	6	6	0	0	0	0	0	0	0	0	0
0	21	1	1	0	0	23	23.5	0	0	0	0	0	0	0	0	0
0	6	1	1	0	0	8	8.5	0	0	0	0	0	0	0	0	0
0	7	0	0	0	0	8	7.2	0	0	0	0	0	0	0	0	0
0	6	1	0	0	0	7	7	0	0	0	0	0	0	0	0	0
0	8	0	0	0	0	8	8	0	0	0	0	0	0	0	0	0
0	27	2	1	0	0	31	30.7	0	0	0	0	0	0	0	0	0
0	7	0	0	1	0	8	9.3	0	0	0	0	0	0	0	0	0
0	4	1	0	0	0	5	5	0	0	0	0	0	0	0	0	0
0	1	0	0	0	0	1	1	0	0	0	0	0	0	0	0	0
0	2	1	0	0	0	3	3	0	0	0	0	0	0	0	0	0
0	14	2	0	1	0	17	18.3	0	0	0	0	0	0	0	0	0
0	4	1	1	0	0	6	6.5	0	0	0	0	0	0	0	0	0
0	8	0	1	0	0	9	9.5	0	0	0	0	0	0	0	0	0
0	6	0	0	0	0	6	6	0	0	0	0	0	0	0	0	0
0	15	0	1	0	0	16	16.5	0	0	0	0	0	0	0	0	0
0	33	1	3	0	0	37	38.5	0	0	0	0	0	0	0	0	0
0	14	1	0	0	0	15	15	0	0	0	0	0	0	0	0	0
0	8	1	0	0	0	9	9	0	0	0	0	0	0	0	0	0
0	7	0	0	0	0	7	7	0	0	0	0	0	0	0	0	0
0	12	0	1	0	0	13	13.5	0	0	1	0	0	0	0	1	1
0	41	2	1	0	0	44	44.5	0	0	1	0	0	0	0	1	1
0	2	0	0	0	0	2	2	0	0	0	0	0	0	0	0	0
0	9	0	0	0	0	9	9	0	0	0	0	0	0	0	0	0
0	7	0	0	0	0	7	7	0	0	0	0	0	0	0	0	0
0	10	1	0	0	0	11	11	0	0	0	0	0	0	0	0	0
0	28	1	0	0	0	29	29	0	0	0	0	0	0	0	0	0
0	5	1	1	0	0	7	7.5	0	0	0	0	0	0	0	0	0
0	10	0	0	0	0	10	10	0	0	0	0	0	0	0	0	0
0	5	0	0	0	0	5	5	0	0	0	0	0	0	0	0	0
0	8	0	0	0	0	8	8	0	0	0	0	0	0	0	0	0
0	28	1	1	0	0	30	30.5	0	0	0	0	0	0	0	0	0
0	385	27	11	1	1	430	433.8	0	0	1	0	0	0	0	1	1



Appendix B – TRICS Data



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

TRIP RATE CALCULATION SELECTION PARAMETERS:

Land Use: 03 - RESIDENTIAL

Category: A - HOUSES PRIVATELY OWNED

Selected Vehicle Type: Total Vehicles

Selected regions and areas:

01	GREATER LONDON		
	BN	BARNET	2 days
	BT	BRENT	1 day
	EG	EALING	3 days
	EN	ENFIELD	2 days
	HO	HOUNSLOW	1 day
	KI	KINGSTON	2 days
	SK	SOUTHWARK	1 day
	SU	SUTTON	1 day
	WF	WALTHAM FOREST	1 day
02	SOUTH EAST		
	BO	BEDFORD	1 day
	CT	CENTRAL BEDFORDSHIRE	1 day
	ES	EAST SUSSEX	14 days
	EX	ESSEX	2 days
	HC	HAMPSHIRE	25 days
	HF	HERTFORDSHIRE	6 days
	KC	KENT	10 days
	MW	MEDWAY	2 days
	ON	LUTON	2 days
	RE	READING	9 days
	SC	SURREY	10 days
	SP	SOUTHAMPTON	1 day
	TK	THURROCK	1 day
	WB	WEST BERKSHIRE	3 days
	WS	WEST SUSSEX	17 days
03	SOUTH WEST		
	BC	BOURNEMOUTH CHRISTCHURCH & POOLE	2 days
	CW	CORNWALL	2 days
	DC	DORSET	4 days
	DV	DEVON	2 days
	GS	GLOUCESTERSHIRE	3 days
	NS	NORTH SOMERSET	6 days
	SD	SWINDON	1 day
	SM	SOMERSET	3 days
	TB	TORBAY	1 day
	WL	WILTSHIRE	1 day
04	EAST ANGLIA		
	CA	CAMBRIDGESHIRE	6 days
	NF	NORFOLK	22 days
	PB	PETERBOROUGH	4 days
	SF	SUFFOLK	9 days
05	EAST MIDLANDS		
	DS	DERBYSHIRE	1 day
	DY	DERBY	1 day
	LE	LEICESTERSHIRE	2 days
	LN	LINCOLNSHIRE	3 days
	NG	NOTTINGHAM	3 days
	NM	WEST NORTHAMPTONSHIRE	2 days
	NN	NORTH NORTHAMPTONSHIRE	1 day
	NT	NOTTINGHAMSHIRE	5 days
06	WEST MIDLANDS		
	OT	STOKE ON TRENT	1 day
	SH	SHROPSHIRE	3 days
	ST	STAFFORDSHIRE	6 days
	TE	TELFORD & WREKIN	3 days



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

	WK	WARWICKSHIRE	3 days
	WM	WEST MIDLANDS	6 days
	WO	WORCESTERSHIRE	6 days
07	YORKSHIRE & NORTH LINCOLNSHIRE		
	BY	BARNSELY	1 day
	DR	DONCASTER	1 day
	KH	KINGSTON UPON HULL	1 day
	LS	LEEDS	1 day
	NE	NORTH EAST LINCOLNSHIRE	3 days
	NY	NORTH YORKSHIRE	11 days
	RI	EAST RIDING OF YORKSHIRE	3 days
	SE	SHEFFIELD	2 days
	YO	YORK	2 days
08	NORTH WEST		
	AC	CHESHIRE WEST & CHESTER	5 days
	BB	BLACKBURN WITH DARWEN	3 days
	BP	BLACKPOOL	1 day
	EC	CHESHIRE EAST	6 days
	GM	GREATER MANCHESTER	11 days
	LC	LANCASHIRE	24 days
	MS	MERSEYSIDE	3 days
09	NORTH		
	CU	CUMBERLAND	2 days
	DH	DURHAM	3 days
	FU	WESTMORLAND & FURNESS	2 days
	IM	ISLE OF MAN	6 days
	TV	TEES VALLEY	1 day
	TW	TYNE & WEAR	3 days
10	WALES		
	CF	CARDIFF	3 days
	CM	CARMARTHENSHIRE	1 day
	CP	CAERPHILLY	1 day
	MT	MERTHYR TYDFIL	1 day
	PS	POWYS	2 days
	RC	RHONDDA CYNON TAFF	3 days
	VG	VALE OF GLAMORGAN	1 day
	WR	WREXHAM	1 day
11	SCOTLAND		
	AG	ANGUS	1 day
	AS	ABERDEENSHIRE	2 days
	EA	EAST AYRSHIRE	2 days
	FA	FALKIRK	2 days
	FI	FIFE	3 days
	GC	GLASGOW CITY	3 days
	HI	HIGHLAND	13 days
	PK	PERTH & KINROSS	1 day
	SR	STIRLING	1 day
12	CONNAUGHT		
	CS	SLIGO	4 days
	GA	GALWAY	4 days
	LT	LEITRIM	2 days
	MA	MAYO	2 days
	RO	ROSCOMMON	4 days
13	MUNSTER		
	CL	CLARE	2 days
	CR	CORK	1 day
	WA	WATERFORD	3 days
14	LEINSTER		
	CC	CARLOW	1 day
	KD	KILDARE	1 day
	KK	KILKENNY	4 days
	LU	LOUTH	1 day
	ME	MEATH	1 day



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

	WC	WICKLOW	2 days
	WX	WEXFORD	1 day
15	GREATER DUBLIN		
	DL	DUBLIN	9 days
16	ULSTER (REPUBLIC OF IRELAND)		
	CV	CAVAN	2 days
	DN	DONEGAL	6 days
	MG	MONAGHAN	2 days
17	ULSTER (NORTHERN IRELAND)		
	AN	ANTRIM	9 days
	AR	ARMAGH	1 day
	DE	DERRY	4 days
	DO	DOWN	2 days
	FE	FERMANAGH	1 day
	TY	TYRONE	1 day

This section displays the number of survey days per TRICS® sub-region in the selected set.

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Primary Filtering Selection:

This data displays the chosen trip rate parameter and its selected range. Only sites that fall within the parameter range are included in the trip rate calculation.

Parameter:	DWELLS
Actual Range:	4 to 4334 (units:DWELLS)
Range Selected by User:	4 to 4334 (units:DWELLS)
Parking Spaces Range:	6 - 2696

Public Transport Provision:

Selection by:	All Surveys Included
Date Range:	05/05/87 to 30/06/25

This data displays the range of survey dates selected. Only surveys that were conducted within this date range are included in the trip rate calculation.

Selected survey days:

Friday	46 days
Monday	57 days
Saturday	7 days
Sunday	33 days
Thursday	111 days
Tuesday	102 days
Wednesday	80 days

This data displays the number of selected surveys by day of the week.

Selected survey types:

Manual count	390
Direction ATC Count	46

This data displays the number of manual classified surveys and the number of unclassified ATC surveys, the total adding up to the overall number of surveys in the selected set. Manual surveys are undertaken using staff, whilst ATC surveys are undertaken using machines

Selected Locations:

Edge of Town	219 days
Edge of Town Centre	29 days
Neighbourhood Centre	72 days
Suburban Area	116 days

This data displays the number of surveys per main location category within the selected set. The main location categories consist of Free Standing, Edge of Town, Suburban Area, Neighbourhood Centre, Edge of Town Centre, Town Centre and Not Known.

Selected Location Sub Categories:

Built-Up Zone	1 days
Development Zone	1 days
No Sub Category	60 days
Residential Zone	317 days
Village	57 days

This data displays the number of surveys per location sub-category within the selected set. The location sub-categories consist of Commercial Zone, Industrial Zone, Development Zone, Residential Zone, Retail Zone, Built-Up Zone, Village, Out of Town, High Street and No Sub Category.

Inclusion of Servicing Vehicle Counts:

Servicing vehicles Excluded	11 days
Servicing vehicles Included	37 days
Servicing vehicles Unknown	388 days

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Secondary Filtering Selection:

Use Class:

C3 436 surveys

This data displays the number of surveys per Use Class classification within the selected set. The Use Classes Order (England) 2020 has been used for this purpose, which can be found within the Library module of TRICS®.

Population within 500m Range:

0 - 15312

Population within 1 mile:

1,000 or Less	5 surveys
1,001 to 5,000	84 surveys
10,001 to 15,000	100 surveys
15,001 to 20,000	56 surveys
20,001 to 25,000	40 surveys
25,001 to 50,000	41 surveys
5,001 to 10,000	89 surveys
50,001 to 100,000	5 surveys
Not Known	16 surveys

This data displays the number of selected surveys within stated 1-mile radii of population.

Population within 5 miles:

100,001 to 125,000	27 surveys
125,001 to 250,000	110 surveys
25,001 to 50,000	63 surveys
250,001 to 500,000	36 surveys
5,000 or Less	7 surveys
5,001 to 25,000	59 surveys
50,001 to 75,000	49 surveys
500,001 or More	25 surveys
75,001 to 100,000	51 surveys
Not Known	9 surveys

This data displays the number of selected surveys within stated 5-mile radii of population.

Car ownership within 5 miles:

0.6 to 1.0	149 surveys
1.1 to 1.5	248 surveys
1.6 to 2.0	30 surveys
Not Known	9 surveys

This data displays the number of selected surveys within stated ranges of average cars owned per residential dwelling, within a radius of 5-miles of selected survey sites.

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Petrol filling station:

This data displays the number of surveys within the selected set that include petrol filling station activity, and the number of surveys that do not.

Travel Plan:

No	356 surveys
Yes	80 surveys

This data displays the number of surveys within the selected set that were undertaken at sites with Travel Plans in place, and the number of surveys that were undertaken at sites without Travel Plans.

PTAL Rating:

1a (Low) - Very poor	1 surveys
1b - Very poor	1 surveys
2 - Poor	2 surveys
3 - Moderate	2 surveys
4 - Good	2 surveys
5 - Very good	1 surveys
No PTAL Present	427 surveys

This data displays the number of surveys within the selected set that include petrol filling station activity, and the number of surveys that do not.

COVID-19 Restrictions:

Yes - At least one survey within the selected data set was undertaken at a time of Covid-19 restrictions



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

1	AC-03-A-01	HOUSING	CESHIRE WEST & CHESTER
DELAMERE PARK NEAR NORTHWICH CUDDINGTON Neighbourhood Centre Village Site area: 37.29999923706055 hect Survey date: Thursday 19/10/1989			
			Survey Type: Manual
2	AC-03-A-02	DETACHED	CESHIRE WEST & CHESTER
WHITCHURCH ROAD CHESTER BOUGHTON HEATH Suburban Area Residential Zone Site area: 0.47999998927116394 hect Survey date: Tuesday 22/05/2012			
			Survey Type: Manual
3	AC-03-A-04	TOWN HOUSES	CESHIRE WEST & CHESTER
LONDON ROAD NORTHWICH LEFTWICH Suburban Area Residential Zone Site area: 0.5 hect Survey date: Thursday 06/06/2019			
			Survey Type: Manual
4	AC-03-A-05	SEMI-DETACHED & TERRACED	CESHIRE WEST & CHESTER
MEADOW DRIVE NORTHWICH BARNTON Neighbourhood Centre Village Site area: 0.9100000262260437 hect Survey date: Friday 30/04/2021			
			Survey Type: Manual
5	AC-03-A-06	DETACHED HOUSES	CESHIRE WEST & CHESTER
COMMON LANE NEAR CHESTER WAVERTON Neighbourhood Centre Village Site area: 6.800000190734863 hect Survey date: Friday 29/04/2022			
			Survey Type: Manual
6	AG-03-A-01	BUNGALOWS/DET.	ANGUS
KEPTIE ROAD ARBROATH Suburban Area Residential Zone Site area: 0.6800000071525574 hect Survey date: Tuesday 22/05/2012			
			Survey Type: Manual
7	AN-03-A-01	SEMI-DETACHED	ANTRIM
CAIRNSHILL ROAD BELFAST CASTLEREAGH Suburban Area Residential Zone Site area: 15 hect Survey date: Thursday 23/02/1995			
			Survey Type: Manual
8	AN-03-A-02	SEMI DETACHED	ANTRIM



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

<p>CAIRNSHILL ROAD BELFAST CAIRNSHILL Edge of Town Residential Zone Site area: 12.699999809265137 hect Survey date: Thursday 14/11/2002</p>				Survey Type: Manual
<p>9 KNOCKMORE ROAD LISBURN Edge of Town Residential Zone Site area: 3.700000047683716 hect Survey date: Thursday 14/11/2002</p>	AN-03-A-03	SEMI DETACHED	ANTRIM	Survey Type: Manual
<p>10 KNOCKMORE ROAD LISBURN Edge of Town Residential Zone Site area: 15.600000381469727 hect Survey date: Saturday 27/09/2003</p>	AN-03-A-05	DETACHED/SEMI DET.	ANTRIM	Survey Type: Manual
<p>11 GLENMOUNT ROAD NEWTOWNABBEY Suburban Area No Sub Category Site area: 3.1500000953674316 hect Survey date: Thursday 10/06/2010</p>	AN-03-A-06	SEMI-DET.	ANTRIM	Survey Type: Manual
<p>12 CASTLE WAY ANTRIM Suburban Area Residential Zone Site area: 2.759999990463257 hect Survey date: Tuesday 20/12/2011</p>	AN-03-A-07	SEMI DETACHED/TERRACED HOUSING	ANTRIM	Survey Type: Manual
<p>13 BALLINDERRY ROAD LISBURN Suburban Area Residential Zone Site area: 8.680000305175781 hect Survey date: Tuesday 29/10/2013</p>	AN-03-A-08	HOUSES & FLATS	ANTRIM	Survey Type: Manual
<p>14 SLOEFIELD DRIVE CARRICKFERGUS Edge of Town No Sub Category Site area: 9.479999542236328 hect Survey date: Wednesday 12/10/2016</p>	AN-03-A-09	DETACHED & SEMI-DETACHED	ANTRIM	Survey Type: Manual
<p>15 FERRARD GRANGE ANTRIM Suburban Area Residential Zone Site area: 3.5 hect</p>	AN-03-A-10	DETACHED & SEMI-DETACHED	ANTRIM	



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Survey date: Friday 07/06/2024

Survey Type: Manual

16 AR-03-A-01 MIXED HOUSES ARMAGH
BIRCHDALE MANOR
LURGAN
Edge of Town
Residential Zone
Site area: 4.039999961853027 hect
Survey date: Tuesday 15/06/2010
Survey Type: Manual

17 AS-03-A-01 DETACHED/SEMI D. ABERDEENSHIRE
BERRYMUIR ROAD
PORTLETHEN
Edge of Town
Residential Zone
Site area: 4.699999809265137 hect
Survey date: Wednesday 09/02/2000
Survey Type: Manual

18 AS-03-A-02 MIXED HOUSES ABERDEENSHIRE
FARROCHIE ROAD
STONEHAVEN
Edge of Town
Residential Zone
Site area: 5.300000190734863 hect
Survey date: Wednesday 20/04/2022
Survey Type: Manual

19 BB-03-A-01 DETACHED/SEMI D. BLACKBURN WITH DARWEN
LAMMACK ROAD
BLACKBURN
LAMMACK
Edge of Town
Residential Zone
Site area: 2 hect
Survey date: Tuesday 20/09/1994
Survey Type: Manual

20 BB-03-A-02 DETACHED/SEMI D. BLACKBURN WITH DARWEN
RHODES AVENUE
BLACKBURN
FOUR LANE ENDS
Edge of Town
Residential Zone
Site area: 4.5 hect
Survey date: Tuesday 20/09/1994
Survey Type: Manual

21 BB-03-A-03 DETACHED/SEMI D. BLACKBURN WITH DARWEN
REVIDGE ROAD
BLACKBURN
FOUR LANE ENDS
Edge of Town
Residential Zone
Site area: 7.599999904632568 hect
Survey date: Thursday 10/06/2004
Survey Type: Manual

22 BC-03-A-01 MIXED HOUSES BOURNEMOUTH
CHRISTCHURCH & POOLE
A351 SANDFORD ROAD
NEAR POOLE
SANDFORD
Neighbourhood Centre
Village
Site area: 7.099999904632568 hect
Survey date: Thursday 18/04/1996
Survey Type: Manual

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

23	BC-03-A-02	BUNGALOWS	BOURNEMOUTH CHRISTCHURCH & POOLE
HURSTDENE ROAD BOURNEMOUTH CASTLE LANE WEST Edge of Town Residential Zone Site area: 1.850000023841858 hect Survey date: Monday 24/03/2014			Survey Type: Manual
24	BN-03-A-01	SEMI DETACHED	BARNET
NORRY'S ROAD COCKFOSTERS Suburban Area Residential Zone Site area: 0.44999998807907104 hect Survey date: Thursday 20/10/2005			Survey Type: Manual
25	BN-03-A-04	MIXED HOUSES & FLATS	BARNET
SWEETS WAY WHETSTONE Neighbourhood Centre Residential Zone Site area: 4.650000095367432 hect Survey date: Tuesday 21/09/2021			Survey Type: Manual
26	BO-03-A-01	DETACHED HOUSES	BEDFORD
CARNOUSTIE DRIVE BEDFORD GREAT DENHAM Edge of Town Residential Zone Site area: 4.230000019073486 hect Survey date: Thursday 15/10/2020			Survey Type: Manual
27	BP-03-A-01	SEMI-DETACHED	BLACKPOOL
WATSON ROAD BLACKPOOL Edge of Town Centre Residential Zone Site area: 0.800000011920929 hect Survey date: Friday 14/06/2013			Survey Type: Manual
28	BT-03-A-01	SEMI DETACHED	BRENT
KENTON ROAD BRENT Suburban Area Residential Zone Site area: 4.420000076293945 hect Survey date: Tuesday 20/11/2007			Survey Type: Manual
29	BY-03-A-01	BUNGALOWS & DETACHED	BARNSELY
CHURCH LANE NEAR BARNSELY WORSBROUGH Neighbourhood Centre Village Site area: 1.1690000295639038 hect Survey date: Wednesday 09/09/2020			Survey Type: Manual
30	CA-03-A-01	SEMI D./TERRACED	CAMBRIDGESHIRE
FALLOWFIELD CAMBRIDGE			

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

CHESTERTON
Edge of Town
Residential Zone
Site area: 5 hect
Survey date: Tuesday 06/02/2001 Survey Type: Manual

31 **CA-03-A-06** **MIXED HOUSES** **CAMBRIDGESHIRE**
CRAFT'S WAY
NEAR CAMBRIDGE
BAR HILL
Neighbourhood Centre
Village
Site area: 10.25 hect
Survey date: Friday 22/06/2018 Survey Type: Manual

32 **CA-03-A-07** **MIXED HOUSES** **CAMBRIDGESHIRE**
FIELD END
NEAR ELY
WITCHFORD
Neighbourhood Centre
Village
Site area: 1.19 hect
Survey date: Thursday 27/05/2021 Survey Type: Manual

33 **CA-03-A-08** **DETACHED & SEMI-DETACHED** **CAMBRIDGESHIRE**
GIDDING ROAD
SAWTRY
Neighbourhood Centre
Village
Site area: 2.680000066757202 hect
Survey date: Thursday 13/10/2022 Survey Type: Manual

34 **CA-03-A-09** **MIXED HOUSES & FLATS** **CAMBRIDGESHIRE**
EDDINGTON AVENUE
CAMBRIDGE
EDDINGTON
Edge of Town
Development Zone
Site area: 3.57 hect
Survey date: Thursday 28/11/2024 Survey Type: Manual

35 **CA-03-A-10** **MIXED HOUSES & FLATS** **CAMBRIDGESHIRE**
FIELD END
NEAR ELY
WITCHFORD
Neighbourhood Centre
Village
Site area: 5.75 hect
Survey date: Thursday 15/05/2025 Survey Type: Manual

36 **CC-03-A-01** **DETACHED HOUSES** **CARLOW**
R417 ANTHY ROAD
CARLOW
Edge of Town
Residential Zone
Site area: 1.4500000476837158 hect
Survey date: Wednesday 25/05/2016 Survey Type: Manual

37 **CF-03-A-01** **MIXED HOUSES** **CARDIFF**
VIRGIL STREET
CARDIFF
NINIAN PARK
Suburban Area

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

No Sub Category
Site area: 15 hect
Survey date: Thursday 17/10/2002
Survey Type: Manual

38 CF-03-A-02 MIXED HOUSES CARDIFF
DROPE ROAD
CARDIFF
Edge of Town
Residential Zone
Site area: 8.100000381469727 hect
Survey date: Friday 05/10/2007
Survey Type: Manual

39 CF-03-A-03 DETACHED CARDIFF
LLANTRISANT ROAD
CARDIFF
Suburban Area
Residential Zone
Site area: 1.5 hect
Survey date: Monday 08/10/2007
Survey Type: Manual

40 CL-03-A-01 PRIVATELY OWNED HOUSES CLARE
TULLA ROAD
ENNIS
KNOCKANOURA
Neighbourhood Centre
Residential Zone
Site area: 2.37 hect
Survey date: Thursday 24/10/2024
Survey Type: Manual

41 CL-03-A-02 PRIVATELY OWNED HOUSES CLARE
GORT ROAD
ENNIS
LIFFORD
Suburban Area
Residential Zone
Site area: 3.72 hect
Survey date: Friday 25/10/2024
Survey Type: Manual

42 CM-03-A-01 DETAT./BG'LOWS CARMARTHENSHIRE
TREVAUGHAN ROAD
CARMARTHEN
TREVAUGHAN
Edge of Town
No Sub Category
Site area: 1.2999999523162842 hect
Survey date: Saturday 13/09/2008
Survey Type: Manual

43 CP-03-A-02 SEMI DETACHED CAERPHILLY
THE RISE
PENGAM
Suburban Area
No Sub Category
Site area: 0.625 hect
Survey date: Monday 05/09/2005
Survey Type: Manual

44 CR-03-A-01 BUNGALOWS CORK
CURRAGH ROAD
CORK
TURNER'S CROSS
Suburban Area
Residential Zone
Site area: 3.4000000953674316 hect
Survey date: Thursday 08/12/2005
Survey Type: Manual



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

45	CS-03-A-01	TERRACED	SLIGO
CIRCULAR ROAD SLIGO Edge of Town Centre No Sub Category Site area: 1.5499999523162842 hect Survey date: Thursday 14/06/2007			
			Survey Type: Manual
46	CS-03-A-02	DETACHED	SLIGO
CHURCH HILL SLIGO Suburban Area No Sub Category Site area: 1.850000023841858 hect Survey date: Thursday 14/06/2007			
			Survey Type: Manual
47	CS-03-A-03	MIXED HOUSES	SLIGO
TOP ROAD STRANDHILL STRANDHILL Neighbourhood Centre Village Site area: 1.2000000476837158 hect Survey date: Thursday 27/10/2016			
			Survey Type: Manual
48	CS-03-A-04	DETACHED & SEMI-DETACHED	SLIGO
R292 STRANDHILL Neighbourhood Centre Village Site area: 1.6799999475479126 hect Survey date: Thursday 27/10/2016			
			Survey Type: Manual
49	CT-03-A-03	MIXED HOUSES	CENTRAL BEDFORDSHIRE
ARLESEY ROAD STOTFOLD Edge of Town Residential Zone Site area: 3.690000057220459 hect Survey date: Tuesday 27/06/2023			
			Survey Type: Manual
50	CU-03-A-02	SEMI DETACHED	CUMBERLAND
HAWKSHEAD AVENUE WORKINGTON Edge of Town Residential Zone Site area: 1.7999999523162842 hect Survey date: Thursday 20/11/2008			
			Survey Type: Manual
51	CU-03-A-03	SEMI DETACHED	CUMBERLAND
MOORCLOSE ROAD WORKINGTON SALTERBACK Edge of Town No Sub Category Site area: 2.9000000953674316 hect Survey date: Friday 24/04/2009			
			Survey Type: Manual
52	CV-03-A-02	DETACHED & SEMI DETACHED	CAVAN
R212 DUBLIN ROAD CAVAN KILLYNEBBER			

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Edge of Town
No Sub Category
Site area: 47 hect
Survey date: Monday 22/05/2017
Survey Type: Manual

53 CV-03-A-03 DETACHED HOUSES CAVAN
R212 DUBLIN ROAD
CAVAN
PULLAMORE NEAR
Edge of Town
No Sub Category
Site area: 2.5999999046325684 hect
Survey date: Monday 22/05/2017
Survey Type: Manual

54 CW-03-A-01 TERRACED CORNWALL
ALVERTON ROAD
PENZANCE
Suburban Area
Residential Zone
Site area: 0.20000000298023224 hect
Survey date: Thursday 30/06/2005
Survey Type: Manual

55 CW-03-A-02 SEMI D./DETACHED CORNWALL
BOSVEAN GARDENS
TRURO
Suburban Area
Residential Zone
Site area: 3.3499999046325684 hect
Survey date: Tuesday 18/09/2007
Survey Type: Manual

56 DC-03-A-01 DETACHED DORSET
ISAACS CLOSE
POOLE
Suburban Area
Residential Zone
Site area: 1.840000033378601 hect
Survey date: Wednesday 16/07/2008
Survey Type: Manual

57 DC-03-A-06 DETACHED DORSET
WOODLANDS ESTATE
NEAR WAREHAM
SANDFORD
Neighbourhood Centre
Village
Site area: 7.099999904632568 hect
Survey date: Thursday 25/04/1991
Survey Type: Manual

58 DC-03-A-10 MIXED HOUSES DORSET
ADDISON CLOSE
GILLINGHAM
Edge of Town
Residential Zone
Site area: 1.399999976158142 hect
Survey date: Wednesday 09/11/2022
Survey Type: Manual

59 DC-03-A-11 MIXED HOUSES DORSET
A350
SHAFTESBURY
Edge of Town
No Sub Category
Site area: 6.630000114440918 hect
Survey date: Tuesday 31/10/2023
Survey Type: Manual



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

60 STATION ROAD MAGHERAFELT Edge of Town Residential Zone Site area: 4.5 hect Survey date: Thursday 07/11/2002	DE-03-A-01	SEMI DET. & DETACHED	DERRY	Survey Type: Manual
61 GREENHALL HIGHWAY COLERAINE Neighbourhood Centre Residential Zone Site area: 7.900000095367432 hect Survey date: Thursday 07/11/2002	DE-03-A-02	DETACHED	DERRY	Survey Type: Manual
62 ABBEYDALE LONDONDERRY KILFENNAN Suburban Area Residential Zone Site area: 9.899999618530273 hect Survey date: Thursday 02/10/2003	DE-03-A-03	BUNGALOWS	DERRY	Survey Type: Manual
63 GREENHALL HIGHWAY COLERAINE Edge of Town Residential Zone Site area: 1.600000023841858 hect Survey date: Thursday 19/05/2022	DE-03-A-04	SEMI-DETACHED & TERRACED	DERRY	Survey Type: Manual
64 GREENFIELDS ROAD BISHOP AUCKLAND Suburban Area Residential Zone Site area: 0.8999999761581421 hect Survey date: Tuesday 28/03/2017	DH-03-A-01	SEMI DETACHED	DURHAM	Survey Type: Manual
65 LEAZES LANE BISHOP AUCKLAND ST HELEN AUCKLAND Neighbourhood Centre Residential Zone Site area: 4.03000020980835 hect Survey date: Monday 27/03/2017	DH-03-A-02	MIXED HOUSES	DURHAM	Survey Type: Manual
66 PILGRIMS WAY DURHAM Edge of Town Residential Zone Site area: 5.603000164031982 hect Survey date: Friday 19/10/2018	DH-03-A-03	SEMI-DETACHED & TERRACED	DURHAM	Survey Type: Manual
67 COLLINS AVENUE DUBLIN Suburban Area Residential Zone	DL-03-A-02	SEMI DETACHED	DUBLIN	

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Site area: 13.899999618530273 hect
Survey date: Monday 25/06/2007

Survey Type: Manual

68 RAHENY ROAD DUBLIN RAHENY Neighbourhood Centre Residential Zone Site area: 5.889999866485596 hect Survey date: Tuesday 20/04/2010	DL-03-A-03	TERRACED/SEMI-DET.	DUBLIN
--	-------------------	---------------------------	---------------

Survey Type: Manual

69 UPPER KILMACUD ROAD DUBLIN DUNDRUM Suburban Area Residential Zone Site area: 9.920000076293945 hect Survey date: Saturday 01/05/2010	DL-03-A-05	MIXED HOUSES	DUBLIN
---	-------------------	---------------------	---------------

Survey Type: Manual

70 UPPER KILMACUD ROAD DUBLIN DUNDRUM Edge of Town Residential Zone Site area: 9.239999771118164 hect Survey date: Friday 30/04/2010	DL-03-A-06	DETACHED	DUBLIN
--	-------------------	-----------------	---------------

Survey Type: Manual

71 CASTLE DAWSON DUBLIN BLACKROCK Edge of Town Centre Residential Zone Site area: 1.7000000476837158 hect Survey date: Monday 26/09/2011	DL-03-A-07	SEMI DET./TERRACED	DUBLIN
--	-------------------	---------------------------	---------------

Survey Type: Manual

72 CASTLE PARK ROAD DUBLIN DALKEY Suburban Area Residential Zone Site area: 1.100000023841858 hect Survey date: Monday 26/09/2011	DL-03-A-08	VARIOUS HOUSES	DUBLIN
---	-------------------	-----------------------	---------------

Survey Type: Manual

73 RATHFARNHAM ROAD DUBLIN RATHFARNHAM Neighbourhood Centre No Sub Category Site area: 0.27000001072883606 hect Survey date: Friday 07/09/2012	DL-03-A-09	TERRACED	DUBLIN
--	-------------------	-----------------	---------------

Survey Type: Manual

74 R124 MALAHIDE SAINT HELENS Edge of Town Residential Zone	DL-03-A-10	SEMI DETACHED & DETACHED	DUBLIN
---	-------------------	-------------------------------------	---------------

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Site area: 2.9000000953674316 hect
Survey date: Wednesday 20/06/2018

Survey Type: Manual

75 **DL-03-A-11** **SEMI-DETACHED HOUSES** **DUBLIN**
GRACE PARK ROAD
DUBLIN
WHITEHALL
Suburban Area
Residential Zone
Site area: 0.38999998569488525 hect
Survey date: Wednesday 19/05/2021

Survey Type: Manual

76 **DN-03-A-03** **DETACHED/SEMI-DETACHED** **DONEGAL**
THE GRANGE
LETTERKENNY
GLENCAR IRISH
Edge of Town
Residential Zone
Site area: 3.200000047683716 hect
Survey date: Monday 01/09/2014

Survey Type: Manual

77 **DN-03-A-04** **SEMI-DETACHED** **DONEGAL**
GORTLEE ROAD
LETTERKENNY
GORTLEE
Edge of Town
Residential Zone
Site area: 4.150000095367432 hect
Survey date: Friday 26/09/2014

Survey Type: Manual

78 **DN-03-A-05** **DETACHED/SEMI-DETACHED** **DONEGAL**
GORTLEE ROAD
LETTERKENNY
GORTLEE
Suburban Area
Residential Zone
Site area: 7.239999771118164 hect
Survey date: Wednesday 03/09/2014

Survey Type: Manual

79 **DN-03-A-06** **DETACHED HOUSING** **DONEGAL**
GLENFIN ROAD
BALLYBOFEY
Edge of Town
Residential Zone
Site area: 1.0199999809265137 hect
Survey date: Wednesday 10/10/2018

Survey Type: Manual

80 **DN-03-A-07** **DETACHED & SEMI-DETACHED** **DONEGAL**
ST ORANS ROAD
BUNCRANA
Edge of Town Centre
Residential Zone
Site area: 0.9919999837875366 hect
Survey date: Wednesday 29/05/2019

Survey Type: Manual

81 **DN-03-A-08** **SEMI DETACHED & DETACHED** **DONEGAL**
CHURCH ROAD
CARNDONAGH
Suburban Area
Residential Zone
Site area: 1.8799999952316284 hect
Survey date: Wednesday 30/09/2020

Survey Type: Manual



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

82 RATHFRILAND ROAD BANBRIDGE Edge of Town No Sub Category Site area: 5.599999904632568 hect Survey date: Friday 18/10/2002	DO-03-A-01	TERRACED	DOWN	Survey Type: Manual
83 OLD MILL HEIGHTS BELFAST DUNDONALD Edge of Town Residential Zone Site area: 4.110000133514404 hect Survey date: Wednesday 23/10/2013	DO-03-A-03	DETACHED/SEMI DETACHED	DOWN	Survey Type: Manual
84 A19 BENTLEY ROAD DONCASTER BENTLEY RISE Suburban Area Residential Zone Site area: 1.7300000190734863 hect Survey date: Wednesday 18/09/2013	DR-03-A-01	SEMI DETACHED HOUSES	DONCASTER	Survey Type: Manual
85 THE AVENUE DRONFIELD HOLMESDALE Neighbourhood Centre Residential Zone Site area: 0.800000011920929 hect Survey date: Thursday 22/06/2006	DS-03-A-01	SEMI D./TERRACED	DERBYSHIRE	Survey Type: Manual
86 MILLHEAD ROAD HONITON Suburban Area Residential Zone Site area: 4.039999961853027 hect Survey date: Friday 25/09/2015	DV-03-A-02	HOUSES & BUNGALOWS	DEVON	Survey Type: Manual
87 LOWER BRAND LANE HONITON Suburban Area Residential Zone Site area: 2.0199999809265137 hect Survey date: Monday 28/09/2015	DV-03-A-03	TERRACED & SEMI DETACHED	DEVON	Survey Type: Manual
88 RADBOURNE LANE DERBY Edge of Town Residential Zone Site area: 16.450000762939453 hect Survey date: Tuesday 10/07/2018	DY-03-A-01	MIXED HOUSES	DERBY	Survey Type: Manual
89 TALISKER AVENUE KILMARNOCK Edge of Town	EA-03-A-01	DETACHED	EAST AYRSHIRE	

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Residential Zone

Site area: 1.7999999523162842 hect

Survey date: Thursday 05/06/2008

Survey Type: Manual

90 DALRY ROAD STEWARTON Edge of Town Residential Zone Site area: 5.400000095367432 hect Survey date:	EA-03-A-02	DETACHED	EAST AYRSHIRE	Survey Type: Manual
91 SYDNEY ROAD CREWE Edge of Town Residential Zone Site area: 6.420000076293945 hect Survey date: Tuesday 14/10/2008	EC-03-A-01	HOUSES/FLATS	CESHIRE EAST	Survey Type: Manual
92 SPRING GARDENS CREWE Suburban Area Residential Zone Site area: 2.4000000953674316 hect Survey date:	EC-03-A-02	SEMI-DETACHED	CESHIRE EAST	Survey Type: Manual
93 LIME TREE AVENUE CREWE Edge of Town Residential Zone Site area: 0.6899999976158142 hect Survey date:	EC-03-A-03	DETACHED/SEMI-DET.	CESHIRE EAST	Survey Type: Manual
94 SYDNEY ROAD CREWE SYDNEY Edge of Town Residential Zone Site area: 0.8399999737739563 hect Survey date: Tuesday 14/10/2008	EC-03-A-04	DETACHED	CESHIRE EAST	Survey Type: Manual
95 CREWE ROAD CREWE Suburban Area No Sub Category Site area: 5.320000171661377 hect Survey date: Tuesday 14/10/2008	EC-03-A-05	SEMI-DET./BUNGALOWS	CESHIRE EAST	Survey Type: Manual
96 GREYSTOKE ROAD MACCLESFIELD HURDSFIELD Edge of Town Residential Zone Site area: 0.7300000190734863 hect Survey date: Monday 24/11/2014	EC-03-A-06	TERRACED HOUSES	CESHIRE EAST	Survey Type: Manual
97	EG-03-A-01	HOUSING	EALING	

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

DELAMERE ROAD EALING COMMON Suburban Area Residential Zone Site area: 4.599999904632568 hect Survey date: Tuesday 09/07/1991 Survey Type: Manual			
98	EG-03-A-02	HOUSING	EALING
WELLAND GARDENS SOUTH GREENFORD Neighbourhood Centre Residential Zone Site area: 35 hect Survey date: Thursday 13/06/1991 Survey Type: Manual			
99	EG-03-A-04	SEMI D./TERRACED	EALING
VALE LANE WEST ACTON Suburban Area No Sub Category Site area: 4.699999809265137 hect Survey date: Thursday 13/06/1991 Survey Type: Manual			
100	EN-03-A-01	TERRACED & SEMI-DETACHED	ENFIELD
BOLLINGBROKE PARK COCKFOSTERS Edge of Town Residential Zone Site area: 0.7099999785423279 hect Survey date: Wednesday 24/11/2021 Survey Type: Manual			
101	EN-03-A-02	DETACHED HOUSES	ENFIELD
DUCHY ROAD HADLEY WOOD Edge of Town Residential Zone Site area: 0.6700000166893005 hect Survey date: Wednesday 14/09/2022 Survey Type: Manual			
102	ES-03-A-01	MIXED HOUSES/FLATS	EAST SUSSEX
OLD MALLING WAY LEWES SOUTH MALLING Edge of Town Residential Zone Site area: 12.699999809265137 hect Survey date: Thursday 29/03/2001 Survey Type: Manual			
103	ES-03-A-02	PRIVATE HOUSING	EAST SUSSEX
SOUTH COAST ROAD PEACEHAVEN Edge of Town Residential Zone Site area: 0.5 hect Survey date: Friday 18/11/2011 Survey Type: Manual			
104	ES-03-A-03	MIXED HOUSES & FLATS	EAST SUSSEX
SHEPHAM LANE POLEGATE Edge of Town Residential Zone Site area: 9.90999984741211 hect Survey date: Monday 11/07/2016 Survey Type: Manual			

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

105 NEW ROAD HAILSHAM HELLINGLY Edge of Town Residential Zone Site area: 3.490000009536743 hect Survey date: Thursday 07/11/2019	ES-03-A-07	MIXED HOUSES & FLATS	EAST SUSSEX	Survey Type: Manual
106 WATERGATE BEXHILL-ON-SEA Edge of Town Residential Zone Site area: 5.409999847412109 hect Survey date: Thursday 28/09/2023	ES-03-A-10	MIXED HOUSES & FLATS	EAST SUSSEX	Survey Type: Manual
107 BISHOPS LANE RINGMER Neighbourhood Centre Village Site area: 4.340000152587891 hect Survey date: Thursday 28/09/2023	ES-03-A-11	MIXED HOUSES	EAST SUSSEX	Survey Type: Manual
108 HOREBEECH LANE HORAM Neighbourhood Centre Village Site area: 8.109999656677246 hect Survey date: Tuesday 03/10/2023	ES-03-A-12	MIXED HOUSES & FLATS	EAST SUSSEX	Survey Type: Manual
109 A265 HEATHFIELD Edge of Town Residential Zone Site area: 1.7000000476837158 hect Survey date: Monday 18/03/2024	ES-03-A-13	DETACHED HOUSES	EAST SUSSEX	Survey Type: Manual
110 RATTLE ROAD NEAR EASTBOURNE STONE CROSS Edge of Town Residential Zone Site area: 3.4000000953674316 hect Survey date: Tuesday 30/04/2024	ES-03-A-14	MIXED HOUSES & FLATS	EAST SUSSEX	Survey Type: Manual
111 RAILWAY ROAD NEWHAVEN Edge of Town Centre No Sub Category Site area: 2.8299999237060547 hect Survey date: Friday 28/06/2024	ES-03-A-17	MIXED HOUSES & FLATS	EAST SUSSEX	Survey Type: Manual
112 WRESTWOOD ROAD BEXHILL-ON-SEA Edge of Town	ES-03-A-19	MIXED HOUSES & FLATS	EAST SUSSEX	

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Residential Zone

Site area: 6.699999809265137 hect

Survey date: Wednesday 09/10/2024

Survey Type: Manual

113 NEW ROAD HAILSHAM HELLINGLY Edge of Town Residential Zone Site area: 0.51 hect Survey date: Wednesday 06/11/2024	ES-03-A-20	DETACHED & SEMI-DETACHED	EAST SUSSEX	Survey Type: Manual
--	-------------------	-------------------------------------	--------------------	---------------------

114 PARK ROAD HAILSHAM HELLINGLY Edge of Town Residential Zone Site area: 8.24 hect Survey date: Wednesday 26/03/2025	ES-03-A-21	MIXED HOUSES & FLATS	EAST SUSSEX	Survey Type: Manual
---	-------------------	---------------------------------	--------------------	---------------------

115 THE FAIRWAY NEWHAVEN Edge of Town Residential Zone Site area: 2.5 hect Survey date: Tuesday 22/04/2025	ES-03-A-22	MIXED HOUSES	EAST SUSSEX	Survey Type: Manual
---	-------------------	---------------------	--------------------	---------------------

116 MANOR ROAD CHIGWELL GRANGE HILL Edge of Town Residential Zone Site area: 6.119999885559082 hect Survey date: Monday 27/11/2017	EX-03-A-02	DETACHED & SEMI-DETACHED	ESSEX	Survey Type: Manual
--	-------------------	-------------------------------------	--------------	---------------------

117 KESTREL GROVE RAYLEIGH Edge of Town Residential Zone Site area: 3.5999999046325684 hect Survey date: Monday 27/09/2021	EX-03-A-03	MIXED HOUSES	ESSEX	Survey Type: Manual
---	-------------------	---------------------	--------------	---------------------

118 MANDELA AVENUE FALKIRK Suburban Area Residential Zone Site area: 0.8399999737739563 hect Survey date: Thursday 30/05/2013	FA-03-A-01	SEMI-DETACHED/TERRACED	FALKIRK	Survey Type: Manual
--	-------------------	-------------------------------	----------------	---------------------

119 ROSEBANK AVENUE & SPRINGFIELD DRIVE FALKIRK Suburban Area Residential Zone Site area: 4.690000057220459 hect Survey date: Wednesday 29/05/2013	FA-03-A-02	MIXED HOUSES	FALKIRK	Survey Type: Manual
---	-------------------	---------------------	----------------	---------------------



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

120 CASTLECOOLE ROAD ENNISKILLEN Edge of Town Residential Zone Site area: 7.199999809265137 hect Survey date: Friday 08/11/2002	FE-03-A-01	MIXED HOUSES	FERMANAGH	Survey Type: Manual
121 HILLVIEW ROAD BALMULLO Neighbourhood Centre Village Site area: 7 hect Survey date: Thursday 24/06/1999	FI-03-A-01	BUNGALOWS	FIFE	Survey Type: Manual
122 WAROUT ROAD GLENROTHES Suburban Area Residential Zone Site area: 3.5 hect Survey date: Monday 16/05/2005	FI-03-A-02	SEMI DETACHED	FIFE	Survey Type: Manual
123 WOODMILL ROAD DUNFERMLINE Edge of Town Residential Zone Site area: 7.5 hect Survey date: Monday 30/04/2007	FI-03-A-03	MIXED HOUSES	FIFE	Survey Type: Manual
124 KENDAL PARK ESTATE KENDAL SOUTH LAKELAND Edge of Town No Sub Category Site area: 11.600000381469727 hect Survey date: Tuesday 25/09/1990	FU-03-A-01	SEMI DETACHED	WESTMORLAND & FURNESS	Survey Type: Manual
125 MACADAM WAY PENRITH Edge of Town Centre Residential Zone Site area: 1.5099999904632568 hect Survey date: Tuesday 21/06/2016	FU-03-A-02	DETACHED/TERRACED HOUSING	WESTMORLAND & FURNESS	Survey Type: Manual
126 HEADFORD ROAD GALWAY KNOCKAYARRAGH Edge of Town No Sub Category Site area: 5.0999999904632568 hect Survey date: Wednesday 20/09/2006	GA-03-A-01	SEMI DETACHED	GALWAY	Survey Type: Manual
127 BOHERMORE GALWAY TOWNPARKS	GA-03-A-02	TERRACED	GALWAY	

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Suburban Area
Residential Zone
Site area: 7 hect
Survey date: Tuesday 19/09/2006 Survey Type: Manual

128 MONEENEGEISHA ROAD GALWAY WELLPARK Suburban Area Built-Up Zone Site area: 0.8999999761581421 hect Survey date: Wednesday 20/09/2006	GA-03-A-03	SEMI DET./TERRACED	GALWAY
---	-------------------	---------------------------	---------------

Survey Type: Manual

129 R347 CAHEROYN ROAD ATHENRY Edge of Town Centre Residential Zone Site area: 1.0800000429153442 hect Survey date: Tuesday 09/10/2012	GA-03-A-04	SEMI DET. & BUNGALOWS	GALWAY
---	-------------------	----------------------------------	---------------

Survey Type: Manual

130 ABERUTHUREN DRIVE GLASGOW SHETTLESTON Suburban Area Residential Zone Site area: 1.100000023841858 hect Survey date: Thursday 17/03/1988	GC-03-A-01	TERRACED	GLASGOW CITY
---	-------------------	-----------------	---------------------

Survey Type: Manual

131 THORNLIEBANK ROAD GLASGOW THORNLIEBANK Edge of Town Residential Zone Site area: 3.5999999046325684 hect Survey date: Thursday 07/04/1988	GC-03-A-03	DET./TERRACED	GLASGOW CITY
--	-------------------	----------------------	---------------------

Survey Type: Manual

132 THORNLIEBANK ROAD GLASGOW THORNLIEBANK Edge of Town Residential Zone Site area: 8.699999809265137 hect Survey date: Thursday 14/04/1988	GC-03-A-04	MIXED HOUSES	GLASGOW CITY
---	-------------------	---------------------	---------------------

Survey Type: Manual

133 COLLINGWOOD WAY BOLTON WESTHOUGHTON Edge of Town Residential Zone Site area: 2.4000000953674316 hect Survey date: Monday 03/03/1997	GM-03-A-01	SEMI DETACHED	GREATER MANCHESTER
---	-------------------	----------------------	---------------------------

Survey Type: Manual

134 BELMONT ROAD BOLTON Edge of Town Residential Zone	GM-03-A-02	HOUSING	GREATER MANCHESTER
--	-------------------	----------------	---------------------------

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Site area: 13 hect
Survey date: Monday 28/01/1991
Survey Type: Manual

135 GM-03-A-03 DETACHED GREATER MANCHESTER

BOARS HEAD AVENUE
NEAR WIGAN
STANDISH
Edge of Town
Residential Zone
Site area: 8.899999618530273 hect
Survey date: Tuesday 19/02/1991

Survey Type: Manual

136 GM-03-A-04 HOUSING GREATER MANCHESTER

BEAUMONT CHASE
BOLTON
HUNGER HILL
Edge of Town
Residential Zone
Site area: 7.199999809265137 hect
Survey date: Monday 25/11/1996

Survey Type: Manual

137 GM-03-A-05 HOUSING GREATER MANCHESTER

STATION ROAD
HYDE
Edge of Town
No Sub Category
Site area: 3.299999952316284 hect
Survey date: Wednesday 27/11/1996

Survey Type: Manual

138 GM-03-A-06 DETACHED GREATER MANCHESTER

RECTORY LANE
NEAR WIGAN
STANDISH
Edge of Town
Residential Zone
Site area: 9.399999618530273 hect
Survey date: Monday 15/06/1998

Survey Type: Manual

139 GM-03-A-07 SEMI DETACHED GREATER MANCHESTER

MILFORD DRIVE
MANCHESTER
LEVENSHULME
Suburban Area
Residential Zone
Site area: 4.099999904632568 hect
Survey date: Friday 09/11/2001

Survey Type: Manual

140 GM-03-A-08 SEMI DETACHED GREATER MANCHESTER

ELM TREE ROAD
STOCKPORT
LOWER BREDBURY
Edge of Town
Residential Zone
Site area: 6.599999904632568 hect
Survey date: Friday 12/10/2001

Survey Type: Manual

141 GM-03-A-09 MIXED HOUSES GREATER MANCHESTER

OLDHAM ROAD
ASHTON-UNDER-LYNE
Edge of Town
Residential Zone
Site area: 13.5 hect
Survey date: Friday 15/05/1998

Survey Type: Manual

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

142 BUTT HILL DRIVE MANCHESTER PRESTWICH Edge of Town Residential Zone Site area: 1.4299999475479126 hect Survey date: Wednesday 12/10/2011	GM-03-A-10	DETACHED/SEMI	GREATER MANCHESTER	Survey Type: Manual
143 RUSHFORD STREET MANCHESTER LEVENSHULME Neighbourhood Centre Residential Zone Site area: 0.28999999165534973 hect Survey date: Monday 26/09/2016	GM-03-A-11	TERRACED & SEMI-DETACHED	GREATER MANCHESTER	Survey Type: Manual
144 KINGSHOLM ROAD GLOUCESTER KINGSHOLM Edge of Town Centre No Sub Category Site area: 1.850000023841858 hect Survey date: Tuesday 25/05/2004	GS-03-A-01	SEMI D./TERRACED	GLOUCESTERSHIRE	Survey Type: Manual
145 OAKRIDGE NEAR GLOUCESTER HIGHNAM Neighbourhood Centre Village Site area: 1.600000023841858 hect Survey date: Friday 23/04/2021	GS-03-A-02	DETACHED HOUSES	GLOUCESTERSHIRE	Survey Type: Manual
146 GREEN LANE TEWKESBURY Suburban Area Residential Zone Site area: 1 hect Survey date: Thursday 10/10/2024	GS-03-A-03	PRIVATLEY OWNED HOUSES	GLOUCESTERSHIRE	Survey Type: Manual
147 KNIGHTWOOD ROAD EASTLEIGH CHANDLERS FORD Edge of Town No Sub Category Site area: 16 hect Survey date: Thursday 19/08/1999	HC-03-A-01	DETACHED	HAMPSHIRE	Survey Type: Manual
148 DORE ESTATE NEAR FAREHAM PORCHESTER Edge of Town Residential Zone Site area: 58.5 hect Survey date: Tuesday 24/05/1988	HC-03-A-02	HOUSING	HAMPSHIRE	Survey Type: Manual

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

149 CONDOR CLOSE NEAR FAREHAM DOWN END Edge of Town Residential Zone Site area: 15 hect Survey date: Wednesday 18/05/1988	HC-03-A-03	HOUSING	HAMPSHIRE	Survey Type: Manual
150 A30 WINCHESTER ROAD BASINGSTOKE Suburban Area Residential Zone Site area: 202 hect Survey date: Wednesday 18/05/1988	HC-03-A-06	HOUSING	HAMPSHIRE	Survey Type: Manual
151 TORWOOD GARDENS NEAR EASTLEIGH BISHOPSTOKE Edge of Town Residential Zone Site area: 3 hect Survey date: Thursday 20/08/1987	HC-03-A-07	HOUSING	HAMPSHIRE	Survey Type: Manual
152 ROMSEY ROAD WINCHESTER PITT Edge of Town Residential Zone Site area: 4.800000190734863 hect Survey date: Thursday 16/06/1988	HC-03-A-08	HOUSING	HAMPSHIRE	Survey Type: Manual
153 READING ROAD YATELEY CRICKET HILL Edge of Town Residential Zone Site area: 1.2999999523162842 hect Survey date: Tuesday 05/05/1987	HC-03-A-10	MIXED HOUSES	HAMPSHIRE	Survey Type: Manual
154 PADNELL ROAD COWPLAIN Edge of Town Residential Zone Site area: 118 hect Survey date: Thursday 26/05/1988	HC-03-A-11	MIXED HOUSES	HAMPSHIRE	Survey Type: Manual
155 ANCELLS ROAD FLEET Edge of Town Residential Zone Site area: 31 hect Survey date: Thursday 05/03/1998	HC-03-A-13	MIXED HOUSES/FLATS	HAMPSHIRE	Survey Type: Manual
156 KNIGHTWOOD ROAD EASTLEIGH	HC-03-A-15	MIXED HOUSES	HAMPSHIRE	

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

BADGER'S COPSE

Suburban Area
No Sub Category
Site area: 32 hect
Survey date: Wednesday 18/08/1999

Survey Type: Manual

157 HC-03-A-16 HOUSES & FLATS HAMPSHIRE

RIDGEWAY/MEADOW WAY

WINCHESTER

BADGER FARM

Edge of Town

Residential Zone

Site area: 45 hect

Survey date: Thursday 09/03/2000

Survey Type: Manual

158 HC-03-A-21 TERRACED & SEMI-DETACHED HAMPSHIRE

PRIESTLEY ROAD

BASINGSTOKE

HOUNDMILLS

Edge of Town

Residential Zone

Site area: 1.2000000476837158 hect

Survey date: Tuesday 13/11/2018

Survey Type: Manual

159 HC-03-A-22 MIXED HOUSES HAMPSHIRE

BOW LAKE GARDENS

NEAR EASTLEIGH

BISHOPSTOKE

Edge of Town

Residential Zone

Site area: 1.690000057220459 hect

Survey date: Wednesday 31/10/2018

Survey Type: Manual

160 HC-03-A-23 HOUSES & FLATS HAMPSHIRE

CANADA WAY

LIPHOOK

Suburban Area

Residential Zone

Site area: 1.399999976158142 hect

Survey date: Tuesday 19/11/2019

Survey Type: Manual

161 HC-03-A-27 MIXED HOUSES HAMPSHIRE

DAIRY ROAD

ANDOVER

Edge of Town

Residential Zone

Site area: 2.5 hect

Survey date: Tuesday 16/11/2021

Survey Type: Manual

162 HC-03-A-28 MIXED HOUSES & FLATS HAMPSHIRE

EAGLE AVENUE

WATERLOOVILLE

LOVEDEAN

Edge of Town

Residential Zone

Site area: 5.96999979019165 hect

Survey date: Monday 08/11/2021

Survey Type: Manual

163 HC-03-A-30 TERRACED HOUSES HAMPSHIRE

MEUDON AVENUE

FARNBOROUGH

Edge of Town Centre

Residential Zone



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Site area: 0.9399999976158142 hect
Survey date: Friday 14/10/2022

Survey Type: Manual

164 HC-03-A-32 MIXED HOUSES & FLATS HAMPSHIRE
GREEN LANE
FARNHAM
WEYBOURNE
Neighbourhood Centre
Residential Zone
Site area: 3.2899999618530273 hect
Survey date: Thursday 29/06/2023

Survey Type: Manual

165 HC-03-A-34 MIXED HOUSES & FLATS HAMPSHIRE
STONEHAM LANE
EASTLEIGH
Edge of Town
Residential Zone
Site area: 8.470000267028809 hect
Survey date: Tuesday 14/11/2023

Survey Type: Manual

166 HC-03-A-35 MIXED HOUSES & FLATS HAMPSHIRE
EAGLE AVENUE
WATERLOOVILLE
LOVEDEAN
Edge of Town
Residential Zone
Site area: 9.100000381469727 hect
Survey date: Tuesday 31/10/2023

Survey Type: Manual

167 HC-03-A-36 MIXED HOUSES & FLATS HAMPSHIRE
HAVANT ROAD
EMSWORTH
Edge of Town
Residential Zone
Site area: 6.230000019073486 hect
Survey date: Tuesday 12/09/2023

Survey Type: Manual

168 HC-03-A-37 MIXED HOUSES HAMPSHIRE
REDFIELDS LANE
FLEET
CHURCH CROOKHAM
Edge of Town
Residential Zone
Site area: 3.46 hect
Survey date: Wednesday 27/03/2024

Survey Type: Manual

169 HC-03-A-38 MIXED HOUSES & FLATS HAMPSHIRE
CROW LANE
RINGWOOD
CROW
Edge of Town
Residential Zone
Site area: 6.199999809265137 hect
Survey date: Wednesday 26/06/2024

Survey Type: Manual

170 HC-03-A-39 MIXED HOUSES & FLATS HAMPSHIRE
KILN ROAD
LIPHOOK
Edge of Town
Residential Zone
Site area: 6.09 hect
Survey date: Thursday 14/11/2024

Survey Type: Manual



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

171 CROW LANE RINGWOOD CROW Edge of Town Residential Zone Site area: 6.2 hect Survey date: Monday 30/06/2025	HC-03-A-41	MIXED HOUSES & FLATS	HAMPSHIRE	Survey Type: Manual
172 LONGCROFT LANE WELWYN GARDEN CITY Edge of Town Centre Residential Zone Site area: 1.7999999523162842 hect Survey date: Friday 06/09/2002	HF-03-A-01	MIXED HOUSES	HERTFORDSHIRE	Survey Type: Manual
173 BLACK FAN ROAD WELWYN GARDEN CITY PANSHANGER Suburban Area Residential Zone Site area: 4.079999923706055 hect Survey date:	HF-03-A-02	HOUSES	HERTFORDSHIRE	Survey Type: Manual
174 HARE STREET ROAD BUNTINGFORD Edge of Town Residential Zone Site area: 5.670000076293945 hect Survey date: Monday 08/07/2019	HF-03-A-03	MIXED HOUSES	HERTFORDSHIRE	Survey Type: Manual
175 HOLMSIDE RISE WATFORD SOUTH OXHEY Edge of Town Residential Zone Site area: 0.1899999976158142 hect Survey date: Monday 05/06/2023	HF-03-A-05	TERRACED HOUSES	HERTFORDSHIRE	Survey Type: Manual
176 A505 ROYSTON Edge of Town Residential Zone Site area: 8 hect Survey date: Tuesday 28/11/2023	HF-03-A-06	MIXED HOUSES & FLATS	HERTFORDSHIRE	Survey Type: Manual
177 BAKER STREET POTTERS BAR Suburban Area Residential Zone Site area: 6.320000171661377 hect Survey date: Monday 25/03/2024	HF-03-A-07	MIXED HOUSES & BUNGALOWS	HERTFORDSHIRE	Survey Type: Manual
178 RIVERFORD CRESCENT CONON BRIDGE RIVERFORD	HI-03-A-01	HOUSING	HIGHLAND	



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

186 STEVENSON ROAD INVERNESS INSHES Edge of Town Residential Zone Site area: 4.599999904632568 hect Survey date: Monday 05/06/2006	HI-03-A-11	BUNGALOWS	HIGHLAND	Survey Type: Manual
187 OLD PERTH ROAD INVERNESS CULCABOCK Edge of Town Residential Zone Site area: 0.5 hect Survey date: Tuesday 01/12/1998	HI-03-A-12	DETACHED/SEMI D.	HIGHLAND	Survey Type: Manual
188 KINGSMILLS ROAD INVERNESS Edge of Town Residential Zone Site area: 0.47999998927116394 hect Survey date: Thursday 21/05/2009	HI-03-A-13	HOUSING	HIGHLAND	Survey Type: Manual
189 KING BRUDE ROAD INVERNESS SCORGUIE Suburban Area Residential Zone Site area: 1.4800000190734863 hect Survey date: Wednesday 23/03/2016	HI-03-A-14	SEMI-DETACHED & TERRACED	HIGHLAND	Survey Type: Manual
190 RIVERSIDE GROVE NEAR FORT WILLIAM LOCHYSIDE Neighbourhood Centre Village Site area: 1.32 hect Survey date: Thursday 10/10/2024	HI-03-A-16	PRIVATLEY OWNED HOUSES	HIGHLAND	Survey Type: Manual
191 HIBERNIAN ROAD HOUNSLOW Edge of Town Centre Residential Zone Site area: 1.3200000524520874 hect Survey date: Monday 29/06/2015	HO-03-A-02	MIXED HOUSES	HOUNSLOW	Survey Type: Manual
192 BALLAKILLOWEY ROAD COLBY BALLAKILLOWEY Neighbourhood Centre Village Site area: 2.119999885559082 hect Survey date: Tuesday 21/05/2024	IM-03-A-01	MIXED HOUSES	ISLE OF MAN	Survey Type: Manual
193 SHORE ROAD	IM-03-A-02	MIXED HOUSES	ISLE OF MAN	

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

KIRK MICHAEL
Neighbourhood Centre
Village
Site area: 1.6100000143051147 hect
Survey date: Thursday 23/05/2024 Survey Type: Manual

194 **IM-03-A-03** **MIXED HOUSES** **ISLE OF MAN**
MAIN ROAD
COLBY
Neighbourhood Centre
Village
Site area: 6.989999771118164 hect
Survey date: Tuesday 21/05/2024 Survey Type: Manual

195 **IM-03-A-04** **MIXED HOUSES** **ISLE OF MAN**
NEW CASTLETOWN ROAD
DOUGLAS
Suburban Area
Residential Zone
Site area: 2.299999952316284 hect
Survey date: Monday 20/05/2024 Survey Type: Manual

196 **IM-03-A-05** **MIXED HOUSES** **ISLE OF MAN**
SCARLETT ROAD
CASTLETOWN
Edge of Town
Residential Zone
Site area: 2.190000057220459 hect
Survey date: Tuesday 21/05/2024 Survey Type: Manual

197 **IM-03-A-06** **MIXED HOUSES** **ISLE OF MAN**
MOORAGH PROMENADE
RAMSEY
Edge of Town
Residential Zone
Site area: 6.900000095367432 hect
Survey date: Thursday 23/05/2024 Survey Type: Manual

198 **KC-03-A-01** **HOUSING** **KENT**
MAIDSTONE
PENENDER HEATH
Suburban Area
Residential Zone
Site area: hect
Survey date: Wednesday 15/06/1988 Survey Type: Manual

199 **KC-03-A-03** **MIXED HOUSES & FLATS** **KENT**
HYTHE ROAD
ASHFORD
WILLESBOROUGH
Suburban Area
Residential Zone
Site area: 1.3799999952316284 hect
Survey date: Thursday 14/07/2016 Survey Type: Manual

200 **KC-03-A-04** **SEMI-DETACHED & TERRACED** **KENT**
KILN BARN ROAD
AYLESFORD
DITTON
Edge of Town
Residential Zone
Site area: 4.309999942779541 hect
Survey date: Friday 22/09/2017 Survey Type: Manual

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

<p>201 MARGATE ROAD HERNE BAY Suburban Area Residential Zone Site area: 8 hect Survey date: Wednesday 27/09/2017</p>	KC-03-A-06	MIXED HOUSES & FLATS	KENT	Survey Type: Manual
<p>202 RECVLVER ROAD HERNE BAY Edge of Town Residential Zone Site area: 9.460000038146973 hect Survey date: Wednesday 27/09/2017</p>	KC-03-A-07	MIXED HOUSES	KENT	Survey Type: Manual
<p>203 MAIDSTONE ROAD CHARING Neighbourhood Centre Village Site area: 0.8600000143051147 hect Survey date: Tuesday 22/05/2018</p>	KC-03-A-08	MIXED HOUSES	KENT	Survey Type: Manual
<p>204 HEADCORN ROAD STAPLEHURST Edge of Town Residential Zone Site area: 3.9100000858306885 hect Survey date: Tuesday 09/05/2023</p>	KC-03-A-10	MIXED HOUSES	KENT	Survey Type: Manual
<p>205 COLDHARBOUR ROAD GRAVESEND Edge of Town No Sub Category Site area: 7.199999809265137 hect Survey date: Monday 20/03/2023</p>	KC-03-A-11	MIXED HOUSES & FLATS	KENT	Survey Type: Manual
<p>206 WESTERN LINK FAVERSHAM DAVINGTON Edge of Town Residential Zone Site area: 6.78000020980835 hect Survey date: Tuesday 19/09/2023</p>	KC-03-A-12	MIXED HOUSES & FLATS	KENT	Survey Type: Manual
<p>207 HEADCORN ROAD STAPLEHURST Edge of Town Residential Zone Site area: 6.84 hect Survey date: Thursday 22/05/2025</p>	KC-03-A-14	MIXED HOUSES	KENT	Survey Type: Manual
<p>208 CEDARWOOD PARK NEWBRIDGE MORRISTOWN ROAD Suburban Area</p>	KD-03-A-02	TERRACED/SEMI-D.	KILDARE	

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Residential Zone

Site area: 2.740000009536743 hect

Survey date: Tuesday 12/05/2009

Survey Type: Manual

209 SPRINGHEAD AVENUE KINGSTON UPON HULL SPRINGHEAD Suburban Area Residential Zone Site area: 17.5 hect Survey date: Thursday 24/06/1993	KH-03-A-01	DETACHED & SEMI DET.	KINGSTON UPON HULL	Survey Type: Manual
210 COOMBE RISE KINGSTON UPON THAMES Suburban Area Residential Zone Site area: 1.3700000047683716 hect Survey date: Thursday 24/06/2010	KI-03-A-01	DETACHED	KINGSTON	Survey Type: Manual
211 WOLSEY CLOSE KINGSTON UPON THAMES Suburban Area Residential Zone Site area: 2.259999990463257 hect Survey date: Thursday 24/06/2010	KI-03-A-02	DETACHED	KINGSTON	Survey Type: Manual
212 ASHLEIGH COURT KILKENNY Edge of Town Centre Residential Zone Site area: 1 hect Survey date: Monday 24/11/2008	KK-03-A-01	DETACHED	KILKENNY	Survey Type: Manual
213 UPPER PATRICK STREET KILKENNY Edge of Town Centre Residential Zone Site area: 2.509999990463257 hect Survey date: Saturday 29/11/2008	KK-03-A-02	SEMI-DETACHED	KILKENNY	Survey Type: Manual
214 FRESHFORD ROAD KILKENNY FRIARSINCH Edge of Town Residential Zone Site area: 6.5 hect Survey date: Wednesday 26/11/2008	KK-03-A-03	MIXED HOUSING	KILKENNY	Survey Type: Manual
215 PATRICK STREET KILKENNY Edge of Town Centre No Sub Category Site area: 1.600000023841858 hect Survey date: Thursday 27/11/2008	KK-03-A-04	TERRACED	KILKENNY	Survey Type: Manual
216	LC-03-A-01	HOUSING	LANCASHIRE	

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

THE FARTHINGS ESTATE
CHORLEY

ASTLEY VILLAGE

Suburban Area

No Sub Category

Site area: 8.300000190734863 hect

Survey date: Wednesday 14/06/1989

Survey Type: Manual

217 LC-03-A-02 HOUSING LANCASHIRE

CHORLEY

GREAT KNOWLEY ESTATE

Edge of Town

No Sub Category

Site area: 13.899999618530273 hect

Survey date: Wednesday 14/06/1989

Survey Type: Manual

218 LC-03-A-03 DETACHED LANCASHIRE

ABBOT MEADOW

PRESTON

PENWORTHAM

Suburban Area

No Sub Category

Site area: 6 hect

Survey date: Thursday 21/03/1991

Survey Type: Manual

219 LC-03-A-04 DETACHED LANCASHIRE

HOWGILLS & PENNINES

PRESTON

FULWOOD

Edge of Town

No Sub Category

Site area: 5.800000190734863 hect

Survey date: Friday 22/03/1991

Survey Type: Manual

220 LC-03-A-05 SEMI DETACHED LANCASHIRE

DEBORAH AVENUE

PRESTON

FULWOOD

Edge of Town

No Sub Category

Site area: 2.4000000953674316 hect

Survey date: Friday 22/03/1991

Survey Type: Manual

221 LC-03-A-06 DETACHED/LINK DET. LANCASHIRE

RIVER PARADE

PRESTON

BROADGATE

Neighbourhood Centre

No Sub Category

Site area: 28.700000762939453 hect

Survey date: Monday 13/05/1991

Survey Type: Manual

222 LC-03-A-08 DETACHED LANCASHIRE

PRESTON ROAD

LONGRIDGE

Edge of Town

Residential Zone

Site area: 2.200000047683716 hect

Survey date: Tuesday 12/07/1994

Survey Type: Manual

223 LC-03-A-09 DETACHED LANCASHIRE

HILL ROAD SOUTH

PRESTON

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

PENWORTHAM Suburban Area Residential Zone Site area: 4.099999904632568 hect Survey date: Wednesday 16/03/1994 Survey Type: Manual			
224	LC-03-A-10	DETACHED	LANCASHIRE
MIDFIELD NEAR BLACKBURN LANGHO Neighbourhood Centre Village Site area: 9.600000381469727 hect Survey date: Thursday 22/09/1994 Survey Type: Manual			
225	LC-03-A-11	DETACHED	LANCASHIRE
MEADOW PARK GARSTANG Edge of Town Residential Zone Site area: 2.4000000953674316 hect Survey date: Thursday 25/08/1994 Survey Type: Manual			
226	LC-03-A-12	BUNGALOWS	LANCASHIRE
PENNINE VIEW GLASSON Neighbourhood Centre Village Site area: 1.600000023841858 hect Survey date: Tuesday 13/05/1997 Survey Type: Manual			
227	LC-03-A-13	DETACHED	LANCASHIRE
WIGAN ROAD NEAR CHORLEY EUXTON Edge of Town Residential Zone Site area: 2.4000000953674316 hect Survey date: Monday 21/07/1997 Survey Type: Manual			
228	LC-03-A-14	DETACHED	LANCASHIRE
DEVONSHIRE ROAD NEAR BLACKBURN RISHTON Edge of Town Residential Zone Site area: 2.4000000953674316 hect Survey date: Friday 21/10/1994 Survey Type: Manual			
229	LC-03-A-15	DETACHED	LANCASHIRE
DEVONSHIRE ROAD NEAR BLACKBURN RISHTON Edge of Town Residential Zone Site area: 1.2000000476837158 hect Survey date: Friday 21/10/1994 Survey Type: Manual			
230	LC-03-A-16	DETACHED	LANCASHIRE
CHORLEY ROAD PRESTON WALTON-LE-DALE Edge of Town			

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

No Sub Category
Site area: 0.800000011920929 hect
Survey date: Thursday 26/03/1998
Survey Type: Manual

231 LC-03-A-17 DETACHED LANCASHIRE
MOSELEY ROAD
BURNLEY
TOWNELEY PARK
Edge of Town
No Sub Category
Site area: hect
Survey date: Tuesday 24/10/1995
Survey Type: Manual

232 LC-03-A-19 DETACHED LANCASHIRE
WEETON ROAD
WESHAM
Edge of Town
Residential Zone
Site area: 7.199999809265137 hect
Survey date: Wednesday 24/05/1995
Survey Type: Manual

233 LC-03-A-21 DETACHED LANCASHIRE
WELLFIELD ROAD
NEAR PRESTON
LOSTOCK HALL
Edge of Town
Residential Zone
Site area: 10.199999809265137 hect
Survey date: Tuesday 26/09/1995
Survey Type: Manual

234 LC-03-A-22 BUNGALOWS LANCASHIRE
CLIFTON DRIVE NORTH
BLACKPOOL
Edge of Town
Residential Zone
Site area: 6.429999828338623 hect
Survey date: Tuesday 18/10/2005
Survey Type: Manual

235 LC-03-A-23 DETACHED/SEMI DET. LANCASHIRE
COPPULL ROAD
CHORLEY
Edge of Town
Residential Zone
Site area: 32.400001525878906 hect
Survey date: Friday 29/04/1994
Survey Type: Manual

236 LC-03-A-24 MIXED HOUSES LANCASHIRE
SPRING HILL
NEAR PRESTON
FRECKLETON
Neighbourhood Centre
Village
Site area: 3 hect
Survey date: Thursday 04/05/1995
Survey Type: Manual

237 LC-03-A-25 DETACHED/SEMI DET. LANCASHIRE
BOURNE WAY
THORNTON
BURN NAZE
Edge of Town
Residential Zone
Site area: hect
Survey date: Monday 01/11/1993
Survey Type: Manual



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

238 SLYNE ROAD LANCASTER SKERTON Edge of Town Residential Zone Site area: 4.199999809265137 hect Survey date: Wednesday 25/06/1997	LC-03-A-28	DETACHED/SEMI D.	LANCASHIRE	Survey Type: Manual
239 GREENSIDE PRESTON COTTAM Edge of Town Residential Zone Site area: 1.315999984741211 hect Survey date: Friday 17/11/2017	LC-03-A-31	DETACHED HOUSES	LANCASHIRE	Survey Type: Manual
240 REDWOOD AVENUE MELTON MOWBRAY Edge of Town Residential Zone Site area: 0.4000000059604645 hect Survey date: Tuesday 03/05/2005	LE-03-A-01	DETACHED	LEICESTERSHIRE	Survey Type: Manual
241 MELBOURNE ROAD IBSTOCK Neighbourhood Centre Village Site area: 3.296999931335449 hect Survey date: Thursday 28/06/2018	LE-03-A-02	DETACHED & OTHERS	LEICESTERSHIRE	Survey Type: Manual
242 BRANT ROAD LINCOLN BRACEBRIDGE Edge of Town Residential Zone Site area: 6 hect Survey date: Tuesday 15/05/2007	LN-03-A-01	MIXED HOUSES	LINCOLNSHIRE	Survey Type: Manual
243 HYKEHAM ROAD LINCOLN Suburban Area Residential Zone Site area: 8.789999961853027 hect Survey date: Monday 14/05/2007	LN-03-A-02	MIXED HOUSES	LINCOLNSHIRE	Survey Type: Manual
244 ROOKERY LANE LINCOLN BOULTHAM Suburban Area Residential Zone Site area: 0.7699999809265137 hect Survey date: Tuesday 18/09/2012	LN-03-A-03	SEMI DETACHED	LINCOLNSHIRE	Survey Type: Manual
245 SPRING VALLEY CRESCENT	LS-03-A-01	MIXED HOUSING	LEEDS	



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

LEEDS BRAMLEY Neighbourhood Centre Residential Zone Site area: 1.379999952316284 hect Survey date: Wednesday 21/09/2016				Survey Type: Manual
246 ARD NA SI CARRICK-ON-SHANNON ATTIRORY Suburban Area Residential Zone Site area: 4.480000019073486 hect Survey date: Friday 24/04/2015	LT-03-A-01	SEMI-DETACHED & DETACHED	LEITRIM	Survey Type: Manual
247 ARD ÁLAINN CARRICK-ON-SHANNON GALLOW'S HILL Edge of Town Centre Residential Zone Site area: 1.305999994277954 hect Survey date: Monday 22/05/2017	LT-03-A-02	BUNGALOWS	LEITRIM	Survey Type: Manual
248 RATHMULLAN ROAD DROGHEDA Neighbourhood Centre Residential Zone Site area: 3.6700000762939453 hect Survey date: Tuesday 21/09/2021	LU-03-A-01	TERRACED & SEMI-DETACHED	LOUTH	Survey Type: Manual
249 N26 STATION ROAD BALLINA Suburban Area Residential Zone Site area: 3.130000114440918 hect Survey date: Friday 15/07/2011	MA-03-A-01	SEMI-DET. & TERRACED	MAYO	Survey Type: Manual
250 CONVENT ROAD CLAREMORRIS Edge of Town Centre No Sub Category Site area: 1.8600000143051147 hect Survey date: Wednesday 15/09/2021	MA-03-A-02	SEMI-DETACHED HOUSES	MAYO	Survey Type: Manual
251 R155 RATOATH Edge of Town Residential Zone Site area: 2.4 hect Survey date: Wednesday 30/10/2024	ME-03-A-01	PRIVATELY OWNED HOUSES	MEATH	Survey Type: Manual
252 ORIEL WAY MONAGHAN Suburban Area Residential Zone Site area: 3.299999952316284 hect	MG-03-A-01	SEMI-DETACHED HOUSES	MONAGHAN	



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Survey date: Tuesday 12/10/2021			Survey Type: Manual
253 GLEN ROAD MONAGHAN Edge of Town Centre Residential Zone Site area: 5.449999809265137 hect Survey date: Tuesday 12/10/2021	MG-03-A-02	MIXED HOUSES	MONAGHAN Survey Type: Manual
254 PALACE FIELDS AVENUE RUNCORN Neighbourhood Centre Residential Zone Site area: 9.399999618530273 hect Survey date: Thursday 06/10/2005	MS-03-A-01	TERRACED	MERSEYSIDE Survey Type: Manual
255 RIVERSIDE DRIVE LIVERPOOL AIGBURTH Suburban Area Residential Zone Site area: 1.2999999523162842 hect Survey date:	MS-03-A-02	DETACHED	MERSEYSIDE Survey Type: Manual
256 BEMPTON ROAD LIVERPOOL OTTERSPOOL Suburban Area Residential Zone Site area: 0.5 hect Survey date: Friday 21/06/2013	MS-03-A-03	DETACHED	MERSEYSIDE Survey Type: Manual
257 EDWARD STREET MERTHYR TYDFIL PANTEG Edge of Town No Sub Category Site area: 7.099999904632568 hect Survey date: Thursday 24/05/1990	MT-03-A-02	TERRACED	MERTHYR TYDFIL Survey Type: Manual
258 ROCHESTER ROAD NEAR CHATHAM BURHAM Neighbourhood Centre Village Site area: 0.20000000298023224 hect Survey date: Friday 22/09/2017	MW-03-A-01	DETACHED & SEMI-DETACHED	MEDWAY Survey Type: Manual
259 OTTERHAM QUAY LANE RAINHAM Edge of Town Residential Zone Site area: 0.699999988079071 hect Survey date: Monday 06/06/2022	MW-03-A-02	MIXED HOUSES	MEDWAY Survey Type: Manual
260	NE-03-A-01	DETACHED	NORTH EAST LINCOLNSHIRE

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

BRADLEY ROAD NEAR CLEETHORPES WALTHAM Edge of Town Residential Zone Site area: 6 hect Survey date: Thursday 08/07/1993				Survey Type: Manual
261 HANOVER WALK SCUNTHORPE Edge of Town No Sub Category Site area: 12 hect Survey date: Monday 12/05/2014	NE-03-A-02	SEMI DETACHED & DETACHED	NORTH EAST LINCOLNSHIRE	Survey Type: Manual
262 STATION ROAD SCUNTHORPE Edge of Town Centre Residential Zone Site area: 8 hect Survey date: Tuesday 20/05/2014	NE-03-A-03	PRIVATE HOUSES	NORTH EAST LINCOLNSHIRE	Survey Type: Manual
263 YARMOUTH ROAD CAISTER-ON-SEA Suburban Area Residential Zone Site area: 1.4900000095367432 hect Survey date: Tuesday 16/10/2012	NF-03-A-01	SEMI DET. & BUNGALOWS	NORFOLK	Survey Type: Manual
264 DEREHAM ROAD NORWICH Suburban Area Residential Zone Site area: 2.200000047683716 hect Survey date: Monday 22/10/2012	NF-03-A-02	HOUSES & FLATS	NORFOLK	Survey Type: Manual
265 HALING WAY THETFORD Edge of Town Residential Zone Site area: 0.6299999952316284 hect Survey date: Wednesday 16/09/2015	NF-03-A-03	DETACHED HOUSES	NORFOLK	Survey Type: Manual
266 HUNSTANTON ROAD HUNSTANTON Edge of Town Residential Zone Site area: 0.699999988079071 hect Survey date: Wednesday 12/09/2018	NF-03-A-10	MIXED HOUSES & FLATS	NORFOLK	Survey Type: Manual
267 NORWICH COMMON WYMONDHAM Edge of Town Residential Zone Site area: 6.539999961853027 hect Survey date: Tuesday 20/10/2015	NF-03-A-16	MIXED HOUSES & FLATS	NORFOLK	Survey Type: Manual



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

268	NF-03-A-21	MIXED HOUSES & FLATS	NORFOLK
SIR ALFRED MUNNINGS RD NEAR NORWICH COSTESSEY Neighbourhood Centre Village Site area: 49.75 hect Survey date: Tuesday 13/10/2020			
			Survey Type: Manual
269	NF-03-A-22	MIXED HOUSES & FLATS	NORFOLK
ROUND HOUSE WAY NORWICH CRINGLEFORD Edge of Town Residential Zone Site area: 44.5099983215332 hect Survey date: Tuesday 13/10/2020			
			Survey Type: Manual
270	NF-03-A-25	MIXED HOUSES & FLATS	NORFOLK
WOODFARM LANE GORLESTON-ON-SEA Edge of Town Residential Zone Site area: 3.0999999046325684 hect Survey date: Tuesday 21/09/2021			
			Survey Type: Manual
271	NF-03-A-27	MIXED HOUSES & FLATS	NORFOLK
YARMOUTH ROAD NEAR NORWICH BLOFIELD Neighbourhood Centre Village Site area: 3.690000057220459 hect Survey date: Thursday 16/09/2021			
			Survey Type: Manual
272	NF-03-A-28	MIXED HOUSES & FLATS	NORFOLK
ATLANTIC AVENUE NORWICH SPROWSTON Edge of Town Residential Zone Site area: 38 hect Survey date: Thursday 22/09/2022			
			Survey Type: Manual
273	NF-03-A-31	MIXED HOUSES	NORFOLK
BRANDON ROAD SWAFFHAM Edge of Town Residential Zone Site area: 16.200000762939453 hect Survey date: Thursday 22/09/2022			
			Survey Type: Manual
274	NF-03-A-32	MIXED HOUSES & FLATS	NORFOLK
HUNSTANTON ROAD HUNSTANTON Edge of Town Residential Zone Site area: 7.300000190734863 hect Survey date: Wednesday 21/09/2022			
			Survey Type: Manual
275	NF-03-A-33	MIXED HOUSES	NORFOLK
LONDON ROAD			

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

ATTLEBOROUGH Edge of Town Residential Zone Site area: 4.78000020980835 hect Survey date: Thursday 29/09/2022 Survey Type: Manual			
276	NF-03-A-35	MIXED HOUSES & FLATS	NORFOLK
REPTON AVENUE NORWICH Edge of Town Residential Zone Site area: 5.340000152587891 hect Survey date: Wednesday 28/09/2022 Survey Type: Manual			
277	NF-03-A-36	MIXED HOUSES	NORFOLK
LONDON ROAD WYMONDHAM Edge of Town No Sub Category Site area: 3.200000047683716 hect Survey date: Thursday 29/09/2022 Survey Type: Manual			
278	NF-03-A-37	MIXED HOUSES	NORFOLK
GREENFIELDS ROAD DEREHAM Edge of Town Residential Zone Site area: 1.6399999856948853 hect Survey date: Tuesday 27/09/2022 Survey Type: Manual			
279	NF-03-A-38	MIXED HOUSES	NORFOLK
BEAUFORT WAY GREAT YARMOUTH BRADWELL Edge of Town Residential Zone Site area: 18.059999465942383 hect Survey date: Tuesday 20/09/2022 Survey Type: Manual			
280	NF-03-A-39	MIXED HOUSES	NORFOLK
HEATH DRIVE HOLT Edge of Town Residential Zone Site area: 7.840000152587891 hect Survey date: Tuesday 27/09/2022 Survey Type: Manual			
281	NF-03-A-44	MIXED HOUSES	NORFOLK
MILL LANE NEAR NORWICH HORSFORD Neighbourhood Centre Village Site area: 5.400000095367432 hect Survey date: Wednesday 21/09/2022 Survey Type: Manual			
282	NF-03-A-47	MIXED HOUSES & FLATS	NORFOLK
BURGH ROAD AYLSHAM Edge of Town Residential Zone Site area: 13.050000190734863 hect Survey date: Wednesday 21/09/2022 Survey Type: Manual			

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

283 CITY ROAD NORWICH LAKENHAM Suburban Area Residential Zone Site area: 1.0299999713897705 hect Survey date: Tuesday 13/09/2022	NF-03-A-51	SEMI-DETACHED	NORFOLK	Survey Type: Manual
284 LYNNSPORT WAY KING'S LYNN Suburban Area Residential Zone Site area: 5.309999942779541 hect Survey date: Tuesday 07/11/2023	NF-03-A-52	MIXED HOUSES	NORFOLK	Survey Type: Manual
285 LODGE FARM LANE NOTTINGHAM GEDLING Edge of Town Residential Zone Site area: 7.900000095367432 hect Survey date: Tuesday 24/11/1998	NG-03-A-01	DETACHED	NOTTINGHAM	Survey Type: Manual
286 BEAUMARIS DRIVE NOTTINGHAM GEDLING Edge of Town Residential Zone Site area: 8.100000381469727 hect Survey date: Tuesday 24/11/1998	NG-03-A-02	DET./BUNGALOWS	NOTTINGHAM	Survey Type: Manual
287 JENNY BURTON WAY NOTTINGHAM ASHFIELD Edge of Town Residential Zone Site area: 5.599999904632568 hect Survey date: Tuesday 08/12/1998	NG-03-A-03	MIXED HOUSES	NOTTINGHAM	Survey Type: Manual
288 BOUGHTON GREEN ROAD NORTHAMPTON KINGSTHORPE Suburban Area Residential Zone Site area: 2.569999933242798 hect Survey date: Saturday 22/09/2012	NM-03-A-01	HOUSES	WEST NORTHAMPTONSHIRE	Survey Type: Manual
289 HARLESTONE ROAD NEAR NORTHAMPTON CHAPEL BRAMPTON Neighbourhood Centre Village Site area: 2.4059998989105225 hect Survey date: Tuesday 20/10/2020	NM-03-A-02	DETACHED & SEMI-DETACHED	WEST NORTHAMPTONSHIRE	Survey Type: Manual



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

290 MAIN STREET NEAR WELLINGBOROUGH LITTLE HARROWDEN Neighbourhood Centre Village Site area: 1.5133999586105347 hect Survey date: Tuesday 20/10/2020	NN-03-A-01	MIXED HOUSES & FLATS	NORTH NORTHAMPTONSHIRE	Survey Type: Manual
291 BROADOAK ROAD NEAR BRISTOL LOWER LANGFORD Neighbourhood Centre Village Site area: 8.199999809265137 hect Survey date: Thursday 17/09/1992	NS-03-A-01	DETACHED	NORTH SOMERSET	Survey Type: Manual
292 STANLEY ROAD WESTON-SUPER-MARE Suburban Area Residential Zone Site area: hect Survey date: Thursday 24/09/1992	NS-03-A-02	TERRACED	NORTH SOMERSET	Survey Type: Manual
293 ROPERS LANE WRINGTON Neighbourhood Centre Village Site area: 1 hect Survey date: Thursday 17/09/1992	NS-03-A-03	DETACHED	NORTH SOMERSET	Survey Type: Manual
294 SILVER STREET WRINGTON Neighbourhood Centre Village Site area: 1 hect Survey date: Thursday 17/09/1992	NS-03-A-04	SEMI D./DETACHED	NORTH SOMERSET	Survey Type: Manual
295 SILVER STREET WRINGTON Neighbourhood Centre Village Site area: 1.399999976158142 hect Survey date: Thursday 17/09/1992	NS-03-A-05	DETACHED	NORTH SOMERSET	Survey Type: Manual
296 SCHOOL ROAD WRINGTON Neighbourhood Centre Village Site area: 1.5 hect Survey date: Thursday 17/09/1992	NS-03-A-06	HOUSING	NORTH SOMERSET	Survey Type: Manual
297 COLLINGHAM Neighbourhood Centre Village Site area: 8.199999809265137 hect	NT-03-A-01	BUNGALOWS	NOTTINGHAMSHIRE	



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Survey date: Thursday 26/11/1998 Survey Type: Manual

298 **NT-03-A-03** **SEMI DETACHED** **NOTTINGHAMSHIRE**
 B6018 SUTTON ROAD
 KIRKBY-IN-ASHFIELD
 Edge of Town
 Residential Zone
 Site area: 7.53000020980835 hect
 Survey date: Wednesday 28/06/2006 Survey Type: Manual

299 **NT-03-A-04** **MIXED HOUSES** **NOTTINGHAMSHIRE**
 BEACON WAY
 NEWARK-ON-TRENT
 BEACON HILL
 Edge of Town
 Residential Zone
 Site area: 16.799999237060547 hect
 Survey date: Thursday 26/11/1998 Survey Type: Manual

300 **NT-03-A-05** **DETACHED/SEMI DET.** **NOTTINGHAMSHIRE**
 LOXLEY DRIVE
 MANSFIELD
 BERRYHILL
 Edge of Town
 No Sub Category
 Site area: 1.899999976158142 hect
 Survey date: Tuesday 08/12/1998 Survey Type: Manual

301 **NT-03-A-08** **DETACHED HOUSES** **NOTTINGHAMSHIRE**
 WIGHAY ROAD
 HUCKNALL
 Edge of Town
 Residential Zone
 Site area: 1.6100000143051147 hect
 Survey date: Monday 18/10/2021 Survey Type: Manual

302 **NY-03-A-02** **DETACHED** **NORTH YORKSHIRE**
 CLOTHERHOLME ROAD
 RIPON
 Edge of Town
 Residential Zone
 Site area: 1.6699999570846558 hect
 Survey date: Survey Type: Manual

303 **NY-03-A-03** **PRIVATE HOUSING** **NORTH YORKSHIRE**
 NEW ROW
 BOROUGHBRIDGE
 Edge of Town Centre
 Residential Zone
 Site area: 0.3499999940395355 hect
 Survey date: Monday 15/09/2008 Survey Type: Manual

304 **NY-03-A-06** **BUNGALOWS & SEMI DET.** **NORTH YORKSHIRE**
 HORSEFAIR
 BOROUGHBRIDGE
 Suburban Area
 Residential Zone
 Site area: 5.230000019073486 hect
 Survey date: Friday 14/10/2011 Survey Type: Manual

305 **NY-03-A-07** **DETACHED & SEMI DET.** **NORTH YORKSHIRE**
 CRAVEN WAY
 BOROUGHBRIDGE

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Edge of Town
No Sub Category
Site area: 0.7699999809265137 hect
Survey date: Tuesday 18/10/2011 Survey Type: Manual

306 NY-03-A-09 MIXED HOUSING NORTH YORKSHIRE
GRAMMAR SCHOOL LANE
NORTHALLERTON
Suburban Area
Residential Zone
Site area: 3.299999952316284 hect
Survey date: Monday 16/09/2013 Survey Type: Manual

307 NY-03-A-10 HOUSES AND FLATS NORTH YORKSHIRE
BOROUGHBRIDGE ROAD
RIPON
Edge of Town
No Sub Category
Site area: 2.2100000381469727 hect
Survey date: Tuesday 17/09/2013 Survey Type: Manual

308 NY-03-A-11 PRIVATE HOUSING NORTH YORKSHIRE
HORSEFAIR
BOROUGHBRIDGE
Edge of Town
Residential Zone
Site area: 1.7899999618530273 hect
Survey date: Wednesday 18/09/2013 Survey Type: Manual

309 NY-03-A-12 TOWN HOUSES NORTH YORKSHIRE
RACECOURSE LANE
NORTHALLERTON
Edge of Town Centre
Residential Zone
Site area: 0.8199999928474426 hect
Survey date: Tuesday 27/09/2016 Survey Type: Manual

310 NY-03-A-13 TERRACED HOUSES NORTH YORKSHIRE
CATTERICK ROAD
CATTERICK GARRISON
OLD HOSPITAL COMPOUND
Suburban Area
Residential Zone
Site area: 0.30000001192092896 hect
Survey date: Wednesday 10/05/2017 Survey Type: Manual

311 NY-03-A-14 DETACHED & BUNGALOWS NORTH YORKSHIRE
PALACE ROAD
RIPON
Edge of Town
Residential Zone
Site area: 2.9000000953674316 hect
Survey date: Wednesday 18/05/2022 Survey Type: Manual

312 NY-03-A-15 DETACHED & SEMI-DETACHED NORTH YORKSHIRE
MILBY ROAD
BOROUGHBRIDGE
MILBY
Edge of Town
Residential Zone
Site area: 6.8 hect
Survey date: Thursday 19/09/2024 Survey Type: Manual



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

313 NEW BEDFORD ROAD LUTON Suburban Area Residential Zone Site area: 5.199999809265137 hect Survey date: Thursday 08/07/2004	ON-03-A-01	SEMI DETACHED	LUTON	Survey Type: Manual
314 RIDDY LANE LUTON Suburban Area Residential Zone Site area: 3.4000000953674316 hect Survey date: Tuesday 06/07/2004	ON-03-A-02	SEMI DETACHED	LUTON	Survey Type: Manual
315 WATERMEET GROVE STOKE-ON-TRENT ETRURIA Suburban Area Residential Zone Site area: 0.5199999809265137 hect Survey date: Wednesday 26/11/2008	OT-03-A-01	TERRACED & DETACHED	STOKE ON TRENT	Survey Type: Manual
316 THORPE ROAD PETERBOROUGH Edge of Town Centre Residential Zone Site area: 11.25 hect Survey date: Thursday 13/05/2004	PB-03-A-01	MIXED HOUSES	PETERBOROUGH	Survey Type: Manual
317 SUGAR WAY PETERBOROUGH WOODSTON Suburban Area Residential Zone Site area: 1.2000000476837158 hect Survey date:	PB-03-A-02	SEMI DETACHED HOUSES	PETERBOROUGH	Survey Type: Manual
318 PETERBOROUGH THORPE PARK ROAD Suburban Area Residential Zone Site area: 0.47999998927116394 hect Survey date: Tuesday 18/10/2011	PB-03-A-03	DETACHED	PETERBOROUGH	Survey Type: Manual
319 EASTFIELD ROAD PETERBOROUGH Suburban Area Residential Zone Site area: 1.7100000381469727 hect Survey date: Monday 17/10/2016	PB-03-A-04	DETACHED HOUSES	PETERBOROUGH	Survey Type: Manual
320 TULLYLUMB TERRACE PERTH CORNHILL Suburban Area	PK-03-A-01	DETAC. & BUNGALOWS	PERTH & KINROSS	



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Residential Zone Site area: 3.1500000953674316 hect Survey date: Wednesday 11/05/2011 Survey Type: Manual			
321 BRYN GLAS WELSHPOOL Edge of Town Centre Residential Zone Site area: 1.1200000047683716 hect Survey date: Monday 11/05/2015 Survey Type: Manual	PS-03-A-01	MIXED HOUSES	POWYS
322 GUNROG ROAD WELSHPOOL Suburban Area Residential Zone Site area: 0.8100000023841858 hect Survey date: Monday 11/05/2015 Survey Type: Manual	PS-03-A-02	DETACHED/SEMI-DETACHED	POWYS
323 ABERLLECHAU ROAD WATTSTOWN Neighbourhood Centre Village Site area: 6.599999904632568 hect Survey date: Tuesday 13/02/1990 Survey Type: Manual	RC-03-A-01	HOUSING	RHONDDA CYNON TAFF
324 FERNDAL ROAD STANLEYTOWN Neighbourhood Centre Village Site area: 4.5 hect Survey date: Tuesday 19/06/1990 Survey Type: Manual	RC-03-A-02	TERRACED	RHONDDA CYNON TAFF
325 PARK CRESCENT TREORCHY CWM PARC Edge of Town Residential Zone Site area: 1.600000023841858 hect Survey date: Tuesday 11/07/1995 Survey Type: Manual	RC-03-A-03	HOUSING	RHONDDA CYNON TAFF
326 MILL LANE READING LOWER EARLEY Edge of Town Residential Zone Site area: 11.100000381469727 hect Survey date: Monday 14/10/1991 Survey Type: Manual	RE-03-A-01	SEMI D./DETACHED	READING
327 RUSHEY WAY READING LOWER EARLEY Edge of Town Residential Zone Site area: 3.9000000953674316 hect Survey date: Monday 21/10/1991 Survey Type: Manual	RE-03-A-02	DETACHED	READING

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

328 HENLEY ROAD READING CAVERSHAM Edge of Town Residential Zone Site area: 12 hect Survey date: Monday 24/10/1988	RE-03-A-03	DETACHED	READING	Survey Type: Manual
329 RUSHEY WAY READING LOWER EARLEY Edge of Town Residential Zone Site area: 6 hect Survey date: Monday 21/10/1991	RE-03-A-04	DETACHED	READING	Survey Type: Manual
330 NORCOT ROAD READING TILEHURST Suburban Area Residential Zone Site area: 14 hect Survey date: Monday 21/10/1991	RE-03-A-05	MIXED HOUSES	READING	Survey Type: Manual
331 RYHILL WAY READING LOWER EARLEY Edge of Town Residential Zone Site area: 5 hect Survey date: Monday 14/10/1991	RE-03-A-06	DETACHED/SEMI DET.	READING	Survey Type: Manual
332 CHALFONT WAY READING LOWER EARLEY Suburban Area Residential Zone Site area: 3.5999999046325684 hect Survey date: Monday 28/10/1991	RE-03-A-07	DET., BUNGALOWS	READING	Survey Type: Manual
333 BEECH LANE READING LOWER EARLEY Suburban Area Residential Zone Site area: 5 hect Survey date: Monday 14/10/1991	RE-03-A-08	DETACHED/SEMI DET.	READING	Survey Type: Manual
334 WATER ROAD READING TILEHURST Suburban Area Residential Zone Site area: 3.799999952316284 hect Survey date: Monday 21/10/1991	RE-03-A-09	BUNGALOWS/DET.	READING	Survey Type: Manual

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

335 VICTORIA ROAD BEVERLEY Edge of Town Residential Zone Site area: 10.100000381469727 hect Survey date: Wednesday 23/06/1993	RI-03-A-01	HOUSING	EAST RIDING OF YORKSHIRE	Survey Type: Manual
336 A1035 HULL BRIDGE ROAD BEVERLEY Edge of Town Residential Zone Site area: 14.100000381469727 hect Survey date: Tuesday 13/02/1990	RI-03-A-02	MIXED HOUSES	EAST RIDING OF YORKSHIRE	Survey Type: Manual
337 MANOR ROAD BEVERLEY MOLESCROFT Suburban Area Residential Zone Site area: 36.70000076293945 hect Survey date: Tuesday 13/02/1990	RI-03-A-03	MIXED HOUSES	EAST RIDING OF YORKSHIRE	Survey Type: Manual
338 GALWAY ROAD ROSCOMMON Edge of Town No Sub Category Site area: 7.199999809265137 hect Survey date: Thursday 07/05/2009	RO-03-A-01	MIXED HOUSES	ROSCOMMON	Survey Type: Manual
339 SLIGO ROAD BALLAGHADERREEN Suburban Area Residential Zone Site area: 1.5499999523162842 hect Survey date: Thursday 14/07/2011	RO-03-A-02	SEMI DET. & BUNGALOWS	ROSCOMMON	Survey Type: Manual
340 N61 BOYLE GREATMEADOW Edge of Town No Sub Category Site area: 4.079999923706055 hect Survey date: Thursday 25/09/2014	RO-03-A-03	DETACHED HOUSES	ROSCOMMON	Survey Type: Manual
341 EAGLE COURT ROSCOMMON ARDNANAGH Suburban Area Residential Zone Site area: 1.9199999570846558 hect Survey date: Friday 26/09/2014	RO-03-A-04	SEMI DET. & BUNGALOWS	ROSCOMMON	Survey Type: Manual
342 GOLDSWORTH PARK WOKING Neighbourhood Centre	SC-03-A-01	HOUSING	SURREY	

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

No Sub Category

Site area: hect

Survey date: Thursday 09/02/1989

Survey Type: Manual

343	SC-03-A-02	SEMI DETACHED	SURREY
------------	-------------------	----------------------	---------------

A24
EPSOM
Edge of Town
Residential Zone
Site area: 20.600000381469727 hect
Survey date: Tuesday 03/10/2000

Survey Type: Manual

344	SC-03-A-03	DETACHED	SURREY
------------	-------------------	-----------------	---------------

A3050 HURST ROAD
EAST MOLESEY
HURST PARK
Suburban Area
Residential Zone
Site area: 3 hect
Survey date: Tuesday 12/11/2002

Survey Type: Manual

345	SC-03-A-04	DETACHED & TERRACED	SURREY
------------	-------------------	--------------------------------	---------------

HIGH ROAD
BYFLEET
Edge of Town
Residential Zone
Site area: 3.200000047683716 hect
Survey date: Thursday 23/01/2014

Survey Type: Manual

346	SC-03-A-08	MIXED HOUSES	SURREY
------------	-------------------	---------------------	---------------

REIGATE ROAD
HORLEY
Edge of Town
Residential Zone
Site area: 46.79999923706055 hect
Survey date: Wednesday 04/05/2022

Survey Type: Manual

347	SC-03-A-09	MIXED HOUSES & FLATS	SURREY
------------	-------------------	---------------------------------	---------------

AMLETS LANE
CRANLEIGH
Neighbourhood Centre
Village
Site area: 13.479999542236328 hect
Survey date: Tuesday 24/05/2022

Survey Type: Manual

348	SC-03-A-11	MIXED HOUSES	SURREY
------------	-------------------	---------------------	---------------

FOLLY HILL
FARNHAM
Edge of Town
Residential Zone
Site area: 5.820000171661377 hect
Survey date: Tuesday 14/05/2024

Survey Type: Manual

349	SC-03-A-12	MIXED HOUSES & FLATS	SURREY
------------	-------------------	---------------------------------	---------------

AARONS HILL
GODALMING
Edge of Town
Residential Zone
Site area: 9.380000114440918 hect
Survey date: Wednesday 12/06/2024

Survey Type: Manual

350	SC-03-A-13	MIXED HOUSES & FLATS	SURREY
------------	-------------------	---------------------------------	---------------

GUILDFORD ROAD

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

ASH
Neighbourhood Centre
Village
Site area: 5.56 hect
Survey date: Thursday 05/09/2024 Survey Type: Manual

351 **SC-03-A-14** **MIXED HOUSES & FLATS** **SURREY**
HOLLOWAY HILL
CHERTSEY
Edge of Town
Residential Zone
Site area: 8.1 hect
Survey date: Tuesday 22/10/2024 Survey Type: Manual

352 **SD-03-A-01** **SEMI DETACHED** **SWINDON**
HEADLANDS GROVE
SWINDON
Suburban Area
Residential Zone
Site area: 1.159999966621399 hect
Survey date: Thursday 22/09/2016 Survey Type: Manual

353 **SE-03-A-01** **DETACHED & BUNGALOWS** **SHEFFIELD**
MANOR ROAD
NEAR SHEFFIELD
WALES
Neighbourhood Centre
Village
Site area: 1.2000000476837158 hect
Survey date: Thursday 10/09/2020 Survey Type: Manual

354 **SE-03-A-02** **MIXED HOUSES & FLATS** **SHEFFIELD**
NEW SCHOOL ROAD
NEAR SHEFFIELD
MOSBOROUGH
Neighbourhood Centre
Village
Site area: 0.36 hect
Survey date: Friday 20/09/2024 Survey Type: Manual

355 **SF-03-A-01** **SEMI DETACHED** **SUFFOLK**
A1156 FELIXSTOWE ROAD
IPSWICH
RACECOURSE
Suburban Area
Residential Zone
Site area: 2.4000000953674316 hect
Survey date: Wednesday 23/05/2007 Survey Type: Manual

356 **SF-03-A-02** **SEMI DET./TERRACED** **SUFFOLK**
STOKE PARK DRIVE
IPSWICH
MAIDENHALL
Edge of Town
Residential Zone
Site area: 7.099999904632568 hect
Survey date: Thursday 24/05/2007 Survey Type: Manual

357 **SF-03-A-04** **DETACHED & BUNGALOWS** **SUFFOLK**
NORMANSTON DRIVE
LOWESTOFT
Suburban Area
Residential Zone

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

358	SF-03-A-05	DETACHED HOUSES	SUFFOLK	VALE LANE BURY ST EDMUNDS Edge of Town Residential Zone Site area: 1.149999976158142 hect Survey date: Wednesday 09/09/2015	Survey Type: Manual
359	SF-03-A-06	DETACHED & SEMI-DETACHED	SUFFOLK	BURY ROAD KENTFORD Neighbourhood Centre Village Site area: 2.680000066757202 hect Survey date: Friday 22/09/2017	Survey Type: Manual
360	SF-03-A-08	MIXED HOUSES	SUFFOLK	STANNINGFIELD ROAD NEAR BURY ST EDMUNDS GREAT WHELNETHAM Neighbourhood Centre Village Site area: 2.339200019836426 hect Survey date: Wednesday 16/09/2020	Survey Type: Manual
361	SF-03-A-09	MIXED HOUSES & FLATS	SUFFOLK	FOXHALL ROAD IPSWICH Suburban Area Residential Zone Site area: 6.659999847412109 hect Survey date: Thursday 24/06/2021	Survey Type: Manual
362	SF-03-A-10	TERRACED & SEMI-DETACHED	SUFFOLK	LOVETOFTS DRIVE IPSWICH WHITEHOUSE Edge of Town Residential Zone Site area: 4.920000076293945 hect Survey date: Tuesday 22/06/2021	Survey Type: Manual
363	SF-03-A-11	BUNGALOWS	SUFFOLK	WHITTON CHURCH LANE IPSWICH WHITTON Edge of Town Residential Zone Site area: 1.55 hect Survey date: Wednesday 06/11/2024	Survey Type: Manual
364	SH-03-A-03	DETACHED	SHROPSHIRE	SOMERBY DRIVE SHREWSBURY BICTON HEATH Edge of Town No Sub Category Site area: 0.5099999904632568 hect Survey date: Friday 26/06/2009	Survey Type: Manual



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

365 ST MICHAEL'S STREET SHREWSBURY Suburban Area No Sub Category Site area: 5.300000190734863 hect Survey date: Thursday 11/06/2009	SH-03-A-04	TERRACED	SHROPSHIRE	Survey Type: Manual
366 ELLESMERE ROAD SHREWSBURY Edge of Town Residential Zone Site area: 0.800000011920929 hect Survey date: Thursday 22/05/2014	SH-03-A-06	BUNGALOWS	SHROPSHIRE	Survey Type: Manual
367 TIMBER POND ROAD CANADA WATER Suburban Area Residential Zone Site area: 0.3400000035762787 hect Survey date: Thursday 23/10/2008	SK-03-A-01	SEMI DET. & TERRACED	SOUTHWARK	Survey Type: Manual
368 WEMBDON ROAD BRIDGWATER NORTHFIELD Edge of Town Residential Zone Site area: 1.399999976158142 hect Survey date: Thursday 24/09/2015	SM-03-A-01	DETACHED & SEMI	SOMERSET	Survey Type: Manual
369 HYDE LANE NEAR TAUNTON CREECH SAINT MICHAEL Neighbourhood Centre Village Site area: 2.869999885559082 hect Survey date: Tuesday 25/09/2018	SM-03-A-02	MIXED HOUSES	SOMERSET	Survey Type: Manual
370 HYDE LANE NEAR TAUNTON CREECH ST MICHAEL Neighbourhood Centre Village Site area: 2.6500000953674316 hect Survey date: Tuesday 25/09/2018	SM-03-A-03	MIXED HOUSES	SOMERSET	Survey Type: Manual
371 LANGTON ROAD NEAR SOUTHAMPTON BISHOPS WALTHAM Edge of Town Centre Residential Zone Site area: 6.800000190734863 hect Survey date: Thursday 22/09/1988	SP-03-A-01	HOUSING	SOUTHAMPTON	Survey Type: Manual
372 BENVIEW STIRLING	SR-03-A-01	DETACHED	STIRLING	

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Suburban Area
Residential Zone
Site area: 4.050000190734863 hect
Survey date: Monday 23/04/2007 Survey Type: Manual

373	ST-03-A-01	SEMI DETACHED	STAFFORDSHIRE
------------	-------------------	----------------------	----------------------

RAKEWAY ROAD
CHEADLE
CHEADLEMILL BROOK
Edge of Town
No Sub Category
Site area: 8.399999618530273 hect
Survey date: Monday 17/07/1995 Survey Type: Manual

374	ST-03-A-02	SEMI D./DETACHED	STAFFORDSHIRE
------------	-------------------	-------------------------	----------------------

A51 LICHFIELD ROAD
TAMWORTH
Edge of Town
No Sub Category
Site area: 24.799999237060547 hect
Survey date: Monday 10/07/1995 Survey Type: Manual

375	ST-03-A-03	MIXED HOUSES	STAFFORDSHIRE
------------	-------------------	---------------------	----------------------

QUEENSVILLE
STAFFORD
Edge of Town
No Sub Category
Site area: 8.5 hect
Survey date: Tuesday 04/07/2000 Survey Type: Manual

376	ST-03-A-06	SEMI-DET. & TERRACED	STAFFORDSHIRE
------------	-------------------	---------------------------------	----------------------

STANFORD ROAD
WOLVERHAMPTON
BLAKENHALL
Edge of Town Centre
No Sub Category
Site area: 0.3700000047683716 hect
Survey date: Friday 09/05/2014 Survey Type: Manual

377	ST-03-A-07	DETACHED & SEMI-DETACHED	STAFFORDSHIRE
------------	-------------------	-------------------------------------	----------------------

BEACONSIDE
STAFFORD
MARSTON GATE
Edge of Town
Residential Zone
Site area: 9 hect
Survey date: Wednesday 22/11/2017 Survey Type: Manual

378	ST-03-A-08	DETACHED HOUSES	STAFFORDSHIRE
------------	-------------------	------------------------	----------------------

SILKMORE CRESCENT
STAFFORD
MEADOWCROFT PARK
Edge of Town
Residential Zone
Site area: 0.800000011920929 hect
Survey date: Wednesday 22/11/2017 Survey Type: Manual

379	SU-03-A-01	MIXED HOUSES & FLATS	SUTTON
------------	-------------------	---------------------------------	---------------

COLLINGWOOD ROAD
SUTTON
Edge of Town Centre
Residential Zone
Site area: 1.5800000429153442 hect



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Survey date: Thursday 13/06/2024 Survey Type: Manual

380 **TB-03-A-01** **TERRACED HOUSES** **TORBAY**
 BRONSHILL ROAD
 TORQUAY
 Suburban Area
 Residential Zone
 Site area: 1.25 hect
 Survey date: Wednesday 30/09/2015 Survey Type: Manual

381 **TE-03-A-01** **MIXED HOUSES** **TELFORD & WREKIN**
 STANLEY LANE
 BRIDGNORTH
 Edge of Town
 No Sub Category
 Site area: 3.4000000953674316 hect
 Survey date: Friday 08/05/1998 Survey Type: Manual

382 **TE-03-A-02** **DETACHED** **TELFORD & WREKIN**
 GATCOMBE WAY
 TELFORD
 PRIORSLEE
 Edge of Town
 Residential Zone
 Site area: 2.700000047683716 hect
 Survey date: Survey Type: Manual

383 **TE-03-A-03** **SEMI-DETACHED/TERRACED** **TELFORD & WREKIN**
 SANDCROFT
 TELFORD
 SUTTON HILL
 Edge of Town
 Residential Zone
 Site area: 1.3200000524520874 hect
 Survey date: Thursday 24/10/2013 Survey Type: Manual

384 **TK-03-A-01** **SEMI-DET.** **THURROCK**
 MILTON ROAD
 STANFORD-LE-HOPE
 CORRINGHAM
 Edge of Town
 Residential Zone
 Site area: 6.840000152587891 hect
 Survey date: Tuesday 13/05/2008 Survey Type: Manual

385 **TV-03-A-01** **HOUSES & FLATS** **TEES VALLEY**
 POWLETT ROAD
 HARTLEPOOL
 Suburban Area
 No Sub Category
 Site area: 6.900000095367432 hect
 Survey date: Thursday 14/04/2005 Survey Type: Manual

386 **TW-03-A-01** **SEMI DETACHED** **TYNE & WEAR**
 LEECHMERE ROAD
 SUNDERLAND
 HILLVIEW
 Edge of Town
 Residential Zone
 Site area: 2.5 hect
 Survey date: Wednesday 18/09/2002 Survey Type: Manual

387 **TW-03-A-02** **SEMI-DETACHED** **TYNE & WEAR**

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

WEST PARK ROAD
GATESHEAD

Suburban Area
Residential Zone
Site area: 0.550000011920929 hect
Survey date: Monday 07/10/2013

Survey Type: Manual

388 TW-03-A-03 MIXED HOUSES TYNE & WEAR

STATION ROAD
NEAR NEWCASTLE
BACKWORTH
Neighbourhood Centre
Village

Site area: 1.8200000524520874 hect
Survey date: Friday 13/11/2015

Survey Type: Manual

389 TY-03-A-01 DETACHED/SEMI DET. TYRONE

OMAGH
Edge of Town
No Sub Category
Site area: 2.200000047683716 hect
Survey date: Saturday 27/09/2003

Survey Type: Manual

390 VG-03-A-01 SEMI-DETACHED & TERRACED VALE OF GLAMORGAN

ARTHUR STREET
BARRY
Edge of Town
Residential Zone
Site area: 0.20999999344348907 hect
Survey date: Monday 08/05/2017

Survey Type: Manual

391 WA-03-A-01 DET./SEMI-DET. WATERFORD

DUNMORE ROAD
WATERFORD
Suburban Area
Residential Zone
Site area: 2.299999952316284 hect
Survey date: Tuesday 18/11/2008

Survey Type: Manual

392 WA-03-A-03 TERR./SEMI-DET. WATERFORD

OLD TRAMORE ROAD
WATERFORD
Suburban Area
Residential Zone
Site area: 3.549999952316284 hect
Survey date:

Survey Type: Manual

393 WA-03-A-04 DETACHED WATERFORD

MAYPARK LANE
WATERFORD
Edge of Town
Residential Zone
Site area: 28.59000015258789 hect
Survey date: Tuesday 24/06/2014

Survey Type: Manual

394 WB-03-A-01 SEMI DETACHED WEST BERKSHIRE

LOWER WAY
THATCHAM
Edge of Town
No Sub Category
Site area: 9.699999809265137 hect
Survey date: Monday 04/11/1991

Survey Type: Manual



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

395 THE MOORS THATCHAM Edge of Town Residential Zone Site area: 25.5 hect Survey date: Monday 28/10/1991	WB-03-A-02	MIXED HOUSES	WEST BERKSHIRE	Survey Type: Manual
396 DORKING WAY READING CALCOT Edge of Town Residential Zone Site area: 7.5 hect Survey date: Thursday 12/09/2024	WB-03-A-04	MIXED HOUSES	WEST BERKSHIRE	Survey Type: Manual
397 STATION ROAD WICKLOW CORPORATION MURRAGH Edge of Town No Sub Category Site area: 2.443000078201294 hect Survey date: Monday 28/05/2018	WC-03-A-01	DETACHED HOUSES	WICKLOW	Survey Type: Manual
398 MARLTON ROAD WICKLOW FRIARSHILL Edge of Town Centre Residential Zone Site area: 2.7200000286102295 hect Survey date: Monday 28/05/2018	WC-03-A-02	DETACHED HOUSES	WICKLOW	Survey Type: Manual
399 PALMERSTON ROAD WALTHAMSTOW Edge of Town Centre Residential Zone Site area: 0.11999999731779099 hect Survey date: Thursday 06/06/2019	WF-03-A-02	SEMI DETACHED & TERRACED	WALTHAM FOREST	Survey Type: Manual
400 ARLINGTON AVENUE LEAMINGTON SPA Suburban Area Residential Zone Site area: 0.10000000149011612 hect Survey date: Friday 21/10/2011	WK-03-A-01	TERRACED/SEMI/DET.	WARWICKSHIRE	Survey Type: Manual
401 BRESE AVENUE WARWICK GUYS CLIFFE Suburban Area Residential Zone Site area: 0.8500000238418579 hect Survey date: Wednesday 25/09/2019	WK-03-A-03	DETACHED HOUSES	WARWICKSHIRE	Survey Type: Manual
402 DALEHOUSE LANE KENILWORTH	WK-03-A-04	DETACHED HOUSES	WARWICKSHIRE	

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Edge of Town
Residential Zone
Site area: 2.424999952316284 hect
Survey date: Friday 27/09/2019 Survey Type: Manual

403 **WL-03-A-01** **SEMI D./TERRACED W. BASSETT WILTSHIRE**
MAPLE DRIVE
WOOTTON BASSETT
Edge of Town
Residential Zone
Site area: 3.0999999046325684 hect
Survey date: Monday 02/10/2006 Survey Type: Manual

404 **WM-03-A-02** **DETACHED & SEMI DET.** **WEST MIDLANDS**
HEATH STREET
STOURBRIDGE
Suburban Area
Residential Zone
Site area: 0.4000000059604645 hect
Survey date: Wednesday 26/04/2006 Survey Type: Manual

405 **WM-03-A-03** **MIXED HOUSING** **WEST MIDLANDS**
BASELEY WAY
COVENTRY
ROWLEYS GREEN
Edge of Town
Residential Zone
Site area: 3.319999933242798 hect
Survey date: Monday 24/09/2007 Survey Type: Manual

406 **WM-03-A-04** **TERRACED HOUSES** **WEST MIDLANDS**
OSBORNE ROAD
COVENTRY
EARLSDON
Neighbourhood Centre
Residential Zone
Site area: 1.100000023841858 hect
Survey date: Monday 21/11/2016 Survey Type: Manual

407 **WM-03-A-05** **TERRACED & DETACHED** **WEST MIDLANDS**
COUNDON ROAD
COVENTRY
Edge of Town Centre
Residential Zone
Site area: 2 hect
Survey date: Monday 21/11/2016 Survey Type: Manual

408 **WM-03-A-06** **BUNGALOWS** **WEST MIDLANDS**
NARBERTH WAY
COVENTRY
POTTERS GREEN
Edge of Town
Residential Zone
Site area: 0.4699999988079071 hect
Survey date: Thursday 17/10/2013 Survey Type: Manual

409 **WM-03-A-07** **DETACHED HOUSES** **WEST MIDLANDS**
EVESON ROAD
STOURBRIDGE
NORTON
Suburban Area
Residential Zone
Site area: 0.7799999713897705 hect



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Survey date: Wednesday 18/09/2024 Survey Type: Manual

410 **WO-03-A-01** **DETACHED** **WORCESTERSHIRE**
 MARLBOROUGH AVENUE
 BROMSGROVE
 ASTON FIELDS
 Suburban Area
 Residential Zone
 Site area: 1 hect
 Survey date: Thursday 23/06/2005 Survey Type: Manual

411 **WO-03-A-02** **SEMI DETACHED** **WORCESTERSHIRE**
 MEADOWHILL ROAD
 REDDITCH
 Edge of Town
 No Sub Category
 Site area: 2.200000047683716 hect
 Survey date: Tuesday 02/05/2006 Survey Type: Manual

412 **WO-03-A-03** **DETACHED** **WORCESTERSHIRE**
 BLAKEBROOK
 KIDDERMINSTER
 BLAKEBROOK
 Suburban Area
 Residential Zone
 Site area: 5.5 hect
 Survey date: Friday 05/05/2006 Survey Type: Manual

413 **WO-03-A-04** **MIXED HOUSES** **WORCESTERSHIRE**
 MALVERN ROAD
 WORCESTER
 Edge of Town
 Residential Zone
 Site area: 39.5 hect
 Survey date: Friday 24/05/2002 Survey Type: Manual

414 **WO-03-A-06** **DET./TERRACED** **WORCESTERSHIRE**
 ST GODWALDS ROAD
 BROMSGROVE
 ASTON FIELDS
 Edge of Town
 No Sub Category
 Site area: 6.699999809265137 hect
 Survey date: Thursday 30/06/2005 Survey Type: Manual

415 **WO-03-A-07** **MIXED HOUSES & FLATS** **WORCESTERSHIRE**
 RYE GRASS LANE
 REDDITCH
 Edge of Town
 Residential Zone
 Site area: 1.1100000143051147 hect
 Survey date: Thursday 01/10/2020 Survey Type: Manual

416 **WR-03-A-01** **SEMI DETACHED** **WREXHAM**
 MOLD ROAD
 WREXHAM
 RHOSDDU
 Edge of Town
 No Sub Category
 Site area: 2.5 hect
 Survey date: Monday 05/07/2004 Survey Type: Manual

417 **WS-03-A-03** **SEMI DET. & TERRACED** **WEST SUSSEX**

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

A266 NEAR CHICHESTER MID LAVANT Neighbourhood Centre Village Site area: 2 hect Survey date: Monday 20/11/2000				Survey Type: Manual
418 HILLS FARM LANE HORSHAM BROADBRIDGE HEATH Edge of Town Residential Zone Site area: 5.449999809265137 hect Survey date: Thursday 11/12/2014	WS-03-A-04	MIXED HOUSES	WEST SUSSEX	Survey Type: Manual
419 UPPER SHOREHAM ROAD SHOREHAM BY SEA Suburban Area Residential Zone Site area: 1.6100000143051147 hect Survey date: Wednesday 18/04/2012	WS-03-A-05	TERRACED & FLATS	WEST SUSSEX	Survey Type: Manual
420 EMMS LANE NEAR HORSHAM BROOKS GREEN Neighbourhood Centre Village Site area: 3.25 hect Survey date: Thursday 19/10/2017	WS-03-A-07	BUNGALOWS	WEST SUSSEX	Survey Type: Manual
421 ROUNDSTONE LANE ANGMERING Edge of Town Residential Zone Site area: 8.859999656677246 hect Survey date: Thursday 19/04/2018	WS-03-A-08	MIXED HOUSES	WEST SUSSEX	Survey Type: Manual
422 ELLIS ROAD WEST HORSHAM S BROADBRIDGE HEATH Edge of Town Residential Zone Site area: 50 hect Survey date: Tuesday 02/04/2019	WS-03-A-11	MIXED HOUSES	WEST SUSSEX	Survey Type: Manual
423 LITTLEHAMPTON ROAD WORTHING WEST DURRINGTON Edge of Town Residential Zone Site area: 5.360000133514404 hect Survey date: Wednesday 23/06/2021	WS-03-A-13	MIXED HOUSES & FLATS	WEST SUSSEX	Survey Type: Manual
424 TODDINGTON LANE LITTLEHAMPTON	WS-03-A-14	MIXED HOUSES	WEST SUSSEX	

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

WICK Edge of Town Residential Zone Site area: 2.8299999237060547 hect Survey date: Wednesday 20/10/2021 Survey Type: Manual			
425	WS-03-A-16	DETACHED & SEMI-DETACHED	WEST SUSSEX
BRACKLESHAM LANE BRACKLESHAM BAY Neighbourhood Centre Village Site area: 1.899999976158142 hect Survey date: Wednesday 09/11/2022 Survey Type: Manual			
426	WS-03-A-18	MIXED HOUSES & FLATS	WEST SUSSEX
LONDON ROAD HASOCKS Neighbourhood Centre Village Site area: 5.460000038146973 hect Survey date: Monday 15/05/2023 Survey Type: Manual			
427	WS-03-A-21	MIXED HOUSES	WEST SUSSEX
HILLAND ROAD BILLINGSHURST Neighbourhood Centre Village Site area: 32.930000030517578 hect Survey date: Thursday 09/11/2023 Survey Type: Manual			
428	WS-03-A-22	MIXED HOUSES & FLATS	WEST SUSSEX
SHOPWHYKE ROAD CHICHESTER Edge of Town Residential Zone Site area: 3.799999952316284 hect Survey date: Tuesday 19/03/2024 Survey Type: Manual			
429	WS-03-A-23	MIXED HOUSES & FLATS	WEST SUSSEX
TURNERS HILL ROAD EAST GRINSTEAD Edge of Town Residential Zone Site area: 6.639999866485596 hect Survey date: Tuesday 14/05/2024 Survey Type: Manual			
430	WS-03-A-24	MIXED HOUSES	WEST SUSSEX
MADGWICK LANE CHICHESTER WESTHAMPNETT Edge of Town Village Site area: 13.489999771118164 hect Survey date: Thursday 23/05/2024 Survey Type: Manual			
431	WS-03-A-25	PRIVATE HOUSES & FLATS	WEST SUSSEX
LIDSEY ROAD WOODGATE Neighbourhood Centre Village Site area: 2.4000000953674316 hect Survey date: Wednesday 18/09/2024 Survey Type: Manual			

Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

432 RUSPER ROAD HORSHAM NORTH HORSHAM Edge of Town Residential Zone Site area: 4 hect Survey date: Tuesday 24/09/2024	WS-03-A-26	MIXED HOUSES & FLATS	WEST SUSSEX	Survey Type: Manual
433 OCKLEY LANE HASSOCKS Edge of Town Residential Zone Site area: 9.42 hect Survey date: Friday 20/09/2024	WS-03-A-27	MIXED HOUSES & FLATS	WEST SUSSEX	Survey Type: Manual
434 CLONARD ROAD WEXFORD Suburban Area No Sub Category Site area: 1.440000057220459 hect Survey date: Thursday 25/09/2014	WX-03-A-01	SEMI-DETACHED	WEXFORD	Survey Type: Manual
435 NICHOLAS STREET YORK Suburban Area Residential Zone Site area: 0.15000000596046448 hect Survey date: Monday 16/09/2013	YO-03-A-01	TERRACED HOUSES	YORK	Survey Type: Manual
436 WATER LANE YORK CLIFTON MOOR Suburban Area Residential Zone Site area: 6.130000114440918 hect Survey date: Wednesday 18/09/2024	YO-03-A-02	MIXED HOUSES & FLATS	YORK	Survey Type: Manual



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

TRIP RATE for Land Use 03 - RESIDENTIAL/A - HOUSES PRIVATELY OWNED

Total Vehicles

Calculation factor: 1 DWELLS

**BOLD print indicates peak (busiest) period*

Period	Trips per 1 DWELLS DWELLS		
	Inbound	Outbound	Total
08:00-09:00	0.160	0.397	0.557
17:00-18:00	0.387	0.214	0.601

Time Range	No. Days	Ave. DWELLS	Arrivals	Departures	Totals
00:00-01:00	35	185	0.066	0.039	0.105
01:00-02:00	35	185	0.034	0.025	0.059
02:00-03:00	35	185	0.017	0.012	0.029
03:00-04:00	35	185	0.010	0.008	0.018
04:00-05:00	35	185	0.007	0.007	0.014
05:00-06:00	35	185	0.008	0.023	0.031
06:00-07:00	43	179	0.022	0.060	0.082
07:00-08:00	431	158	0.074	0.274	0.348
08:00-09:00	436	156	0.160	0.397	0.557
09:00-10:00	436	156	0.151	0.201	0.352
10:00-11:00	436	156	0.139	0.171	0.310
11:00-12:00	436	156	0.157	0.169	0.326
12:00-13:00	436	156	0.196	0.175	0.371
13:00-14:00	436	156	0.187	0.184	0.371
14:00-15:00	436	156	0.187	0.187	0.374
15:00-16:00	436	156	0.257	0.198	0.455
16:00-17:00	436	156	0.296	0.193	0.489
17:00-18:00	436	156	0.387	0.214	0.601
18:00-19:00	436	156	0.303	0.213	0.516
19:00-20:00	52	167	0.271	0.215	0.486
20:00-21:00	49	167	0.204	0.162	0.366
21:00-22:00	42	183	0.156	0.112	0.268
22:00-23:00	35	185	0.127	0.087	0.214
23:00-00:00	35	185	0.088	0.048	0.136
Total Rates:			3.504	3.374	6.878

This section displays the trip rate results based on the selected set of surveys and the selected count type (shown just above the table). It is split by three main columns, representing arrivals trips, departures trips, and total trips (arrivals plus departures). Within each of these main columns are three sub-columns. These display the number of survey days where count data is included (per time period), the average value of the selected trip rate calculation parameter (per time period), and the trip rate result (per time period). Total trip rates (the sum of the column) are also displayed at the foot of the table.

To obtain a trip rate, the average (mean) trip rate parameter value (TRP) is first calculated for all selected survey days that have count data available for the stated time period. The average (mean) number of arrivals, departures or totals (whichever applies) is also calculated (COUNT) for all selected survey days that have count data available for the stated time period. Then, the average count is divided by the average trip rate parameter value, and multiplied by the stated calculation factor (shown just above the table and abbreviated here as FACT). So, the method is: $COUNT/TRP*FACT$. Trip rates are then rounded to 3 decimal places.

The survey data, graphs and all associated supporting information, contained within the TRICS Database are published by TRICS Consortium Limited ("the Company") and the Company claims copyright and database rights in this published work. The Company authorises those who possess a current TRICS licence to access the TRICS Database and copy the data contained within the TRICS Database for the licence holders' use only. Any resulting copy must retain all copyrights and other proprietary notices, and any disclaimer contained thereon.

The Company accepts no responsibility for loss which may arise from reliance on data contained in the TRICS Database. [No warranty of any kind, express or implied, is made as to the data contained in the TRICS Database.]



Audit Code: 51b745af-61c1-46a3-a53c-fa2c2ea50d0c

Parameter Summary:

Trip rate parameter range selected:	4 - 4334 (units: DWELLS)
Survey date date range:	05/05/1987 - 30/06/2025
Number of weekdays (Monday-Friday):	396
Number of Saturdays:	7
Number of Sundays:	33
Surveys automatically removed from selection:	330
Surveys manually removed from selection:	0

This section displays a quick summary of some of the data filtering selections made by the TRICS® user. The trip rate calculation parameter range of all selected surveys is displayed first, followed by the range of minimum and maximum survey dates selected by the user. Then, the total number of selected weekdays and weekend days in the selected set of surveys are show. Finally, the number of survey days that have been manually removed from the selected set outside of the standard filtering procedure are displayed.



Appendix C – Junctions11 Modelling Data

<h1>Junctions 11</h1>
<h2>PICADY 11 - Priority Intersection Module</h2>
Version: 11.1.0.2307 © Copyright TRL Software Limited, 2024
For sales and distribution information, program advice and maintenance, contact TRL Software: +44 (0)1344 379777 software@trl.co.uk trlsoftware.com
The users of this computer program for the solution of an engineering problem are in no way relieved of their responsibility for the correctness of the solution

Filename: 252139 - JCT1.j11

Path: C:\Users\AngelikiKalatha\OneDrive - ORS\252139 TTA - New Resi Dev, Raheen & Pairc na hAbhainn, Athenry, Galway - Documents\01_WIP\Design\13g_Transportation_Reports\01_TTA\01_Raheen_site\01_WIP\03_JUNCTIONS11

Report generation date: 16/12/2025 17:26:47

-
- »D1 - 2025 | Base | AM
 - »D2 - 2025 | Base | PM
 - »D3 - 2027 | Do-nothing | AM
 - »D4 - 2027 | Do-nothing | PM
 - »D5 - 2027 | Do-something | AM
 - »D6 - 2027 | Do-something | PM
 - »D7 - 2032 | Do-nothing | AM
 - »D8 - 2032 | Do-nothing | PM
 - »D9 - 2032 | Do-something | AM
 - »D10 - 2032 | Do-something | PM
 - »D11 - 2042 | Do-nothing | AM
 - »D12 - 2042 | Do-nothing | PM
 - »D13 - 2042 | Do-something | AM
 - »D14 - 2042 | Do-something | PM
 - »D15 - | Com. Dev. | AM
 - »D16 - | Com. Dev. | PM
 - »D17 - | Development | AM
 - »D18 - | Development | PM

Summary of junction performance

	AM				PM			
	Set ID	Queue (PCU)	RFC	LOS	Set ID	Queue (PCU)	RFC	LOS
2025 - Base								
Stream B-AC	D1	0.8	0.43	B	D2	0.6	0.39	B
Stream C-AB		0.3	0.18	A		0.2	0.15	A
2027 - Do-nothing								
Stream B-AC	D3	1.0	0.50	C	D4	0.8	0.44	B
Stream C-AB		0.3	0.21	A		0.3	0.17	A
2027 - Do-something								
Stream B-AC	D5	1.1	0.51	C	D6	0.8	0.45	B
Stream C-AB		0.3	0.21	A		0.3	0.18	A
2032 - Do-nothing								
Stream B-AC	D7	1.3	0.56	C	D8	1.0	0.49	B
Stream C-AB		0.4	0.23	A		0.3	0.19	A
2032 - Do-something								
Stream B-AC	D9	1.4	0.57	C	D10	1.0	0.50	B
Stream C-AB		0.4	0.24	A		0.4	0.20	A
2042 - Do-nothing								
Stream B-AC	D11	1.7	0.63	C	D12	1.3	0.56	C
Stream C-AB		0.5	0.27	A		0.4	0.22	A
2042 - Do-something								
Stream B-AC	D13	1.9	0.65	C	D14	1.3	0.57	C
Stream C-AB		0.5	0.27	A		0.4	0.23	A
- Com. Dev.								
Stream B-AC	D15	0.0	0.02	A	D16	0.0	0.01	A
Stream C-AB		0.0	0.01	A		0.0	0.01	A
- Development								
Stream B-AC	D17	0.0	0.01	A	D18	0.0	0.00	A
Stream C-AB		0.0	0.00	A		0.0	0.00	A

There are warnings associated with one or more model runs - see the 'Data Errors and Warnings' tables for each Analysis or Demand Set.

Values shown are the highest values encountered over all time segments. Delay is the maximum value of average delay per arriving vehicle.

File summary

File Description

Title	252139
Location	Gort Mhaoilir
Site number	
Date	15/12/2025
Version	
Status	(new file)
Identifier	
Client	
Jobnumber	
Enumerator	AzureAD\AngelikiKalatha
Description	

Units

Distance units	Speed units	Traffic units input	Traffic units results	Flow units	Average delay units	Total delay units	Rate of delay units
m	kph	PCU	PCU	perHour	s	-Min	perMin

Analysis Options

PICADY short flare model	Vehicle length (m)	Calculate Queue Percentiles	Calculate detailed queueing delay	Show lane queues in feet / metres	Show all PICADY stream intercepts	Calculate residual capacity	RFC Threshold	Average Delay threshold (s)	Queue threshold (PCU)	Use simulation for HCM roundabouts	Use iterations for HCM roundabouts
PICADY 4.1	5.75						0.85	36.00	20.00		

Demand Set Summary

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D1	2025	Base	AM	ONE HOUR	08:00	09:30	15	✓		
D2	2025	Base	PM	ONE HOUR	16:15	17:45	15	✓		
D3	2027	Do-nothing	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G1)+D15
D4	2027	Do-nothing	PM	ONE HOUR	16:15	17:45	15	✓	Simple	(D2*G1)+D16
D5	2027	Do-something	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G1)+D15+D17
D6	2027	Do-something	PM	ONE HOUR	16:15	17:45	15	✓	Simple	(D2*G1)+D16+D18
D7	2032	Do-nothing	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G2)+D15
D8	2032	Do-nothing	PM	ONE HOUR	16:15	17:45	15	✓	Simple	(D2*G2)+D16
D9	2032	Do-something	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G2)+D15+D17
D10	2032	Do-something	PM	ONE HOUR	16:15	17:45	15	✓	Simple	(D2*G2)+D16+D18
D11	2042	Do-nothing	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G3)+D15
D12	2042	Do-nothing	PM	ONE HOUR	16:15	17:45	15	✓	Simple	(D2*G3)+D16
D13	2042	Do-something	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G3)+D15+D17
D14	2042	Do-something	PM	ONE HOUR	16:15	17:45	15	✓	Simple	(D2*G3)+D16+D18
D15		Com. Dev.	AM	ONE HOUR	08:00	09:30	15	✓		
D16		Com. Dev.	PM	ONE HOUR	16:15	17:45	15	✓		
D17		Development	AM	ONE HOUR	08:00	09:30	15	✓		
D18		Development	PM	ONE HOUR	16:15	17:45	15	✓		

Growth Factors

ID	Description	Use TEMPRO	Growth Factor
G1	2027		1.0525
G2	2032		1.1613
G3	2042		1.2932

Growth factors are only active if a Demand Set references them in a Relationship.

Analysis Set Details

ID	Include in report	Network flow scaling factor (%)	Network capacity scaling factor (%)
A1	✓	100.000	100.000

D1 - 2025 | Base | AM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		5.43	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		5.43	A

Arms

Arms

Arm	Name	Description	Arm type
A	R3103, NW		Major
B	Raheen Woods		Minor
C	L3103, SE		Major

Major Arm Geometry

Arm	Width of carriageway (m)	Has kerbed central reserve	Has right-turn storage	Visibility for right turn (m)	Blocks?	Blocking queue (PCU)
C	6.50			150.0	✓	0.00

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

Minor Arm Geometry

Arm	Minor arm type	Lane width (m)	Visibility to left (m)	Visibility to right (m)
B	One lane	3.50	27	25

Slope / Intercept / Capacity

Priority Intersection Slopes and Intercepts

Stream	Intercept (PCU/hr)	Slope for A-B	Slope for A-C	Slope for C-A	Slope for C-B
B-A	524	0.093	0.236	0.148	0.337
B-C	672	0.101	0.255	-	-
C-B	661	0.250	0.250	-	-

The slopes and intercepts shown above include custom intercept adjustments only.

Streams may be combined, in which case capacity will be adjusted.

Values are shown for the first time segment only; they may differ for subsequent time segments.

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D1	2025	Base	AM	ONE HOUR	08:00	09:30	15	✓

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	219	100.000
B		ONE HOUR	✓	190	100.000
C		ONE HOUR	✓	204	100.000

Origin-Destination Data

Demand (PCU/hr)

From	To		
	A	B	C
A	0	113	106
B	126	0	64
C	111	93	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

From	To		
	A	B	C
A	0	1	4
B	5	0	2
C	6	2	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.43	13.66	0.8	B	174	261
C-AB	0.18	6.64	0.3	A	101	151
C-A					86	129
A-B					103	155
A-C					97	146

Main Results for each time segment

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	143	36	0.00	509	0.280	141	0.0	0.4	10.121	B
C-AB	80	20	0.00	674	0.118	79	0.0	0.2	6.197	A
C-A	73	18	0.00			73				
A-B	85	21	0.00			85				
A-C	80	20	0.00			80				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	170	43	0.00	498	0.342	170	0.4	0.5	11.381	B
C-AB	98	25	0.00	677	0.145	98	0.2	0.2	6.372	A
C-A	85	21	0.00			85				
A-B	101	25	0.00			101				
A-C	95	24	0.00			95				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	209	52	0.00	483	0.432	208	0.5	0.8	13.564	B
C-AB	125	31	0.00	682	0.183	125	0.2	0.3	6.631	A
C-A	99	25	0.00			99				
A-B	124	31	0.00			124				
A-C	117	29	0.00			117				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	209	52	0.00	483	0.432	209	0.8	0.8	13.658	B
C-AB	125	31	0.00	682	0.183	125	0.3	0.3	6.642	A
C-A	99	25	0.00			99				
A-B	124	31	0.00			124				
A-C	117	29	0.00			117				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	170	43	0.00	498	0.342	171	0.8	0.6	11.491	B
C-AB	98	25	0.00	677	0.145	98	0.3	0.2	6.391	A
C-A	85	21	0.00			85				
A-B	101	25	0.00			101				
A-C	95	24	0.00			95				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	143	36	0.00	509	0.280	143	0.6	0.4	10.244	B
C-AB	80	20	0.00	674	0.119	80	0.2	0.2	6.219	A
C-A	73	18	0.00			73				
A-B	85	21	0.00			85				
A-C	80	20	0.00			80				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D2 - 2025 | Base | PM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		4.08	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		4.08	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D2	2025	Base	PM	ONE HOUR	16:15	17:45	15	✓

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	249	100.000
B		ONE HOUR	✓	181	100.000
C		ONE HOUR	✓	226	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	115	134
	B	84	0	98
	C	155	71	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	1	6
	B	2	0	2
	C	11	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.39	11.74	0.6	B	166	249
C-AB	0.15	6.11	0.2	A	83	124
C-A					125	188
A-B					105	158
A-C					123	184

Main Results for each time segment

16:15 - 16:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	136	34	0.00	539	0.253	135	0.0	0.3	9.063	A
C-AB	64	16	0.00	691	0.093	64	0.0	0.1	5.835	A
C-A	106	27	0.00			106				
A-B	86	22	0.00			86				
A-C	101	25	0.00			101				

16:30 - 16:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	163	41	0.00	528	0.309	162	0.3	0.4	10.041	B
C-AB	80	20	0.00	698	0.115	80	0.1	0.2	5.936	A
C-A	124	31	0.00			124				
A-B	103	26	0.00			103				
A-C	120	30	0.00			120				

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	200	50	0.00	512	0.389	199	0.4	0.6	11.680	B
C-AB	103	26	0.00	707	0.146	103	0.2	0.2	6.095	A
C-A	146	36	0.00			146				
A-B	126	32	0.00			126				
A-C	148	37	0.00			148				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	200	50	0.00	512	0.389	199	0.6	0.6	11.737	B
C-AB	103	26	0.00	707	0.146	103	0.2	0.2	6.112	A
C-A	146	36	0.00			146				
A-B	126	32	0.00			126				
A-C	148	37	0.00			148				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	163	41	0.00	528	0.309	164	0.6	0.5	10.109	B
C-AB	80	20	0.00	698	0.115	80	0.2	0.2	5.969	A
C-A	124	31	0.00			124				
A-B	103	26	0.00			103				
A-C	120	30	0.00			120				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	136	34	0.00	539	0.253	137	0.5	0.4	9.150	A
C-AB	64	16	0.00	691	0.093	65	0.2	0.1	5.859	A
C-A	106	26	0.00			106				
A-B	86	22	0.00			86				
A-C	101	25	0.00			101				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D3 - 2027 | Do-nothing | AM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		5.94	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		5.94	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D3	2027	Do-nothing	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G1)+D15

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	270	100.000
B		ONE HOUR	✓	210	100.000
C		ONE HOUR	✓	230	100.000

Origin-Destination Data

Demand (PCU/hr)

From	To		
	A	B	C
A	0	125	145
B	140	0	71
C	127	103	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

From	To		
	A	B	C
A	0	0.95	7
B	5	0	2
C	7	2	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.50	15.96	1.0	C	193	290
C-AB	0.21	6.89	0.3	A	115	172
C-A					96	144
A-B					114	172
A-C					133	200

Main Results for each time segment

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	158	40	0.00	498	0.318	157	0.0	0.5	10.882	B
C-AB	90	23	0.00	673	0.134	90	0.0	0.2	6.322	A
C-A	83	21	0.00			83				
A-B	94	23	0.00			94				
A-C	109	27	0.00			109				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	189	47	0.00	484	0.391	188	0.5	0.7	12.590	B
C-AB	111	28	0.00	676	0.165	111	0.2	0.2	6.541	A
C-A	95	24	0.00			95				
A-B	112	28	0.00			112				
A-C	130	33	0.00			130				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	232	58	0.00	466	0.498	230	0.7	1.0	15.776	C
C-AB	143	36	0.00	681	0.210	142	0.2	0.3	6.874	A
C-A	111	28	0.00			111				
A-B	137	34	0.00			137				
A-C	160	40	0.00			160				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	232	58	0.00	466	0.498	232	1.0	1.0	15.955	C
C-AB	143	36	0.00	681	0.210	143	0.3	0.3	6.889	A
C-A	110	28	0.00			110				
A-B	137	34	0.00			137				
A-C	160	40	0.00			160				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	189	47	0.00	484	0.391	191	1.0	0.7	12.772	B
C-AB	112	28	0.00	677	0.165	112	0.3	0.2	6.565	A
C-A	95	24	0.00			95				
A-B	112	28	0.00			112				
A-C	130	33	0.00			130				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	158	40	0.00	498	0.318	159	0.7	0.5	11.059	B
C-AB	90	23	0.00	673	0.134	91	0.2	0.2	6.348	A
C-A	83	21	0.00			83				
A-B	94	23	0.00			94				
A-C	109	27	0.00			109				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D4 - 2027 | Do-nothing | PM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		4.31	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		4.31	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D4	2027	Do-nothing	PM	ONE HOUR	16:15	17:45	15	✓	Simple	(D2*G1)+D16

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	283	100.000
B		ONE HOUR	✓	198	100.000
C		ONE HOUR	✓	276	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	127	157
	B	92	0	106
	C	196	80	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	0.95	7
	B	2	0	2
	C	12	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.44	13.12	0.8	B	181	272
C-AB	0.17	6.17	0.3	A	99	148
C-A					154	232
A-B					116	174
A-C					144	216

Main Results for each time segment

16:15 - 16:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	149	37	0.00	529	0.282	147	0.0	0.4	9.585	A
C-AB	76	19	0.00	705	0.108	75	0.0	0.2	5.851	A
C-A	132	33	0.00			132				
A-B	95	24	0.00			95				
A-C	118	29	0.00			118				

16:30 - 16:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	178	44	0.00	515	0.345	177	0.4	0.5	10.831	B
C-AB	95	24	0.00	715	0.133	95	0.2	0.2	5.961	A
C-A	153	38	0.00			153				
A-B	114	28	0.00			114				
A-C	141	35	0.00			141				

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	218	54	0.00	497	0.438	217	0.5	0.8	13.035	B
C-AB	125	31	0.00	729	0.172	125	0.2	0.3	6.145	A
C-A	179	45	0.00			179				
A-B	140	35	0.00			140				
A-C	172	43	0.00			172				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	218	54	0.00	497	0.438	218	0.8	0.8	13.125	B
C-AB	125	31	0.00	729	0.172	125	0.3	0.3	6.169	A
C-A	179	45	0.00			179				
A-B	140	35	0.00			140				
A-C	172	43	0.00			172				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	178	44	0.00	515	0.345	179	0.8	0.5	10.930	B
C-AB	95	24	0.00	715	0.133	96	0.3	0.2	6.007	A
C-A	153	38	0.00			153				
A-B	114	28	0.00			114				
A-C	141	35	0.00			141				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	149	37	0.00	528	0.282	149	0.5	0.4	9.696	A
C-AB	76	19	0.00	705	0.108	76	0.2	0.2	5.878	A
C-A	132	33	0.00			132				
A-B	95	24	0.00			95				
A-C	118	29	0.00			118				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D5 - 2027 | Do-something | AM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		6.17	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		6.17	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D5	2027	Do-something	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G1) +D15+D17

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	271	100.000
B		ONE HOUR	✓	216	100.000
C		ONE HOUR	✓	231	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	126	145
	B	144	0	73
	C	127	104	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	0.94	7
	B	5	0	2
	C	7	2	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.51	16.43	1.1	C	199	298
C-AB	0.21	6.91	0.3	A	116	174
C-A					96	144
A-B					115	173
A-C					133	200

Main Results for each time segment

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	163	41	0.00	498	0.327	161	0.0	0.5	11.020	B
C-AB	91	23	0.00	673	0.135	90	0.0	0.2	6.333	A
C-A	83	21	0.00			83				
A-B	95	24	0.00			95				
A-C	109	27	0.00			109				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	195	49	0.00	484	0.402	194	0.5	0.7	12.822	B
C-AB	113	28	0.00	676	0.166	112	0.2	0.2	6.555	A
C-A	95	24	0.00			95				
A-B	113	28	0.00			113				
A-C	130	33	0.00			130				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	238	60	0.00	465	0.512	237	0.7	1.1	16.227	C
C-AB	144	36	0.00	681	0.212	144	0.2	0.3	6.894	A
C-A	110	28	0.00			110				
A-B	138	35	0.00			138				
A-C	160	40	0.00			160				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	238	60	0.00	465	0.512	238	1.1	1.1	16.430	C
C-AB	144	36	0.00	681	0.212	144	0.3	0.3	6.912	A
C-A	110	28	0.00			110				
A-B	138	35	0.00			138				
A-C	160	40	0.00			160				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	195	49	0.00	484	0.402	196	1.1	0.7	13.027	B
C-AB	113	28	0.00	676	0.167	113	0.3	0.2	6.582	A
C-A	95	24	0.00			95				
A-B	113	28	0.00			113				
A-C	130	33	0.00			130				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	163	41	0.00	497	0.328	164	0.7	0.5	11.211	B
C-AB	91	23	0.00	673	0.136	92	0.2	0.2	6.361	A
C-A	83	21	0.00			83				
A-B	95	24	0.00			95				
A-C	109	27	0.00			109				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D6 - 2027 | Do-something | PM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		4.39	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		4.39	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D6	2027	Do-something	PM	ONE HOUR	16:15	17:45	15	✓	Simple	(D2*G1) +D16+D18

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	286	100.000
B		ONE HOUR	✓	201	100.000
C		ONE HOUR	✓	278	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	130	157
	B	93	0	108
	C	196	82	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	0.93	7
	B	2	0	2
	C	12	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.45	13.31	0.8	B	185	277
C-AB	0.18	6.21	0.3	A	101	152
C-A					154	231
A-B					119	179
A-C					144	216

Main Results for each time segment

16:15 - 16:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	151	38	0.00	529	0.286	150	0.0	0.4	9.646	A
C-AB	78	19	0.00	705	0.110	77	0.0	0.2	5.868	A
C-A	131	33	0.00			131				
A-B	98	24	0.00			98				
A-C	118	29	0.00			118				

16:30 - 16:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	181	45	0.00	515	0.351	180	0.4	0.5	10.928	B
C-AB	98	24	0.00	714	0.137	98	0.2	0.2	5.988	A
C-A	152	38	0.00			152				
A-B	117	29	0.00			117				
A-C	141	35	0.00			141				

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	221	55	0.00	497	0.446	220	0.5	0.8	13.215	B
C-AB	128	32	0.00	728	0.176	128	0.2	0.3	6.185	A
C-A	178	44	0.00			178				
A-B	143	36	0.00			143				
A-C	172	43	0.00			172				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	221	55	0.00	497	0.446	221	0.8	0.8	13.311	B
C-AB	128	32	0.00	728	0.176	128	0.3	0.3	6.212	A
C-A	178	44	0.00			178				
A-B	143	36	0.00			143				
A-C	172	43	0.00			172				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	181	45	0.00	515	0.351	182	0.8	0.6	11.033	B
C-AB	98	24	0.00	714	0.137	98	0.3	0.2	6.037	A
C-A	152	38	0.00			152				
A-B	117	29	0.00			117				
A-C	141	35	0.00			141				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	151	38	0.00	528	0.287	152	0.6	0.4	9.762	A
C-AB	78	20	0.00	705	0.111	78	0.2	0.2	5.904	A
C-A	131	33	0.00			131				
A-B	98	24	0.00			98				
A-C	118	29	0.00			118				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D7 - 2032 | Do-nothing | AM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		6.78	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		6.78	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D7	2032	Do-nothing	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G2)+D15

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	293	100.000
B		ONE HOUR	✓	231	100.000
C		ONE HOUR	✓	252	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	137	156
	B	153	0	78
	C	139	113	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	0.96	7
	B	5	0	2
	C	7	2	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.56	18.47	1.3	C	212	318
C-AB	0.23	7.09	0.4	A	129	193
C-A					103	154
A-B					126	188
A-C					144	215

Main Results for each time segment

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	174	43	0.00	492	0.354	172	0.0	0.6	11.598	B
C-AB	101	25	0.00	675	0.149	100	0.0	0.2	6.419	A
C-A	89	22	0.00			89				
A-B	103	26	0.00			103				
A-C	118	29	0.00			118				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	208	52	0.00	477	0.436	207	0.6	0.8	13.786	B
C-AB	125	31	0.00	679	0.184	124	0.2	0.3	6.675	A
C-A	102	26	0.00			102				
A-B	123	31	0.00			123				
A-C	141	35	0.00			141				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	254	64	0.00	456	0.558	253	0.8	1.3	18.154	C
C-AB	161	40	0.00	684	0.235	160	0.3	0.4	7.074	A
C-A	117	29	0.00			117				
A-B	151	38	0.00			151				
A-C	172	43	0.00			172				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	254	64	0.00	456	0.558	254	1.3	1.3	18.474	C
C-AB	161	40	0.00	684	0.235	161	0.4	0.4	7.092	A
C-A	117	29	0.00			117				
A-B	151	38	0.00			151				
A-C	172	43	0.00			172				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	208	52	0.00	477	0.436	210	1.3	0.8	14.079	B
C-AB	125	31	0.00	679	0.184	125	0.4	0.3	6.707	A
C-A	102	25	0.00			102				
A-B	123	31	0.00			123				
A-C	141	35	0.00			141				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	174	43	0.00	491	0.354	175	0.8	0.6	11.839	B
C-AB	101	25	0.00	675	0.149	101	0.3	0.2	6.450	A
C-A	89	22	0.00			89				
A-B	103	26	0.00			103				
A-C	118	29	0.00			118				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D8 - 2032 | Do-nothing | PM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		4.80	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		4.80	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D8	2032	Do-nothing	PM	ONE HOUR	16:15	17:45	15	✓	Simple	(D2*G2)+D16

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	310	100.000
B		ONE HOUR	✓	217	100.000
C		ONE HOUR	✓	301	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	139	171
	B	101	0	116
	C	213	87	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	0.96	7
	B	2	0	2
	C	12	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.49	14.76	1.0	B	200	299
C-AB	0.19	6.30	0.3	A	111	167
C-A					164	246
A-B					128	192
A-C					157	236

Main Results for each time segment

16:15 - 16:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	164	41	0.00	522	0.313	162	0.0	0.5	10.129	B
C-AB	85	21	0.00	709	0.120	84	0.0	0.2	5.906	A
C-A	141	35	0.00			141				
A-B	105	26	0.00			105				
A-C	129	32	0.00			129				

16:30 - 16:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	195	49	0.00	508	0.385	195	0.5	0.6	11.691	B
C-AB	107	27	0.00	720	0.149	107	0.2	0.2	6.043	A
C-A	163	41	0.00			163				
A-B	125	31	0.00			125				
A-C	154	38	0.00			154				

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	239	60	0.00	488	0.491	238	0.6	1.0	14.610	B
C-AB	142	35	0.00	735	0.193	141	0.2	0.3	6.268	A
C-A	189	47	0.00			189				
A-B	153	38	0.00			153				
A-C	189	47	0.00			189				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	239	60	0.00	488	0.491	239	1.0	1.0	14.759	B
C-AB	142	35	0.00	735	0.193	142	0.3	0.3	6.296	A
C-A	189	47	0.00			189				
A-B	153	38	0.00			153				
A-C	189	47	0.00			189				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	195	49	0.00	508	0.385	197	1.0	0.7	11.844	B
C-AB	107	27	0.00	720	0.149	108	0.3	0.2	6.092	A
C-A	163	41	0.00			163				
A-B	125	31	0.00			125				
A-C	154	38	0.00			154				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	164	41	0.00	522	0.313	164	0.7	0.5	10.275	B
C-AB	85	21	0.00	709	0.120	86	0.2	0.2	5.942	A
C-A	141	35	0.00			141				
A-B	105	26	0.00			105				
A-C	129	32	0.00			129				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D9 - 2032 | Do-something | AM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		7.06	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		7.06	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D9	2032	Do-something	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G2) +D15+D17

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	294	100.000
B		ONE HOUR	✓	237	100.000
C		ONE HOUR	✓	253	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	138	156
	B	157	0	80
	C	139	114	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	0.95	7
	B	5	0	2
	C	7	2	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.57	19.12	1.4	C	218	326
C-AB	0.24	7.11	0.4	A	130	195
C-A					102	154
A-B					127	190
A-C					144	215

Main Results for each time segment

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	178	45	0.00	491	0.363	176	0.0	0.6	11.755	B
C-AB	102	25	0.00	675	0.151	101	0.0	0.2	6.430	A
C-A	89	22	0.00			89				
A-B	104	26	0.00			104				
A-C	118	29	0.00			118				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	213	53	0.00	476	0.447	212	0.6	0.8	14.069	B
C-AB	126	31	0.00	678	0.185	126	0.2	0.3	6.690	A
C-A	102	25	0.00			102				
A-B	124	31	0.00			124				
A-C	141	35	0.00			141				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	261	65	0.00	456	0.573	259	0.8	1.3	18.751	C
C-AB	162	41	0.00	684	0.237	162	0.3	0.4	7.096	A
C-A	117	29	0.00			117				
A-B	152	38	0.00			152				
A-C	172	43	0.00			172				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	261	65	0.00	456	0.573	261	1.3	1.4	19.119	C
C-AB	162	41	0.00	684	0.237	162	0.4	0.4	7.114	A
C-A	117	29	0.00			117				
A-B	152	38	0.00			152				
A-C	172	43	0.00			172				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	213	53	0.00	476	0.447	215	1.4	0.9	14.393	B
C-AB	126	31	0.00	679	0.186	126	0.4	0.3	6.719	A
C-A	102	25	0.00			102				
A-B	124	31	0.00			124				
A-C	141	35	0.00			141				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	178	45	0.00	491	0.363	180	0.9	0.6	12.016	B
C-AB	102	25	0.00	675	0.151	102	0.3	0.2	6.461	A
C-A	89	22	0.00			89				
A-B	104	26	0.00			104				
A-C	118	29	0.00			118				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D10 - 2032 | Do-something | PM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		4.90	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		4.90	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D10	2032	Do-something	PM	ONE HOUR	16:15	17:45	15	✓	Simple	(D2*G2) +D16+D18

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	313	100.000
B		ONE HOUR	✓	221	100.000
C		ONE HOUR	✓	303	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	142	171
	B	102	0	119
	C	213	89	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

	To			
	A	B	C	
From	A	0	0.94	7
	B	2	0	2
	C	12	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.50	15.00	1.0	B	203	304
C-AB	0.20	6.34	0.4	A	114	171
C-A					164	245
A-B					130	196
A-C					157	236

Main Results for each time segment

16:15 - 16:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	166	42	0.00	522	0.318	164	0.0	0.5	10.196	B
C-AB	87	22	0.00	708	0.123	86	0.0	0.2	5.930	A
C-A	141	35	0.00			141				
A-B	107	27	0.00			107				
A-C	129	32	0.00			129				

16:30 - 16:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	199	50	0.00	508	0.391	198	0.5	0.6	11.807	B
C-AB	110	27	0.00	719	0.153	110	0.2	0.2	6.074	A
C-A	162	41	0.00			162				
A-B	128	32	0.00			128				
A-C	154	38	0.00			154				

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	243	61	0.00	488	0.499	242	0.6	1.0	14.839	B
C-AB	145	36	0.00	734	0.198	145	0.2	0.3	6.311	A
C-A	188	47	0.00			188				
A-B	157	39	0.00			157				
A-C	189	47	0.00			189				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	243	61	0.00	488	0.499	243	1.0	1.0	14.999	B
C-AB	145	36	0.00	734	0.198	145	0.3	0.4	6.339	A
C-A	188	47	0.00			188				
A-B	157	39	0.00			157				
A-C	189	47	0.00			189				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	199	50	0.00	508	0.391	200	1.0	0.7	11.966	B
C-AB	110	27	0.00	719	0.153	110	0.4	0.3	6.124	A
C-A	162	40	0.00			162				
A-B	128	32	0.00			128				
A-C	154	38	0.00			154				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	166	42	0.00	522	0.318	167	0.7	0.5	10.352	B
C-AB	87	22	0.00	709	0.123	88	0.3	0.2	5.968	A
C-A	140	35	0.00			140				
A-B	107	27	0.00			107				
A-C	129	32	0.00			129				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D11 - 2042 | Do-nothing | AM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		8.19	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		8.19	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D11	2042	Do-nothing	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G3)+D15

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	322	100.000
B		ONE HOUR	✓	256	100.000
C		ONE HOUR	✓	279	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	152	170
	B	170	0	86
	C	154	125	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

	To			
	A	B	C	
From	A	0	0.96	7
	B	5	0	2
	C	7	2	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.63	22.83	1.7	C	235	352
C-AB	0.27	7.37	0.5	A	146	219
C-A					110	165
A-B					139	209
A-C					156	235

Main Results for each time segment

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	193	48	0.00	484	0.398	190	0.0	0.7	12.599	B
C-AB	114	28	0.00	677	0.168	113	0.0	0.2	6.544	A
C-A	96	24	0.00			96				
A-B	114	29	0.00			114				
A-C	128	32	0.00			128				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	230	58	0.00	468	0.492	229	0.7	1.0	15.570	C
C-AB	141	35	0.00	681	0.208	141	0.2	0.3	6.853	A
C-A	109	27	0.00			109				
A-B	136	34	0.00			136				
A-C	153	38	0.00			153				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	282	70	0.00	445	0.634	279	1.0	1.7	22.137	C
C-AB	183	46	0.00	688	0.267	183	0.3	0.5	7.342	A
C-A	124	31	0.00			124				
A-B	167	42	0.00			167				
A-C	188	47	0.00			188				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	282	70	0.00	445	0.634	282	1.7	1.7	22.833	C
C-AB	183	46	0.00	688	0.267	183	0.5	0.5	7.371	A
C-A	124	31	0.00			124				
A-B	167	42	0.00			167				
A-C	188	47	0.00			188				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	230	58	0.00	467	0.492	233	1.7	1.0	16.121	C
C-AB	142	35	0.00	682	0.208	142	0.5	0.3	6.891	A
C-A	109	27	0.00			109				
A-B	136	34	0.00			136				
A-C	153	38	0.00			153				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	193	48	0.00	484	0.398	194	1.0	0.7	12.959	B
C-AB	114	28	0.00	677	0.168	114	0.3	0.3	6.581	A
C-A	96	24	0.00			96				
A-B	114	29	0.00			114				
A-C	128	32	0.00			128				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D12 - 2042 | Do-nothing | PM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		5.57	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		5.57	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D12	2042	Do-nothing	PM	ONE HOUR	16:15	17:45	15	✓	Simple	(D2*G3)+D16

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	343	100.000
B		ONE HOUR	✓	241	100.000
C		ONE HOUR	✓	330	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	154	189
	B	112	0	129
	C	234	97	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	0.96	7
	B	2	0	2
	C	12	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.56	17.39	1.3	C	221	332
C-AB	0.22	6.47	0.4	A	128	192
C-A					175	263
A-B					142	212
A-C					173	260

Main Results for each time segment

16:15 - 16:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	182	45	0.00	515	0.353	180	0.0	0.5	10.873	B
C-AB	97	24	0.00	714	0.136	96	0.0	0.2	5.982	A
C-A	152	38	0.00			152				
A-B	116	29	0.00			116				
A-C	142	36	0.00			142				

16:30 - 16:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	217	54	0.00	499	0.435	216	0.5	0.8	12.935	B
C-AB	123	31	0.00	726	0.169	122	0.2	0.3	6.152	A
C-A	174	44	0.00			174				
A-B	139	35	0.00			139				
A-C	170	42	0.00			170				

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	266	66	0.00	476	0.558	264	0.8	1.2	17.100	C
C-AB	164	41	0.00	743	0.220	163	0.3	0.4	6.436	A
C-A	200	50	0.00			200				
A-B	170	42	0.00			170				
A-C	208	52	0.00			208				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	266	66	0.00	476	0.558	266	1.2	1.3	17.386	C
C-AB	164	41	0.00	743	0.220	164	0.4	0.4	6.472	A
C-A	200	50	0.00			200				
A-B	170	42	0.00			170				
A-C	208	52	0.00			208				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	217	54	0.00	499	0.435	219	1.3	0.8	13.195	B
C-AB	123	31	0.00	726	0.169	123	0.4	0.3	6.211	A
C-A	174	44	0.00			174				
A-B	139	35	0.00			139				
A-C	170	42	0.00			170				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	182	45	0.00	515	0.353	183	0.8	0.6	11.086	B
C-AB	97	24	0.00	714	0.136	97	0.3	0.2	6.025	A
C-A	152	38	0.00			152				
A-B	116	29	0.00			116				
A-C	142	36	0.00			142				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D13 - 2042 | Do-something | AM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		8.59	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		8.59	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D13	2042	Do-something	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G3) +D15+D17

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	323	100.000
B		ONE HOUR	✓	262	100.000
C		ONE HOUR	✓	280	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	153	170
	B	174	0	88
	C	154	126	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	0.95	7
	B	5	0	2
	C	7	2	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.65	23.82	1.9	C	240	361
C-AB	0.27	7.39	0.5	A	147	221
C-A					110	164
A-B					140	210
A-C					156	235

Main Results for each time segment

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	197	49	0.00	484	0.408	195	0.0	0.7	12.787	B
C-AB	115	29	0.00	677	0.169	114	0.0	0.2	6.556	A
C-A	96	24	0.00			96				
A-B	115	29	0.00			115				
A-C	128	32	0.00			128				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	236	59	0.00	467	0.504	234	0.7	1.0	15.928	C
C-AB	143	36	0.00	681	0.209	142	0.2	0.3	6.869	A
C-A	109	27	0.00			109				
A-B	137	34	0.00			137				
A-C	153	38	0.00			153				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	289	72	0.00	445	0.649	285	1.0	1.8	23.011	C
C-AB	185	46	0.00	687	0.269	184	0.3	0.5	7.368	A
C-A	124	31	0.00			124				
A-B	168	42	0.00			168				
A-C	188	47	0.00			188				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	289	72	0.00	444	0.649	288	1.8	1.9	23.823	C
C-AB	185	46	0.00	688	0.269	185	0.5	0.5	7.393	A
C-A	123	31	0.00			123				
A-B	168	42	0.00			168				
A-C	188	47	0.00			188				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	236	59	0.00	467	0.504	239	1.9	1.1	16.550	C
C-AB	143	36	0.00	681	0.210	143	0.5	0.3	6.905	A
C-A	109	27	0.00			109				
A-B	137	34	0.00			137				
A-C	153	38	0.00			153				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	197	49	0.00	483	0.408	199	1.1	0.7	13.176	B
C-AB	115	29	0.00	677	0.170	115	0.3	0.3	6.596	A
C-A	96	24	0.00			96				
A-B	115	29	0.00			115				
A-C	128	32	0.00			128				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D14 - 2042 | Do-something | PM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		5.70	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		5.70	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D14	2042	Do-something	PM	ONE HOUR	16:15	17:45	15	✓	Simple	(D2*G3) +D16+D18

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	346	100.000
B		ONE HOUR	✓	245	100.000
C		ONE HOUR	✓	332	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	157	189
	B	113	0	131
	C	234	99	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	0.94	7
	B	2	0	2
	C	12	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.57	17.73	1.3	C	225	337
C-AB	0.23	6.52	0.4	A	130	196
C-A					175	262
A-B					144	217
A-C					173	260

Main Results for each time segment

16:15 - 16:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	184	46	0.00	515	0.358	182	0.0	0.6	10.955	B
C-AB	99	25	0.00	713	0.138	98	0.0	0.2	6.007	A
C-A	151	38	0.00			151				
A-B	118	30	0.00			118				
A-C	142	36	0.00			142				

16:30 - 16:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	220	55	0.00	499	0.441	219	0.6	0.8	13.078	B
C-AB	125	31	0.00	725	0.173	125	0.2	0.3	6.184	A
C-A	173	43	0.00			173				
A-B	141	35	0.00			141				
A-C	170	42	0.00			170				

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	269	67	0.00	476	0.566	267	0.8	1.3	17.413	C
C-AB	167	42	0.00	742	0.225	166	0.3	0.4	6.483	A
C-A	199	50	0.00			199				
A-B	173	43	0.00			173				
A-C	208	52	0.00			208				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	269	67	0.00	476	0.566	269	1.3	1.3	17.725	C
C-AB	167	42	0.00	742	0.225	167	0.4	0.4	6.517	A
C-A	199	50	0.00			199				
A-B	173	43	0.00			173				
A-C	208	52	0.00			208				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	220	55	0.00	499	0.441	222	1.3	0.8	13.353	B
C-AB	126	31	0.00	725	0.173	126	0.4	0.3	6.243	A
C-A	173	43	0.00			173				
A-B	141	35	0.00			141				
A-C	170	42	0.00			170				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	184	46	0.00	515	0.358	185	0.8	0.6	11.175	B
C-AB	99	25	0.00	713	0.139	99	0.3	0.2	6.053	A
C-A	151	38	0.00			151				
A-B	118	30	0.00			118				
A-C	142	36	0.00			142				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D15 - | Com. Dev. | AM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		1.52	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		1.52	A

Traffic Demand

Demand Set Details

ID	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D15	Com. Dev.	AM	ONE HOUR	08:00	09:30	15	✓

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	39	100.000
B		ONE HOUR	✓	11	100.000
C		ONE HOUR	✓	16	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	6	33
	B	7	0	4
	C	11	5	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	0	20
	B	0	0	0
	C	20	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.02	6.61	0.0	A	10	15
C-AB	0.01	5.54	0.0	A	5	7
C-A					10	15
A-B					6	8
A-C					31	46

Main Results for each time segment

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	8	2	0.00	561	0.015	8	0.0	0.0	6.513	A
C-AB	4	0.95	0.00	659	0.006	4	0.0	0.0	5.508	A
C-A	8	2	0.00			8				
A-B	5	1	0.00			5				
A-C	25	6	0.00			25				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	10	2	0.00	559	0.018	10	0.0	0.0	6.551	A
C-AB	5	1	0.00	658	0.007	5	0.0	0.0	5.519	A
C-A	10	2	0.00			10				
A-B	5	1	0.00			5				
A-C	30	8	0.00			30				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	12	3	0.00	557	0.022	12	0.0	0.0	6.605	A
C-AB	6	1	0.00	658	0.009	6	0.0	0.0	5.536	A
C-A	12	3	0.00			12				
A-B	7	2	0.00			7				
A-C	37	9	0.00			37				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	12	3	0.00	557	0.022	12	0.0	0.0	6.605	A
C-AB	6	1	0.00	658	0.009	6	0.0	0.0	5.539	A
C-A	12	3	0.00			12				
A-B	7	2	0.00			7				
A-C	37	9	0.00			37				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	10	2	0.00	559	0.018	10	0.0	0.0	6.554	A
C-AB	5	1	0.00	658	0.007	5	0.0	0.0	5.522	A
C-A	10	2	0.00			10				
A-B	5	1	0.00			5				
A-C	30	8	0.00			30				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	8	2	0.00	561	0.015	8	0.0	0.0	6.513	A
C-AB	4	0.95	0.00	659	0.006	4	0.0	0.0	5.512	A
C-A	8	2	0.00			8				
A-B	5	1	0.00			5				
A-C	25	6	0.00			25				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D16 - | Com. Dev. | PM

Data Errors and Warnings

No errors or warnings

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		1.11	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		1.11	A

Traffic Demand

Demand Set Details

ID	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D16	Com. Dev.	PM	ONE HOUR	16:15	17:45	15	✓

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	22	100.000
B		ONE HOUR	✓	7	100.000
C		ONE HOUR	✓	38	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	6	16
	B	4	0	3
	C	33	5	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	0	20
	B	0	0	0
	C	20	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.01	6.42	0.0	A	6	10
C-AB	0.01	5.42	0.0	A	5	7
C-A					30	45
A-B					6	8
A-C					14	21

Main Results for each time segment

16:15 - 16:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	5	1	0.00	572	0.009	5	0.0	0.0	6.355	A
C-AB	4	0.98	0.00	672	0.006	4	0.0	0.0	5.418	A
C-A	24	6	0.00			24				
A-B	5	1	0.00			5				
A-C	12	3	0.00			12				

16:30 - 16:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	6	2	0.00	570	0.011	6	0.0	0.0	6.381	A
C-AB	5	1	0.00	675	0.007	5	0.0	0.0	5.410	A
C-A	29	7	0.00			29				
A-B	5	1	0.00			5				
A-C	14	4	0.00			14				

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	8	2	0.00	569	0.014	8	0.0	0.0	6.418	A
C-AB	6	1	0.00	678	0.009	6	0.0	0.0	5.401	A
C-A	36	9	0.00			36				
A-B	7	2	0.00			7				
A-C	17	4	0.00			17				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	8	2	0.00	568	0.014	8	0.0	0.0	6.418	A
C-AB	6	1	0.00	678	0.009	6	0.0	0.0	5.405	A
C-A	36	9	0.00			36				
A-B	7	2	0.00			7				
A-C	17	4	0.00			17				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	6	2	0.00	570	0.011	6	0.0	0.0	6.382	A
C-AB	5	1	0.00	675	0.007	5	0.0	0.0	5.418	A
C-A	29	7	0.00			29				
A-B	5	1	0.00			5				
A-C	14	4	0.00			14				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	5	1	0.00	572	0.009	5	0.0	0.0	6.358	A
C-AB	4	0.98	0.00	672	0.006	4	0.0	0.0	5.424	A
C-A	24	6	0.00			24				
A-B	5	1	0.00			5				
A-C	12	3	0.00			12				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D17 - | Development | AM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Vehicle Mix		HV% is zero for all movements / time segments. Vehicle Mix matrix should be completed whether working in PCUs or Vehs. If HV% at the junction is genuinely zero, please ignore this warning.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		6.44	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		6.44	A

Traffic Demand

Demand Set Details

ID	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D17	Development	AM	ONE HOUR	08:00	09:30	15	✓

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	1	100.000
B		ONE HOUR	✓	6	100.000
C		ONE HOUR	✓	1	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	1	0
	B	4	0	2
	C	0	1	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	0	0
	B	0	0	0
	C	0	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.01	6.44	0.0	A	6	8
C-AB	0.00	0.00	0.0	A	0	0
C-A					0	0
A-B					0	0
A-C					0	0

Main Results for each time segment

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	5	1	0.00	565	0.008	4	0.0	0.0	6.419	A
C-AB	0	0	0.00	661	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	5	1	0.00	565	0.010	5	0.0	0.0	6.429	A
C-AB	0	0	0.00	661	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	7	2	0.00	565	0.012	7	0.0	0.0	6.443	A
C-AB	0	0	0.00	661	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	7	2	0.00	565	0.012	7	0.0	0.0	6.443	A
C-AB	0	0	0.00	661	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	5	1	0.00	565	0.010	5	0.0	0.0	6.429	A
C-AB	0	0	0.00	661	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	5	1	0.00	565	0.008	5	0.0	0.0	6.419	A
C-AB	0	0	0.00	661	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D18 - | Development | PM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Vehicle Mix		HV% is zero for all movements / time segments. Vehicle Mix matrix should be completed whether working in PCUs or Vehs. If HV% at the junction is genuinely zero, please ignore this warning.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
1	Raheen Woods/L3103	T-Junction	Two-way	Two-way	Two-way		0.00	F

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		0.00	F

Traffic Demand

Demand Set Details

ID	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D18	Development	PM	ONE HOUR	16:15	17:45	15	✓

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	3	100.000
B		ONE HOUR	✓	3	100.000
C		ONE HOUR	✓	2	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	3	0
	B	1	0	2
	C	0	2	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	0	0
	B	0	0	0
	C	0	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.00	0.00	0.0	A	0	0
C-AB	0.00	0.00	0.0	A	0	0
C-A					0	0
A-B					0	0
A-C					0	0

Main Results for each time segment

16:15 - 16:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	0	0	0.00	589	0.000	0	0.0	0.0	0.000	A
C-AB	0	0	0.00	661	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

16:30 - 16:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	0	0	0.00	589	0.000	0	0.0	0.0	0.000	A
C-AB	0	0	0.00	661	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	0	0	0.00	589	0.000	0	0.0	0.0	0.000	A
C-AB	0	0	0.00	661	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	0	0	0.00	589	0.000	0	0.0	0.0	0.000	A
C-AB	0	0	0.00	661	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	0	0	0.00	589	0.000	0	0.0	0.0	0.000	A
C-AB	0	0	0.00	661	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	0	0	0.00	589	0.000	0	0.0	0.0	0.000	A
C-AB	0	0	0.00	661	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

<h1>Junctions 11</h1>
<h2>PICADY 11 - Priority Intersection Module</h2>
Version: 11.1.0.2307 © Copyright TRL Software Limited, 2024
For sales and distribution information, program advice and maintenance, contact TRL Software: +44 (0)1344 379777 software@trl.co.uk trlsoftware.com
The users of this computer program for the solution of an engineering problem are in no way relieved of their responsibility for the correctness of the solution

Filename: 252139 - JCT2.j11

Path: C:\Users\AngelikiKalatha\OneDrive - ORS\252139 TTA - New Resi Dev, Raheen & Pairc na hAbhainn, Athenry, Galway - Documents\01_WIP\Design\13g_Transportation_Reports\01_TTA\01_Raheen_site\01_WIP\03_JUNCTIONS11

Report generation date: 16/12/2025 17:58:26

-
- »D1 - 2025 | Base | AM
 - »D2 - 2025 | Base | PM
 - »D3 - 2027 | Do-nothing | AM
 - »D4 - 2027 | Do-nothing | PM
 - »D5 - 2027 | Do-something | AM
 - »D6 - 2027 | Do-something | PM
 - »D7 - 2032 | Do-nothing | AM
 - »D8 - 2032 | Do-nothing | PM
 - »D9 - 2032 | Do-something | AM
 - »D10 - 2032 | Do-something | PM
 - »D11 - 2042 | Do-nothing | AM
 - »D12 - 2042 | Do-nothing | PM
 - »D13 - 2042 | Do-something | AM
 - »D14 - 2042 | Do-something | PM
 - »D15 - | Com. Dev. | AM
 - »D16 - | Com. Dev. | PM
 - »D17 - | Development | AM
 - »D18 - | Development | PM

Summary of junction performance

	AM				PM			
	Set ID	Queue (PCU)	RFC	LOS	Set ID	Queue (PCU)	RFC	LOS
2025 - Base								
Stream B-AC	D1	0.5	0.33	B	D2	0.9	0.48	B
Stream C-AB		0.2	0.12	A		0.1	0.05	A
2027 - Do-nothing								
Stream B-AC	D3	0.8	0.43	B	D4	1.4	0.59	C
Stream C-AB		0.2	0.15	A		0.1	0.07	A
2027 - Do-something								
Stream B-AC	D5	0.8	0.45	B	D6	1.5	0.60	C
Stream C-AB		0.2	0.15	A		0.1	0.07	A
2032 - Do-nothing								
Stream B-AC	D7	0.9	0.48	C	D8	1.8	0.65	C
Stream C-AB		0.2	0.16	A		0.1	0.08	A
2032 - Do-something								
Stream B-AC	D9	1.0	0.49	C	D10	1.9	0.66	C
Stream C-AB		0.2	0.16	A		0.1	0.08	A
2042 - Do-nothing								
Stream B-AC	D11	1.1	0.53	C	D12	2.5	0.73	D
Stream C-AB		0.3	0.18	A		0.1	0.08	A
2042 - Do-something								
Stream B-AC	D13	1.2	0.55	C	D14	2.7	0.74	D
Stream C-AB		0.3	0.19	A		0.1	0.09	A
- Com. Dev.								
Stream B-AC	D15	0.1	0.07	A	D16	0.1	0.05	A
Stream C-AB		0.0	0.01	A		0.0	0.01	A
- Development								
Stream B-AC	D17	0.0	0.01	A	D18	0.0	0.00	A
Stream C-AB		0.0	0.00	A		0.0	0.00	A

There are warnings associated with one or more model runs - see the 'Data Errors and Warnings' tables for each Analysis or Demand Set.

Values shown are the highest values encountered over all time segments. Delay is the maximum value of average delay per arriving vehicle.

File summary

File Description

Title	252139
Location	Gort Mhaoilir
Site number	
Date	15/12/2025
Version	
Status	(new file)
Identifier	
Client	
Jobnumber	
Enumerator	AzureAD\AngelikiKalatha
Description	

Units

Distance units	Speed units	Traffic units input	Traffic units results	Flow units	Average delay units	Total delay units	Rate of delay units
m	kph	PCU	PCU	perHour	s	-Min	perMin

Analysis Options

PICADY short flare model	Vehicle length (m)	Calculate Queue Percentiles	Calculate detailed queueing delay	Show lane queues in feet / metres	Show all PICADY stream intercepts	Calculate residual capacity	RFC Threshold	Average Delay threshold (s)	Queue threshold (PCU)	Use simulation for HCM roundabouts	Use iterations for HCM roundabouts
PICADY 4.1	5.75						0.85	36.00	20.00		

Demand Set Summary

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D1	2025	Base	AM	ONE HOUR	08:00	09:30	15	✓		
D2	2025	Base	PM	ONE HOUR	16:45	18:15	15	✓		
D3	2027	Do-nothing	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G1)+D15
D4	2027	Do-nothing	PM	ONE HOUR	16:45	18:15	15	✓	Simple	(D2*G1)+D16
D5	2027	Do-something	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G1)+D15+D17
D6	2027	Do-something	PM	ONE HOUR	16:45	18:15	15	✓	Simple	(D2*G1)+D16+D18
D7	2032	Do-nothing	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G2)+D15
D8	2032	Do-nothing	PM	ONE HOUR	16:45	18:15	15	✓	Simple	(D2*G2)+D16
D9	2032	Do-something	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G2)+D15+D17
D10	2032	Do-something	PM	ONE HOUR	16:45	18:15	15	✓	Simple	(D2*G2)+D16+D18
D11	2042	Do-nothing	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G3)+D15
D12	2042	Do-nothing	PM	ONE HOUR	16:45	18:15	15	✓	Simple	(D2*G3)+D16
D13	2042	Do-something	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G3)+D15+D17
D14	2042	Do-something	PM	ONE HOUR	16:45	18:15	15	✓	Simple	(D2*G3)+D16+D18
D15		Com. Dev.	AM	ONE HOUR	08:00	09:30	15	✓		
D16		Com. Dev.	PM	ONE HOUR	16:45	18:15	15	✓		
D17		Development	AM	ONE HOUR	08:00	09:30	15	✓		
D18		Development	PM	ONE HOUR	16:45	18:15	15	✓		

Growth Factors

ID	Description	Use TEMPRO	Growth Factor
G1	2027		1.0525
G2	2032		1.1613
G3	2042		1.2932

Growth factors are only active if a Demand Set references them in a Relationship.

Analysis Set Details

ID	Include in report	Network flow scaling factor (%)	Network capacity scaling factor (%)
A1	✓	100.000	100.000

D1 - 2025 | Base | AM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		4.15	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		4.15	A

Arms

Arms

Arm	Name	Description	Arm type
A	R3105, SE		Major
B	Raheen Woods		Minor
C	L3105, NW		Major

Major Arm Geometry

Arm	Width of carriageway (m)	Has kerbed central reserve	Has right-turn storage	Visibility for right turn (m)	Blocks?	Blocking queue (PCU)
C	6.00			200.0	✓	0.00

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

Minor Arm Geometry

Arm	Minor arm type	Lane width (m)	Visibility to left (m)	Visibility to right (m)
B	One lane	3.00	23	30

Slope / Intercept / Capacity

Priority Intersection Slopes and Intercepts

Stream	Intercept (PCU/hr)	Slope for A-B	Slope for A-C	Slope for C-A	Slope for C-B
B-A	500	0.091	0.230	0.145	0.329
B-C	643	0.099	0.249	-	-
C-B	690	0.267	0.267	-	-

The slopes and intercepts shown above include custom intercept adjustments only.

Streams may be combined, in which case capacity will be adjusted.

Values are shown for the first time segment only; they may differ for subsequent time segments.

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D1	2025	Base	AM	ONE HOUR	08:00	09:30	15	✓

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	199	100.000
B		ONE HOUR	✓	136	100.000
C		ONE HOUR	✓	150	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	147	52
	B	108	0	28
	C	85	65	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

	To			
	A	B	C	
From	A	0	2	4
	B	0	0	0
	C	0	2	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.33	11.54	0.5	B	125	188
C-AB	0.12	6.01	0.2	A	68	101
C-A					70	105
A-B					135	203
A-C					48	72

Main Results for each time segment

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	103	26	0.00	482	0.213	102	0.0	0.3	9.444	A
C-AB	54	13	0.00	691	0.078	54	0.0	0.1	5.751	A
C-A	59	15	0.00			59				
A-B	111	28	0.00			111				
A-C	39	10	0.00			39				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	123	31	0.00	473	0.259	122	0.3	0.3	10.242	B
C-AB	66	16	0.00	691	0.095	66	0.1	0.1	5.859	A
C-A	69	17	0.00			69				
A-B	132	33	0.00			132				
A-C	47	12	0.00			47				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	150	38	0.00	462	0.325	150	0.3	0.5	11.502	B
C-AB	83	21	0.00	692	0.120	83	0.1	0.2	6.012	A
C-A	82	21	0.00			82				
A-B	162	41	0.00			162				
A-C	57	14	0.00			57				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	150	38	0.00	462	0.325	150	0.5	0.5	11.539	B
C-AB	83	21	0.00	692	0.120	83	0.2	0.2	6.012	A
C-A	82	21	0.00			82				
A-B	162	41	0.00			162				
A-C	57	14	0.00			57				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	123	31	0.00	473	0.259	123	0.5	0.4	10.291	B
C-AB	66	16	0.00	691	0.095	66	0.2	0.1	5.862	A
C-A	69	17	0.00			69				
A-B	132	33	0.00			132				
A-C	47	12	0.00			47				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	103	26	0.00	482	0.213	103	0.4	0.3	9.516	A
C-AB	54	13	0.00	691	0.078	54	0.1	0.1	5.757	A
C-A	59	15	0.00			59				
A-B	111	28	0.00			111				
A-C	39	10	0.00			39				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D2 - 2025 | Base | PM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		6.30	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		6.30	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D2	2025	Base	PM	ONE HOUR	16:45	18:15	15	✓

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	189	100.000
B		ONE HOUR	✓	215	100.000
C		ONE HOUR	✓	104	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	111	78
	B	137	0	78
	C	75	29	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	1	1
	B	0	0	1
	C	1	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.48	14.03	0.9	B	198	296
C-AB	0.05	5.54	0.1	A	30	44
C-A					65	98
A-B					102	153
A-C					71	107

Main Results for each time segment

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	162	41	0.00	510	0.318	160	0.0	0.5	10.277	B
C-AB	24	6	0.00	688	0.035	24	0.0	0.0	5.423	A
C-A	54	14	0.00			54				
A-B	83	21	0.00			83				
A-C	58	15	0.00			58				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	194	48	0.00	503	0.384	193	0.5	0.6	11.609	B
C-AB	29	7	0.00	688	0.042	29	0.0	0.1	5.469	A
C-A	64	16	0.00			64				
A-B	100	25	0.00			100				
A-C	70	17	0.00			70				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	237	59	0.00	494	0.479	236	0.6	0.9	13.913	B
C-AB	36	9	0.00	688	0.053	36	0.1	0.1	5.533	A
C-A	78	19	0.00			78				
A-B	122	31	0.00			122				
A-C	86	21	0.00			86				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	237	59	0.00	494	0.480	237	0.9	0.9	14.031	B
C-AB	36	9	0.00	688	0.053	36	0.1	0.1	5.536	A
C-A	78	19	0.00			78				
A-B	122	31	0.00			122				
A-C	86	21	0.00			86				

17:45 - 18:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	194	48	0.00	503	0.384	195	0.9	0.6	11.743	B
C-AB	29	7	0.00	688	0.042	29	0.1	0.1	5.472	A
C-A	64	16	0.00			64				
A-B	100	25	0.00			100				
A-C	70	17	0.00			70				

18:00 - 18:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	162	41	0.00	510	0.318	163	0.6	0.5	10.426	B
C-AB	24	6	0.00	688	0.035	24	0.1	0.0	5.427	A
C-A	54	14	0.00			54				
A-B	83	21	0.00			83				
A-C	58	15	0.00			58				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D3 - 2027 | Do-nothing | AM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		4.88	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		4.88	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D3	2027	Do-nothing	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G1)+D15

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	251	100.000
B		ONE HOUR	✓	174	100.000
C		ONE HOUR	✓	203	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	174	78
	B	140	0	33
	C	128	75	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

	To			
	A	B	C	
From	A	0	2	3
	B	0.90	0	0
	C	0	2	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.43	14.50	0.8	B	159	239
C-AB	0.15	6.03	0.2	A	83	125
C-A					104	155
A-B					159	239
A-C					71	107

Main Results for each time segment

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	131	33	0.00	467	0.280	129	0.0	0.4	10.685	B
C-AB	65	16	0.00	702	0.093	65	0.0	0.1	5.740	A
C-A	88	22	0.00			88				
A-B	131	33	0.00			131				
A-C	59	15	0.00			59				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	156	39	0.00	456	0.342	156	0.4	0.5	12.040	B
C-AB	81	20	0.00	705	0.114	80	0.1	0.2	5.858	A
C-A	102	26	0.00			102				
A-B	156	39	0.00			156				
A-C	70	17	0.00			70				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	191	48	0.00	441	0.434	190	0.5	0.8	14.392	B
C-AB	103	26	0.00	709	0.146	103	0.2	0.2	6.030	A
C-A	121	30	0.00			121				
A-B	191	48	0.00			191				
A-C	86	21	0.00			86				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	191	48	0.00	441	0.434	191	0.8	0.8	14.497	B
C-AB	103	26	0.00	709	0.146	103	0.2	0.2	6.031	A
C-A	121	30	0.00			121				
A-B	191	48	0.00			191				
A-C	86	21	0.00			86				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	156	39	0.00	456	0.342	157	0.8	0.5	12.162	B
C-AB	81	20	0.00	705	0.115	81	0.2	0.2	5.862	A
C-A	102	26	0.00			102				
A-B	156	39	0.00			156				
A-C	70	17	0.00			70				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	131	33	0.00	467	0.280	131	0.5	0.4	10.821	B
C-AB	66	16	0.00	702	0.093	66	0.2	0.1	5.749	A
C-A	88	22	0.00			88				
A-B	131	33	0.00			131				
A-C	59	15	0.00			59				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D4 - 2027 | Do-nothing | PM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		7.56	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		7.56	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D4	2027	Do-nothing	PM	ONE HOUR	16:45	18:15	15	✓	Simple	(D2*G1)+D16

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	260	100.000
B		ONE HOUR	✓	252	100.000
C		ONE HOUR	✓	140	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	133	128
	B	164	0	88
	C	105	35	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

	To			
	A	B	C	
From	A	0	0.88	0.64
	B	0.58	0	0.94
	C	0.75	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.59	18.66	1.4	C	231	347
C-AB	0.07	5.61	0.1	A	38	57
C-A					91	136
A-B					122	183
A-C					117	176

Main Results for each time segment

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	190	47	0.00	494	0.384	187	0.0	0.6	11.739	B
C-AB	30	8	0.00	688	0.044	30	0.0	0.1	5.471	A
C-A	75	19	0.00			75				
A-B	100	25	0.00			100				
A-C	96	24	0.00			96				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	226	57	0.00	484	0.468	225	0.6	0.9	13.952	B
C-AB	37	9	0.00	689	0.054	37	0.1	0.1	5.529	A
C-A	89	22	0.00			89				
A-B	119	30	0.00			119				
A-C	115	29	0.00			115				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	277	69	0.00	471	0.589	275	0.9	1.4	18.303	C
C-AB	47	12	0.00	689	0.068	47	0.1	0.1	5.611	A
C-A	107	27	0.00			107				
A-B	146	37	0.00			146				
A-C	141	35	0.00			141				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	277	69	0.00	471	0.589	277	1.4	1.4	18.659	C
C-AB	47	12	0.00	689	0.068	47	0.1	0.1	5.615	A
C-A	107	27	0.00			107				
A-B	146	37	0.00			146				
A-C	141	35	0.00			141				

17:45 - 18:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	226	57	0.00	484	0.468	228	1.4	0.9	14.285	B
C-AB	37	9	0.00	689	0.054	37	0.1	0.1	5.535	A
C-A	89	22	0.00			89				
A-B	119	30	0.00			119				
A-C	115	29	0.00			115				

18:00 - 18:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	190	47	0.00	494	0.384	191	0.9	0.6	12.011	B
C-AB	30	8	0.00	688	0.044	30	0.1	0.1	5.478	A
C-A	75	19	0.00			75				
A-B	100	25	0.00			100				
A-C	96	24	0.00			96				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D5 - 2027 | Do-something | AM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		5.05	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		5.05	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D5	2027	Do-something	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G1) +D15+D17

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	252	100.000
B		ONE HOUR	✓	179	100.000
C		ONE HOUR	✓	205	100.000

Origin-Destination Data

Demand (PCU/hr)

	From	To		
		A	B	C
	A	0	175	78
	B	144	0	34
	C	128	76	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

	From	To		
		A	B	C
	A	0	2	3
	B	0.87	0	0
	C	0	2	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.45	14.85	0.8	B	164	246
C-AB	0.15	6.05	0.2	A	84	127
C-A					103	155
A-B					160	240
A-C					71	107

Main Results for each time segment

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	135	34	0.00	467	0.288	133	0.0	0.4	10.807	B
C-AB	66	17	0.00	701	0.095	66	0.0	0.1	5.749	A
C-A	88	22	0.00			88				
A-B	131	33	0.00			131				
A-C	59	15	0.00			59				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	161	40	0.00	456	0.352	160	0.4	0.5	12.234	B
C-AB	82	20	0.00	704	0.116	82	0.1	0.2	5.871	A
C-A	102	25	0.00			102				
A-B	157	39	0.00			157				
A-C	70	17	0.00			70				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	197	49	0.00	441	0.446	196	0.5	0.8	14.730	B
C-AB	105	26	0.00	709	0.148	105	0.2	0.2	6.048	A
C-A	120	30	0.00			120				
A-B	192	48	0.00			192				
A-C	86	21	0.00			86				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	197	49	0.00	441	0.447	197	0.8	0.8	14.849	B
C-AB	105	26	0.00	709	0.148	105	0.2	0.2	6.049	A
C-A	120	30	0.00			120				
A-B	192	48	0.00			192				
A-C	86	21	0.00			86				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	161	40	0.00	456	0.353	162	0.8	0.6	12.365	B
C-AB	82	20	0.00	704	0.116	82	0.2	0.2	5.873	A
C-A	102	25	0.00			102				
A-B	157	39	0.00			157				
A-C	70	17	0.00			70				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	135	34	0.00	467	0.288	135	0.6	0.4	10.954	B
C-AB	67	17	0.00	701	0.095	67	0.2	0.1	5.761	A
C-A	87	22	0.00			87				
A-B	131	33	0.00			131				
A-C	59	15	0.00			59				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D6 - 2027 | Do-something | PM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		7.72	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		7.72	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D6	2027	Do-something	PM	ONE HOUR	16:45	18:15	15	✓	Simple	(D2*G1) +D16+D18

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	264	100.000
B		ONE HOUR	✓	255	100.000
C		ONE HOUR	✓	141	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	137	128
	B	166	0	89
	C	105	36	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	0.85	0.64
	B	0.57	0	0.93
	C	0.75	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.60	19.05	1.5	C	234	351
C-AB	0.07	5.63	0.1	A	39	59
C-A					90	136
A-B					125	188
A-C					117	176

Main Results for each time segment

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	192	48	0.00	493	0.389	189	0.0	0.6	11.839	B
C-AB	31	8	0.00	687	0.045	31	0.0	0.1	5.485	A
C-A	75	19	0.00			75				
A-B	103	26	0.00			103				
A-C	96	24	0.00			96				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	229	57	0.00	484	0.474	228	0.6	0.9	14.125	B
C-AB	38	9	0.00	688	0.055	38	0.1	0.1	5.546	A
C-A	89	22	0.00			89				
A-B	123	31	0.00			123				
A-C	115	29	0.00			115				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	281	70	0.00	470	0.596	278	0.9	1.4	18.658	C
C-AB	48	12	0.00	688	0.070	48	0.1	0.1	5.632	A
C-A	107	27	0.00			107				
A-B	150	38	0.00			150				
A-C	141	35	0.00			141				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	281	70	0.00	470	0.596	280	1.4	1.5	19.051	C
C-AB	48	12	0.00	688	0.070	48	0.1	0.1	5.634	A
C-A	107	27	0.00			107				
A-B	150	38	0.00			150				
A-C	141	35	0.00			141				

17:45 - 18:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	229	57	0.00	484	0.474	231	1.5	0.9	14.482	B
C-AB	38	9	0.00	688	0.055	38	0.1	0.1	5.551	A
C-A	89	22	0.00			89				
A-B	123	31	0.00			123				
A-C	115	29	0.00			115				

18:00 - 18:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	192	48	0.00	493	0.389	193	0.9	0.7	12.126	B
C-AB	31	8	0.00	688	0.045	31	0.1	0.1	5.492	A
C-A	75	19	0.00			75				
A-B	103	26	0.00			103				
A-C	96	24	0.00			96				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D7 - 2032 | Do-nothing | AM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		5.32	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		5.32	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D7	2032	Do-nothing	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G2)+D15

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	273	100.000
B		ONE HOUR	✓	189	100.000
C		ONE HOUR	✓	220	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	190	83
	B	152	0	37
	C	138	82	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

	To			
	A	B	C	
From	A	0	2	3
	B	0.83	0	0
	C	0	2	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.48	15.96	0.9	C	173	260
C-AB	0.16	6.14	0.2	A	92	138
C-A					109	164
A-B					174	261
A-C					77	115

Main Results for each time segment

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	142	35	0.00	463	0.307	140	0.0	0.4	11.180	B
C-AB	72	18	0.00	702	0.103	72	0.0	0.1	5.800	A
C-A	93	23	0.00			93				
A-B	143	36	0.00			143				
A-C	63	16	0.00			63				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	170	42	0.00	451	0.376	169	0.4	0.6	12.823	B
C-AB	90	22	0.00	705	0.127	89	0.1	0.2	5.936	A
C-A	108	27	0.00			108				
A-B	170	43	0.00			170				
A-C	75	19	0.00			75				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	208	52	0.00	435	0.478	206	0.6	0.9	15.795	C
C-AB	115	29	0.00	710	0.162	115	0.2	0.2	6.140	A
C-A	127	32	0.00			127				
A-B	209	52	0.00			209				
A-C	92	23	0.00			92				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	208	52	0.00	435	0.478	208	0.9	0.9	15.955	C
C-AB	115	29	0.00	710	0.162	115	0.2	0.2	6.144	A
C-A	127	32	0.00			127				
A-B	209	52	0.00			209				
A-C	92	23	0.00			92				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	170	42	0.00	451	0.376	171	0.9	0.6	12.994	B
C-AB	90	22	0.00	705	0.127	90	0.2	0.2	5.939	A
C-A	108	27	0.00			108				
A-B	170	43	0.00			170				
A-C	75	19	0.00			75				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	142	35	0.00	462	0.307	143	0.6	0.5	11.354	B
C-AB	73	18	0.00	702	0.103	73	0.2	0.1	5.812	A
C-A	93	23	0.00			93				
A-B	143	36	0.00			143				
A-C	63	16	0.00			63				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D8 - 2032 | Do-nothing | PM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		8.99	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		8.99	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D8	2032	Do-nothing	PM	ONE HOUR	16:45	18:15	15	✓	Simple	(D2*G2)+D16

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	281	100.000
B		ONE HOUR	✓	275	100.000
C		ONE HOUR	✓	151	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	145	136
	B	179	0	96
	C	113	39	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

	To			
	A	B	C	
From	A	0	0.89	0.66
	B	0.53	0	0.94
	C	0.77	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.65	22.16	1.8	C	253	379
C-AB	0.08	5.66	0.1	A	42	63
C-A					97	145
A-B					133	199
A-C					125	188

Main Results for each time segment

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	207	52	0.00	490	0.423	204	0.0	0.7	12.563	B
C-AB	33	8	0.00	688	0.048	33	0.0	0.1	5.497	A
C-A	81	20	0.00			81				
A-B	109	27	0.00			109				
A-C	103	26	0.00			103				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	247	62	0.00	480	0.516	246	0.7	1.0	15.416	C
C-AB	41	10	0.00	689	0.059	41	0.1	0.1	5.561	A
C-A	95	24	0.00			95				
A-B	130	33	0.00			130				
A-C	122	31	0.00			122				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	303	76	0.00	466	0.651	300	1.0	1.8	21.486	C
C-AB	52	13	0.00	689	0.075	52	0.1	0.1	5.653	A
C-A	115	29	0.00			115				
A-B	159	40	0.00			159				
A-C	150	37	0.00			150				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	303	76	0.00	466	0.651	303	1.8	1.8	22.159	C
C-AB	52	13	0.00	689	0.075	52	0.1	0.1	5.657	A
C-A	115	29	0.00			115				
A-B	159	40	0.00			159				
A-C	150	37	0.00			150				

17:45 - 18:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	247	62	0.00	480	0.516	250	1.8	1.1	15.972	C
C-AB	41	10	0.00	689	0.059	41	0.1	0.1	5.565	A
C-A	95	24	0.00			95				
A-B	130	33	0.00			130				
A-C	122	31	0.00			122				

18:00 - 18:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	207	52	0.00	490	0.423	209	1.1	0.8	12.946	B
C-AB	33	8	0.00	688	0.048	33	0.1	0.1	5.504	A
C-A	81	20	0.00			81				
A-B	109	27	0.00			109				
A-C	103	26	0.00			103				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D9 - 2032 | Do-something | AM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		5.52	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		5.52	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D9	2032	Do-something	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G2) +D15+D17

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	274	100.000
B		ONE HOUR	✓	194	100.000
C		ONE HOUR	✓	221	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	191	83
	B	156	0	38
	C	138	83	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

	To			
	A	B	C	
From	A	0	2	3
	B	0.81	0	0
	C	0	2	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.49	16.38	1.0	C	178	266
C-AB	0.16	6.16	0.2	A	94	141
C-A					109	164
A-B					175	262
A-C					77	115

Main Results for each time segment

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	146	36	0.00	462	0.315	144	0.0	0.5	11.315	B
C-AB	73	18	0.00	702	0.105	73	0.0	0.1	5.810	A
C-A	93	23	0.00			93				
A-B	143	36	0.00			143				
A-C	63	16	0.00			63				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	174	44	0.00	450	0.386	173	0.5	0.6	13.042	B
C-AB	91	23	0.00	705	0.129	91	0.1	0.2	5.950	A
C-A	108	27	0.00			108				
A-B	171	43	0.00			171				
A-C	75	19	0.00			75				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	213	53	0.00	434	0.491	212	0.6	0.9	16.197	C
C-AB	117	29	0.00	710	0.164	116	0.2	0.2	6.159	A
C-A	127	32	0.00			127				
A-B	210	52	0.00			210				
A-C	92	23	0.00			92				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	213	53	0.00	434	0.491	213	0.9	1.0	16.383	C
C-AB	117	29	0.00	710	0.164	117	0.2	0.2	6.160	A
C-A	127	32	0.00			127				
A-B	210	52	0.00			210				
A-C	92	23	0.00			92				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	174	44	0.00	450	0.386	175	1.0	0.6	13.230	B
C-AB	91	23	0.00	705	0.129	91	0.2	0.2	5.955	A
C-A	108	27	0.00			108				
A-B	171	43	0.00			171				
A-C	75	19	0.00			75				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	146	36	0.00	462	0.315	146	0.6	0.5	11.504	B
C-AB	74	18	0.00	702	0.105	74	0.2	0.1	5.820	A
C-A	93	23	0.00			93				
A-B	143	36	0.00			143				
A-C	63	16	0.00			63				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D10 - 2032 | Do-something | PM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		9.20	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		9.20	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D10	2032	Do-something	PM	ONE HOUR	16:45	18:15	15	✓	Simple	(D2*G2) +D16+D18

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	285	100.000
B		ONE HOUR	✓	278	100.000
C		ONE HOUR	✓	152	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	149	136
	B	181	0	97
	C	113	40	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	0.87	0.66
	B	0.52	0	0.93
	C	0.77	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.66	22.71	1.9	C	255	383
C-AB	0.08	5.68	0.1	A	43	65
C-A					97	145
A-B					136	205
A-C					125	188

Main Results for each time segment

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	209	52	0.00	490	0.428	207	0.0	0.7	12.679	B
C-AB	34	8	0.00	688	0.049	34	0.0	0.1	5.511	A
C-A	81	20	0.00			81				
A-B	112	28	0.00			112				
A-C	103	26	0.00			103				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	250	63	0.00	479	0.522	249	0.7	1.1	15.634	C
C-AB	42	10	0.00	688	0.061	42	0.1	0.1	5.578	A
C-A	95	24	0.00			95				
A-B	134	33	0.00			134				
A-C	122	31	0.00			122				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	306	77	0.00	465	0.659	303	1.1	1.8	21.975	C
C-AB	53	13	0.00	688	0.077	53	0.1	0.1	5.675	A
C-A	114	29	0.00			114				
A-B	164	41	0.00			164				
A-C	150	37	0.00			150				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	306	77	0.00	465	0.659	306	1.8	1.9	22.710	C
C-AB	53	13	0.00	688	0.077	53	0.1	0.1	5.677	A
C-A	114	29	0.00			114				
A-B	164	41	0.00			164				
A-C	150	37	0.00			150				

17:45 - 18:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	250	63	0.00	479	0.522	253	1.9	1.1	16.225	C
C-AB	42	10	0.00	688	0.061	42	0.1	0.1	5.584	A
C-A	95	24	0.00			95				
A-B	134	33	0.00			134				
A-C	122	31	0.00			122				

18:00 - 18:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	209	52	0.00	489	0.428	211	1.1	0.8	13.077	B
C-AB	34	9	0.00	688	0.050	34	0.1	0.1	5.518	A
C-A	81	20	0.00			81				
A-B	112	28	0.00			112				
A-C	103	26	0.00			103				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D11 - 2042 | Do-nothing | AM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		5.99	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		5.99	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D11	2042	Do-nothing	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G3)+D15

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	299	100.000
B		ONE HOUR	✓	207	100.000
C		ONE HOUR	✓	239	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	209	90
	B	166	0	40
	C	149	91	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

	To			
	A	B	C	
From	A	0	2	3
	B	0.76	0	0
	C	0	2	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.53	18.17	1.1	C	190	284
C-AB	0.18	6.29	0.3	A	104	156
C-A					116	174
A-B					192	288
A-C					83	124

Main Results for each time segment

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	156	39	0.00	457	0.340	153	0.0	0.5	11.849	B
C-AB	81	20	0.00	702	0.115	80	0.0	0.2	5.873	A
C-A	99	25	0.00			99				
A-B	157	39	0.00			157				
A-C	68	17	0.00			68				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	186	46	0.00	444	0.418	185	0.5	0.7	13.876	B
C-AB	101	25	0.00	706	0.143	100	0.2	0.2	6.037	A
C-A	115	29	0.00			115				
A-B	188	47	0.00			188				
A-C	81	20	0.00			81				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	227	57	0.00	426	0.533	226	0.7	1.1	17.904	C
C-AB	130	32	0.00	711	0.183	129	0.2	0.3	6.283	A
C-A	134	33	0.00			134				
A-B	230	58	0.00			230				
A-C	99	25	0.00			99				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	227	57	0.00	426	0.533	227	1.1	1.1	18.173	C
C-AB	130	32	0.00	711	0.183	130	0.3	0.3	6.286	A
C-A	134	33	0.00			134				
A-B	230	58	0.00			230				
A-C	99	25	0.00			99				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	186	46	0.00	444	0.418	187	1.1	0.7	14.181	B
C-AB	101	25	0.00	706	0.143	101	0.3	0.2	6.044	A
C-A	115	29	0.00			115				
A-B	188	47	0.00			188				
A-C	81	20	0.00			81				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	156	39	0.00	457	0.340	156	0.7	0.5	12.084	B
C-AB	81	20	0.00	703	0.116	81	0.2	0.2	5.889	A
C-A	99	25	0.00			99				
A-B	157	39	0.00			157				
A-C	68	17	0.00			68				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D12 - 2042 | Do-nothing | PM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		11.59	B

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		11.59	B

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D12	2042	Do-nothing	PM	ONE HOUR	16:45	18:15	15	✓	Simple	(D2*G3)+D16

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	306	100.000
B		ONE HOUR	✓	304	100.000
C		ONE HOUR	✓	165	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	159	146
	B	197	0	106
	C	123	42	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

	To			
	A	B	C	
From	A	0	0.90	0.68
	B	0.48	0	0.95
	C	0.79	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.73	28.59	2.5	D	279	418
C-AB	0.08	5.71	0.1	A	47	70
C-A					105	157
A-B					146	219
A-C					134	202

Main Results for each time segment

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	229	57	0.00	486	0.471	225	0.0	0.9	13.726	B
C-AB	37	9	0.00	688	0.054	37	0.0	0.1	5.529	A
C-A	87	22	0.00			87				
A-B	120	30	0.00			120				
A-C	110	28	0.00			110				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	273	68	0.00	475	0.575	271	0.9	1.3	17.647	C
C-AB	45	11	0.00	689	0.066	45	0.1	0.1	5.601	A
C-A	103	26	0.00			103				
A-B	143	36	0.00			143				
A-C	132	33	0.00			132				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	334	84	0.00	459	0.728	330	1.3	2.4	27.006	D
C-AB	58	15	0.00	690	0.084	58	0.1	0.1	5.706	A
C-A	124	31	0.00			124				
A-B	175	44	0.00			175				
A-C	161	40	0.00			161				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	334	84	0.00	459	0.728	334	2.4	2.5	28.592	D
C-AB	58	15	0.00	690	0.084	58	0.1	0.1	5.710	A
C-A	124	31	0.00			124				
A-B	175	44	0.00			175				
A-C	161	40	0.00			161				

17:45 - 18:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	273	68	0.00	475	0.575	277	2.5	1.4	18.768	C
C-AB	45	11	0.00	689	0.066	46	0.1	0.1	5.608	A
C-A	103	26	0.00			103				
A-B	143	36	0.00			143				
A-C	132	33	0.00			132				

18:00 - 18:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	229	57	0.00	486	0.471	231	1.4	0.9	14.312	B
C-AB	37	9	0.00	688	0.054	37	0.1	0.1	5.534	A
C-A	87	22	0.00			87				
A-B	120	30	0.00			120				
A-C	110	28	0.00			110				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D13 - 2042 | Do-something | AM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		6.23	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		6.23	A

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D13	2042	Do-something	AM	ONE HOUR	08:00	09:30	15	✓	Simple	(D1*G3) +D15+D17

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	300	100.000
B		ONE HOUR	✓	212	100.000
C		ONE HOUR	✓	241	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	210	90
	B	170	0	41
	C	149	92	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

	To			
	A	B	C	
From	A	0	2	3
	B	0.74	0	0
	C	0	2	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.55	18.73	1.2	C	194	291
C-AB	0.19	6.31	0.3	A	105	158
C-A					116	173
A-B					193	289
A-C					83	124

Main Results for each time segment

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	159	40	0.00	457	0.349	157	0.0	0.5	12.001	B
C-AB	82	21	0.00	702	0.117	82	0.0	0.2	5.884	A
C-A	99	25	0.00			99				
A-B	158	40	0.00			158				
A-C	68	17	0.00			68				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	190	48	0.00	444	0.429	189	0.5	0.7	14.179	B
C-AB	102	25	0.00	706	0.144	102	0.2	0.2	6.052	A
C-A	114	29	0.00			114				
A-B	189	47	0.00			189				
A-C	81	20	0.00			81				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	233	58	0.00	426	0.547	231	0.7	1.2	18.423	C
C-AB	132	33	0.00	711	0.185	131	0.2	0.3	6.304	A
C-A	133	33	0.00			133				
A-B	231	58	0.00			231				
A-C	99	25	0.00			99				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	233	58	0.00	426	0.547	233	1.2	1.2	18.731	C
C-AB	132	33	0.00	711	0.185	132	0.3	0.3	6.306	A
C-A	133	33	0.00			133				
A-B	231	58	0.00			231				
A-C	99	25	0.00			99				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	190	48	0.00	444	0.429	192	1.2	0.8	14.468	B
C-AB	102	26	0.00	706	0.145	102	0.3	0.2	6.056	A
C-A	114	29	0.00			114				
A-B	189	47	0.00			189				
A-C	81	20	0.00			81				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	159	40	0.00	457	0.349	160	0.8	0.5	12.253	B
C-AB	82	21	0.00	702	0.117	83	0.2	0.2	5.897	A
C-A	99	25	0.00			99				
A-B	158	40	0.00			158				
A-C	68	17	0.00			68				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D14 - 2042 | Do-something | PM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		11.94	B

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		11.94	B

Traffic Demand

Demand Set Details

ID	Year	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically	Relationship type	Relationship
D14	2042	Do-something	PM	ONE HOUR	16:45	18:15	15	✓	Simple	(D2*G3) +D16+D18

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	310	100.000
B		ONE HOUR	✓	307	100.000
C		ONE HOUR	✓	166	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	163	146
	B	199	0	107
	C	123	43	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

	To			
	A	B	C	
From	A	0	0.88	0.68
	B	0.48	0	0.94
	C	0.79	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.74	29.50	2.7	D	281	422
C-AB	0.09	5.73	0.1	A	48	72
C-A					104	157
A-B					150	225
A-C					134	202

Main Results for each time segment

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	231	58	0.00	485	0.476	227	0.0	0.9	13.863	B
C-AB	38	9	0.00	688	0.055	37	0.0	0.1	5.542	A
C-A	87	22	0.00			87				
A-B	123	31	0.00			123				
A-C	110	28	0.00			110				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	276	69	0.00	474	0.581	274	0.9	1.3	17.919	C
C-AB	47	12	0.00	688	0.068	46	0.1	0.1	5.618	A
C-A	103	26	0.00			103				
A-B	147	37	0.00			147				
A-C	132	33	0.00			132				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	338	84	0.00	459	0.736	333	1.3	2.5	27.748	D
C-AB	60	15	0.00	689	0.086	59	0.1	0.1	5.728	A
C-A	123	31	0.00			123				
A-B	180	45	0.00			180				
A-C	161	40	0.00			161				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	338	84	0.00	459	0.736	337	2.5	2.7	29.498	D
C-AB	60	15	0.00	689	0.086	60	0.1	0.1	5.731	A
C-A	123	31	0.00			123				
A-B	180	45	0.00			180				
A-C	161	40	0.00			161				

17:45 - 18:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	276	69	0.00	474	0.581	280	2.7	1.5	19.140	C
C-AB	47	12	0.00	688	0.068	47	0.1	0.1	5.623	A
C-A	103	26	0.00			103				
A-B	147	37	0.00			147				
A-C	132	33	0.00			132				

18:00 - 18:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	231	58	0.00	485	0.476	233	1.5	0.9	14.478	B
C-AB	38	9	0.00	688	0.055	38	0.1	0.1	5.550	A
C-A	87	22	0.00			87				
A-B	123	31	0.00			123				
A-C	110	28	0.00			110				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D15 - | Com. Dev. | AM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		2.38	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		2.38	A

Traffic Demand

Demand Set Details

ID	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D15	Com. Dev.	AM	ONE HOUR	08:00	09:30	15	✓

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	42	100.000
B		ONE HOUR	✓	30	100.000
C		ONE HOUR	✓	46	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	19	23
	B	26	0	4
	C	39	7	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	0	0
	B	5	0	0
	C	0	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.07	8.06	0.1	A	28	42
C-AB	0.01	5.18	0.0	A	6	9
C-A					35	53
A-B					17	26
A-C					21	32

Main Results for each time segment

08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	23	6	0.00	504	0.045	23	0.0	0.0	7.794	A
C-AB	5	1	0.00	700	0.007	5	0.0	0.0	5.182	A
C-A	29	7	0.00			29				
A-B	14	4	0.00			14				
A-C	17	4	0.00			17				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	27	7	0.00	502	0.054	27	0.0	0.1	7.907	A
C-AB	6	2	0.00	702	0.009	6	0.0	0.0	5.175	A
C-A	35	9	0.00			35				
A-B	17	4	0.00			17				
A-C	21	5	0.00			21				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	33	8	0.00	499	0.067	33	0.1	0.1	8.058	A
C-AB	8	2	0.00	704	0.011	8	0.0	0.0	5.166	A
C-A	42	11	0.00			42				
A-B	20	5	0.00			20				
A-C	25	6	0.00			25				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	33	8	0.00	499	0.067	33	0.1	0.1	8.059	A
C-AB	8	2	0.00	704	0.011	8	0.0	0.0	5.166	A
C-A	42	11	0.00			42				
A-B	20	5	0.00			20				
A-C	25	6	0.00			25				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	27	7	0.00	502	0.054	27	0.1	0.1	7.910	A
C-AB	6	2	0.00	702	0.009	6	0.0	0.0	5.176	A
C-A	35	9	0.00			35				
A-B	17	4	0.00			17				
A-C	21	5	0.00			21				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	23	6	0.00	504	0.045	23	0.1	0.0	7.801	A
C-AB	5	1	0.00	700	0.007	5	0.0	0.0	5.184	A
C-A	29	7	0.00			29				
A-B	14	4	0.00			14				
A-C	17	4	0.00			17				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D16 - | Com. Dev. | PM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		1.90	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		1.90	A

Traffic Demand

Demand Set Details

ID	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D16	Com. Dev.	PM	ONE HOUR	16:45	18:15	15	✓

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	62	100.000
B		ONE HOUR	✓	25	100.000
C		ONE HOUR	✓	31	100.000

Origin-Destination Data

Demand (PCU/hr)

		To		
		A	B	C
From	A	0	16	46
	B	20	0	5
	C	26	5	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

		To		
		A	B	C
From	A	0	0	0
	B	5	0	0
	C	0	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.05	7.82	0.1	A	23	35
C-AB	0.01	5.27	0.0	A	5	7
C-A					24	36
A-B					15	22
A-C					42	63

Main Results for each time segment

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	19	5	0.00	512	0.037	19	0.0	0.0	7.582	A
C-AB	4	0.95	0.00	690	0.006	4	0.0	0.0	5.249	A
C-A	19	5	0.00			19				
A-B	12	3	0.00			12				
A-C	35	9	0.00			35				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	23	6	0.00	509	0.044	23	0.0	0.0	7.682	A
C-AB	5	1	0.00	690	0.007	5	0.0	0.0	5.255	A
C-A	23	6	0.00			23				
A-B	14	4	0.00			14				
A-C	41	10	0.00			41				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	28	7	0.00	506	0.055	28	0.0	0.1	7.817	A
C-AB	6	1	0.00	690	0.008	6	0.0	0.0	5.263	A
C-A	28	7	0.00			28				
A-B	18	4	0.00			18				
A-C	51	13	0.00			51				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	28	7	0.00	506	0.055	28	0.1	0.1	7.819	A
C-AB	6	1	0.00	690	0.008	6	0.0	0.0	5.265	A
C-A	28	7	0.00			28				
A-B	18	4	0.00			18				
A-C	51	13	0.00			51				

17:45 - 18:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	23	6	0.00	509	0.044	23	0.1	0.0	7.685	A
C-AB	5	1	0.00	690	0.007	5	0.0	0.0	5.255	A
C-A	23	6	0.00			23				
A-B	14	4	0.00			14				
A-C	41	10	0.00			41				

18:00 - 18:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	19	5	0.00	512	0.037	19	0.0	0.0	7.586	A
C-AB	4	0.95	0.00	690	0.006	4	0.0	0.0	5.249	A
C-A	19	5	0.00			19				
A-B	12	3	0.00			12				
A-C	35	9	0.00			35				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D17 - | Development | AM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.
Warning	Vehicle Mix		HV% is zero for all movements / time segments. Vehicle Mix matrix should be completed whether working in PCUs or Vehs. If HV% at the junction is genuinely zero, please ignore this warning.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		6.96	A

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		6.96	A

Traffic Demand

Demand Set Details

ID	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D17	Development	AM	ONE HOUR	08:00	09:30	15	✓

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	1	100.000
B		ONE HOUR	✓	5	100.000
C		ONE HOUR	✓	1	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	1	0
	B	4	0	1
	C	0	1	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

From	To		
	A	B	C
A	0	0	0
B	0	0	0
C	0	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.01	6.96	0.0	A	5	7
C-AB	0.00	0.00	0.0	A	0	0
C-A					0	0
A-B					0	0
A-C					0	0

Main Results for each time segment
08:00 - 08:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	4	0.94	0.00	523	0.007	4	0.0	0.0	6.932	A
C-AB	0	0	0.00	690	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

08:15 - 08:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	4	1	0.00	523	0.009	4	0.0	0.0	6.942	A
C-AB	0	0	0.00	690	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

08:30 - 08:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	6	1	0.00	523	0.011	5	0.0	0.0	6.956	A
C-AB	0	0	0.00	690	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

08:45 - 09:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	6	1	0.00	523	0.011	6	0.0	0.0	6.956	A
C-AB	0	0	0.00	690	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

09:00 - 09:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	4	1	0.00	523	0.009	5	0.0	0.0	6.945	A
C-AB	0	0	0.00	690	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

09:15 - 09:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	4	0.94	0.00	523	0.007	4	0.0	0.0	6.933	A
C-AB	0	0	0.00	690	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000

D18 - | Development | PM

Data Errors and Warnings

Severity	Area	Item	Description
Warning	Major arm width	Arm C - Major arm geometry	For two-way major roads, please interpret results with caution if the total major carriageway width is less than 6m.
Warning	Vehicle Mix		HV% is zero for all movements / time segments. Vehicle Mix matrix should be completed whether working in PCUs or Vehs. If HV% at the junction is genuinely zero, please ignore this warning.

Junction Network

Junctions

Junction	Name	Junction type	Arm A Direction	Arm B Direction	Arm C Direction	Use circulating lanes	Junction Delay (s)	Junction LOS
2	Raheen Woods/L3105	T-Junction	Two-way	Two-way	Two-way		0.00	F

Junction Network

Driving side	Lighting	In London	Network delay (s)	Network LOS
Left	Normal/unknown		0.00	F

Traffic Demand

Demand Set Details

ID	Scenario	Time period	Traffic profile type	Start time (HH:mm)	Finish time (HH:mm)	Time segment length (min)	Run automatically
D18	Development	PM	ONE HOUR	16:45	18:15	15	✓

Demand overview (Traffic)

Arm	Linked arm	Profile type	Use O-D data	Average Demand (PCU/hr)	Scaling Factor (%)
A		ONE HOUR	✓	4	100.000
B		ONE HOUR	✓	3	100.000
C		ONE HOUR	✓	1	100.000

Origin-Destination Data

Demand (PCU/hr)

	To			
	A	B	C	
From	A	0	4	0
	B	2	0	1
	C	0	1	0

Vehicle Mix

HV data entry mode	PCU Factor for a HV (PCU)
HV Percentages	2.00

Heavy Vehicle %

From	To		
	A	B	C
A	0	0	0
B	0	0	0
C	0	0	0

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)
B-AC	0.00	0.00	0.0	A	0	0
C-AB	0.00	0.00	0.0	A	0	0
C-A					0	0
A-B					0	0
A-C					0	0

Main Results for each time segment

16:45 - 17:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	0	0	0.00	562	0.000	0	0.0	0.0	0.000	A
C-AB	0	0	0.00	690	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

17:00 - 17:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	0	0	0.00	562	0.000	0	0.0	0.0	0.000	A
C-AB	0	0	0.00	690	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

17:15 - 17:30

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	0	0	0.00	562	0.000	0	0.0	0.0	0.000	A
C-AB	0	0	0.00	690	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

17:30 - 17:45

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	0	0	0.00	562	0.000	0	0.0	0.0	0.000	A
C-AB	0	0	0.00	690	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

17:45 - 18:00

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	0	0	0.00	562	0.000	0	0.0	0.0	0.000	A
C-AB	0	0	0.00	690	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

18:00 - 18:15

Stream	Total Demand (PCU/hr)	Junction Arrivals (PCU)	Pedestrian demand (Ped/hr)	Capacity (PCU/hr)	RFC	Throughput (PCU/hr)	Start queue (PCU)	End queue (PCU)	Delay (s)	Unsignalised level of service
B-AC	0	0	0.00	562	0.000	0	0.0	0.0	0.000	A
C-AB	0	0	0.00	690	0.000	0	0.0	0.0	0.000	A
C-A	0	0	0.00			0				
A-B	0	0	0.00			0				
A-C	0	0	0.00			0				

Accident Prediction

Accident Prediction Options

Accident prediction type	Junction Environment
Simple (M0)	Urban

Accident Parameters

Arm	Kerbed island present	Zebra crossing	Pelican crossing
A			
B			
C			

Accident prediction: Flows (AADT x 1000)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Accident Prediction (detailed): Pedestrian Flows

Arm	Pedestrian flow (peds x 1000)
A	0.000
B	0.000
C	0.000

Accident Prediction: Results

Total vehicle accidents (Accidents/year)	Total pedestrian accidents (Accidents/year)	Total Accident Rate (Accidents/year)
0.000	0.000	0.000



A World-Class Multidisciplinary Building Consultancy

10 SERVICES, 1 TEAM

Have a project in mind? View our brochure to learn more about how our multidisciplinary team can support you.

The image shows a laptop and a tablet. The laptop screen displays a grid of 10 service icons with labels: Environmental, Project Management, Infrastructure, Health & Safety, Assigned Certifier, Fire Safety, Energy Management, Civil & Structural, Building Surveying, and Mechanical & Electrical. The tablet displays the 'Core Values' section with five items: People-First, Quality, Flexibility, Relationships, and Ambition. A green button with a mouse cursor icon and the text 'CLICK HERE' is positioned below the laptop, with a dotted line pointing to the 'OUR SERVICES' header on the laptop screen.

OUR SERVICES

- Environmental
- Project Management
- Infrastructure
- Health & Safety
- Assigned Certifier
- Fire Safety
- Energy Management
- Civil & Structural
- Building Surveying
- Mechanical & Electrical

Core Values.

- People-First.**
Empowering you to thrive
- Quality.**
Always
- Flexibility.**
It's what we're built on
- Relationships.**
Matter
- Ambition.**
It's our mindset

Best Workplaces
Great Place to Work. IRELAND 2025

CLICK HERE