



Comhairle Chontae na Gaillimhe
Galway County Council

**Proposed Development of 1 No. Domestic Dwelling
House & Associated Works at Carrowmore West,
Clontuskert, Ballinasloe, Co. Galway**

EPA Site Suitability Assessment Report

November 2020



Jennings O'Donovan & Partners Ltd.,
Consulting Engineers, Finisklin Business Park, Sligo.
Tel.: 071 916 1416 Fax: 071 916 1080
e mail: info@jodireland.com
Web: www.jodireland.com



JENNINGS O'DONOVAN & PARTNERS LIMITED
 Project, Civil and Structural Consulting Engineers,
 FINISKLIN BUSINESS PARK,
 SLIGO,
 IRELAND.



Telephone (071) 9161416
 Fax (071) 9161080



Email info@jodireland.com
 Web Site www.jodireland.com

DOCUMENT APPROVAL

PROJECT	Proposed Development of 1 No. Domestic Dwelling House & Associated Works	
CLIENT / JOB NO	Galway County Council	6140
DOCUMENT TITLE	Site: Carrowmore West, Clontuskert, Ballinasloe, Co. Galway EPA Site Suitability Assessment Report	



Prepared by

Reviewed/Approved by

Document DRAFT	Name PJ Regan	Name Mark Forbes
Date July 2020	Signature 	Signature 

Prepared by

Reviewed/Approved by

Document FINAL	Name Brian Murphy	Name Mark Forbes
Date 20th Nov 2020	Signature 	Signature 

This document, and information or advice which it contains, is provided by JENNINGS O'DONOVAN & PARTNERS LIMITED solely for internal use and reliance by its Client in performance of JENNINGS O'DONOVAN & PARTNERS LIMITED's duties and liabilities under its contract with the Client. Any advice, opinions, or recommendations within this document should be read and relied upon only in the context of the document as a whole. The advice and opinions in this document are based upon the information made available to JENNINGS O'DONOVAN & PARTNERS LIMITED at the date of this document and on current standards, codes, technology and construction practices as at the date of this document. Following final delivery of this document to the Client, JENNINGS O'DONOVAN & PARTNERS LIMITED will have no further obligations or duty to advise the Client on any matters, including development affecting the information or advice provided in this document. This document has been prepared by JENNINGS O'DONOVAN & PARTNERS LIMITED in their professional capacity as Consulting Engineers. The contents of the document does not, in any way, purport to include any manner of legal advice or opinion. This document is prepared in accordance with the terms and conditions of JENNINGS O'DONOVAN & PARTNERS LIMITED contract with the Client. Regard should be had to those terms and conditions when considering and/or placing any reliance on this document. Should the Client wish to release this document to a Third Party for that party's reliance, JENNINGS O'DONOVAN & PARTNERS LIMITED may, at its discretion, agree to such release provided that:

- (a) JENNINGS O'DONOVAN & PARTNERS LIMITED written agreement is obtained prior to such release, and
- (b) By release of the document to the Third Party, that Third Party does not acquire any rights, contractual or otherwise, whatsoever against JENNINGS O'DONOVAN & PARTNERS LIMITED and JENNINGS O'DONOVAN & PARTNERS LIMITED, accordingly, assume no duties, liabilities or obligations to that Third Party, and
- (c) JENNINGS O'DONOVAN & PARTNERS LIMITED accepts no responsibility for any loss or damage incurred by the Client or for any conflict of JENNINGS O'DONOVAN & PARTNERS LIMITED's interests arising out of the Client's release of this document to the Third Party

Directors: D. Kiely, C. McCarthy
Regional Director: A. Phelan
Consultants: C. Birney, M. Gavin, R. Gillan

Senior Associates: R. Davis, S. Gilmartin, J. Healy, J. McElvaney, T. McGloin
Associates: L. Brennan, S. Lee, S. Martyn, L. McCormack, S. Molloy
Company Reg No. 149104 **VAT Reg. No.** IE6546504D



6140/510/05/PJR

TABLE OF CONTENTS

1. INTRODUCTION..... 1

2. SITE CHARACTERISATION FORM..... 1

APPENDICES

Appendix A – Site Suitability Assessment - Supporting Maps

Appendix B - Site Suitability Assessment - Supporting Photographs

Appendix C - Site Suitability Assessment - Supporting Drawings

**Appendix D - Site Suitability Assessment – Supporting Document relating to
Proposed Effluent Treatment System**

1. INTRODUCTION

Jennings O'Donovan & Partners Limited (JOD) have been appointed by Galway County Council to carry out Site Suitability Assessment on several single rural dwelling sites at various locations in County Galway.

This report relates to Site at Carrowmore West, Clontuskert, Ballinasloe, Co. Galway.

2. SITE CHARACTERISATION FORM

Please see overleaf completed Site Characterisation Form for Carrowmore West, Clontuskert, Ballinasloe, Co. Galway in accordance with the EPA Code of Practice for Wastewater Treatment and Disposal Systems Serving Single Houses (p.e,<10).

APPENDIX B: SITE CHARACTERISATION FORM

File Reference:

1.0 GENERAL DETAILS (From planning application)

Prefix: First Name: Surname:

Address:

Site Location and Townland:

Telephone No: Fax No:

E-Mail:

Maximum no. of Residents: No. of Double Bedrooms: No. of Single Bedrooms:

Proposed Water Supply: Mains Private Well/Borehole Group Well/Borehole

2.0 GENERAL DETAILS (From planning application)

Soil Type, (Specify Type):

Aquifer Category: Regionally Important Locally Important Poor

Vulnerability: Extreme High Moderate Low High to Low Unknown

Bedrock Type:

Name of Public/Group Scheme Water Supply within 1 km:

Groundwater Protection Scheme (Y/N): Source Protection Area: SI SO

Groundwater Protection Response:

Presence of Significant Sites (Archaeological, Natural & Historical):

Past experience in the area:

Comments:
(Integrate the information above in order to comment on: the potential suitability of the site, potential targets at risk, and/or any potential site restrictions).

SITE SUITABILITY:-
R1 ACCEPTABLE SUBJECT TO NORMAL GOOD PRACTICE,

POTENTIAL TARGETS AT RISK:-
SURFACE WATER, GROUND WATER

Note: Only information available at the desk study stage should be used in this section.

3.0 ON-SITE ASSESSMENT

3.1 Visual Assessment

Landscape Position:

Slope: Steep (>1:5) Shallow (1:5-1:20) Relatively Flat (<1:20)

Surface Features within a minimum of 250m (Distance To Features Should Be Noted In Metres)

Houses:

Existing Land Use:

Vegetation Indicators:

Groundwater Flow Direction:

Ground Condition:

Site Boundaries:

Roads:

Outcrops (Bedrock And/Or Subsoil):

Surface Water Ponding: Lakes:

Beaches/Shellfish: Areas/Wetlands:

Karst Features:

Watercourse/Stream*:

Drainage Ditches*:

Springs / Wells*:

Comments:

(Integrate the information above in order to comment on: the potential suitability of the site, potential targets at risk, the suitability of the site to treat the wastewater and the location of the proposed system within the site).

POTENTIAL TARGETS AT RISK:-

GROUND WATER

SITE APPEARS SUITABLE FOR A WASTEWATER TREATMENT AND DISPOSAL SYSTEM PROVIDING FAVOURABLE T / P IS ACHIEVABLE.

THERE ARE NO SITE RESTRICTIONS, RELATIVELY LARGE SITE.

*Note and record water level

3.2 Trial Hole (should be a minimum of 2.1m deep (3m for regionally important aquifers))

To avoid any accidental damage, a trial hole assessment or percolation tests should not be undertaken in areas, which are at or adjacent to significant sites (e.g. NHAs, SACs, SPAs, and/or Archaeological etc.), without prior advice from National Parks and Wildlife Service or the Heritage Service.

Depth of trial hole (m):

Depth from ground surface to bedrock (m) (if present):

Depth from ground surface to water table (m) (if present):

Depth of water ingress:

Rock type (if present):

Date and time of excavation:

Date and time of examination:

Depth of P/T Test*	Soil/Subsoil Texture & Classification**	Plasticity and dilatancy***	Soil Structure	Density/ Compactness	Colour****	Preferential flowpaths
0.1 m <input type="text"/>	medium bedded sandy SILT/CLAY	DILATANCY WITH DIFFICULTY	CRUMB	SOFT	MEDIUM BROWN	GRASS ROOTS TO -0.6M B.G.L.
0.2 m <input type="text"/>						
0.3 m <input type="text"/>	medium bedded slightly gravelly, sandy SILT	DILATANCY WITH DIFFICULTY	ANGULAR	SOFT	MEDIUM BROWN	
0.4 m <input type="text" value="P1,2,3"/>						
0.5 m <input type="text"/>						
0.6 m <input type="text"/>						
0.7 m <input type="text"/>						
0.8 m <input type="text"/>	thickly bedded sandy, gravelly SILT/CLAY with medium spaced cobbles and widely spaced boulders	DILATANCY WITH DIFFICULTY	BLOCKY	STIFF	SANDY BROWN	Preferential flow paths:- GRAVELS, COBLES
0.9 m <input type="text" value="T 1,2,3"/>						
1.0 m <input type="text"/>	WATER TABLE	WATER TABLE	WATER TABLE	WATER TABLE	WATER TABLE	WATER TABLE
1.1 m <input type="text"/>	1.1m	1.1m	1.1m	1.1m	1.1m	1.1m
1.2 m <input type="text"/>						
1.3 m <input type="text"/>						
1.4 m <input type="text"/>						
1.5 m <input type="text"/>						
1.6 m <input type="text"/>	TRIAL PIT	TIAL PIT	TRIAL PIT	TRIAL PIT	TRIAL PIT	TRIAL PIT
1.7 m <input type="text"/>	TO 1.6M B.G.LEVEL	TO 1.6M B.G.L	1.6m B.G.L	TO 1.6m B.G.L	1.6m B.G.L	TO 1.6m B.G.L
1.8 m <input type="text"/>						
1.9 m <input type="text"/>						
2.0 m <input type="text"/>						
2.1 m <input type="text"/>						
2.2 m <input type="text"/>						
2.3 m <input type="text"/>						
2.4 m <input type="text"/>						
2.5 m <input type="text"/>						
2.6 m <input type="text"/>						
2.7 m <input type="text"/>						
2.8 m <input type="text"/>						
2.9 m <input type="text"/>						
3.0 m <input type="text"/>						

Likely T value:

Note: *Depth of percolation test holes should be indicated on log above. (Enter P or T at depths as appropriate).
 ** See Appendix E for BS 5930 classification.
 *** 3 samples to be tested for each horizon and results should be entered above for each horizon.
 **** All signs of mottling should be recorded.

3.2 Trial Hole (contd.) Evaluation:

The Trial pit shows a top soil layer of 0.2m sandy SILT/CLAY, with a 0.4m subsoil layer of slightly gravely sandy SILT below the topsoil and a 1.0m subsoil layer of silty, gravely SAND to the base of the trial pit, with with medium spaced cobbles and widely spaced boulders throughout the subsoil layers.

The soil and subsoil layers are likely to produce favorable percolation rates for the 'P' & 'T' tests.

The trial pit was excavated to a depth of 1.6m below ground. There were significant boulders noted to the base of the trial pit at time of excavation. There was no water ingress at time of excavation. There was a Water Table recorded within the trial pit at 1.1m below ground level.

3.3(a) Percolation (“T”) Test for Deep Subsoils and/or Water Table

Step 1: Test Hole Preparation

Percolation Test Hole

	1		2		3	
Depth from ground surface to top of hole (mm) (A)	550		550		550	
Depth from ground surface to base of hole (mm) (B)	950		950		950	
Depth of hole (mm) [B - A]	400		400		400	
Dimensions of hole [length x breadth (mm)]	300	x 300	300	x 300	300	x 300

Step 2: Pre-Soaking Test Holes

Date and Time pre-soaking started	29/06/2020	09:12	29/06/2020	09:18	29/06/2020	09:20
-----------------------------------	------------	-------	------------	-------	------------	-------

Each hole should be pre-soaked twice before the test is carried out. Each hole should be empty before refilling.

Step 3: Measuring T_{100}

Percolation Test Hole No.

	1		2		3	
Date of test	30/06/2020		30/06/2020		30/06/2020	
Time filled to 400 mm	12:18		12:13		12:14	
Time water level at 300 mm	15:08		13:29		14:16	
Time to drop 100 mm (T_{100})	170.00		76.00		122.00	
Average T_{100}						122.67

If $T_{100} > 300$ minutes then T-value >90 – site unsuitable for discharge to ground

If $T_{100} \leq 210$ minutes then go to Step 4;

If $T_{100} > 210$ minutes then go to Step 5;

Step 4: Standard Method (where $T_{100} \leq 210$ minutes)

Percolation Test Hole	1			2			3		
Fill no.	Start Time (at 300 mm)	Finish Time (at 200 mm)	Δt (min)	Start Time (at 300 mm)	Finish Time (at 200 mm)	Δt (min)	Start Time (at 300 mm)	Finish Time (at 200 mm)	Δt (min)
1	15:08	18:00	172.00	13:29	15:28	119.00	14:16	16:42	146.00
2	18:00	20:56	175.00	15:28	18:20	172.00	16:42	19:37	175.00
3	20:56	23:57	181.00	18:20	22:16	236.00	19:37	23:11	214.00
Average Δt Value	176.00			175.67			178.33		
	Average $\Delta t/4 =$ [Hole No.1] 44.00 (t_1)			Average $\Delta t/4 =$ [Hole No.2] 43.92 (t_2)			Average $\Delta t/4 =$ [Hole No.3] 44.58 (t_3)		

Result of Test: T = **44.17** (min/25 mm)

Comments:

THE RESULT OF THE 'T' TEST CARRIED OUT ON SITE INDICATE THAT THE SITE IS SUITABLE FOR A SEPTIC TANK SYSTEM OR A SECONDARY TREATMENT SYSTEM WITH A POLISHING FILTER DISCHARGING TO GROUNDWATER.

Step 5: Modified Method (where $T_{100} > 210$ minutes)

Percolation Test Hole No.	1				2				3			
Fall of water in hole (mm)	Time Factor = T_f	Time of fall (mins) = T_m	$K_{fs} = T_f / T_m$	T - Value = $4.45 / K_{fs}$	Time Factor = T_f	Time of fall (mins) = T_m	$K_{fs} = T_f / T_m$	T - Value = $4.45 / K_{fs}$	Time Factor = T_f	Time of fall (mins) = T_m	$K_{fs} = T_f / T_m$	T - Value = $4.45 / K_{fs}$
300 - 250	8.1				8.1				8.1			
250 - 200	9.7				9.7				9.7			
200 - 150	11.9				11.9				11.9			
150 - 100	14.1				14.1				14.1			
Average T- Value	T- Value Hole 1= (t_1) 0.00				T- Value Hole 1= (t_2) 0.00				T- Value Hole 1= (t_3) 0.00			

Result of Test: T = **0.00** (min/25 mm)

Comments:

3.3(b) Percolation (“P”) Test for Shallow Soil / Subsoils and/or Water Table

Step 1: Test Hole Preparation

Percolation Test Hole	1		2		3	
Depth from ground surface to top of hole (mm)	0		0		0	
Depth from ground surface to base of hole (mm)	400		400.00		400	
Depth of hole (mm)	400		400		400	
Dimensions of hole [length x breadth (mm)]	300 x 300		300 x 300		300 x 300	

Step 2: Pre-Soaking Test Holes

Date and Time pre-soaking started	29/06/2020 09:51		29/06/2020 09:55		29/06/2020 09:56	
-----------------------------------	------------------	--	------------------	--	------------------	--

Each hole should be pre-soaked twice before the test is carried out. Each hole should be empty before refilling.

Step 3: Measuring P₁₀₀

Percolation Test Hole No.	1		2		3	
Date of test	30/06/2020		30/06/2020		30/06/2020	
Time filled to 400 mm	12:13		12:10		12:16	
Time water level at 300 mm	12:18		12:20		12:25	
Time to drop 100 mm (P ₁₀₀)	5.00		10.00		9.00	
Average P ₁₀₀						8.00

If P₁₀₀ > 300 minutes then P-value >90 – site unsuitable for discharge to ground

If P₁₀₀ ≤ 210 minutes then go to Step 4;

If P₁₀₀ > 210 minutes then go to Step 5;

Step 4: Standard Method (where $P_{100} \leq 210$ minutes)

Percolation Test Hole	1			2			3		
Fill no.	Start Time (at 300 mm)	Finish Time (at 200 mm)	Δp (min)	Start Time (at 300 mm)	Finish Time (at 200 mm)	Δp (min)	Start Time (at 300 mm)	Finish Time (at 200 mm)	Δp (min)
1	12:18	12:33	15.00	12:20	12:57	37.00	12:25	12:52	27.00
2	12:33	13:54	81.00	12:57	13:41	44.00	12:52	13:29	37.00
3	13:54	14:18	24.00	13:41	14:30	49.00	13:29	15:11	102.00
Average Δp Value	40.00			43.33			55.33		
	Average $\Delta p/4 =$ [Hole No.1] 10.00 (p_1)			Average $\Delta p/4 =$ [Hole No.2] 10.83 (p_2)			Average $\Delta p/4 =$ [Hole No.3] 13.83 (p_3)		

Result of Test: $P =$ 11.56 (min/25 mm)

Comments:

THE RESULT OF THE 'P' TEST CARRIED OUT ON SITE INDICATE THE UPPER SOIL LAYER IS SUITABLE FOR A SECONDARY TREATMENT SYSTEM WITH POLISHING FILTER AT GROUND SURFACE OR OVERGROUND.

Step 5: Modified Method (where $P_{100} > 210$ minutes)

Percolation Test Hole No.	1				2				3			
Fall of water in hole (mm)	Time Factor = T_f	Time of fall (mins) = T_m	$K_{fs} = T_f / T_m$	P - Value = $4.45 / K_{fs}$	Time Factor = T_f	Time of fall (mins) = T_m	$K_{fs} = T_f / T_m$	P - Value = $4.45 / K_{fs}$	Time Factor = T_f	Time of fall (mins) = T_m	$K_{fs} = T_f / T_m$	P - Value = $4.45 / K_{fs}$
300 - 250	8.1				8.1				8.1			
250 - 200	9.7				9.7				9.7			
200 - 150	11.9				11.9				11.9			
150 - 100	14.1				14.1				14.1			
Average P- Value	P- Value Hole 1= (p_1) 0.00				P- Value Hole 1= (p_2) 0.00				P- Value Hole 1= (p_3) 0.00			

Result of Test: $P =$ 0.00 (min/25 mm)

Comments:

3.4 The following associated Maps, Drawings and Photographs should be appended to this site characterisation form.

1. Discovery Series 1:50,000 Map indicating overall drainage, groundwater flow direction and housing density in the area.
2. Supporting maps for vulnerability, aquifer classification, soil, bedrock.
3. North point should always be included.
4. (a) Sketch of site showing measurements to Trial Hole location and
 - (b) Percolation Test Hole locations,
 - (c) wells and
 - (d) direction of groundwater flow (if known),
 - (e) proposed house (incl. distances from boundaries)
 - (f) adjacent houses,
 - (g) watercourses,
 - (h) significant sites
 - (i) and other relevant features.
5. Cross sectional drawing of the site and the proposed layout¹ should be submitted.
6. Photographs of the trial hole, test holes and site (date and time referenced).

¹ The calculated percolation area or polishing filter area should be set out accurately on the site layout drawing in accordance with the code of practice's requirements.

4.0 CONCLUSION of SITE CHARACTERISATION

Integrate the information from the desk study and on-site assessment (i.e. visual assessment, trial hole and percolation tests) above and conclude the type of system(s) that is (are) appropriate. This information is also used to choose the optimum final disposal route of the treated wastewater.

Not Suitable for Development

Suitable for ¹

- | | |
|---|----------------------------------|
| 1. Septic tank system (septic tank and percolation area) | <input type="text" value="Yes"/> |
| 2. Secondary Treatment System | |
| a. septic tank and filter system constructed on-site and polishing filter; or | <input type="text" value="Yes"/> |
| b. packaged wastewater treatment system and polishing filter | <input type="text" value="Yes"/> |

Discharge Route

5.0 RECOMMENDATION

Propose to install:

and discharge to:

Trench Invert level (m):

Site Specific Conditions (e.g. special works, site improvement works testing etc.)

DUE TO SITE RESTRICTIONS REGARDING SEPERATION DISTANCE REQUIRMENTS, IT IS RECOMMENDED TO INSTALL A SECONDARY EFFLUENT TREATMENT SYSTEM FOLLOWED BY A POLISHING FILTER - TRENCH INVERT AT +0.1m ABOVE GROUND LEVEL (AS PER SITE LAYOUT PLAN & SECTION A-A THROUGH POLISHING FILTER DRAWING NUMBER 6140-JOD-XX-ZZ-DR-B-2042 & 2043 (A3 @ 1:500, 1:100))

SECONDARY TREATMENT SYSTEM:-

THE PACKAGED WASTEWATER TREATMENT SYSTEM SHALL BE IN ACCORDANCE THE REQUIREMENTS OUTLINED IN THE EPA CODE OF PRACTICE - WASTEWATER TREATMENT AND DISPOSAL SYSTEMS SERVING SINGLE HOUSES 2009 AND SHALL BE CERTIFIED IN ACCORDANCE WITH EN12566-3.

RAISED POSISHING FILTER:-

THE POLISHING FILTER SHALL BE INSTALLED AS PER SITE LAYOUT PLAN, SECTION A-A THROUGH POLISHING FILTER DRAWING NUMBER 6140-JOD-XX-ZZ-DR-B-2042 & 2043 (A3 @ 1:500, 1:100) i.e. INSTALL A STILLING CHAMBER, DISTRUBTION BOX WITH 4 No. 9m RUNS OF 110mm uPVC PIPEWORK AT GROUND LEVEL, LAID AT A 1:200 GRADIENT, WITH 8mm PERFORATIONS (TYPICALLY AT 4,6,8 o'clock) AT 75mm CENTRES, PIPE WORK TO BE LAID 2.5M CENTER TO CENTER WITHIN A 500mm WIDE TRENCH ON 300mm DEEP 8-32mm WASHED GRAVEL AND 150mm WASHED GRAVEL OVER PIPEWORK WITH GEOTEXTILE MEMBRANE OVER GRAVEL AND 300mm DEEP TOPSOIL COVER OVER GEOTEXTILE.

¹ note: more than one option may be suitable for a site and this should be recorded

² A discharge of sewage effluent to "waters" (definition includes any or any part of any river, stream, lake, canal, reservoir, aquifer, pond, watercourse or other inland waters, whether natural or artificial) will require a licence under the Water Pollution Acts 1977-90. Refer to Section 2.6.2.

6.0 TREATMENT SYSTEM DETAILS

SYSTEM TYPE: Septic Tank System

Tank Capacity (m ³)	<input type="text"/>	Percolation Area		Mounded Percolation Area	
		No. of Trenches	<input type="text"/>	No. of Trenches	<input type="text"/>
		Length of Trenches (m)	<input type="text"/>	Length of Trenches (m)	<input type="text"/>
		Invert Level (m)	<input type="text"/>	Invert Level (m)	<input type="text"/>

SYSTEM TYPE: Secondary Treatment System

Filter Systems

Media Type	Area (m ²)*	Depth of Filter	Invert Level
Sand/Soil	<input type="text"/>	<input type="text"/>	<input type="text"/>
Soil	<input type="text"/>	<input type="text"/>	<input type="text"/>
Constructed Wetland	<input type="text"/>	<input type="text"/>	<input type="text"/>
Other	<input type="text"/>	<input type="text"/>	<input type="text"/>

Package Treatment Systems

Type	<input type="text" value="SOLIDO SMART - S.B.R."/>
Capacity PE	<input type="text" value="6.00"/>
Sizing of Primary Compartment	<input type="text" value="3.00"/> m ³

SYSTEM TYPE: Tertiary Treatment System

Polishing Filter: Surface Area (m ² *) <input type="text" value="67.50"/> or Gravity Fed: No. of Trenches <input type="text" value="4"/> Length of Trenches (m) <input type="text" value="9.00"/> Invert Level (m) <input type="text" value="0.10"/>	Package Treatment System: Capacity (pe) <input type="text"/> Constructed Wetland: Surface Area (m ² *) <input type="text"/>
---	---

DISCHARGE ROUTE:

Groundwater <input checked="" type="checkbox"/>	Hydraulic Loading Rate * (l/m ² .d)	<input type="text"/>
Surface Water ** <input type="checkbox"/>	Discharge Rate (m ³ /hr)	<input type="text"/>

TREATMENT STANDARDS:

Treatment System Performance Standard (mg/l)	BOD	SS	NH ₄ - N	Total N	Total P
EN 12566-3	5.00	13.00	0.70	5.00	2.00

QUALITY ASSURANCE:

Installation & Commissioning

THE PACKAGED SYSTEM AND POLISHING FILTER SHALL BE INSTALLED IN ACCORDANCE THE REQUIREMENTS OUTLINED IN THE EPA CODE OF PRACTICE - WASTEWATER TREATMENT AND DISPOSAL SYSTEMS SERVING SINGLE HOUSES 2009. COMMISSIONING BY MANUFACTURES REPRESENTATIVE.

On-going Maintenance

DE-SLUDGING SHALL BE CARRIED OUT A MINIMUM OF ONCE PER YEAR AND IN ACCORDANCE THE REQUIREMENTS OUTLINED IN THE EPA CODE OF PRACTICE - WASTEWATER TREATMENT AND DISPOSAL SYSTEMS SERVING SINGLE HOUSES 2009.

* Hydraulic loading rate is determined by the percolation rate of subsoil

** Water Pollution Act discharge licence required

7.0 SITE ASSESSOR DETAILS

Company: JENNINGS O'DONOVAN & PARTNERS

Prefix: Mr. First Name: PJ Surname: REGAN

Address: FINISKLIN, SLIGO, CO. SLIGO.

Qualifications/Experience: B. Sc. (Bld. Surv), FETAC Site Suitability Assessment

Date of Report: 20/07/2020

Phone: 071 9161416 Fax: e-mail: pjregan@jodireland.com

Indemnity Insurance Number:


Signature:  -----


APPENDIX A


SITE SUITABILITY ASSESSMENT SUPPORTING MAPS


- Soil Classification Map
- Aquifer Classification Map
 - Vulnerability Map
 - Bedrock Map
 - Karst Map
 - Wells & Springs Map
- National Parks & Wildlife Map
- National Monuments Map













Karst Features Map



Wells & Springs Map




National Monuments Map



APPENDIX B

SITE SUITABILITY ASSESSMENT SUPPORTING PHOTOGRAPHS

- Overview of site
 - Trial Hole
 - P Tests
 - T Tests



Overview of percolation test area, showing Trial Pit, T & P text holes.



Trial Pit dug to 1.6m deep 29-06-2020.



Trial Pit dug to 1.6m deep 29-06-2020.



Trial Pit dug to 1.6m deep 29-06-2020.



P1 dug to 400mm 29-06-2020



P1 dug to 400mm 29-06-2020



P2 dug to 400mm 29-06-2020



P2 dug to 400mm 29-06-2020



P3 dug to 400mm 29-06-2020



P3 dug to 400mm 29-06-2020



T1 dug to 400mm 29-06-2020



T1 dug to 400mm 29-06-2020



T2 dug to 400mm 29-06-2020



T2 dug to 400mm 29-06-2020



T3 dug to 400mm 29-06-2020



T3 dug to 400mm 29-06-2020

APPENDIX C

SITE SUITABILITY ASSESSMENT SUPPORTING DRAWINGS

- 6140-JOD-XX-ZZ-DR-B-2039 – Site Identification Map, 1:50,000
 - 6140-JOD-XX-ZZ-DR-B-2040 – Site Location Map, 1:2,500.
- 6140-JOD-XX-ZZ-DR-B-2041 – Existing Site Layout Plan, 1:500
- 6140-JOD-XX-ZZ-DR-B-2042 – Proposed Site Layout Plan, 1:500
 - 6140-JOD-XX-ZZ-DR-B-2043 – Polishing Filter Section A-A



SITE IDENTIFICATION MAP Scale 1:50,000

Rebuilding Ireland

NOTES:-

- THIS DRAWING IS NOT TO BE USED FOR CONSTRUCTION**
- 1 FIGURED DIMENSIONS ONLY TO BE TAKEN FROM THIS DRAWING.
 - 2 ALL LEVELS REFER TO ORDNANCE DATUM (MALIN HEAD).
 - 3 ENGINEER TO BE INFORMED OF ANY DISCREPANCIES BEFORE ANY WORK COMMENCES.
 - 4 THIS DRAWING TO BE READ IN CONJUNCTION WITH ALL OTHER RELEVANT DRAWINGS AND SPECIFICATIONS.

LEGEND:-

NORTH SIGN INDICATED THUS

SITE LOCATION

Ordnance Survey Ireland Licence No.EN 0002620
© Government of Ireland.

OS Sheet No. 2543

PL.01	Issued for PLANNING APPROVAL	BM	MF	20.11.20
rev.	modifications	by	chkd	date

file	P:\lod-job6140_GCC-Sheltered Housing\700 Drawings\703 Planning\Site No. 5 Clontuskert, Ballinasloe\01 WIP\6140-JOD-XX-ZZ-DR-B-2039 - Discovery Map.dwg			
------	--	--	--	--

client

Comhairle Chontae na Gaillimhe
Galway County Council

project

PROPOSED DEVELOPMENT OF 1 NO. DOMESTIC DWELLING HOUSE & ASSOCIATED WORKS AT CARROWMORE WEST, CLONTUSKERT, BALLINASLOE, CO. GALWAY

stage

PLANNING

title

SITE IDENTIFICATION MAP

scale

1:50,000 @A4


surveyed	drawn	checked	date
osi	BM	MF	NOV 2020

© COPYRIGHT OF

JENNINGS O'DONOVAN & PARTNERS
CONSULTING ENGINEERS,
FINISKLIN,
SLIGO,
IRELAND.

TEL. +353 (0)71 916 1416
FAX. +353 (0)71 916 1080
Email: info@jodireland.com

drawing no.	revision
6140-JOD-XX-ZZ-DR-B-2039	PL.01



SITE LOCATION MAP Scale 1:2,500





NOTES:-


THIS DRAWING IS NOT TO BE USED FOR CONSTRUCTION

- 1 FIGURED DIMENSIONS ONLY TO BE TAKEN FROM THIS DRAWING.
- 2 ALL LEVELS REFER TO ORDNANCE DATUM (MALIN HEAD).
- 3 ENGINEER TO BE INFORMED OF ANY DISCREPANCIES BEFORE ANY WORK COMMENCES.
- 4 THIS DRAWING TO BE READ IN CONJUNCTION WITH ALL OTHER RELEVANT DRAWINGS AND SPECIFICATIONS.

LEGEND:-



SITE BOUNDARY APPLICABLE TO PLANNING APPLICATION LINED RED 

LAND UNDER CONTROL OF APPLICANT LINED IN BLUE 

NORTH SIGN INDICATED THUS 

Site Area:-
2158 m2, 0.533 Acres, 0.216 Hectares

ITM Co-Ordinates of site:-
582404, 723771

Ordnance Survey Ireland Licence No.EN 0002620
© Government of Ireland. 
OS Sheet No. 2543 

PL.01	issued for PLANNING APPROVAL	BM	MF	20.11.20
rev.	modifications		by chkd	date

file P:\jod\jba6140_GCC-Sheltered Housing\700 Drawings\703 Planning\Site No. 5 Clontuskert, Ballinasloe\01 WP\6140-JOD-XX-ZZ-DR-B-2040 - Site Location Map.dwg

client  **Comhairle Chontae na Gaillimhe**
Galway County Council

project
PROPOSED DEVELOPMENT OF 1 NO. DOMESTIC DWELLING HOUSE & ASSOCIATED WORKS AT CARROWMORE WEST, CLONTUSKERT, BALLINASLOE, CO. GALWAY

stage
PLANNING

title
SITE LOCATION MAP

scale
1:2,500 @A4

surveyed	drawn	checked	date
osi	BM	MF	NOV 20

© COPYRIGHT OF
JENNINGS O'DONOVAN & PARTNERS
CONSULTING ENGINEERS,
FINISKLIN,
SLIGO,
IRELAND.

TEL. +353 (0)71 916 1416
FAX. +353 (0)71 916 1080
Email: info@jodireland.com



drawing no.	revision
6140-JOD-XX-ZZ-DR-B-2040	PL.01

NOTES:-

- 1. THIS DRAWING IS NOT TO BE USED FOR CONSTRUCTION
- 2. FIGURED DIMENSIONS ONLY TO BE TAKEN FROM THIS DRAWING.
- 3. ALL LEVELS REFER TO ORDNANCE DATUM (MALIN HEAD).
- 4. ENGINEER TO BE INFORMED OF ANY DISCREPANCIES BEFORE ANY WORK COMMENCES.
- 5. THIS DRAWING TO BE READ IN CONJUNCTION WITH ALL OTHER RELEVANT DRAWINGS AND SPECIFICATIONS.

LEGEND:-

- SITE BOUNDARY APPLICABLE TO PLANNING APPLICATION LINED RED
- LAND UNDER CONTROL OF APPLICANT LINED IN BLUE
- NORTH SIGN INDICATED THUS
- EXISTING GROUND LEVELS INDICATED THUS
- EXISTING ESB OVERHEAD POWER LINE INDICATED THUS
- EXISTING TREES/HEDGEROW
- PERCOLATION TEST AREA
- PERCOLATION 'T' & 'P' TEST LOCATIONS
- TRAIL PIT No. 1 / 2 TEXT LOCATIONS

Site Area:-
2158 m², 0.533 Acres, 0.216 Hectares

ITM Co-Ordinates of site:-
582404, 723771

Ordnance Survey Ireland Licence No. EN 0002620
© Government of Ireland.
OS Sheet No. 2678

PL.01	Issued for PLANNING APPROVAL	BM	MF	20.11.20
rev.	modifications	by	chkd	date
Layout Ref.:				
file: P:\jod-jobs\6140_GCC_Sheltered Housing\700 Drawings\703 Planning\Site No. 5 Clontuskert, Ballinasloe\01 WPI\6140-JOD-XX-ZZ-DR-B-2041 - Existing Site Layout.dwg				

client **Comhairle Chontae na Gaillimhe**
Galway County Council

project
PROPOSED DEVELOPMENT OF 1 NO. DOMESTIC DWELLING HOUSE & ASSOCIATED WORKS CARROWMORE WEST, CLONTUSKERT, BALLINASLOE, CO. GALWAY

stage
PLANNING


title
EXISTING SITE LAYOUT PLAN

scale
1:500 @ A3

surveyed	drawn	checked	date
OSI	BM	MF	NOV 2020


© COPYRIGHT OF
JENNINGS O'DONOVAN & PARTNERS
CONSULTING ENGINEERS,
FINISKLIN,
SLIGO,
IRELAND.
TEL. +353 (0)71 916 1416
FAX. +353 (0)71 916 1080
Email: info@jodireland.com

drawing no.	revision
6140-JOD-XX-ZZ-DR-B-2041	PL.01



EXISTING SITE LAYOUT PLAN Scale 1:500

DEVELOPMENT TO COMPLY WITH COUNTY COUNCIL DEVELOPMENT PLAN



NOTES:-
 THIS DRAWING IS NOT TO BE USED FOR CONSTRUCTION
 1 FIGURED DIMENSIONS ONLY TO BE TAKEN FROM THIS DRAWING.
 2 ALL LEVELS REFER TO ORDNANCE DATUM (MALIN HEAD).
 3 ENGINEER TO BE INFORMED OF ANY DISCREPANCIES BEFORE ANY WORK COMMENCES.
 4 THIS DRAWING TO BE READ IN CONJUNCTION WITH ALL OTHER RELEVANT DRAWINGS AND SPECIFICATIONS.

LEGEND:-

- SITE BOUNDARY APPLICABLE TO PLANNING APPLICATION LINED RED
- LAND UNDER CONTROL OF APPLICANT LINED IN BLUE
- NORTH SIGN INDICATED THUS
- EXISTING GROUND LEVELS INDICATED THUS
- EXISTING ESB OVERHEAD POWER LINE INDICATED THUS
- SIGHT LINE DISTANCE AS SHOWN INDICATED THUS
- EXISTING DWELLING TO BE DEMOLISHED INDICATED THUS
- PERCOLATION TEST AREA
- PERCOLATION 'T' & 'P' TEST LOCATIONS
- TRAIL PIT No. 1 / 2 TEXT LOCATIONS

Site Area:-
 2158 m2, 0.533 Acres, 0.216 Hectares

ITM Co-Ordinates of site:-
 582404, 723771

Ordnance Survey Ireland Licence No. EN 0002620
 © Government of Ireland.
 OS Sheet No. 2678

PL.01	Issued for PLANNING APPROVAL	BM	MF	20.11.20
rev.	modifications	by	chkd	date
Layout Ref.:				
File: P:\jod-jobs\6140_GCC-Sheltered Housing\700 Drawings\703 Planning\Site No. 5 Clontuskert, Ballinasloe\01 WIP\6140-JOD-XX-ZZ-DR-B-2042 - Proposed Site Layout.dwg				

client
 Comhairle Chontae na Gaillimhe
 Galway County Council

project
 PROPOSED DEVELOPMENT OF 1 NO. DOMESTIC DWELLING HOUSE & ASSOCIATED WORKS AT CARROWMORE WEST, CLONTUSKERT, BALLINASLOE, CO. GALWAY

stage
 PLANNING

title
 PROPOSED SITE LAYOUT PLAN

scale
 1:500 @ A3

surveyed	drawn	checked	date
OSI	BM	MF	NOV 2020

© COPYRIGHT OF
JENNINGS O'DONOVAN & PARTNERS
 CONSULTING ENGINEERS,
 FINISKLIN,
 SLIGO,
 IRELAND.
 TEL. +353 (0)71 916 1416
 FAX. +353 (0)71 916 1080
 Email: info@jodireland.com




drawing no.	revision
6140-JOD-XX-ZZ-DR-B-2042	PL.01

PROPOSED SITE LAYOUT PLAN Scale 1:500

NOTES:-

- THIS DRAWING IS NOT TO BE USED FOR CONSTRUCTION
- 1 FIGURED DIMENSIONS ONLY TO BE TAKEN FROM THIS DRAWING.
- 2 ALL LEVELS REFER TO ORDINANCE DATUM (MALIN HEAD).
- 3 ENGINEER TO BE INFORMED OF ANY DISCREPANCIES BEFORE ANY WORK COMMENCES.
- 4 THIS DRAWING TO BE READ IN CONJUNCTION WITH ALL OTHER RELEVANT DRAWINGS AND SPECIFICATIONS.

LEGEND:-



POLISHING FILTER LONGITUDINAL SECTION A-A THROUGH TRENCH
Scale 1:100

PL.01	Issued for PLANNING APPROVAL	BM	MF	20.11.20
rev.	modifications	by	chkd	date
Layout Ref.:				
File P:\jod-jobs\6140_GCC-Sheltered Housing\700 Drawings\703 Planning\Site No. 5 Clontuskert, Ballinasloe\01 WIP\6140-JOD-XX-ZZ-DR-B-2042 - Proposed Site Layout.dwg				

client **Comhairle Chontae na Gaillimhe**
Galway County Council

project
PROPOSED DEVELOPMENT OF 1 NO. DOMESTIC DWELLING HOUSE & ASSOCIATED WORKS AT AT CARROWMORE WEST, CLONTUSKERT, BALLINASLOE, CO. GALWAY

stage
PLANNING

title
POLISHING FILTER SECTION A-A

scale
1:100 @ A3

surveyed	drawn	checked	date
OSI	BM	MF	NOV 2020

© COPYRIGHT OF
JENNINGS O'DONOVAN & PARTNERS
CONSULTING ENGINEERS,
FINISKLIN,
SLIGO,
IRELAND.
TEL: +353 (0)71 916 1416
FAX: +353 (0)71 916 1080
Email: info@jodireland.com

drawing no.	revision
6140-JOD-XX-ZZ-DR-B-2043	PL.01


APPENDIX D

SUPPORTING DOCUMENTS RELATING TO PROPOSED EFFLUENT TREATMENT SYSTEM

Proposed Secondary Treatment System – Solido SMART (6PE)

- Solido SMART (S.B.R.) Brochure
- Solido SMART (S.B.R.) PIA Certification

The new generation in Decentralised Wastewater Treatment




The new generation in Decentralised Wastewater Treatment

The Solido SMART from Premier Tech, is a decentralised wastewater treatment plant and the perfect solution for residential and commercial projects where mains drainage is unavailable.

Serving a population of up to 9 PE and fast becoming the industry's system of choice; this low-profile unit offers a reliable design and low installation costs. Available in gravity and integrated pumped outlet versions. Installed to treat wastewater with minimal impact on the environment, typical applications include single dwellings, small communities.

Superior Technical Performance

The highly successful Solido SMART is designed and tested in accordance with EN12566-3, in compliance with S.R 66:2015. This plant is able to produce a final effluent quality better than 10:20:5 (BOD:SS:NH₃). Removal of total nitrogen and total phosphorus (TN and TP) is expected to reach 83% and 68% respectively.



Solido SMART

State of the art SBR Treatment

Advanced Technical Qualities

The Solido SMART solution makes decentralised wastewater treatment easier and more efficient than ever. Trust its high-quality design and durable components to provide long-term performances and peace of mind.

- Low operational cost, offering long term savings.
- Discrete and silent treatment plant.
- Reduced installation and maintenance costs, Solido SMART tanks are lightweight, compact and have low installation depth requirements.
- Fully CE marked. Designed and tested in accordance with EN 12566-3.
- Polyethylene material - durable, recyclable and impact resistant.

! How it works

Solido SMART combines the benefits of an ultra-compact solution with the trusted performance of Solido technology. Integrating with SBR technology comparable to large municipal applications, the proven technology operates with direct aeration of the wastewater and without the need for primary treatment. This simple principle provides efficient wastewater treatment results without the emission of any odours.

1. Technology Capsule

Safely housed in the capsule, the compressor requires only 0.80 - 1.04 kWh/d for 6 - 9 PE plants respectively - providing an efficient and quiet treatment without disturbance to the homeowner.

2. Tube Diffuser

The incoming wastewater is immediately supplied with oxygen to ensure a very efficient and odourless treatment.

3. The SMART Pipe

Slows down the incoming influent and simplifies inspections. Makes part desludging safe and easy.


4. Clearwater Pump (Pumped outlet only)

5. Clearwater Air Lift (Gravity outlet only)

The patented self-flushing airlift prevents sludge loss and ensures high performances.


6. Solido-Tank

Manufactured seamlessly as one-piece from eco-friendly PE, with 25 years warranty.



Solido SMART Plant Size

Plant Size (PE)	discharge	Tank Type	Length (m)	Width (m)	Height (m)	INLET Height to base (m)	OUTLET Height to base (m)	Pipe Diameter (mm)	reference code
6 (max. 0.9 m ³ /d)	pumped	3000	2.42	1.42	2.06 – 2.47	1.47	1.73	110	KEBL3026
9 (max. 1.35 m ³ /d)	pumped	4500	2.42	1.79	2.34 – 2.75	1.74	2.06	110	KEBL4526
6 (max. 0.9 m ³ /d)	gravity	3000	2.42	1.42	2.06 – 2.47	1.47	1.40	110	KCBL3020
9 (max. 1.35 m ³ /d)	gravity	4500	2.42	1.79	2.34 – 2.75	1.74	1.73	110	KCBL4520



Installation



The Solido SMART Sewage Treatment Plant requires a relatively low cost and easy installation process. As the tank is super reinforced, concrete is not needed and the tank can be fully installed in free flowing granular backfill.

Warranty

All Premier Tech PE tanks come with a 25 year warranty as standard. Individual product and part warranties are available upon request.

Premier Tech work closely with a nationwide network of installation partners and detailed installation guidelines are provided with each product.

All electric work should be carried out in accordance with current regulations.




* tolerance -40/+10 mm

B	HOF S2	03.07.2020	Steigrohr aktualisiert.		
Rev	Name	Datum	Änderung		gepr.
Erstellt	HOF S2	13.03.2020	Allgemeintoleranz: DIN 16742 TG9 / DIN ISO 2768 - mK	Gewicht:	kg
Gepr.	HER J3	03.07.2020	DIN 6 T1 Projektionsmethode 1	Kantenbruch nach ISO 13715	Wanddicke: mm
CAD-System: SolidWorks2018				Werkstoff:	PE-LLD
PREMIER TECH Am Gammgraben 2 19258 Boizenburg Germany Fon+49 38847 6239 0			Benennung	Farbe:	schwarz
			Solido SMART EBL-30 (6 PE) pump PT Ireland small SBR WWTP compliant with EN 12566-3 / SR66	Zchn.-Nr.:	314_05047
				Art.-Nr.:	KEBL3026
			Hauptabmessungen	Maßstab: 1:20	A3 Blatt 1 von 3

Letzte Speicherung: Freitag, 3. Juli 2020 17:40:43


Für diese Unterlagen behalten wir uns alle Rechte vor, auch für den Fall der Patenterteilung oder Gebrauchsmustererteilung. Sie darf ohne unsere vorherige schriftliche Zustimmung weder vervielfältigt noch sonstwie benutzt, noch Dritten zugänglich gemacht werden.



Rev	Name	Datum	Änderung		gepr.
Erstellt	HOF52	13.03.2020	Allgemeintoleranz: DIN 16742 TG9 / DIN ISO 2768 - mK		Gewicht: kg
Gepr.	HERJ3	03.07.2020	DIN 6 T1 Projektions- methode 1	Kantenbruch nach ISO 13715	Wanddicke: mm
CAD-System: SolidWorks2018			Benennung		Werkstoff: PE-LLD
PREMIER TECH Am Gammgraben 2 19258 Boizenburg Germany Fon+49 38847 6239 0			Solido SMART EBL-30 (6 PE) pump PT Ireland small SBR WWTP compliant with EN 12566-3 / SR66		Farbe: schwarz
					Zchng.-Nr.: 314_05047
					Art.-Nr.: KEBL3026
			Hauptabmessungen		Maßstab: 1:20
					A3 Blatt 2 von 3

Letzte Speicherung: Freitag, 3. Juli 2020 17:40:43

Für diese Unterlagen behalten wir uns alle Rechte vor, auch für den Fall der Patenterteilung oder Gebrauchsmustereintragung. Sie darf ohne unsere vorherige schriftliche Zustimmung weder vervielfältigt noch sonstwie benutzt, noch Dritten zugänglich gemacht werden.



Rev	Name	Datum	Änderung		gepr.
Erstellt	HOF52	13.03.2020	Allgemeintoleranz: DIN 16742 TG9 / DIN ISO 2768 - mK		Gewicht: kg
Gepr.	HERJ3	03.07.2020	DIN 6 T1 Projektions- methode 1	Kantenbruch nach ISO 13715	Wanddicke: mm
CAD-System: SolidWorks2018					Werkstoff: PE-LLD
			Benennung		Farbe: schwarz
Am Gammgraben 2 19258 Boizenburg Germany Fon+49 38847 6239 0			Solido SMART EBL-30 (6 PE) pump PT Ireland small SBR WWTP compliant with EN 12566-3 / SR66		Zchng.-Nr.: 314_05047
					Art.-Nr.: KEBL3026
Hauptabmessungen			Maßstab: 1:20		A3 Blatt 3 von 3

Letzte Speicherung: Freitag, 3. Juli 2020 17:40:43

Für diese Unterlagen behalten wir uns alle Rechte vor, auch für den Fall der Patenterteilung oder Gebrauchsmustererteilung. Sie darf ohne unsere vorherige schriftliche Zustimmung weder vervielfältigt noch sonstwie benutzt, noch Dritten zugänglich gemacht werden.



Certificate

TREATMENT PERFORMANCE RESULTS

Premier Tech Aqua GmbH
Bei der neuen Münze 11, 22145 Hamburg, Germany

EN 12566-3

Results corresponding to EN 12566-3 and S.R. 66

PIA-SR66-1604-1055.02

SOLIDO smart

One-chamber SBR system in one PE tank

Nominal organic daily load	0.30 kg/d															
Nominal hydraulic daily load	0.90 m ³ /d															
Material	Polyethylene															
Watertightness	Pass															
Structural behaviour (Pit Test)	Pass (also wet conditions)															
Durability	Pass															
Treatment efficiency (nominal sequences)	<table><thead><tr><th></th><th>Efficiency</th><th>Effluent</th></tr></thead><tbody><tr><td>COD</td><td>95.1 %</td><td>39 mg/l</td></tr><tr><td>BOD5</td><td>98.5 %</td><td>5 mg/l</td></tr><tr><td>NH4-N</td><td>98.0 %</td><td>0.7 mg/l</td></tr><tr><td>SS</td><td>97.1 %</td><td>13 mg/l</td></tr></tbody></table>		Efficiency	Effluent	COD	95.1 %	39 mg/l	BOD5	98.5 %	5 mg/l	NH4-N	98.0 %	0.7 mg/l	SS	97.1 %	13 mg/l
	Efficiency	Effluent														
COD	95.1 %	39 mg/l														
BOD5	98.5 %	5 mg/l														
NH4-N	98.0 %	0.7 mg/l														
SS	97.1 %	13 mg/l														
Number of desludging	Not more than once															
Electrical consumption	0.81 kWh/d															

Performance tested by:

PIA - Prüfinstitut für Abwassertechnik GmbH
Hergenrather Weg 30
52074 Aachen
Germany




This document replaces neither the declaration of performance nor the CE marking.









PIA - Sustainable Certification
Oliver Völkner
J. Wenter
geprüft - tested - testé


Verschitz / Wermter September 2019


SOLIDO smart range and its referring test reports:

Population equivalent (PE)	Drawing of model of the range	Watertightness (EN 12566-3 Annex A)	Treatment Efficiency (EN 12566-3 Annex B)	Structural Behaviour (EN 12566-3 Annex C)	Durability
Initial Type Test (ITT) 6 900 l/d		Pass PIA2007-WD-003	Pass PIA2015-239B22.e	Pass For wet ground conditions also, 0.95 m installation depth from inlet invert	Pass PIA2016-DH-1510-1052.01
6 900 l/d		Pass PIA2007-WD-003	Pass Range conformity according to S.R. 66:2015	Pass For wet ground conditions, For wet ground conditions also, 1.00 m installation depth from inlet invert	Pass PIA2016-DH-1510-1052.01
7 1050 l/d		Pass PIA2007-WD-003	Pass Range conformity according to S.R. 66:2015	Pass For wet ground conditions, For wet ground conditions also, 1.00 m installation depth from inlet invert	Pass PIA2016-DH-1510-1052.01

Population equivalent (PE)	Drawing of model of the range	Watertightness (EN 12566-3 Annex A)	Treatment Efficiency (EN 12566-3 Annex B)	Structural Behaviour (EN 12566-3 Annex C)	Durability
9 1350 l/d		Pass PIA2007-WD-003	Pass Range conformity according to S.R. 66:2015	Pass For wet ground conditions also, 0.95 m installation depth from inlet invert	Pass PIA2016-DH-1510-1052.01
10 1500 l/d		Pass PIA2007-WD-003	Pass Range conformity according to S.R. 66:2015	Pass PIA2006-BT-004 PIA2011-ST-PIT-1105-1032 For wet ground conditions also, 1.00 m installation depth from inlet invert	Pass PIA2016-DH-1510-1052.01
12 1800 l/d		Pass PIA2007-WD-003	Pass Range conformity according to S.R. 66:2015	Pass For wet ground conditions also, 0.95 m installation depth from inlet invert	Pass PIA2016-DH-1510-1052.01

Population equivalent (PE)	Drawing of model of the range	Watertightness (EN 12566-3 Annex A)	Treatment Efficiency (EN 12566-3 Annex B)	Structural Behaviour (EN 12566-3 Annex C)	Durability
18 2700 l/d		Pass PIA2007-WD-003	Range conformity according to S.R. 66:2015	Pass For wet ground conditions also, 0.95 m installation depth from inlet invert	PIA2016-DH-1510-1052.01 pass
25 3750 l/d		Pass PIA2007-WD-003	Range conformity according to S.R. 66:2015	PIA2015-ST-PIT-1406-1043.01 Pass For wet ground conditions also, 0.95 m installation depth from inlet invert	PIA2016-DH-1510-1052.01 pass
40 6,000 l/d		Pass PIA2007-WD-003	Range conformity according to S.R. 66:2015	Pass For wet ground conditions also, 0.95 m installation depth from inlet invert	PIA2016-DH-1510-1052.01 pass

Population equivalent (PE)	Drawing of model of the range	Watertightness (EN 12566-3 Annex A)	Treatment Efficiency (EN 12566-3 Annex B)	Structural Behaviour (EN 12566-3 Annex C)	Durability
50 7,500 l/d		Pass PIA2007-WD-003	Range conformity according to S.R. 66:2015	Pass For wet ground conditions also, 0.95 m installation depth from inlet invert	PIA2016-DH-1510-1052.01 pass




Die hier dargestellten Zeichnungen sind als Fertigungszeichnungen zu verstehen. Die hier dargestellten Zeichnungen sind als Fertigungszeichnungen zu verstehen. Die hier dargestellten Zeichnungen sind als Fertigungszeichnungen zu verstehen.

Rev.	Name	Datum	Änderung	Druck
01	Hofmann	18.08.2016		
02	Hofmann	18.08.2016		
03	Hofmann	18.08.2016		
04	Hofmann	18.08.2016		
05	Hofmann	18.08.2016		
06	Hofmann	18.08.2016		
07	Hofmann	18.08.2016		
08	Hofmann	18.08.2016		
09	Hofmann	18.08.2016		
10	Hofmann	18.08.2016		
11	Hofmann	18.08.2016		
12	Hofmann	18.08.2016		
13	Hofmann	18.08.2016		
14	Hofmann	18.08.2016		
15	Hofmann	18.08.2016		
16	Hofmann	18.08.2016		
17	Hofmann	18.08.2016		
18	Hofmann	18.08.2016		
19	Hofmann	18.08.2016		
20	Hofmann	18.08.2016		
21	Hofmann	18.08.2016		
22	Hofmann	18.08.2016		
23	Hofmann	18.08.2016		
24	Hofmann	18.08.2016		
25	Hofmann	18.08.2016		
26	Hofmann	18.08.2016		
27	Hofmann	18.08.2016		
28	Hofmann	18.08.2016		
29	Hofmann	18.08.2016		
30	Hofmann	18.08.2016		
31	Hofmann	18.08.2016		
32	Hofmann	18.08.2016		
33	Hofmann	18.08.2016		
34	Hofmann	18.08.2016		
35	Hofmann	18.08.2016		
36	Hofmann	18.08.2016		
37	Hofmann	18.08.2016		
38	Hofmann	18.08.2016		
39	Hofmann	18.08.2016		
40	Hofmann	18.08.2016		
41	Hofmann	18.08.2016		
42	Hofmann	18.08.2016		
43	Hofmann	18.08.2016		
44	Hofmann	18.08.2016		
45	Hofmann	18.08.2016		
46	Hofmann	18.08.2016		
47	Hofmann	18.08.2016		
48	Hofmann	18.08.2016		
49	Hofmann	18.08.2016		
50	Hofmann	18.08.2016		
51	Hofmann	18.08.2016		
52	Hofmann	18.08.2016		
53	Hofmann	18.08.2016		
54	Hofmann	18.08.2016		
55	Hofmann	18.08.2016		
56	Hofmann	18.08.2016		
57	Hofmann	18.08.2016		
58	Hofmann	18.08.2016		
59	Hofmann	18.08.2016		
60	Hofmann	18.08.2016		
61	Hofmann	18.08.2016		
62	Hofmann	18.08.2016		
63	Hofmann	18.08.2016		
64	Hofmann	18.08.2016		
65	Hofmann	18.08.2016		
66	Hofmann	18.08.2016		
67	Hofmann	18.08.2016		
68	Hofmann	18.08.2016		
69	Hofmann	18.08.2016		
70	Hofmann	18.08.2016		
71	Hofmann	18.08.2016		
72	Hofmann	18.08.2016		
73	Hofmann	18.08.2016		
74	Hofmann	18.08.2016		
75	Hofmann	18.08.2016		
76	Hofmann	18.08.2016		
77	Hofmann	18.08.2016		
78	Hofmann	18.08.2016		
79	Hofmann	18.08.2016		
80	Hofmann	18.08.2016		
81	Hofmann	18.08.2016		
82	Hofmann	18.08.2016		
83	Hofmann	18.08.2016		
84	Hofmann	18.08.2016		
85	Hofmann	18.08.2016		
86	Hofmann	18.08.2016		
87	Hofmann	18.08.2016		
88	Hofmann	18.08.2016		
89	Hofmann	18.08.2016		
90	Hofmann	18.08.2016		
91	Hofmann	18.08.2016		
92	Hofmann	18.08.2016		
93	Hofmann	18.08.2016		
94	Hofmann	18.08.2016		
95	Hofmann	18.08.2016		
96	Hofmann	18.08.2016		
97	Hofmann	18.08.2016		
98	Hofmann	18.08.2016		
99	Hofmann	18.08.2016		
100	Hofmann	18.08.2016		

PTAD
 An Gammelsberg 2
 19200 Bolanden
 Germany
 Fon: +49 3949 9299 0


Letzte Speicherung: Donnerstag, 18. August 2016 15:24:21



* -40/+10 mm tolerance

Rev.	Name	Datum	Änderung	gepr.
01	Hoffmann	09.04.2016		
02	Hoffmann	14.07.2016		
03	Hoffmann	14.07.2016		
04	Hoffmann	14.07.2016		
05	Hoffmann	14.07.2016		
06	Hoffmann	14.07.2016		
07	Hoffmann	14.07.2016		
08	Hoffmann	14.07.2016		
09	Hoffmann	14.07.2016		
10	Hoffmann	14.07.2016		
11	Hoffmann	14.07.2016		
12	Hoffmann	14.07.2016		
13	Hoffmann	14.07.2016		
14	Hoffmann	14.07.2016		
15	Hoffmann	14.07.2016		
16	Hoffmann	14.07.2016		
17	Hoffmann	14.07.2016		
18	Hoffmann	14.07.2016		
19	Hoffmann	14.07.2016		
20	Hoffmann	14.07.2016		
21	Hoffmann	14.07.2016		
22	Hoffmann	14.07.2016		
23	Hoffmann	14.07.2016		
24	Hoffmann	14.07.2016		
25	Hoffmann	14.07.2016		
26	Hoffmann	14.07.2016		
27	Hoffmann	14.07.2016		
28	Hoffmann	14.07.2016		
29	Hoffmann	14.07.2016		
30	Hoffmann	14.07.2016		
31	Hoffmann	14.07.2016		
32	Hoffmann	14.07.2016		
33	Hoffmann	14.07.2016		
34	Hoffmann	14.07.2016		
35	Hoffmann	14.07.2016		
36	Hoffmann	14.07.2016		
37	Hoffmann	14.07.2016		
38	Hoffmann	14.07.2016		
39	Hoffmann	14.07.2016		
40	Hoffmann	14.07.2016		
41	Hoffmann	14.07.2016		
42	Hoffmann	14.07.2016		
43	Hoffmann	14.07.2016		
44	Hoffmann	14.07.2016		
45	Hoffmann	14.07.2016		
46	Hoffmann	14.07.2016		
47	Hoffmann	14.07.2016		
48	Hoffmann	14.07.2016		
49	Hoffmann	14.07.2016		
50	Hoffmann	14.07.2016		
51	Hoffmann	14.07.2016		
52	Hoffmann	14.07.2016		
53	Hoffmann	14.07.2016		
54	Hoffmann	14.07.2016		
55	Hoffmann	14.07.2016		
56	Hoffmann	14.07.2016		
57	Hoffmann	14.07.2016		
58	Hoffmann	14.07.2016		
59	Hoffmann	14.07.2016		
60	Hoffmann	14.07.2016		
61	Hoffmann	14.07.2016		
62	Hoffmann	14.07.2016		
63	Hoffmann	14.07.2016		
64	Hoffmann	14.07.2016		
65	Hoffmann	14.07.2016		
66	Hoffmann	14.07.2016		
67	Hoffmann	14.07.2016		
68	Hoffmann	14.07.2016		
69	Hoffmann	14.07.2016		
70	Hoffmann	14.07.2016		
71	Hoffmann	14.07.2016		
72	Hoffmann	14.07.2016		
73	Hoffmann	14.07.2016		
74	Hoffmann	14.07.2016		
75	Hoffmann	14.07.2016		
76	Hoffmann	14.07.2016		
77	Hoffmann	14.07.2016		
78	Hoffmann	14.07.2016		
79	Hoffmann	14.07.2016		
80	Hoffmann	14.07.2016		
81	Hoffmann	14.07.2016		
82	Hoffmann	14.07.2016		
83	Hoffmann	14.07.2016		
84	Hoffmann	14.07.2016		
85	Hoffmann	14.07.2016		
86	Hoffmann	14.07.2016		
87	Hoffmann	14.07.2016		
88	Hoffmann	14.07.2016		
89	Hoffmann	14.07.2016		
90	Hoffmann	14.07.2016		
91	Hoffmann	14.07.2016		
92	Hoffmann	14.07.2016		
93	Hoffmann	14.07.2016		
94	Hoffmann	14.07.2016		
95	Hoffmann	14.07.2016		
96	Hoffmann	14.07.2016		
97	Hoffmann	14.07.2016		
98	Hoffmann	14.07.2016		
99	Hoffmann	14.07.2016		
100	Hoffmann	14.07.2016		

Letzte Speicherung: Donnerstag, 18. August 2016 15:20:57





Die Abmessungen sind in mm angegeben. Die Abmessungen sind in mm angegeben. Die Abmessungen sind in mm angegeben. Die Abmessungen sind in mm angegeben. Die Abmessungen sind in mm angegeben.


Rev.	Name	Datum	Änderung	Gezeichnet
01	W. H. H.	18.08.2016		
02	W. H. H.	18.08.2016		
03	W. H. H.	18.08.2016		
04	W. H. H.	18.08.2016		
05	W. H. H.	18.08.2016		
06	W. H. H.	18.08.2016		
07	W. H. H.	18.08.2016		
08	W. H. H.	18.08.2016		
09	W. H. H.	18.08.2016		
10	W. H. H.	18.08.2016		
11	W. H. H.	18.08.2016		
12	W. H. H.	18.08.2016		
13	W. H. H.	18.08.2016		
14	W. H. H.	18.08.2016		
15	W. H. H.	18.08.2016		
16	W. H. H.	18.08.2016		
17	W. H. H.	18.08.2016		
18	W. H. H.	18.08.2016		
19	W. H. H.	18.08.2016		
20	W. H. H.	18.08.2016		
21	W. H. H.	18.08.2016		
22	W. H. H.	18.08.2016		
23	W. H. H.	18.08.2016		
24	W. H. H.	18.08.2016		
25	W. H. H.	18.08.2016		
26	W. H. H.	18.08.2016		
27	W. H. H.	18.08.2016		
28	W. H. H.	18.08.2016		
29	W. H. H.	18.08.2016		
30	W. H. H.	18.08.2016		
31	W. H. H.	18.08.2016		
32	W. H. H.	18.08.2016		
33	W. H. H.	18.08.2016		
34	W. H. H.	18.08.2016		
35	W. H. H.	18.08.2016		
36	W. H. H.	18.08.2016		
37	W. H. H.	18.08.2016		
38	W. H. H.	18.08.2016		
39	W. H. H.	18.08.2016		
40	W. H. H.	18.08.2016		
41	W. H. H.	18.08.2016		
42	W. H. H.	18.08.2016		
43	W. H. H.	18.08.2016		
44	W. H. H.	18.08.2016		
45	W. H. H.	18.08.2016		
46	W. H. H.	18.08.2016		
47	W. H. H.	18.08.2016		
48	W. H. H.	18.08.2016		
49	W. H. H.	18.08.2016		
50	W. H. H.	18.08.2016		
51	W. H. H.	18.08.2016		
52	W. H. H.	18.08.2016		
53	W. H. H.	18.08.2016		
54	W. H. H.	18.08.2016		
55	W. H. H.	18.08.2016		
56	W. H. H.	18.08.2016		
57	W. H. H.	18.08.2016		
58	W. H. H.	18.08.2016		
59	W. H. H.	18.08.2016		
60	W. H. H.	18.08.2016		
61	W. H. H.	18.08.2016		
62	W. H. H.	18.08.2016		
63	W. H. H.	18.08.2016		
64	W. H. H.	18.08.2016		
65	W. H. H.	18.08.2016		
66	W. H. H.	18.08.2016		
67	W. H. H.	18.08.2016		
68	W. H. H.	18.08.2016		
69	W. H. H.	18.08.2016		
70	W. H. H.	18.08.2016		
71	W. H. H.	18.08.2016		
72	W. H. H.	18.08.2016		
73	W. H. H.	18.08.2016		
74	W. H. H.	18.08.2016		
75	W. H. H.	18.08.2016		
76	W. H. H.	18.08.2016		
77	W. H. H.	18.08.2016		
78	W. H. H.	18.08.2016		
79	W. H. H.	18.08.2016		
80	W. H. H.	18.08.2016		
81	W. H. H.	18.08.2016		
82	W. H. H.	18.08.2016		
83	W. H. H.	18.08.2016		
84	W. H. H.	18.08.2016		
85	W. H. H.	18.08.2016		
86	W. H. H.	18.08.2016		
87	W. H. H.	18.08.2016		
88	W. H. H.	18.08.2016		
89	W. H. H.	18.08.2016		
90	W. H. H.	18.08.2016		
91	W. H. H.	18.08.2016		
92	W. H. H.	18.08.2016		
93	W. H. H.	18.08.2016		
94	W. H. H.	18.08.2016		
95	W. H. H.	18.08.2016		
96	W. H. H.	18.08.2016		
97	W. H. H.	18.08.2016		
98	W. H. H.	18.08.2016		
99	W. H. H.	18.08.2016		
100	W. H. H.	18.08.2016		


PTAD
 Air Generation GmbH
 19230 Binz/Bahnhof
 Germany
 Phone: +359 89 8230 0

Letzte Zeichnung: Donnerstag, 18. August 2016 11:52:38









*-40/+10 mm tolerance

Rev.	Name	Content	Änderung	Größe
1	HCK2	17/08/2016		
2	ENWUPF	ENWUPF		
3	Substanz	Substanz		
Allgemeine Anmerkungen: DIN 10242 T09 / DIN 80 270 B - m6 DIN 411 Perforationsmethode 1 Kantenbruch nach BO 18116 Benennung: Solido SMART BL7 6 (18 PEI) one-chamber SBR WWTP				Gewicht: mm Wandsdike Werkstoff: Farbe: Sammelnr.: 314_02145 Zeichn.: KSTA 7600
Maßstab: 1:20 Modifik.: 1 von 1				Maßstab: 1:20 Modifik.: 1 von 1

Letzte Speicherversion: 17. August 2016 15:22:26

